

## Vehicle document wallet

This contains a physical copy of comprehensive information about operating your vehicle and about services and your vehicle's warranty.



Order no. P254 0187 13 Part no. 254 584 59 04 Edition B-2024 ر ان



GLC

Operator's Manual

Mercedes-Benz



## Front passenger air bag warning





Air bag warning sticker for USA and Canada

# **WARNING** Risk of injury or fatal injuries if the front passenger air bag is enabled

If the front passenger air bag is enabled, a child on the front passenger seat may be struck by the front passenger air bag in the event of an accident.

NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIR BAG. This can result in the DEATH of or SERIOUS INJURY to the CHILD.

Observe the chapter "Children in the vehicle".

## Publication details

#### Internet

Further information about Mercedes-Benz vehicles and about Mercedes-Benz AG can be found on the following websites:

https://www.mbusa.com (USA only) https://www.mercedes-benz.ca (Canada only)

#### Documentation team

<sup>©</sup>Mercedes-Benz AG: Not to be reprinted, translated or otherwise reproduced, in whole or in part, without written permission from Mercedes-Benz AG.

## Vehicle manufacturer

Mercedes-Benz AG Mercedesstraße 120 70372 Stuttgart Germany

As at 24.04.23

#### Welcome to the world of Mercedes-Benz

Before your first drive, please read this Operator's Manual carefully and familiarize yourself with your vehicle. For your own safety and a longer service life of the vehicle, follow the instructions and warning notices in this Operator's Manual. Disregarding them may lead to damage to the vehicle or injury to people.

Damage to the vehicle resulting from the disregard of the instructions is not covered by the Mercedes-Benz Limited warranty.

The standard equipment and product description of your vehicle may vary and depends on the following factors:

- Model
- Order
- · National version
- Availability

Your vehicle may therefore differ from that shown in the descriptions and illustrations in individual cases.

Mercedes-Benz reserves the right to introduce changes in the following areas:

- Design
- Equipment
- · Technical features

The following documents are components of the vehicle:

- · Digital Operator's Manual
- Printed Operator's Manual
- · Maintenance Booklet
- Supplementary manuals relating to specific equipment
- Supplementary documents

Keep these documents in the vehicle at all times. Ensure that all documents are in the vehicle or passed on in the event of sale or rental.

Mercedes-Benz USA, LLC

Mercedes-Benz Canada, Inc.

A Mercedes-Benz Group AG Company

2545845904



## 2 Contents

	<b>6</b>	National information for components relevant to radio regulation Diagnostics connection Qualified specialist workshop Correct use of the vehicle Notes for persons with electronic medical aids Problems with your vehicle	29 30 31 31 31 32	Children in the vehicle Brief overview of most important points Important safety notes Suitable child restraint systems for the transport of children Securing the child restraint system Child safety locks Occupant presence reminder	5 5 6 6 7
Door operating unit and seat adjustment	16 18	Reporting safety defects	33 33	Opening and closing	7
Digital Operator's Manual	<b>20</b> 20	Copyright	38	Doors	7 8
Protecting the environment Mercedes-Benz Genuine Parts	<b>21</b> 21 22 23	Occupant safety  Brief overview of the most important points  Information on the automatic functions of the restraint system	<b>40</b> 40 48	Side windows	9
Touch-sensitive controls  Mercedes me App  Service and vehicle operation	24 25	Purpose and function of the restraint system		Seats and stowing  Notes on the correct driver's seat position  Notes on grab handles  Seats  Steering wheel  Easy entry and exit feature	9 9 9 10

Memory function Stowage areas Cup holder Sockets Wireless charging of the mobile phone and connection with the exterior antenna Installing/removing the floor mats	113 125 128 130 132	DYNAMIC SELECT Automatic transmission	192 197 197 200 216 225 299	System settings	334 336 337 348 351 359 362
Exterior lighting	142 144 149	Driver's display	<b>305</b> 305 305 306 307	Maintenance and care  ASSYST PLUS service interval display  Maintenance Management  Telediagnosis  Engine compartment  Cleaning and care	369 370 370 371
Climate control	153	system Function of the power meter Overview of status indicators on the driver display	310	Breakdown assistance Emergency Flat tire	387 388
<b>Driving and parking</b> Driving		MBUX multimedia system Overview and operation		Battery (vehicle)	395 403 408

## 4 Contents

Wheels and tires  Notes on noise or unusual handling characteristics  Notes on regularly inspecting wheels and tires  Notes on snow chains  Turning snow chain mode on or off  Tire pressure  Loading the vehicle  Tire labeling  Definition of terms for tires and loading  Changing a wheel  Emergency spare wheel  Collapsible spare wheel	412 412 413 413 413 420 424 430 432 442 443
Technical data  Notes on technical data  Vehicle electronics  Radio regulations  Vehicle identification plate, VIN and engine number overview  Operating fluids  Vehicle data  Trailer hitch	446 446 448 448 450 457 459

amps	461

In this Operator's Manual, you will find the following symbols:

WARNING Danger due to failure to observe the warning notices

Warning notices draw your attention to hazards that may endanger your health or life, or the health or life of others.

Observe the warning notices.

**ENVIRONMENTAL NOTE** Environmental damage due to failure to observe environmental notes

Environmental notes include information on environmentally responsible behavior or environmentally responsible disposal.

Observe environmental notes.

NOTE Damage to property due to failure to observe notes on material damage

Notes on material damage inform you of risks which may lead to your vehicle being damaged.

Observe notes on material damage.

(i) These symbols indicate useful instructions or further information that could be helpful to you.

Instruction

(→ page) Further information on a topic

Display

Display in the central display

Highest menu level, which is to be selected in the multimedia system


**>>** 

Relevant submenus, which are to be selected in the multimedia system

Indicates a cause



# 6 At a glance - Cockpit




Left-hand drive vehicles

<ul><li>Steering wheel paddle shifters</li></ul>	$\rightarrow$	195
Combination switch	$\rightarrow$	134
Oriver's display	$\rightarrow$	305
DIRECT SELECT lever	$\rightarrow$	192
ENGINE   Start/stop button	$\rightarrow$	170
(A) ECO start/stop function	$\rightarrow$	181
© Central display	$\rightarrow$	313
O Glove box	$\rightarrow$	116
Stowage compartment	$\rightarrow$	116
Switch panel for:		
DYNAMIC SELECT button	$\rightarrow$	190
Active Parking Assist	$\rightarrow$	285
Quick vehicle access		
Fingerprint sensor		
ੁੱ Switches the MBUX multimedia system on/off	$\rightarrow$	313

烒 Switches sound on/off	$\rightarrow$	313
Adjusts the volume	$\rightarrow$	313
Mazard warning light system	$\rightarrow$	135
Control panel for the MBUX multimedia system	$\rightarrow$	318
Adjusts the steering wheel	$\rightarrow$	109
Control panel:		
Driver's display	$\rightarrow$	305
Cruise control	$\rightarrow$	235
Active Distance Assist DISTRONIC	$\rightarrow$	240
Diagnostics connection	$\rightarrow$	30
Opens the hood	$\rightarrow$	371
Electric parking brake	$\rightarrow$	220
Light switch	$\rightarrow$	133

## 8 At a glance – Cockpit (plug-in hybrid)



Left-hand-drive vehicles

Increases recuperation	$\rightarrow$	184	Plug-in hybrid settings
② Driver display:			Energy flow display
READY Operational readiness	$\rightarrow$	310	Sets charging times
Power meter	$\rightarrow$	310	DYNAMIC SELECT button
Trip computer			Maptic accelerator pedal
ECO Assist	$\rightarrow$	185	Depressurizes the fuel tank and opera-
③ + Reduces recuperation	$\rightarrow$	184	tion for refueling
Central display:			

Driver display


🚺 🗘 Turn signal lights	$\rightarrow$	134	Drive system: reduced power	$\rightarrow$	539
Irailer hitch	$\rightarrow$	540		$\rightarrow$	191
3 🔋 Indicator lamp inoperative			⑥ ♣ Coolant temperature	$\rightarrow$	542
Electrical malfunction	$\rightarrow$	542	© Coolant temperature display		
	$\rightarrow$	540	Electric parking brake (yellow)	$\rightarrow$	546
<b>⊚</b> ! Power steering (yellow)	$\rightarrow$	540	© Electric parking brake (red)	$\rightarrow$	546
<b>⊚</b> ! Rear axle steering (red)	$\rightarrow$	540	PARK USA only		
<b>⊚</b> ! Rear axle steering (yellow)	$\rightarrow$	540	(P) Canada only		
🗿 😰 Restraint system	$\rightarrow$	537	Brakes (red)	$\rightarrow$	546
🦻 🛕 Seat belt	$\rightarrow$	537	BRAKE USA only		
B 🛕 Distance warning	$\rightarrow$	549	(D) Canada only		
9 (a) ABS	$\rightarrow$	549	RBS Recuperative Brake System, USA only	$\rightarrow$	546
Tire pressure monitoring system	$\rightarrow$	553	(D) Brakes (yellow), Canada only	$\rightarrow$	546
🕦 🔼 Engine diagnostics	$\rightarrow$	542	Reserve fuel with fuel filler flap location	$\rightarrow$	542
☑ 🐉 ESP® OFF	$\rightarrow$	549	indicator		
₹ ESP®	$\rightarrow$	549	② Fuel level ② IID High beam	$\rightarrow$	134

# 12 At a glance – Indicator and warning lamps

<b>■D</b> Low beam	$\rightarrow$	133		$\rightarrow$	134
€00€ Side lights	$\rightarrow$	133	Mercedes-Benz emergency call system	$\rightarrow$	553




# 14 At a glance - Overhead control panel



<ul> <li>Sun visors (folding, available in extendable design as an optional extra)</li> </ul>		
② Switches the front interior lighting on/off	$\rightarrow$	142
Switches the rear interior lighting on/off	$\rightarrow$	142
	$\rightarrow$	351
(5) Switches automatic interior lighting control on/off	$\rightarrow$	142
Sos Sos button	$\rightarrow$	351

Switches the right-hand reading lamp on/off	$\rightarrow$	142
Opens/closes the panorama roof with power tilt/sliding panel	$\rightarrow$	91
Opens/closes the panorama roof with power tilt/sliding panel roller sunblind	$\rightarrow$	91
PASSENGER AIR BAG indicator lamp	$\rightarrow$	45
Inside rear-view mirror	$\rightarrow$	150
Switches the left-hand reading lamp on/off	$\rightarrow$	142

# 16 At a glance – Door operating unit and seat adjustment




# At a glance – Door operating unit and seat adjustment 17

● D Locks/unlocks the vehicle	$\rightarrow$	78
Opening the door	$\rightarrow$	78
Adjusts the seats electrically	$\rightarrow$	101
Switches the seat heating on/off	$\rightarrow$	106
Switches the seat ventilation on/off	$\rightarrow$	107
Operates the memory function	$\rightarrow$	113
Operates the outside mirrors	$\rightarrow$	149
(i) Opens/closes the tailgate	$\rightarrow$	82
Opens/closes the right side window	$\rightarrow$	88
Opens/closes the rear right side window	$\rightarrow$	88
① Child safety lock for the rear side windows	$\rightarrow$	72

Opens/closes the rear left side window	$\rightarrow$	88
Opens/closes the left side window	$\rightarrow$	88
Adjusting the head restraints	$\rightarrow$	102
Seat adjustment using the multimedia system	$\rightarrow$	105
Adjusts the seat fore-and-aft position	$\rightarrow$	99
Adjusts the 4-way lumbar support	$\rightarrow$	102
Adjusts the seat backrest inclination	$\rightarrow$	99
Adjusts the seat height	$\rightarrow$	99
Adjusts the seat cushion inclination	$\rightarrow$	99

# 18 At a glance – Emergencies and breakdowns



Δt a	glance -	Emerger	ncies	and	breakdowns
AL a	gianice -	LITTELEC	ICICS !	ariu	DIEGRUUWIIS

		🕡 🛕 Hazard warning light system	$\rightarrow$	135
$\rightarrow$	33	Fuel filler flap with:		
$\rightarrow$	387	information label on fuel type	$\rightarrow$	197
$\rightarrow$	351	information label on tire pressure	$\rightarrow$	415
$\rightarrow$	351	QR code for accessing the rescue card	$\rightarrow$	33
$\rightarrow$	450	Tow-starting or towing away	$\rightarrow$	404
$\rightarrow$	400	Warning triangle	$\rightarrow$	388
$\rightarrow$	404	1 TIREFIT kit	$\rightarrow$	391
$\rightarrow$	388	First-aid kit (soft sided)	$\rightarrow$	388
	→	→ 387 → 351 → 351 → 450 → 400 → 404	<ul> <li>→ 33</li> <li>Fuel filler flap with:         <ul> <li>→ 387</li> <li>information label on fuel type</li> </ul> </li> <li>→ 351</li> <li>→ QR code for accessing the rescue card</li> <li>→ 450</li> <li>→ Tow-starting or towing away</li> <li>→ 400</li> <li>→ Warning triangle</li> <li>→ 404</li> <li>→ TIREFIT kit</li> </ul>	<ul> <li>→ 33</li> <li>Fuel filler flap with:         <ul> <li>information label on fuel type</li> <li>⇒ 351</li> <li>information label on tire pressure</li> <li>→ 351</li> <li>QR code for accessing the rescue card</li> <li>→ 450</li> <li>Tow-starting or towing away</li> <li>→ 400</li> <li>Warning triangle</li> <li>→ 404</li> </ul> </li> <li>TIREFIT kit</li> </ul>

## Calling up the Digital Operator's Manual


Multimedia system:

- → 🔝 **>>** Settings **>>** Info
- >> Operator's Manual
- >> Open Digital Operator's Manual

The Digital Operator's Manual describes the functions and operation of the vehicle and the multimedia system.

- Select one of the following menu items in the Digital Operator's Manual:
- Quick start: find the first steps towards adjusting your seat (driver's side).
- Tips: find information that prepares you for certain everyday situations with your vehicle.
- Animations: watch animations of the vehicle functions.
- Messages: receive additional information about the messages in the driver's display.
- Language: select the language for the Digital Operator's Manual.

You can search for keywords using the search field Search, in order to find quick answers to questions about the operation of the vehicle.



- Menu
- Search
- 3 Back
- 4 Contents section

Some sections in the Digital Operator's Manual, such as warning notes, can be expanded and collapsed.

Additional methods of calling up the Digital Operator's Manual:

**Driver's display:** call up brief information as display messages in the driver's display

MBUX Voice Assistant: call up via the voice control system

**Global search:** call up search results for contents of the Digital Operator's Manual in the home screen

For safety reasons, the Digital Operator's Manual is deactivated while driving.

## Protecting the environment

ENVIRONMENTAL NOTE Environmental damage due to operating conditions and personal driving style

The pollutant emission of the vehicle is directly related to the way you operate the vehicle.

Operate your vehicle in an environmentally responsible manner to help protect the environment. Please observe the following recommendations on operating conditions and personal driving style.

#### Operating conditions:

- Make sure that the tire pressure is correct.
- Do not carry any unnecessary weight (e.g. roof luggage racks once you no longer need them).
- Adhere to the service intervals. A regularly serviced vehicle will contribute to environmental protection.

Always have maintenance work carried out at a qualified specialist workshop.

## Personal driving style:

- Do not depress the accelerator pedal when starting the engine.
- Do not warm up the vehicle while stationary.
- Drive carefully and maintain a suitable distance from the vehicle in front.
- Avoid frequent, sudden acceleration and braking.
- Change gear in good time and use each gear only up to ¾ of its maximum engine speed.
- Switch off the vehicle in stationary traffic, e.g. by using the ECO start/stop function.
- Drive in a fuel-efficient manner. Observe the ECO display for an economical driving style.

## Plug-in hybrid



**ENVIRONMENTAL NOTE** Environmental pollution caused by irresponsible disposal of the high-voltage battery

A high-voltage battery contains materials which are harmful to the environment.

Dispose of defective high-voltage batteries at a qualified specialist workshop.

## Environmental issues and recommendations:

It is recommended that you re-use or recycle materials instead of just disposing of them.

The relevant environmental guidelines and regulations serve to protect the environment and must be strictly observed.

## Mercedes-Benz Genuine Parts



**ENVIRONMENTAL NOTE** Environmental damage due to not using recycled reconditioned components

Mercedes-Benz AG offers recycled reconditioned components and parts with the same quality as new parts. The same entitlement from the Limited Warranty is valid as for new parts.

- Use recycled reconditioned components and parts from Mercedes-Benz AG.
- NOTE Impairment of the operating efficiency of the restraint systems from installing accessory parts or from repairs or welding

Air bags and Emergency Tensioning Devices, as well as control units and sensors for the restraint systems, may be installed in the following areas of your vehicle:

doors

- door pillars
- sill
- seats
- cockpit
- · driver's display
- center console
- lateral roof frame
- Do not install accessory parts such as audio systems in these areas.
- Do not carry out repairs or welding.
- Have accessories retrofitted at a qualified specialist workshop.

You could jeopardize the operating safety of your vehicle if you use parts, tires and wheels as well as accessories relevant to safety that have not been approved by Mercedes-Benz. Safety-critical systems (e.g. the brake system) may malfunction. Use only Mercedes-Benz Genuine Parts or parts of equal quality. Use only tires, wheels and accessory parts that have been specifically approved for your vehicle model.

Mercedes-Benz Genuine Parts are subject to strict quality inspections. Each part has been specially developed, manufactured or selected for Mercedes-Benz vehicles and adapted to them. Therefore, only Mercedes-Benz Genuine Parts should be used.

More than 300,000 different Mercedes-Benz Genuine Parts are available for Mercedes-Benz models.

All authorized Mercedes-Benz Service Centers maintain a supply of Mercedes-Benz Genuine Parts for necessary service and repair work. In addition, strategically located parts delivery centers provide for quick and reliable parts service.

Always specify the vehicle identification number (VIN) ( $\rightarrow$  page 448) when ordering Mercedes-Benz Genuine Parts.

## Operator's Manual

This Operator's Manual and the Digital Operator's Manual in the vehicle describe the following models and the standard and special equipment for your vehicle:

- The models and the standard and special equipment available at the time of this Operator's Manual going to press.
- The models and the standard and special equipment available only in certain countries.
- The models and the standard and special equipment that will become available only at a later date.

Please note that your vehicle may not be equipped with all features described. This also applies to systems relevant to safety. The equipment on your vehicle may therefore differ from that in the descriptions and illustrations.

The original purchase agreement for your vehicle includes a list of the equipment in your vehicle at the time of delivery.

Should you have any questions concerning equipment and operation, please consult an authorized Mercedes-Benz Center.

(i) Please bear in mind that all the speed values stated in this Operator's Manual are approximate and are subject to a certain tolerance.

The Operator's Manual, supplement, further supplementary documents and Maintenance Booklet are important documents and should be kept in the vehicle.

#### Touch-sensitive controls

In addition to conventional switches and buttons, your vehicle is equipped with touch-sensitive controls.

These are located in the following areas of your vehicle:

- · Roof and door control panel
- · Climate control
- · Steering wheel
- MBUX multimedia system

The controls have touch-sensitive user interface surfaces. You can control these surfaces by pressing or swiping to adjust settings or to trigger functions, for example.

When using touch-sensitive user interfaces, note the following points to avoid problems:

- Do not affix stickers or similar objects to the surfaces
- Do not attach smartphone holders or other mountings to the surface of the central display.
- Keep the surfaces protected from moisture and wet conditions.
- Keep the surfaces free of dust and dirt (→ page 383).

Some touch-sensitive controls have both a symbol and integrated indicator lamps. Be sure to press on the symbol of the control element when using it

#### 24 General notes

## Mercedes me App

#### Notes about the on-demand feature

You can also activate various functions (ondemand feature) subsequently via Mercedes me after purchasing your vehicle.

Information is available at any authorized Mercedes-Benz Center.

## Activating on-demand feature using Mercedes me

#### Requirements

- The vehicle has a wireless connection.
- The vehicle is linked to the Mercedes me user account.

## Ordering and activating on-demand feature

- Add the desired on-demand feature for the vehicle to the shopping basket in the Mercedes me Store.
- Complete the order. The on-demand feature is activated when operating the vehicle.

## Speeding up activation

- Switch the vehicle off and lock it.
- Unlock the vehicle after about two minutes and switch on the vehicle.
   The on-demand feature has been activated.
   For some features, a notification also appears in the vehicle's multimedia system.

If the activation was not successful, repeat the process.

## Service and vehicle operation

## Vehicle operation outside the USA or Canada

When you are abroad with your vehicle, observe the following points:

- service points or replacement parts may not be available immediately.
- unleaded fuel may not be available for vehicles with a catalytic converter. Leaded fuel may cause damage to the catalytic converter.
- the fuel may have an extremely low octane number. Unsuitable fuel can cause engine damage.

Some Mercedes-Benz models are available in Europe through our European Delivery Program. For more information, please consult a Mercedes-Benz service outlet, or write to one of the following addresses:

#### in the USA:

Mercedes-Benz USA, LLC One Mercedes-Benz Drive Sandy Springs, GA 30328

#### in Canada:

Mercedes-Benz Canada, Inc. 2680 Matheson Blvd E, Suite 500 Mississauga, ON L4W 0A5

## Maintenance

Your customer advisor confirms the service in the service report.

#### Roadside Assistance

The Mercedes-Benz Roadside Assistance Program offers technical help in the case of a breakdown.

Your calls to the toll-free Roadside Assistance Hotline are answered by our agents 24 hours a day, 365 days a year.

1-800-FOR-MERCedes (1-800-367-6372) (USA)

1-800-387-0100 (Canada)

You can find further information in the Mercedes-Benz Roadside Assistance Program brochure (USA) or the "Roadside Assistance" section in the Service and Warranty booklet (Canada). You will find both in the vehicle document wallet

## Change of address or change of ownership

In the event of a change of address, please send us the "Notification of address change" in the Service and Guarantee booklet or simply call the Mercedes-Benz Customer Assistance Center (USA) on the hotline number

1-800-FOR-MERCedes (1-800-367-6372) or Customer Service (Canada) on 1-800-387-0100. We can then reach you in a timely fashion, if necessary.

If you sell your Mercedes, please leave all literature in the vehicle so that it is available to the next owner. If you have purchased a used vehicle. please send us the "Notice of Purchase of Used Car" in the Service and Guarantee booklet or simply call the Mercedes-Benz Customer Assistance Center (USA) at the hotline number 1-800-FOR-MERCedes (1-800-367-6372) or Cus-

## Possible danger due to substances hazardous to health

tomer Service (Canada) at 1-800-387-0100.

In compliance with Proposition 65 ("Prop65"), the following detachable label has been added to each vehicle sold in California:

# WARNING

Operating, servicing and maintaining a passenger vehicle, pickup truck, van or off-road motor vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to www.P65Warnings.ca.gov/passenger-vehicle A 000 817 82 02

## Operating safety

≘(i

WARNING Risk of accident due to malfunctions or system failures

If you do not have the prescribed service / maintenance work or any required repairs carried out, this could result in malfunctions or system failures.

Always have the prescribed service and maintenance work or any required repairs carried out in a qualified specialist workshop.

WARNING Risk of accident or injury due

to incorrect modifications on electronic component parts

Modification of electronic components, their software or wiring could impair their function and/or the function of other networked component parts or safety-relevant systems.

This can endanger the operating safety of the vehicle.

#### 26 General notes

- Never tamper with the wiring and electronic component parts or their software.
- You should have all work on electrical and electronic components carried out at a qualified specialist workshop.

Observe the "On-board electronics" section in "Technical data".

WARNING Risk of fire caused by flammable material on hot exhaust system components

Flammable material such as leaves, grass or twigs may ignite if they come into contact with hot parts of the exhaust system.

- When driving on an unpaved road or offroad, check the vehicle underside regularly.
- In particular, remove trapped plant parts or other flammable material.
- If there is damage, consult a qualified specialist workshop immediately.

NOTE Damage to the vehicle due to driving too fast and due to impacts to the vehicle underbody or suspension components

In the following situations, in particular, there is a risk of damage to the vehicle:

- The vehicle becomes grounded, e.g. on a high curb or an unpaved road
- The vehicle is driven too fast over an obstacle, e.g. a curb, speed bump or pothole
- A heavy object strikes the underbody or suspension components

In situations such as these, damage to the body, underbody, suspension components, wheels or tires may not be visible. Components damaged in this way can unexpectedly fail or, in the case of an accident, may no longer absorb the resulting force as intended.

If the underbody paneling is damaged, flammable materials such as leaves, grass or twigs can collect between the underbody and the underbody paneling. These materials may ignite if they come into contact with hot parts of the exhaust system.

Have the vehicle checked and repaired immediately at a qualified specialist workshop.

or

If driving safety is impaired while continuing your journey, pull over and stop the vehicle immediately, while paying attention to road and traffic conditions, and contact a qualified specialist workshop.

## Plug-in hybrid

Hybrid vehicles have a combustion engine and at least one electric motor. The energy supply for operating the vehicle electrically is provided by the vehicle's high-voltage electrical system.

DANGER Risk of death and fire due to modified and/or damaged components of the high-voltage on-board electrical system


The vehicle's high-voltage on-board electrical system is under high voltage. If you modify component parts in the vehicle's high-voltage on-board electrical system or touch damaged component parts, you may be electrocuted. In addition, modified and/or damaged components may cause a fire.

In the event of an accident or impact to the underbody, components of the high-voltage electrical system may be damaged although the damage is not visible.

- Never make any modifications to the high-voltage on-board electrical system.
- Do not switch on or use the vehicle if its high-voltage on-board electrical system components have been modified or damaged.

- Never touch damaged components of the high-voltage on-board electrical system.
- After an accident, do not touch any components of the high-voltage on-board electrical system.
- After an accident, have the vehicle transported away.
- Have the components of the high-voltage on-board electrical system checked at a qualified specialist workshop and replaced if necessary.

The components of the vehicle's high-voltage onboard electrical system are marked with yellow warning stickers. The cables of the vehicle's highvoltage on-board electrical system are orange in color.



## Example

High-voltage components that can become very hot are marked with an additional warning sticker:



#### 28 General notes

Vehicles with hybrid systems generate significantly less noise when stationary and when being driven compared with vehicles that have combustion engines.

When you are driving in electric mode, the vehicle may not be heard by other road users due to the significantly reduced noise generated when driving and when stationary.

It is for this reason that the vehicle is equipped with a sound generator, which serves as an acoustic vehicle alerting system (AVAS). This safety system is prescribed by law.

The external noise produced by the sound generator (AVAS) can be heard in the passenger compartment at low speeds and does not represent a malfunction.

## Vehicles with a 48 V on-board electrical system

**DANGER** Risk of fatal injury by touching damaged high-voltage components

Vehicles with a 48 V on-board electrical system contain individual high-voltage compo-


nents. These high-voltage components are under high voltage.

If you modify component parts of these highvoltage components or touch damaged component parts, you may be electrocuted.

High voltage components may be damaged in an accident, although the damage may not be visible.

- Never perform modifications to component parts of high-voltage components.
- Never touch damaged component parts of high-voltage components.
- Never touch component parts of highvoltage components after an accident.


Vehicles with a 48 V on-board electrical system contain high-voltage components. These components are marked with a high-voltage label:



#### Example

All work on high-voltage components must be carried out at a qualified specialist workshop.

# Installing the license plate on the front license plate bracket



The information label can be found on the license plate bracket, either embossed or in sticker form.

I NOTE Malfunctions and system failures due to incorrect mounting of the license plate on the front license plate holder

If the license plate is incorrectly mounted on the front license plate holder, sensors, cameras or driving and safety systems may malfunction or fail. Observe the following points when mounting the license plate on the front license plate holder:

- Mount the license plate directly on the license plate holder without advertising media or other holders.
- Mount the license plate so that it does not protrude above or to the side of the license plate adapter.

National information for components relevant to radio regulation

## Information on crossing national borders

You must observe the radio regulations for the country in which you are currently operating your vehicle.

Wireless vehicle components



USA: "Radio based devices of this vehicle comply with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) These devices may not cause harmful interference, and 2) These devices must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment."

Canada: "This vehicle contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: (1) These devices may not cause interference. (2) These devices must accept any interference, including interference that may cause undesired operation of the devices." "Les émetteurs/récepteurs dans cette véhicule sont conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: 1) Ces appareils ne doivent pas produire de brouillage; 2) Ces appareils doivent

accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement."

## Diagnostics connection

The diagnostics connection is a technical interface in the vehicle. It is used, for example, in the context of repair and maintenance work or for reading out vehicle data in a specialist workshop. Diagnostic devices should therefore only be connected in a qualified specialist workshop.

▲ WARNING Risk of accident due to connecting devices to the diagnostics connection

If you connect devices to the diagnostics connection of the vehicle, the function of vehicle systems and operating safety may be impaired.

For safety reasons, we recommend that you use and connect only products approved by an authorized Mercedes-Benz Service Center. **WARNING** Risk of accident due to objects in the driver's footwell

Objects in the driver's footwell may impede pedal travel or block a depressed pedal.


This will jeopardize the operating- and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Make sure that there is always sufficient clearance for the pedals.
- Always install the floor mats securely and as prescribed.
- Do not use loose floor mats and do not place floor mats on top of one another.
- NOTE Battery discharging from using devices connected to the diagnostics connection

Using devices at the diagnostics connection drains the battery.

- Check the charge level of the battery.
- If the charge level is low, charge the battery, e.g. by driving a considerable distance

Please also observe the notes on the 12 V battery and on short-distance trips in the chapter "Driving and Parking" ( $\rightarrow$  page 174).



Connecting and using another device with the diagnostics connection can have the following effects:

- · Malfunctions in the vehicle system
- · Permanent damage to vehicle components

Please refer to the warranty terms and conditions for this matter.

Moreover, connecting equipment to the diagnostics connection can lead to emissions monitoring information being reset, for example. This may lead to the vehicle failing to meet the requirements of the next emissions inspection during the main inspection.

## Qualified specialist workshop

A Mercedes-Benz Service Center is a qualified specialist workshop. It has the necessary special skills, tools and qualifications to correctly carry out the work required on your vehicle. This particularly applies to safety-relevant work.

Always have the following work on your vehicle carried out at a Mercedes-Benz Service Center:

- Safety-relevant work
- · Service- and maintenance work
- · Repair work
- Modifications as well as installations- and conversions
- Work on electronic components
- Plug-in hybrid: Work on the hybrid drive system
- Vehicles with 48 V on-board electrical system:
   Work on the high-voltage components of the 48 V on-board electrical system

Mercedes-Benz recommends a Mercedes-Benz Service Center.

## Correct use of the vehicle

If you remove any warning stickers, you or others could fail to recognize certain dangers. Leave warning stickers in position.

Observe the following information in particular when driving your vehicle:

- the safety notes in this Operator's Manual, vehicle-specific supplements and further supplementary documents
- · technical data for the vehicle
- traffic laws and regulations of the country you are currently driving in
- laws pertaining to motor vehicles and safety standards of the country you are currently driving in
- radio regulatory requirements of the country you are currently driving in

## Notes for persons with electronic medical aids

Mercedes-Benz AG cannot, despite carefully developing vehicle systems, completely rule out the interaction of vehicle systems with electronic medical aids such as cardiac pacemakers.

In addition, there are components installed in the vehicle that, regardless of the operating status of the vehicle, can generate magnetic fields on a par with permanent magnets. These fields can be

#### 32 General notes

found, for example, in the area around the multimedia and sound system or also in the area of the seats, depending on the vehicle equipment.

For this reason, the following can occur in isolated cases, depending on the aids used:

- · Medical aids malfunctioning
- · Adverse health effects

Observe the notes and warnings of the manufacturer of the medical aids; if in doubt, contact the device manufacturer and/or your doctor. If there is continuing uncertainty concerning the possibility of medical aids malfunctioning, Mercedes-Benz AG recommends using only few electrical vehicle systems and/or maintaining a distance from the components.

## Plug-in hybrid

When charging the high-voltage battery, keep a distance of at least an arm's length between the medical aid and the following components:

• The power supply equipment

This includes charging stations in the form of a wallbox or a public charging point, for example.

Vehicle components carrying live voltage
 This includes the charging cable and the charging control box, for example.

Only have repairs and maintenance work in the area of the following components carried out at a qualified specialist workshop:

- Vehicle components carrying live voltage
- · Transmission antenna
- Multimedia system and sound system

If you have any queries or suggestions, consult a qualified specialist workshop.

## Problems with your vehicle

If you should experience any problem with your vehicle, particularly one that you believe may affect its safe operation, we urge you to contact a Mercedes-Benz Service Center immediately to have the problem diagnosed and rectified. If the problem is not resolved to your satisfaction there,

please contact a Mercedes-Benz Service Center again or write to one of the following addresses.

#### In the USA:

Mercedes-Benz USA, LLC Customer Assistance Center One Mercedes-Benz Drive Sandy Springs, GA 30328

#### In Canada:

Mercedes-Benz Canada, Inc. Customer Assistance Center 2680 Matheson Blvd E, Suite 500 Mississauga, ON L4W 0A5

## Reporting safety defects

## USA only:

The following text is published as required of manufacturers under Title 49, Code of U.S. Federal Regulations, Part 575 pursuant to the "National Traffic and Motor Vehicle Safety Act of 1966".

If you believe that your vehicle has a defect which could cause a crash or could cause injury or

death, you should immediately inform the National Highway Traffic Safety Administration (NHTSA) in addition to notifying Mercedes-Benz USA, LLC.

If NHTSA receives similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, NHTSA cannot become involved in individual problems between you, your dealer, or Mercedes-Benz USA, LLC.

To contact NHTSA, you may call the Vehicle Safety Hotline toll-free at 1-888-327-4236 (TTY: 1-800-424-9153); go to https://www.safercar.gov; or write to: Administrator, NHTSA, 400 Seventh Street, SW., Washington, DC 20590, USA.

You can also obtain other information about motor vehicle safety from https://www.safercar.gov.

#### Canada only:

The following text is published as required of manufacturers under subsection 18.4 (4) of the Motor Vehicle Safety Regulations.

If you believe that your vehicle has a defect which could cause a crash or could cause injury or death, you should immediately inform Transport

Canada in addition to notifying Mercedes-Benz Canada Inc.

If Transport Canada received similar complaints, it may open an investigation, and if it finds that a safety defect exists in a group of vehicles, it may order a recall and remedy campaign. However, Transport Canada cannot become involved in individual problems between you, your dealer, or Mercedes-Benz Canada Inc.

To contact Transport Canada, you may call the Defect Investigations and Recalls Division toll-free in Canada at 1-800-333-0510 or 819-994-3328 in the Gatineau-Ottawa area or internationally; may also go to the following websites for more information:

- English: https://www.tc.gc.ca/recalls
- French: https://www.tc.gc.ca/rappels

## Limited Warranty

! NOTE Damage to the vehicle arising from violation of these operating instructions.

Damage to the vehicle can arise from violation of these operating instructions.

This damage is not covered either by the Mercedes-Benz implied warranty or by the New- or Used-Vehicle Warranty.

Follow the instructions in these operating instructions on proper operation of your vehicle as well as on possible vehicle damage.

## QR code for rescue card

QR codes are attached in the fuel filler flap and on the opposite side on the B-pillar. In the event of an accident, rescue services can use the QR code to quickly find the appropriate rescue card for your vehicle. The current rescue card contains the most important information about your vehicle (e.g. the routing of the electric lines) in compact form.

#### 34 General notes

Further information can be obtained at https://www.mercedes-benz.de/gr-code

#### Data storage

## Data processing in the vehicle

#### Electronic control units

There are electronic control units installed in your vehicle. Control units process data that they e.g. receive from vehicle sensors, generate themselves or exchange among themselves. Some control units are required for the safe operation of your vehicle. For example, some assist you when you are driving, such as driver assistance systems, while others enable convenience or infotainment functions.

The following provides you with general information regarding data processing in the vehicle. Additional information on what specific data is collected, stored and transmitted to third parties for what purpose in your vehicle can be found in the notes on the functional features in question in the respective operating instructions. These are

also available online and, depending on the equipment, digitally in the vehicle.

#### Personal data

Each vehicle is marked with a unique vehicle identification number. Depending on the country, this vehicle identification number can be used by, for example, government authorities to determine the identity of the owner. There are other possibilities for using data collected from the vehicle to identify the owner or driver, such as the license plate number.

The data generated or processed by control units may therefore be personal or, in certain circumstances, become personal. Depending on which vehicle data are available, it may be possible to make inferences about, for example, your driving behavior, your location, your route or your use patterns.

## Legal requirements for the disclosure of data

If legal regulations exist, manufacturers are generally obligated to release data stored by the manufacturer to the necessary extent in individual cases at the request of state authorities. This may

be the case during the investigation of a criminal offense, for example.

Within the framework of applicable law, state authorities are also authorized to take data readouts from vehicles themselves in specific cases. In the event of an accident, for example, information readouts can be taken from the air bag control unit to help to establish what happened.

#### Operating data in the vehicle

Control units process data to operate the vehicle. This includes the following data, for example:

- Vehicle status information such as speed, longitudinal acceleration, lateral acceleration, number of wheel revolutions or the fastened seat belts indicator
- Ambient conditions, such as temperature, rain sensor or distance sensor

As a rule, this data is volatile, is not stored beyond the operating time and is processed only in the vehicle itself. Control units (e.g. the vehicle key) often contain data memories. These are used to temporarily or permanently document information about the vehicle's operating state, component

stress, maintenance requirements or technical events and malfunctions.

Depending on the technical equipment, the following data will be stored:

- Operating status of system components (e.g. fill levels, tire pressure, battery status)
- Malfunctions or faults in important system components (e.g. lights, brakes)
- System reactions in special driving situations (e.g. air bag deployment, the intervention of stability control systems
- Information on events leading to vehicle damage

In special cases, it may be necessary to store data that would otherwise only be volatile. This may be the case if the vehicle has detected a malfunction, for example.

If you use services such as repair services or maintenance work, stored operational data readouts can be taken and used together with the vehicle identification number, where necessary. Readouts can be taken by service network employees such as workshops and manufactur-

ers, or third parties, such as breakdown services. The same is true in the case of warranty claims and quality assurance measures.

The readout will usually be taken via the diagnostics connection in the vehicle, which is required by law. The operating data readout taken documents technical conditions of the vehicle or individual components and helps to diagnose malfunctions, meet warranty obligations and improve quality. This data, particularly information on component stress, technical events, operating errors and other malfunctions, will be transmitted to the manufacturer for this purpose together with the vehicle identification number if necessary. In addition, the manufacturer is subject to product liability. For this reason, the manufacturer also uses operational data from the vehicle for e.g. recalls. This data can also be used to check customer claims for warranty and guarantee.

Fault memories in the vehicle can be reset by a service outlet or at your request as part of repair or maintenance work.

#### Comfort and infotainment functions

You can save comfort settings and individualization in the vehicle and change or reset them at any time.

Depending on the vehicle equipment, this includes the following settings, for example:

- · Seat positions and steering wheel positions
- Suspension tuning and climate control settings
- · Custom settings (e.g. interior lighting)

You can incorporate data into the vehicle's infotainment functions yourself as part of the selected equipment.

Depending on the vehicle equipment, this includes the following data, for example:

- Multimedia data (e.g. music, films or photos for playback in an integrated multimedia system)
- Address book data for use in conjunction with an integrated hands-free system or an integrated navigation system

#### 36 General notes

- Navigation destinations that have been entered
- Data about the use of internet services

This data for comfort and infotainment functions can be saved locally in the vehicle or stored on a device that you have connected to the vehicle (e.g. smartphone, USB flash drive or MP3 player). If you have entered data yourself, you can delete it at any time.

The transfer of this data out of the vehicle will take place exclusively at your request. This applies in particular when you are using online services according to the settings you have selected.

## Smartphone integration (e.g. Android Auto or Apple CarPlay®)

If your vehicle is equipped appropriately, you can connect your smartphone or another mobile device to the vehicle. You will then be able to control them using the controls integrated in the vehicle. The smartphone's picture and sound can be output via the multimedia system. Specific items of information will also be transferred to your smartphone. Depending on the type of integration, this may include position data, day/night

mode and other general vehicle statuses. Please refer to the vehicle Operator's Manual / infotainment system operating instructions for further information.

This integration allows the use of selected smartphone apps (e.g. navigation apps, music player apps). There will be no further interaction between your smartphone and the vehicle; in particular, vehicle data will not be directly accessible. The type of additional data processing is determined by the provider of the app being used. Whether you can configure settings for it and, if so, which ones, depend on the app and your smartphone's operating system.

#### Online services

### Wireless network connection

If your vehicle has a wireless network connection, it enables data to be exchanged between your vehicle and additional systems. The wireless network connection is made possible by the vehicle's own transmitter and receiver or by a mobile end device that you have brought into the vehicle, for example, a smartphone. Online functions can be

used via the wireless network connection. This includes online services and applications/apps provided to you by the manufacturer or by other providers.

#### Manufacturer's services

Regarding the manufacturer's online services, the individual functions are described by the manufacturer in a suitable place, for example, in the Operator's Manual or on the manufacturer's website, where the relevant data protection information is also given. Personal data may be used for the provision of online services. Data is exchanged via a secure connection, such as the manufacturer's designated IT systems. Any personal data which is collected, processed and used, other than for the provision of services, is done so exclusively on the basis of legal permission. This is the case, for example, for a legally prescribed emergency call system, a contractual agreement or when consent has been given.

You can have services and functions, some of which are subject to a fee, activated or deactivated. This excludes legally prescribed functions and services, such as an emergency call system.

### Third-party services

If you use online services from other providers (third parties), these services are the responsibility of the provider in question and subject to that provider's data protection conditions and terms of use. As a general rule, the manufacturer has no influence on the content exchanged.

For this reason, when services are provided by third parties, please ask the service provider in question for information about the type, extent and purpose of the collection and use of personal data.

### Data protection rights

Depending on your country or the equipment and range of functions of your vehicle as well as the services you use and the services on offer, you are entitled to different data protection rights. Further information on data protection and your data protection rights can either be found on the manufacturer's website or you will receive this information as part of the various services and service offers. There you will also find the contact

information for the manufacturer and its data protection officers.

At a workshop, for example, with the support of a specialist and possibly for a fee, you can have data read out which is stored only locally in the vehicle.

### MBUX multimedia system/Mercedes me connect

If the vehicle is equipped with the MBUX multimedia system or Mercedes me connect, additional data about the vehicle's operation, the use of the vehicle in certain situations, and the location of the vehicle may be compiled by the MBUX multimedia system or Mercedes me connect.

For additional information, please refer to the "MBUX multimedia system" section and/or the Mercedes me connect Terms and Conditions.

### Event data recorder

USA only:

This vehicle is equipped with an event data recorder (EDR). The main purpose of an EDR is to

record, in certain crash or near crash-like situations, such as an air bag deployment or hitting a road obstacle, data that will assist in understanding how a vehicle's systems performed. The EDR is designed to record data related to vehicle dynamics and safety systems for a short period of time, typically 30 seconds or less.

The EDR in this vehicle is designed to record such data as:

- How various systems in your vehicle were operating;
- Whether or not the driver and passenger safety belts were buckled/fastened;
- How far (if at all) the driver was depressing the accelerator and/or brake pedal; and,
- · How fast the vehicle was traveling.

These data can help provide a better understanding of the circumstances in which crashes and injuries occur. NOTE: EDR data are recorded by your vehicle only if a non-trivial crash situation occurs; no data are recorded by the EDR under normal driving conditions and no personal data (e.g., name, gender, age, and crash location) are

recorded. However, other parties, such as law enforcement could combine the EDR data with the type of personally identifying data routinely acquired during a crash investigation.

To read data recorded by an EDR, special equipment is required, and access to the vehicle or the EDR is needed. In addition to the vehicle manufacturer, other parties, such as law enforcement, that have the special equipment, can read the information if they have access to the vehicle or the EDR.

EDR data may be used in civil and criminal matters as a tool in accident reconstruction, accident claims, and vehicle safety. Since the Crash Data Retrieval CDR tool that is used to extract data from the EDR is commercially available, Mercedes-Benz USA, LLC ("MBUSA") expressly disclaims any and all liability arising from the extraction of this information by unauthorized Mercedes-Benz personnel.

MBUSA will not share EDR data with others without the consent of the vehicle owners or, if the vehicle is leased, without the consent of the lessee. Exceptions to this representation include responses to subpoenas by law enforcement; by federal, state or local government; in connection with or arising out of litigation involving MBUSA or its subsidiaries and affiliates; or, as required by law.

Warning: The EDR is a component of the Restraint System Module. Tampering with, altering, modifying or removing the EDR component may result in a malfunction of the Restraint System Module and other systems.

State laws or regulations regarding EDRs that conflict with federal regulation are pre\-empted. This means that in the event of such conflict, the federal regulation governs. As of Dec 2016, 17 states have enacted laws relating to EDRs.

### Copyright

### Free and open source software

Information on licenses for free and open-source software used in your vehicle can be found on the data carrier in your vehicle document wallet and with updates on the following website:

https://www.mercedes-benz.com/opensource

### Registered trademarks

- Bluetooth<sup>®</sup> is a registered trademark of Bluetooth SIG. Inc.
- DTS™ is a registered trademark of DTS, Inc.
- Dolby<sup>®</sup> and MLP™ are registered trademarks of DOLBY Laboratories.
- ESP® and PRE-SAFE® are registered trademarks of Mercedes-Benz Group AG.
- HomeLink<sup>®</sup> is a registered trademark of Gentex Corporation.
- iPod<sup>®</sup> and iTunes<sup>®</sup> are registered trademarks of Apple Inc.
- Burmester<sup>®</sup> is a registered trademark of Burmester Audiosysteme GmbH.
- Microsoft<sup>®</sup> and Windows Media<sup>®</sup> are registered trademarks of Microsoft Corporation.
- SiriusXM<sup>®</sup> is a registered trademark of Sirius XM Radio Inc.
- HD Radio™ is a registered trademark of iBiquity Digital Corporation.

- $\bullet$   $\,$  Gracenote  $^{\circledR}$  is a registered trademark of Gracenote, Inc.
- $\bullet~$  ZAGAT Survey  $^{\circledR}$  and related brands are registered trademarks of Zagat Survey, LLC.

### Brief overview of the most important points

#### **Basic information**

Make sure that the following prerequisites in particular have been met so that the components of the restraint system are able to provide the intended level of protection:

- Sit correctly (→ page 41).
- Fasten the seat belt correctly ( $\rightarrow$  page 42).
  - Function of the seat belt warning lamp
     (→ page 44).
  - Function of the rear seat belt status display (→ page 45).
- The PASSENGER AIR BAG indicator lamps display the correct status for the front passenger air bag (→ page 45).

### Helping you to understand clearly

The "Occupant safety" chapter includes information on equipment, functions and behaviors that

contribute directly to the safety of vehicle occupants.

The information is structured as follows:

- Brief overview of the most important points: this chapter provides an overview of the relationship between the restraint system and the correct behavior of all vehicle occupants.
- Specific information: in further sections of the "Occupant safety" chapter, you can find specific information on the equipment and functions of the restraint system.
- Index: you can also find certain topics in this Operator's Manual using the index.

The "Occupant safety" chapter does not provide information on topics including the following:

- Children in the vehicle (→ page 58)
- Driving and driving safety systems
   (→ page 225)
- Stowage areas (→ page 113)

### Defining generic terms clearly

The following generic terms are used in this Operator's Manual:

- Occupant safety: comprises the components and system functions that help to minimize, as much as possible, the stresses and consequences for vehicle occupants caused by an accident.
- Restraint system: comprises those components that, along with the vehicle structure, help prevent vehicle occupants from potentially coming into contact with parts of the vehicle interior. The seat belts and air bags, for example, are components of the restraint system.
- Child restraint system: you can find all information on this topic in the chapter "Children in the vehicle" (→ page 58).

### Be diligent

For the components of the restraint system to provide the intended level of protection, it is essential for your posture to be correct and for the seat belt to be fastened correctly. Bear in mind that negligence when adopting your sitting position and fastening your seat belt may have serious consequences. Be diligent and make sure that all vehicle occupants are sitting correctly and have fastened their seat belts properly before starting every journey.

### Information on the correct seat position

The seat position must be correct in order for the components of the restraint system to provide the intended level of protection.

The seat position influences both the protection provided by the seat belt and the additional protection provided by the air bag.

The correct seat position with an almost upright posture and a correctly fastened seat belt also reduce the risk posed by the air bag when it is deployed.

When choosing the seat, take note of the available space. When you are sitting with the right posture in a nearly upright position, your head should not touch the roof.

## **WARNING** Risk of injury or death due to an incorrect seat position

If you deviate from the correct seat position, the air bag cannot provide its intended protective function.

Each vehicle occupant must make sure of the following.

- Put the seat in the correct position.
- Fasten seat belts correctly. Pregnant women must take particular care to ensure that the lap belt never lies across the abdomen.
- Observe the following information.

In order for the restraint system to provide the intended level of protection, observe the following information:

 Before starting your journey, adjust your seat correctly (→ page 98).

When doing so, make sure you are able to fasten your seat belt correctly. The shoulder belt strap must be routed forward from the seat belt outlet over the center of your shoulder.

- Keep your distance from the air bags, especially the front air bags. Set the driver's seat and front passenger seat as far back as possible while making sure the seat belt is fastened correctly.
- If persons are sitting on the rear seats, vehicle occupants should maintain a sufficient distance to the parts of the vehicle interior in front of them.
- Make sure there are no people, animals or objects between the vehicle occupants and an air bag.
- If you are the driver, observe the following information on the correct position of the driver's seat (→ page 98).

Hold the steering wheel only by the steering wheel rim. This allows the driver's air bag to fully deploy.

 Assume a nearly upright position, with your buttocks as far back as possible in the gap between the seat cushion and seat backrest.

This ensures that your back lies as flat and firmly as possible against the seat backrest.

### 42 Occupant safety - Brief overview of the most important points

- While driving, do not lean forward and do not lean against the door or side window. You may otherwise be in the deployment area of the air bags.
- Sit with your feet resting on the floor, if possible. Your thighs are slightly supported by the seat cushion
  - Do not put your feet up on the cockpit, for example. Your feet may otherwise be in the deployment area of the air bag.
- Fasten the seat belt correctly.

### Notes on wearing the seat belt correctly

Always fasten your seat belt correctly before starting a journey. A seat belt can provide the best level of protection only if it is worn correctly.

**WARNING** Risk of injury or death due to incorrectly fastened seat belt

If the seat belt is not worn correctly, it cannot perform its intended protective function.

In addition, an incorrectly fastened seat belt can also cause injuries, for example, in the event of an accident or when braking or changing direction suddenly.

Always ensure that all vehicle occupants have their seat belts fastened correctly and are sitting properly.

A

**WARNING** Risk of injury or death when additional restraint systems are not used for persons with a smaller stature

Persons under 5 ft (1.50 m) tall cannot wear the seat belt correctly without a suitable additional restraint system.

Always secure persons under 5 ft (1.50 m) tall in a suitable restraint system.

Each vehicle occupant must observe the following notes in particular:

• The seat belt must not be twisted:

- The shoulder belt strap must be routed forward from the seat belt outlet over the center of your shoulder.
- The shoulder belt strap should neither touch your neck nor be routed under your arm or behind your back.
- The lap belt must be routed as low down across the hips as possible.

In addition, push the lap belt down as far as possible across your hips and pull tight with the shoulder belt strap. Never route the lap belt across your abdomen.

Pregnant women must also take particular care with this.

- The shoulder belt strap and lap belt must fit snugly against the body after being tightened.
- Avoid wearing bulky clothing, e.g. a winter coat.
- Never route the seat belt across sharp, pointed, abrasive or fragile objects.
- Only one person should use each seat belt at any one time.

 Never secure objects with a seat belt if the seat belt is also being used by one of the vehicle's occupants.

Also ensure that no objects, e.g. a cushion, are ever placed between a person and the seat.

### Fastening and adjusting seat belts

If the seat belt is pulled quickly or sharply, the seat belt retractor locks. The seat belt strap cannot be pulled out any further.



- Always engage seat belt tongue ① of the seat belt into seat belt buckle ② of the corresponding seat.
- To adjust the seat belt height: press button on the seat belt outlet and slide the seat belt outlet to the desired position.
- To engage the seat belt outlet: release button and ensure that the seat belt outlet engages.

NOTE Deployment of components of the restraint system when the front passenger seat is unoccupied and a seat belt is buckled

When the front passenger seat is unoccupied and the seat belt tongue of the seat belt is engaged in the seat belt buckle, components of the restraint system may deploy unnecessarily on the front passenger side, e.g. the Emergency Tensioning Device.

- Only buckle the seat belts as intended.
- (i) Observe the information on child seat safety feature of the seat belt ( $\rightarrow$  page 66).

### Function of the restraint system warning lamp

When the vehicle is switched on, a self-test is performed, during which the restraint system warning lamp ② lights up. It goes out no later than a few seconds after the vehicle is started. The components of the restraint system are then functional.

A malfunction has occurred in the restraint system if:

- the restraint system warning lamp does not light up or lights up continuously when the vehicle is switched on.
- the restraint system warning lamp ights up continuously or repeatedly during a journey.

If components of the restraint system have been deployed, the restraint system warning lamp \*\*
will light up continuously.

**WARNING** Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

Have the restraint system checked and repaired immediately at a qualified specialist workshop. **Plug-in hybrid:** if the restraint system is malfunctioning, the automatic high-voltage emergency shutoff may not function.

 $\mathbf{A}$ 

**DANGER** Risk of fatal injuries due to malfunctions of the automatic high-voltage emergency shutoff

In the event of an accident, the high-voltage on-board electrical system may not be deactivated as intended.

You may be electrocuted if you touch the damaged component parts of the high-voltage on-board electrical system.

- Have the automatic high-voltage emergency shutoff checked and repaired immediately at a qualified specialist workshop.
- After an accident, switch off the vehicle immediately.

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop.

### Function of the seat belt warning lamp

The seat belt warning lamp lights up for six seconds every time the vehicle is started.

In addition, a warning tone may sound.

When the driver's and front passengers doors are closed and the driver and front passenger have fastened their seat belts, the seat belt warning goes out.

In the following cases, the seat belt warning lights up during a journey if:

- The driver or front passenger has not fastened their seat belt and the following criteria is met:
  - The vehicle speed exceeds 5 mph (9 km/h) for more than 20 seconds.
  - The vehicle speed exceeds 15 mph (25 km/h) once.
- The driver or front passenger unfastens their seat belt while the vehicle is in motion.

### Function of the rear seat belt status display

The rear seat belt status display in the driver's display is a reminder that all vehicle occupants must wear their seat belts correctly.

In addition, a warning tone may sound.

If a person unfastens a seat belt in the rear passenger compartment while the vehicle is motion, the rear seat belt status display appears again.

### Display in the driver's display

Every time the vehicle is switched on, the rear seat belt status display informs you for a certain amount of time which rear seat belt is not fastened.



You can determine the status of the rear seat belt by the color of the seat symbol in the driver's display as follows:

- Gray: the rear seat belt is not fastened.
- Green: the seat belt tongue of a rear seat belt is engaged in the seat belt buckle of the displayed seat.
- Red: the person in the rear seat has unfastened their seatbelt.

# Function of the PASSENGER AIR BAG indicator lamps (front passenger air bag)



The PASSENGER AIR BAG indicator lamps display the status of the front passenger air bag.

If the front passenger seat is occupied or a child restraint system is installed on the front passenger seat, you must make sure, both before and during a journey, that the status of the front

A

**WARNING** Risk of potentially fatal injuries due to objects trapped under the front passenger seat

Objects trapped under the front passenger seat may interfere with the function of the automatic front passenger air bag shutoff or damage the system.

- Do not stow any objects under the front passenger seat.
- When the front passenger seat is occupied, ensure that no objects have become trapped beneath the front passenger seat.

**Self-test:** when the vehicle is switched on, both the PASSENGER AIR BAG ON and OFF indicator lamps light up simultaneously for several seconds.

After the self-test, you can determine the status of the front passenger air bag as follows:

• Front passenger air bag disabled: PASSENGER AIR BAG OFF lights up continuously.

The front passenger air bag will not be deployed in the event of an accident. If PASSENGER AIR BAG OFF is lit, no one may use the front passenger seat.

If a rearward-facing child restraint system is installed on the front passenger seat, PASSENGER AIR BAG OFF must be lit continuously.

 Front passenger air bag enabled: PASSENGER AIR BAG ON lights up for up to 60 seconds or both the PASSENGER AIR BAG ON and OFF indicator lamps do not light up.

The front passenger air bag may be deployed during an accident. If the front passenger air bag has this status, no rearward-facing child restraint system may be installed on the front passenger seat.

(i) If you are driving with a child in the vehicle, observe the information in the chapter "Children in the vehicle" (→ page 58)

**WARNING** Risk of injury or death due to a disabled front passenger airbag

The front passenger airbag is disabled when the PASSENGER AIR BAG OFF indicator lamp is lit.

A person in the front passenger seat could then, for example, come into contact with the vehicle interior, especially if the person is sitting too close to the cockpit.

If the front passenger seat is occupied, always ensure that:

- The classification of the person in the front passenger seat is correct and the front passenger airbag is enabled or disabled in accordance with the person in the front passenger seat.
- The front passenger seat has been moved as far back as possible.
- The person is seated correctly.
- Both before and during the journey, ensure that the status of the front passenger airbag is correct.

## Malfunction of the automatic front passenger air bag shutoff

In this case, no one may use the front passenger seat and no child restraint system may be installed on the front passenger seat.

Have the automatic front passenger air bag shutoff checked and repaired immediately at a qualified specialist workshop.

Be sure to also observe the following further related subjects:

 Child restraint system on the front passenger seat (→ page 62)

### Disabling or enabling the front passenger air bag

The automatic front passenger air bag shutoff can disable or enable the front passenger air bag and front passenger knee bag according to the situation.

This happens automatically as a result of the classification of the person or child restraint system on the front passenger seat.

You cannot manually disable or enable the front passenger air bag.

Also observe the following information:

- For the status of the front passenger air bag, see "Function of the PASSENGER AIR BAGindicator lamps" (→ page 45)
- For information on using the automatic front passenger air bag shutoff, see "Information on the automatic front passenger air bag shutoff" (→ page 48)
- If you are driving with a child in the vehicle, observe the chapter "Children in the vehicle" (→ page 58)

### Information on the child restraint system

When installing a child restraint system, observe the notes in "Children in the vehicle"  $(\rightarrow$  page 58).

## Notes on the child restraint system on the front passenger seat

A

**WARNING** Risk of injury or fatal injuries if the front passenger air bag is enabled

If the front passenger air bag is enabled, a child on the front passenger seat may be struck by the front passenger air bag in the event of an accident.

NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIR BAG. This can result in the DEATH of or SERIOUS INJURY to the CHILD.

Also pay particular attention to the notes on rearward-facing or forward-facing child restraint systems on the front passenger seat ( $\rightarrow$  page 62).

## Information on the automatic functions of the restraint system

## Function of the automatic front passenger air bag shutoff

A person on the front passenger seat must observe the following information:

- Sit correctly (→ page 41).
- Fasten the seat belt correctly ( $\rightarrow$  page 42).

The automatic front passenger air bag shutoff can activate or deactivate the front passenger air bag and front passenger knee bag according to the situation.

Make sure you observe the following information:

- Status of the front passenger air bag: see
   "Function of the PASSENGER AIR BAG indicator lamps" (→ page 45).
- When installing a child restraint system on the front passenger seat, observe the vehicle-specific information (→ page 62).

Status of the front passenger air bag in relation to the stature of the person:

 Front passenger air bag disabled: PASSENGER AIR BAG OFF lights up continuously.

The front passenger air bag will not be deployed in the event of an accident. If PASSENGER AIR BAG OFF is lit, no one may use the front passenger seat.

 Front passenger air bag enabled: PASSENGER AIR BAG ON lights up for up to 60 seconds or until both the PASSENGER AIR BAG ON and OFF indicator lamps go out.

The front passenger air bag may be deployed during an accident. Observe the following information on the correct seat position  $(\rightarrow page 41)$ .

**Vehicles with rear seats:** a person of smaller stature should use a rear seat.

#### System limits

The front passenger air bag may otherwise be disabled by mistake, for example, in the following situation:

- The front passenger transfers their weight by supporting themselves on a vehicle armrest.
- The front passenger sits in such a way that their weight is raised from the seat surface.
- NOTE Deployment of components of the restraint system when the front passenger seat is unoccupied

In an accident, the components of the restraint system may deploy unnecessarily on the front passenger side if:

- There are heavy objects on the front passenger seat.
- The seat belt tongue is engaged in the seat belt buckle of the front passenger seat and the front passenger seat is unoccupied.
- Store objects in a suitable place.

Only one person should use each seat belt at any one time.

Depending on the detected accident situation, the window air bag on the front passenger side may deploy. The air bag is deployed regardless of whether the front passenger seat is occupied.

## Function of PRE-SAFE® (anticipatory occupant protection)

PRE-SAFE® is able to detect certain critical driving situations and implement pre-emptive measures to protect the vehicle occupants.

PRE-SAFE® can implement the following measures independently of each other:

- Tightening the seat belts on the driver's seat and front passenger seat.
- · Closing the side windows.
- Vehicles with sliding sunroof: closing the sliding sunroof.

- Vehicles with memory function: moving the front passenger seat to a more favorable seat position.
- PRE-SAFE® Sound: provided that the multimedia system is switched on, generating a brief noise signal to stimulate the innate protective mechanism of a person's hearing.
- I NOTE Damage caused by objects in the footwell or behind the seat

The automatic adjustment of the seat position may result in damage to the seat and/or the object.

Stow objects in a suitable place.

### Reverting the PRE-SAFE® system measures

If an accident did not occur, the pre-emptive measures that were taken will be reversed.

You will need to perform certain settings yourself.

 If the seat belt pre-tensioning is not reduced, move the seat backrest back slightly.
 The locking mechanism will release.

# Function of PRE-SAFE® PLUS (anticipatory occupant protection plus)

PRE-SAFE® PLUS can detect certain impacts, particularly an imminent rear impact, and take preemptive measures to protect the vehicle occupants. These measures may not necessarily prevent an imminent impact.

PRE-SAFE® PLUS can implement the following measures independently of each other:

- Tightening the seat belts on the driver's seat and front passenger seat.
- Increasing brake pressure when the vehicle is stationary. This brake application is canceled automatically when the vehicle pulls away.

If an accident did not occur, the pre-emptive measures that were taken will be reversed.

#### System limits

The system will not initiate any action in the following situations:

 If the vehicle is backing up or • When the vehicle is towing a trailer and there is a risk of a rear-end collision

The system will not initiate a brake application in the following situations:

- During a journey or
- When the vehicle is entering or exiting a parking space using Active Parking Assist

### Function of PRE-SAFE® Impulse Side

If an imminent side impact is detected, PRE-SAFE® Impulse Side can pre-emptively move the front seat vehicle occupant's upper body towards the center of the vehicle. It does this by rapidly inflating an air cushion in the outer seat side bolster of the seat backrest on the side on which the impact is anticipated. This increases the distance between the door and the vehicle occupant.

If PRE-SAFE® Impulse Side has been deployed or is faulty, a display message reading PRE-SAFE Pulse Side Inoperative See Operator's Manual ( $\rightarrow$  page 462) will appear.

### Seat belt adjustment function

Vehicles with PRE-SAFE®: after you have fastened the seat belt of the front seat, it may adjust itself against your body by pulling at the shoulder until somewhat tight. Do not hold the seat belt tightly while it is adjusting.

This function is a reminder that all vehicle occupants must wear their seat belts correctly.

You can activate and deactivate the seat belt adjustment function using the multimedia system ( $\rightarrow$  page 50).

## Activating/deactivating seat belt adjustment via the multimedia system

Multimedia system:

- → 🔝 >> Settings >> Vehicle
- >> Occupant Protection
- Activate or deactivate Belt adjustment.

## Overview of the automatic measures after an accident

Depending on the type and severity of the accident, and depending on the vehicle's equipment, the following measures can be implemented, forexample:

- automatic braking (post-collision brake)
- · activating the hazard warning lights
- triggering an automatic emergency call
   (→ page 359)
- Switching off the engine

  To start the validate again

To start the vehicle again, switch the vehicle off and on once more ( $\rightarrow$  page 170). Depending on the type and severity of the accident, you may no longer be able to start the vehicle.

- switching off the fuel supply
- Plug-in hybrid: switching off the hybrid system and high-voltage on-board electrical system
- · unlocking the vehicle doors
- · lowering the side windows
- displaying the emergency guide in the central display

· switching on the interior lighting

## Function of the post-collision brake after an accident

Depending on the accident situation, the post-collision brake can minimise the severity of a further collision or even avoid it.

If an accident is detected, the post-collision brake can initiate automatic braking. When the vehicle has come to a standstill, the electric parking brake is automatically applied.

The driver can cancel automatic braking by taking the following actions:

- · Braking more strongly than automatic braking
- Fully depressing the accelerator pedal with force

### Purpose and function of the restraint system

## Overview of deployment situations (restraint system)

Make sure that the following prerequisites in particular have been met so that the components of the restraint system are able to provide the intended level of protection:

- Sit correctly ( $\rightarrow$  page 41).
- Fasten the seat belt correctly (→ page 42).
  - Function of the seat belt warning lamp  $(\rightarrow)$  page 44).
  - Function of the rear seat belt status display ( $\rightarrow$  page 45).
- The restraint system warning lamp 

  is not lit up after the self-test (→ page 43).
- The PASSENGER AIR BAG indicator lamps display the correct status of the front passenger air bag (→ page 45).

Depending on the detected deployment situation, the components of the restraint system can be activated or deployed independently of each other:

- Emergency Tensioning Device: frontal impact, rear impact, side impact, rollover
- Driver's air bag, front passenger air bag: frontal impact
- · Knee air bag: frontal impact
- · Side impact air bag: side impact
- Window curtain air bag: side impact, rollover, frontal impact
- PRE-SAFE® Impulse Side: side impact

The installation location of an air bag is identified by the AIRBAG symbol ( $\rightarrow$  page 57).

Observe the information on the function of the restraint system ( $\rightarrow$  page 52).

### Information on how the restraint system works

How the restraint system functions depends on the severity of the impact detected and the apparent type of accident.

For more information about types of accidents, see "Overview of deployment situations" ( $\rightarrow$  page 51).

The activation thresholds for the components of the restraint system are determined based on the evaluation of the sensor values measured at various points in the vehicle. This process is pre-emptive in nature. The triggering/deployment of the components of the restraint system must take place in good time at the start of the collision.

Factors that can be seen and measured only after a collision has occurred cannot play a decisive role in air bag deployment. Nor do they provide an indication of air bag deployment.

The vehicle may be deformed significantly without an air bag being deployed. This is the case if only parts which are relatively easily deformed are affected and the rate of vehicle deceleration is not high. Conversely, an air bag may be deployed even though the vehicle suffers only minor defor-

mation. If very rigid vehicle parts such as longitudinal members are hit, this may result in sufficiently high levels of vehicle deceleration.

Depending on the apparent type of accident and the detected deployment situation, Emergency Tensioning Devices and/or air bags can supplement the protection offered by a correctly worn seat belt.

When enabled, an air bag can provide additional protection for the respective vehicle occupant.

Potential protection provided by each air bag:

- Knee air bag: thigh, knee and lower leg
- Driver's air bag, front passenger air bag: head and ribcage
- · Window air bag: head
- Side air bag: ribcage, also pelvis for front seat occupants

However, no system available today can completely eliminate injuries and fatalities in every accident situation. In particular, the seat belt and air bag generally do not protect against objects penetrating the vehicle from the outside. It is also

not possible to completely rule out the risk of injury caused by the air bag deploying.

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop after an accident. Take this into account, particularly if an Emergency Tensioning Device is triggered or an air bag deployed.

If the Emergency Tensioning Devices are triggered or an air bag is deployed, you will hear a bang, and a small amount of powder may also be released:

- · The bang will not generally affect your hearing.
- In general, the powder released is not hazardous to health but may cause short-term breathing difficulties to persons suffering from asthma or other pulmonary conditions.

Provided it is safe to do so, leave the vehicle immediately or open the window in order to prevent breathing difficulties.

Air bags and pyrotechnic Emergency Tensioning Devices contain perchlorate material, which may require special handling or environmental protection measures. National guidelines regarding waste disposal must be observed. In California, see the https://dtsc.ca.gov/. Using the search function, you will find information on perchlorate, for example.

## Information on the limited protection provided by the restraint system

## Risk due to the incorrect behavior of vehicle occupants

All vehicle occupants must make sure of the following in particular:

- They observe the information on the correct seat position (→ page 41).
- There are no heavy, sharp-edged or fragile objects in the pockets of their clothing. Store such objects in a suitable place.

**WARNING** Risk of injury or death due to an incorrect seat position

The seat belt does not offer the intended level of protection if you have not moved the seat backrest to an almost vertical position.

In particular, you could slip beneath the seatbelt and become injured.

- Adjust the seat properly before beginning your journey.
- Always ensure that the seat backrest is in an almost vertical position and that the shoulder belt is routed across the center of your shoulder.

### Risk due to objects in the vehicle interior

All vehicle occupants must make sure of the following in particular:

- They observe the information on the correct seat position (→ page 41).
- There are no objects between the seat, door and door pillar (B-pillar).
- There are no hard objects, e.g. coat hangers, hanging on the grab handles or coat hooks.
- There are no heavy, sharp-edged or fragile objects in the pockets of their clothing. Store such objects in a suitable place.

WARNING Risk of injury or death due to blocked seat belt buckle or seat belt anchorage

Objects next to the front seat that block the seat belt buckle or the moving seat belt anchorage on the front seat impair the function of the Emergency Tensioning Devices.

 Before starting the journey, make sure that there are no objects around the seat belt buckle or between the front seat and door.

**WARNING** Risk of injury from objects in the deployment area of an airbag

Objects in the deployment area of an airbag can hinder or prevent the correct deployment of the airbag.

The airbag may then deploy in an uncontrolled manner and may even cause additional injuries to the vehicle occupants by deploying. This may be the case in particular if the airbag is integrated into the seat.

- Always stow and secure objects correctly.
- Before commencing your journey, make sure that no objects are stowed in the deployment area of an airbag.

The installation location of an air bag is identified by the AIRBAG ( $\rightarrow$  page 57) symbol.

### Risk due to installing accessories

Do not attach accessories such as mobile navigation devices, mobile phones or cup holders within the deployment area of an air bag, e.g. on the cockpit, on the door, on the side window or on the side trim.

In addition, no connecting cables, tensioning straps or retaining straps may be routed or attached to the vehicle within the deployment area of an air bag. Always comply with the accessory manufacturer's installation instructions and, in particular, the notes on suitable places for installation.

### A

**WARNING** Risk of injury or death due to unsuitable protective covers

Unsuitable protective covers mean that air bags can no longer protect vehicle occupants as they are designed to do.

Use only protective covers approved by Mercedes-Benz for the seat in question.

In addition, the function of the automatic passenger air bag deactivation may be restricted by an unsuitable protective cover. If the front passenger seat is occupied, ensure that the PASSENGER AIR BAG indicator lamps display the correct status of the front passenger air bag ( $\rightarrow$  page 45).

### Risk due to pets in the vehicle interior



**WARNING** Risk of accident and injury due to animals left unsecured or unattended in the vehicle

If you leave animals in the vehicle unattended or unsecured, they could possibly press buttons or switches.

#### An animal may:

- Activate vehicle equipment and become trapped, for example
- Switch systems on or off and endanger other road users

Unsecured animals may be thrown around in the vehicle in the event of an accident or sudden steering and braking maneuvers and injure vehicle occupants in the process.

- Never leave animals in the vehicle unattended.
- Always correctly secure animals while driving, e.g. using a suitable animal carrier.

# Risk due to modification, damage or wear to the components of the restraint system



**WARNING** Risk of injury or death due to modifications to the restraint system

Vehicle occupants may no longer be protected as intended if alterations are made to the restraint system.

- Never alter the parts of the restraint system.
- Never tamper with the wiring or any electronic component parts or their software.

If it is necessary to modify the vehicle to accommodate a person with disabilities, contact an authorized Mercedes-Benz Center for details.

USA only: for details, contact our Customer Assistance Center on 1-800-FOR-MERCedes (1-800-367-6372).

**WARNING** Risk of injury or death due to damaged or modified seat belts

Seat belts cannot provide protection in the following situations:

- The seat belt is damaged, has been modified, is extremely dirty, bleached or dyed
- The seat belt buckle is damaged or extremely dirty

 Modifications have been made to the Emergency Tensioning Device, seat belt anchorage or seat belt retractor

Seat belts may sustain non-visible damage in an accident, e.g. due to glass splinters.

Modified or damaged seat belts could tear or fail in the event of an accident, for example.

Modified Emergency Tensioning Devices could accidentally trigger or fail to function as intended.

- Never modify the seat belt system, for example the seat belt, seat belt buckle, Emergency Tensioning Device, seat belt anchorage and seat belt retractor.
- Make sure that the seat belts are undamaged, not worn and clean.
- Always have the seat belts checked immediately after an accident at a qualified specialist workshop.

Use only seat belts that have been approved for your vehicle by Mercedes-Benz.

**WARNING** Risk of injury due to modifications to the cover of an airbag

If you change the cover of an airbag or attach objects, e.g. even stickers, to it, the airbag may no longer function as intended.

- Never modify the cover of an airbag.
- ▶ Do not attach any objects to the cover.

The installation location of an air bag is identified by the AIRBAG symbol ( $\rightarrow$  page 57).

**WARNING** Risk of injury due to malfunctioning sensors in the door

The function of the airbags can be impaired due to modifications or incorrect work performed on the doors or door trim, or if the doors are damaged.

- Never modify the doors or parts of the doors.
- Always have work on the doors or door trim carried out at a qualified specialist workshop.

#### 56 Occupant safety

## Risk due to components of the restraint system that have already been deployed

Mercedes-Benz recommends that you have the vehicle towed to a qualified specialist workshop after an accident.

▲ WA

**WARNING** Risk of burns from hot air bag components

The air bag parts are hot after an air bag has been deployed.

- Do not touch the air bag parts.
- Have a deployed air bag replaced at a qualified specialist workshop as soon as possible.



**WARNING** Risk of injury due to deployed airbag

A deployed airbag no longer offers any protection.

Have the vehicle towed to a qualified specialist workshop in order to have the deployed airbag replaced. Have deployed air bags replaced immediately.



**WARNING** Risk of injury or death from deployed pyrotechnic Emergency Tensioning Devices

Pyrotechnic Emergency Tensioning Devices that have been deployed are no longer operational and are unable to perform their intended protective function.

Therefore, have deployed pyrotechnic Emergency Tensioning Devices immediately replaced at a qualified specialist workshop.

#### Seat belts

### Releasing seat belts


Press the release button in the seat belt buckle and guide the seat belt back with the seat belt tongue. NOTE Damage caused by trapping the seat belt

If an unused seat belt is not fully retracted, it may become trapped in the door or in the seat mechanism.

Always ensure that an unused seat belt is fully retracted.

### Airbags

### Overview of air bags




- 1 Knee air bag
- ② Driver's air bag
- Front passenger air bag
- Window curtain air bag
- Side impact air bag

The installation location of an air bag is identified by the AIRBAG symbol. An additional arrow symbol ▶ indicates the installation location for certain air bags.

Observe the information under "Overview of deployment situations" ( $\rightarrow$  page 51).

# Brief overview of most important points Safely transporting children in the vehicle



Always observe the following when transporting children:

• Do not leave children unsupervised in the vehicle (→ page 60).

- Secure children up to a height of 5 ft (1.50 m) on the respective seat (see illustration above) properly with a suitable and approved child restraint system, and secure small children in a rearward-facing child restraint system.
- Observe the child restraint system manufacturer's installation instructions.

### Left/right rear seat (preferred seats)

Preferred securing system:

LATCH-type (ISOFIX) securing ring

and

Also secure Top Tether if present (→ page 68).

Alternative securing system:

ž

Vehicle seat belt ( $\rightarrow$  page 70)



Additionally attach Top Tether if recommended by the manufacturer of the child restraint system ( $\rightarrow$  page 68).

### Front passenger seat

Securing system:

 $\checkmark$  Vehicle seat belt ( $\rightarrow$  page 70)

Be sure to observe:

 If the front passenger seat is occupied, ensure that the status of the front passenger air bag is correct for the current situation (→ page 45).

#### Center rear seat

Securing system:

\* V

Vehicle seat belt ( $\rightarrow$  page 70)



Additionally attach Top Tether if recommended by the manufacturer of the child restraint system ( $\rightarrow$  page 68).

### Important safety notes

Basic information

### Be diligent

Bear in mind that negligence when securing a child in the child restraint system may have seri-

ous consequences. Always be diligent in securing a child carefully before every journey.

Never allow babies and children to travel sitting on the lap of another vehicle occupant.

To improve protection for children younger than twelve years old or under 5 ft (1.50 m) in height, Mercedes-Benz recommends you observe the following information:

- Always secure a child in a child restraint system suitable for your Mercedes-Benz vehicle.
- The child restraint system must be appropriate to the age, weight and size of the child.
- The vehicle seat must be suitable for the child restraint system to be installed:

Accident statistics show that children secured on the rear seats are generally safer than children secured on the front seats. For this reason, Mercedes-Benz strongly advises that you install a child restraint system on a rear seat.

### The generic term child restraint system

The generic term child restraint system is used in this Operator's Manual. A child restraint system is, for example:

- · a baby car seat
- · a rearward-facing child seat
- · a forward-facing child seat
- a child booster seat Mercedes-Benz recommends using a child booster seat with a backrest and seat belt guides.

### Observe laws and legal requirements

Always observe the legal requirements when using a child restraint system in the vehicle.

## Securing systems for child restraint systems in the vehicle

Only use the following securing systems for child restraint systems:

- the LATCH-type (ISOFIX) securing rings
- · the vehicle's seat belt system
- · the Top Tether anchorages

Simply attaching to the LATCH-type (ISOFIX) securing rings in the vehicle can reduce the risk of installing the child restraint system incorrectly.

When securing a child with the integrated seat belt of the ISOFIX/LATCH child restraint system, always comply with the permissible gross weight for the child and child restraint system ( $\rightarrow$  page 67).

A child booster seat may be necessary to achieve proper seat belt positioning for children over 40 lbs (18 kg) in weight or until they reach a height where a three-point seat belt can be installed properly without a child booster seat.

Mercedes-Benz recommends a suitable child booster seat with a backrest and seat belt guides.

### Observe standards for child restraint systems

All child restraint systems must meet the following standards:

- U.S. Federal Motor Vehicle Safety Standards 213
- Canadian Motor Vehicle Safety Standards 213

Confirmation that the child restraint system complies with the standards can be found on an instruction label on the child restraint system. This confirmation can also be found in the installation instructions that are included with the child restraint system.

### Important warning notices

### Always secure a child restraint system correctly

WARNING Risk of injury or death due to incorrect installation of the child restraint system

The child can then not be protected or restrained as intended.

- Be sure to comply with the manufacturer's installation instructions for the child restraint system and its correct use.
- Make sure that the entire base of the child restraint system always rests on the sitting surface of the seat.

- Never place objects (e.g. cushions) under or behind the child restraint system.
- Use child restraint systems only with the original cover designed for them.
- Always replace damaged covers with genuine covers.
- Always observe the vehicle-specific information.
  - Installing the ISOFIX child restraint system on the right and left rear seats (→ page 67).
  - Securing the child restraint system with the seat belt (→ page 70).
- Observe the warning labels in the vehicle interior and on the child restraint system.

▲ WARNING Risk of injury or death due to unsecured child restraint systems in the vehicle

If the child restraint system is incorrectly mounted or unsecured, it may come loose.

The child can then not be protected or restrained as intended.

Unused child restraint systems could be flung around and hit vehicle occupants.

- Always comply with the manufacturer's installation instructions for the child restraint system and its correct use.
- Always fit child restraint systems correctly, even if they are transported in the vehicle unused.

### Do not modify the child restraint system

**WARNING** Risk of injury due to modifications to the child restraint system

The child restraint system can no longer function properly. This poses an increased risk of injury.

- Never modify a child restraint system.
- Only affix accessories which have been specially approved for this child restraint system by the child restraint system's manufacturer.

### Use only child restraint systems that are in proper working condition



WARNING Risk of injury or death caused by the use of damaged child restraint systems

Child restraint systems or their retaining systems that have been subjected to stress in an accident may not be able to perform their intended protective function.

It may be the case that the child cannot be properly restrained.

- Always immediately replace child restraint systems that have been damaged or involved in an accident.
- Have the securing systems for the child restraint systems checked at a qualified specialist workshop before installing a child restraint system again.

### Avoid direct sunlight



WARNING Risk of burns when the child seat is exposed to direct sunlight

If the child restraint system is exposed to direct sunlight or heat, parts could heat up excessively.

Children could suffer burns from these parts, particularly the metallic parts of the child restraint system.

- Always make sure that the child restraint system is not exposed to direct sunlight.
- Cover the child restraint system with a blanket, for example.
- If the child restraint system has been exposed to direct sunlight, allow it to cool before securing a child into it.
- Never leave children unattended in the vehicle.

### Observe when stopping or parking



WARNING Risk of fatal injury due to exposure to extreme heat or cold in the vehicle

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold. there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.



WARNING Risk of accident and injury if children are left unattended in the vehicle

If children are left unattended in the vehicle, they could in particular:

- · open doors, thereby endangering other persons or road users.
- · get out and be struck by oncoming traffic.
- · operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion, for example by:

- · releasing the parking brake.
- · changing gear.
- starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the SmartKev with you and lock the vehicle.
- Keep the SmartKey out of the reach of children.

### Notes on rearward-facing and forward-facing child restraint systems on the front passenger seat

WARNING Risk of injury or fatal injury when using a rearward-facing child restraint system while the co-driver airbag is enabled

If you secure a child in a rearward-facing child restraint system on the co-driver seat and the

PASSENGER AIR BAG OFF indicator lamp is off, the co-driver airbag can deploy in the event of an accident.

The child could be struck by the airbag.

- Always ensure that the co-driver airbag is disabled. The PASSENGER AIR BAG OFF indicator lamp must be lit.
- NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIRBAG: DEATH or SERI-OUS INJURY to the CHILD can occur.

Observe the specific instructions for the rearward-facing and forward-facing child restraint systems ( $\rightarrow$  page 64).

If it is absolutely necessary to install a child restraint system on the front passenger seat, always observe the following notes:

 When using a rearward-facing child restraint system on the front passenger seat, the front passenger air bag must always be disabled. This is only the case if the PASSENGER AIR BAG OFF indicator lamp is lit continuously  $(\rightarrow page 45)$ .

• The front passenger air bag is enabled when the PASSENGER AIR BAG OFF indicator lamp is not lit. The front passenger air bag may be deployed during an accident. In that case, do not use rearward-facing child restraint systems

### Information on automatic front passenger air bag shutoff

If the front passenger seat is occupied, ensure, both before and during the journey, that the status of the front passenger air bag is correct for the current situation.

WARNING Risk of injury or death due to objects between the seat surface and the child restraint system

Objects between the seat surface and the child restraint system can interfere with the function of the automatic front passenger air bag shutoff.

- Do not place any objects between the seat surface and the child restraint system.
- Make sure that the entire base of the child restraint system rests on the seat cushion of the front passenger seat.
- The backrest of a forward-facing child restraint system must, as far as possible, be resting against the seat backrest of the front passenger seat.
- Always comply with the installation instructions from the child restraint system manufacturer.

When installing a child restraint system on the front passenger seat, observe the vehicle-specific information ( $\rightarrow$  page 62).

## Rearward-facing child restraint system on the front passenger seat

If a rearward-facing child restraint system is installed on the front passenger seat, the front passenger air bag must be disabled. The PASSENGER AIR BAG OFF indicator lamp must be continuously lit ( $\rightarrow$  page 45).

WARNING Risk of injury or fatal injury when using a rearward-facing child restraint system while the co-driver airbag is enabled

If you secure a child in a rearward-facing child restraint system on the co-driver seat and the PASSENGER AIR BAG OFF indicator lamp is off, the co-driver airbag can deploy in the event of an accident.

The child could be struck by the airbag.

- Always ensure that the co-driver airbag is disabled. The PASSENGER AIR BAG OFF indicator lamp must be lit.
- NEVER use a rearward-facing child restraint system on a seat with an ENA-BLED FRONT AIRBAG; DEATH or SERI-OUS INJURY to the CHILD can occur.
- (i) Depending on the child restraint system and the stature of the child, the front passenger air bag will be enabled. The PASSENGER AIR BAG OFF indicator lamp will not light up. The front passenger air bag may be deployed during an accident. If the front passenger air

bag has this status, no rearward-facing child restraint system may be installed on the front passenger seat.

Instead, install the rearward-facing child restraint system on a suitable rear seat.

## Forward-facing child restraint system on the front passenger seat

If a forward-facing child restraint system is installed on the front passenger seat, the front passenger air bag may be automatically enabled or disabled. The status of the front passenger air bag depends on the child restraint system and the stature of the child.

The PASSENGER AIR BAG OFF indicator lamp will either light up continuously or not light up ( $\rightarrow$  page 45). Always observe the following information.

WARNING Risk of injury or death due to incorrect positioning of the child restraint system

If you secure a child in a forward-facing child restraint system on the co-driver seat and you position the co-driver seat too close to the dashboard, in the event of an accident, the child could:

- come into contact with the vehicle's interior if the PASSENGER AIR BAG OFF indicator lamp is lit, for example
- be struck by the airbag if the PASSENGER AIR BAG OFF indicator lamp is off
- Always move the co-driver seat as far back as possible. In doing so, always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of the vehicle to the shoulder belt guide on the child restraint system. The shoulder belt strap must be routed forwards and downwards from the seat belt outlet.

If necessary, adjust the seat belt outlet and the co-driver seat accordingly.

 Always comply with the child restraint system manufacturer's installation instructions.

Be sure to also observe the following further related subjects:

 Function of the automatic front passenger air bag shutoff (→ page 45)

## Suitable child restraint systems for the transport of children

Information on the benefit of a rearward-facing child restraint system

Transport a baby in a suitable rearward-facing child restraint system only. It is also preferable to transport a small child in a suitable rearward-facing child restraint system. In this case, the child sits in the opposite direction to the direction of travel and faces backwards.

Babies and small children have comparatively weak neck muscles in relation to the size and weight of their head. The risk of injury to the cervical spine during an accident can be reduced in a rearward-facing child restraint system.

### Securing the child restraint system

Adjusting the seat correctly

When installing a child restraint system on the left or right rear seat, always observe the following:

Make sure that the child's feet do not touch the front seat. If necessary, move the front seat slightly forwards.

If the head restraint of the child restraint system cannot be fully extended when it is installed in the vehicle, this will result in restrictions on the maximum size setting for certain child restraint systems. Observe the child restraint system manufacturer's installation instructions.

(i) Contact with the roof when the head restraint is fully extended and locked in place will not result in any restrictions on use.

## Also observe the following when installing an ISOFIX child restraint system:

- When using a rearward-facing child restraint system on a rear seat: adjust the front seat so that it does not touch the child restraint system.
- When using a forward-facing child restraint system with integrated child seat belt: adjust the head restraint of the respective seat so that it does not push the child restraint system forwards. If necessary, the respective head restraint can be removed. In addition, the backrest of the child restraint system must lie as flat as possible against the backrest of the vehicle seat. After the child restraint system has been removed, replace the vehicle head restraint immediately and adjust it correctly.
- The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction. Where possible, adjust the seat cushion angle accordingly.

Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.

# When installing a belt-secured child restraint system, also observe the following:

- When using a rearward-facing child restraint system on a rear seat: adjust the front seat so that it does not touch the child restraint system.
- Also secure Top Tether if present (→ page 68).
  - When using a forward-facing child restraint system with integrated child seat belt: adjust the head restraint of the respective seat so that it does not push the child restraint system forwards. If necessary, the respective head restraint can be removed. In addition, the backrest of the child restraint system must lie as flat as possible against the backrest of the vehicle seat. After the child restraint system has been removed, replace the vehicle head restraint immediately and adjust it correctly.

- The backrest of the forward-facing child restraint system must, as far as possible, be resting on the seat backrest of the rear seat.
- The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction. Where possible, adjust the seat cushion angle accordingly.
- Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.
- Make sure that the child's feet do not touch the front seat. If necessary, move the front seat slightly forwards.
- A Depending on the vehicle equipment, always observe the following when installing a belt-secured child restraint system on the front passenger seat:
- Observe the notes on rearward-facing and forward-facing child restraint systems on the front passenger seat (→ page 62).
- When using a forward-facing child restraint system integrated child seat belt: remove the

head restraint from the front passenger seat. if possible. After the child restraint system has been removed, immediately replace the head restraint and adjust it correctly.

- The backrest of the forward-facing child restraint system must, as far as possible, be resting on the seat backrest of the front passenger seat.
- The child restraint system must not be put under strain between the roof and the seat cushion and/or be installed facing the wrong direction.
- Adjust the vehicle head restraints so that the child restraint system is not put under strain by the head restraint.
- Never place objects (e.g. cushions) under or behind the child restraint system.
- Set the front passenger seat as far back as possible and move the seat into the highest position if possible. Always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of the vehicle to the shoulder belt guide on the child restraint system. The shoulder belt strap must be routed for-

wards from the seat belt outlet and, where possible, downwards to the child restraint system

- Fully retract the seat cushion length adjustment.
- Adjust the seat cushion inclination so that the front edge of the seat cushion is in the highest position and the rear edge of the seat cushion is in the lowest position.
- Set the seat backrest to the most vertical position possible.

### Activating or deactivating the special seat belt retractor of the seat belt

**WARNING** Risk of injury or death if a seat belt is unfastened while the vehicle is in motion

If the seat belt is released while the vehicle is in motion, the special seat belt retractor is deactivated and the child restraint system is no longer correctly secured. The seat belt is

drawn in slightly by the inertia reel and cannot be immediately closed again.

- Stop the vehicle immediately in accordance with the traffic conditions
- Activate the special seat belt retractor again and correctly secure the child restraint system.

When enabled, the child seat safety feature ensures that the seat belts of the front passenger seat and rear seats do not slacken once the child restraint system is secured.

The seat belts on the following seats are equipped with a child seat safety feature:

- Front passenger seat
- · Rear seats

### Installing a child restraint system

When installing a child restraint system, always observe the manufacturer's installation and operating instructions as well as the information in this Operator's Manual.

- Pull the seat belt smoothly from the seat belt outlet.
- Engage the seat belt tongue in the belt buckle.

### Activating the special seat belt retractor:

- Pull the seat belt out fully and let the inertia reel retract it again.
   When the special seat belt retractor is activated, you should hear a ratcheting sound.
- Push the child restraint system down until the seat belt sits tightly.

### Deactivating the special seat belt retractor:

- Press the release button of the seat belt buckle.
- Hold the seat belt tongue and guide back to the seat belt outlet.

### Installing an ISOFIX child restraint system

A

**WARNING** Risk of accident if the rear bench seat, rear seat and seat backrest are not engaged

The rear bench seat, rear seat and seat backrest may fold forwards, even when you are driving.

- As a result, the vehicle occupant will be pushed into the seat belt with increased force. The seat belt will not be able to protect as intended and could cause additional injury.
- Objects or loads in the trunk or cargo compartment will not be restrained by the seat backrest.
- Make sure that the rear bench seat, the rear seat and the seat backrest are engaged before every trip.

If the rear seat backrest is not engaged and locked in place, the red lock verification indicator will be visible.

A

WARNING Risk of injury or death if the permissible gross mass of the child and child restraint system together is exceeded.

Too much load may be placed on the LATCHtype (ISOFIX) or iSize child restraint systems and the child may not be restrained correctly in the event of an accident, for example.

▶ If the child is secured in a LATCH-type (ISOFIX) child restraint system with integrated seat belt, the total mass of the child and child restraint system must not exceed 73 lb (33 kg).

Always observe the information on the mass of the child:


- in the installation instructions and Operator's Manual of the manufacturer of the child restraint system used
- on a label on the child restraint system, if present

Regularly check that the permissible total mass of the child and child restraint system is still being adhered to

When installing a child restraint system, also observe the following:

Always observe the area of use and the suitability of the seats for attaching a child restraint system.

ISOFIX mounting brackets



ISOFIX mounting bracket

Before every journey always ensure that the ISO-FIX child restraint system is correctly engaged in both mounting brackets on the vehicle.

- NOTE Damage to the seat belt for the center seat during installation of the child restraint system
- Make sure that the seat belt is not trapped.
- Fold the covers of the ISOFIX mounting brackets 
   back.
- Attach the ISOFIX child restraint system to both mounting brackets (1) in the vehicle.

### Fastening a Top Tether

WARNING Risk of injury or death if the rear seat backrests are not locked after Top Tether belts are installed

The rear seat backrests may fold forwards when you are driving.

As a result, child restraint systems will no longer be able to perform their intended protective function. This may also cause additional injuries.


- Always lock rear seat backrests after installing Top Tether belts.
- Observe the lock verification indicator.

If the rear seat backrest is not engaged and locked in place, the red lock verification indicator will be visible.



If the child restraint system is equipped with a Top Tether belt:

> The risk of injury may be reduced by Top Tether. The Top Tether belt enables an additional connection between the child restraint system attached with ISOFIX (left and right rear seats) or the seat belt (all rear seats) and the vehicle.





- If necessary, slide head restraint 1 upwards  $(\rightarrow page 103)$ .
- Install the ISOFIX/LATCH or belt-secured child restraint system with Top Tether. In doing so, comply with the child restraint system manufacturer's installation instructions.
- Guide Top Tether belt (5) under head restraint between the two head restraint bars.
- Guide Top Tether belt (5) downwards between cargo compartment cover (3) and seat backrest 2.
- Hook Top Tether hook 6 of Top Tether belt (5) into Top Tether anchorage (4) without twisting.
- Tension Top Tether belt (5). In doing so, comply with the child restraint system manufacturer's installation instructions.
- If necessary, slide head restraint 1 downwards ( $\rightarrow$  page 103). Make sure that you do not interfere with the correct routing of Top Tether belt 6.

### Securing the child restraint system with the seat belt



WARNING Risk of accident if the rear bench seat, rear seat and seat backrest are not engaged

The rear bench seat, rear seat and seat backrest may fold forwards, even when you are driving.

- As a result, the vehicle occupant will be pushed into the seat belt with increased force. The seat belt will not be able to protect as intended and could cause additional injury.
- Objects or loads in the trunk or cargo compartment will not be restrained by the seat backrest.
- Make sure that the rear bench seat, the rear seat and the seat backrest are engaged before every trip.

If the rear seat backrest is not engaged and locked in place, the red lock verification indicator will be visible.

The seat belts on the following seats are equipped with a special seat belt retractor:

- Front passenger seat
- Rear seats

When enabled, the special seat belt retractor ensures that the seat belts of the front passenger seat and rear seats do not slacken once the child restraint system is secured.

- For a child restraint system of the category "Universal" or "Semi-Universal" ensure that this is approved for the vehicle seat.
- Install the child restraint system. The entire base of the child restraint system must always rest on the sitting surface of the seat.
- Always make sure that the shoulder belt strap is correctly routed from the seat belt outlet of the vehicle to the shoulder belt guide on the child restraint system.

The shoulder belt strap must be routed forwards from the seat belt outlet and, where possible, downwards to the child restraint system.

- When installing on the rear seat: also secure Top Tether, if present.
- When installing on the front passenger seat: if necessary, adjust the belt sash guide and the front passenger seat appropriately.

### Child safety locks

Activating or deactivating the child safety lock for the rear doors



WARNING Risk of accident and injury if children are left unattended in the vehicle

If children are left unattended in the vehicle. they could in particular:

- open doors, thereby endangering other persons or road users.
- · get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion, for example by:

- · releasing the parking brake.
- · changing gear.
- starting the vehicle.
- Never leave children unattended in the vehicle.
- ▶ When leaving the vehicle, always take the SmartKey with you and lock the vehicle.
- Keep the SmartKey out of the reach of children.

WARNING Risk of fatal injury due to exposure to extreme heat or cold in the vehicle

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold, there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.


**A** WARNING Risk of accident and injury due to children left unattended in the vehicle

If children are traveling in the vehicle, they could, in particular:

- Open doors, thereby endangering other persons or road users.
- Get out and be struck by oncoming traffic.
- Operate vehicle equipment and become trapped, for example.
- Always activate the installed child safety locks if children are traveling in the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.

There are child safety locks for the rear doors and the rear side windows.


The child safety lock on the rear doors secures each door separately. The doors can no longer be opened from the inside.



- Press the lever in direction (1) (activate) or (2) (deactivate).
- Make sure that the child-proof locks are working properly.

#### 72 Children in the vehicle

# Activating and deactivating the child safety lock for the rear side windows



To activate/deactivate: press button ②.

The rear side window can be opened or closed in the following cases:

 Indicator lamp is off: via the switch on the corresponding rear door or driver's door

# Occupant presence reminder

# Function of the occupant presence reminder

The occupant presence reminder can help to remind you about a child who may have been forgotten in the rear passenger compartment of the vehicle. It activates and deactivates automatically when a rear door is open for an extended period of time and a child, which the system presumes to be present, could enter or exit the vehicle.

When the vehicle is switched off, the Do Not Leave People or Animals in the Vehicle message will appear on the driver's display if the system has previously activated automatically.

# Activating or deactivating the occupant presence reminder in the multimedia system

Multimedia system:

- → 🙀 >> Settings >> Vehicle
- ➤ Occupant Protection
- Activate or deactivate the function.

### SmartKey

# Overview of key functions

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle. they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- · operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- releasing the parking brake.
- changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.

- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.
- NOTE Damage to the SmartKey caused by magnetic fields
- Keep the SmartKey away from strong magnetic fields.



Vehicle key with panic alarm

- Opens/closes the tailgate
- Unlocks (with embossed surface)
- Locks

- Indicator lamp
- Panic alarm
- (i) If indicator lamp (4) does not light up after you press the a or button, the battery is weak or possibly discharged. Replace the battery as soon as possible.

Replace the key battery ( $\rightarrow$  page 75).

The key locks and unlocks the following components:

- Doors
- Fuel filler flap
- Socket flap (plug-in hybrid)
- Tailgate

If the vehicle is not opened within approximately 40 seconds after unlocking, it will lock again. Antitheft protection will be armed again.

Do not keep the key together with electronic devices or metal objects. This may affect the key's functionality.

# Activating/deactivating the acoustic locking verification signal

Multimedia system:

- → 🔝 >> Settings >> Vehicle
- ▶ Open/Close
- Activate or deactivate the Acoustic Lock.

## Activating/deactivating the panic alarm

### Requirements

· The vehicle is switched off.



- ➤ To activate: press button **(1)** for approximately one second.
  - A visual and audible alarm is triggered.
- To deactivate: briefly press button ① again.

or

Press the start/stop button.

A key belonging to the vehicle must be detected in the vehicle.

# Changing the unlocking settings

Possible unlocking functions of the key:

- Central unlocking
- · Unlocking the driver's door and fuel filler flap
- Plug-in hybrid: unlocking the driver's door and fuel filler flap/socket flap
- To switch between settings: press the and buttons simultaneously for approximately six seconds until the indicator lamp flashes twice.

Options if the unlocking function for the driver's door and fuel filler flap has been selected:

- To unlock the vehicle centrally: press the button twice.
- Vehicles with KEYLESS-GO: if you touch the inner surface of the door handle on the driver's door, only the driver's door and the fuel filler flap are unlocked.

Options if the unlocking function for the driver's door and fuel filler flap / socket flap has been selected (plug-in hybrid):

- To unlock the vehicle centrally: press the button twice.
- Vehicles with KEYLESS-GO: if you touch the inner surface of the door handle on the driver's door, only the driver's door and the fuel filler flap / socket flap are unlocked.

# Deactivating the function of the key

Vehicles with KEYLESS-GO: if you deactivate the function of the SmartKey, the KEYLESS-GO functions will also be deactivated. Access or drive

authorization by KEYLESS-GO will then no longer be possible with that particular SmartKey. Activate the function of the SmartKey so that all its functions will again be available.

You can also deactivate the function of the Smart-Key to reduce the energy consumption of the SmartKey if you do not use the vehicle or a Smart-Key for an extended period of time.

- Press and hold the A button on the Smart-Key.
- With the key button A pressed, immediately press key button 🔁 twice in quick succession

The indicator light of the key lights up once briefly and once for a long time.

- (i) The following options for re-activating the SmartKey are available:
  - Press any button on the SmartKey.
  - Start the vehicle with the SmartKev in the marked space in the center console  $(\rightarrow page 171)$ .


## Removing/inserting the mechanical key

# Removing the mechanical key



- Press release button 1. Emergency key 2 is pushed out slightly.
- Fully remove mechanical key 2.

#### Inserting the mechanical key



- Insert mechanical key 2 at marking 3 until it engages.
- (i) You can use mechanical key (2) to attach the key to a key ring.

## Replacing the key battery

**DANGER** Risk of fatal injuries due to swallowing batteries

Batteries contain toxic and corrosive substances. If batteries are swallowed or otherwise

enter the body, severe internal burns can occur within two hours.

There is a risk of fatal injury.

- Keep batteries out of the reach of children.
- If the battery compartment cover and/or lid do not close securely, stop using the key and keep it away from children.
- If batteries are swallowed or otherwise enter the body, seek immediate medical attention.

ENVIRONMENTAL NOTE Environmental damage due to improper disposal of batteries

Batteries contain pollutants. It is illegal to dispose of them with the household rubbish.

Dispose of batteries in an environmentally responsible manner. Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

#### Requirements

• You require a CR 2032 3 V cell battery.

Mercedes-Benz recommends that you have the battery replaced at a qualified specialist workshop.

Remove the emergency key ( $\rightarrow$  page 75).



Press emergency key ② into the opening in the key in the direction of the arrow until cover ① opens. When doing so, do not hold cover ① closed.





- Insert emergency key (2) into the opening and lift up covering (3) and remove it.
- Repeatedly tap the key against your palm until battery (a) falls out of the key.
- Insert the new battery with the positive pole facing upwards. Use a lint-free cloth to do so.
- Make sure that the surface of the battery is free of lint, grease and other impurities.
- Insert the front tabs of covering (3) into the housing and then press on both sides to close
- Make sure that covering (3) is completely closed.
- Insert the front tabs of cover (1) into the housing and then press until it is completely closed.
- Insert the emergency key again ( $\rightarrow$  page 75).

# Problems with the key, troubleshooting

# You can no longer lock or unlock the vehicle

Possible causes are:

- The key battery is weak or discharged.
- Check the battery using the indicator lamp  $(\rightarrow page 73)$ .
- Replace the key battery, if necessary  $(\rightarrow page 75)$ .
- Use the replacement key.
- Use the mechanical key to lock or unlock  $(\rightarrow page 80)$ .
- Have key checked at a qualified specialist workshop.

### There is interference from a powerful radio signal source

Possible causes if the function of the key is impaired:

- · high voltage power lines
- mobile phones
- electronic devices (notebooks, tablets)

- shielding due to metal objects or induction loops for electrical gate systems or automatic **barriers**
- Make sure that there is sufficient distance between the key and the potential source of interference.

### You have lost a key

- Have the key deactivated at a qualified specialist workshop.
- If necessary, have the mechanical lock replaced as well.


# Doors

# Unlocking/opening the doors from the inside



- To unlock and open a front door: pull door handle ①.
- To unlock a rear door: pull the rear door handle.
- To open a rear door: pull the rear door handle again.

# Centrally locking and unlocking the vehicle from the inside



- To unlock: press button 1.
- To lock: press button ②.
   The red indicator lamp on button ② will light up once the vehicle is locked.
- i The buttons are also on the front passenger and rear doors.

This does not lock or unlock the fuel filler flap.

**Plug-in hybrid:** the socket flap is also locked and unlocked. The socket flap can be opened even if a SmartKey is detected in the vehicle.

The vehicle will not be unlocked:

- if you have locked the vehicle using the Smart-Key
- if you have locked the vehicle using KEYLESS-GO

# Locking/unlocking the vehicle with KEYLESS-GO

### Requirements

- The key is outside the vehicle.
- The distance between the key and the vehicle does not exceed 3 ft (1 m).
- The driver's door and the door at which the door handle is used are closed.
- NOTE Vehicle damage due to unintentional opening of the tailgate
- When using an automatic car wash


- When using a high pressure cleaner
- Deactivate the function of the SmartKev in these situations

or

Make sure that the SmartKey is at a minimum distance of 10 ft (3 m) away from the vehicle.

#### Observe the information:

- on washing the vehicle in a car wash  $(\rightarrow page 377)$
- on using a power washer ( $\rightarrow$  page 379)



- To unlock the vehicle: touch the inside surface of the door handle.
- To lock the vehicle: touch the sensor surface ① or ②.
- Convenience closing: touch the recessed sensor surface (2) for a prolonged period.
- (i) Further information on convenience closing  $(\rightarrow page 90)$ .

### Problems with KEYLESS-GO, troubleshooting

## You can no longer lock or unlock the vehicle using KEYLESS-GO

Possible causes:

- The function of the SmartKey has been deactivated.
- The SmartKey battery is weak or discharged.
- Activate the function of the SmartKey  $(\rightarrow page 74)$ .
- Check the battery using the indicator lamp  $(\rightarrow page 73)$ .
- Replace the SmartKey battery, if necessary  $(\rightarrow page 75)$ .
- Use the replacement SmartKey.
- Use the emergency key to lock or unlock  $(\rightarrow page 80)$ .
- Have the vehicle and SmartKev checked at a qualified specialist workshop.

# There is interference from a powerful radio signal source

Possible causes if the function of KEYLESS-GO is impaired:

- · High voltage power lines
- · Mobile phones
- Electronic devices (notebooks, tablets)
- Shielding due to metal objects or induction loops for electrical gate systems or automatic barriers
- Make sure that there is sufficient distance between the SmartKey and the potential source of interference.

# Activating/deactivating automatic locking in the MBUX multimedia system

Multimedia system:

→ 🔝 >> Settings >> Vehicle

- ▶ Open/Close
- (i) The vehicle is locked automatically when the vehicle is switched on and the wheels are turning faster than walking pace.
- Activate or deactivate Automatic Door Lock.


In the following situations, there is a danger of being locked out when the function is activated:

- The vehicle is being towed or pushed.
- If the vehicle is being tested on a roller dynamometer.


# Locking/unlocking the vehicle with the emergency key

# Unlocking a left-hand vehicle door with the emergency key

- i If you unlock and open the driver's door with the emergency key, this triggers the anti-theft alarm system.
- i If you unlock the driver's door with the emergency key, the tailgate will not be unlocked.
- (i) Information regarding starting the vehicle with the key in the storage compartment (emergency operation mode) (→ page 171).
- $\triangleright$  Remove the emergency key ( $\rightarrow$  page 75).




Pull and hold the door handle ①.



- Insert the emergency key 2 into the lock cylinder as shown.
- ► Turn the emergency key ② counter-clockwise to position 1.
- Turn the emergency key 2 back to its starting position.
- Remove the emergency key 2 and release the door handle ①.

# Locking the doors



- Insert a suitable object, e.g. the emergency key, into opening 1 on the door lock.
- To lock the left-hand side of the vehicle: turn the emergency key counter-clockwise as far as it will go.

To lock the right-hand side of the vehicle: turn the emergency key clockwise as far as it will go.

If the locked door is closed, it can no longer be opened from the outside.

### Running boards

### Notes on running boards

Your vehicle is equipped with running boards. Observe the following instructions for using the running boards.

Keep the running boards and footwear free of dirt and step only on the studded area. This will make your footing safer.

! NOTE Damage to the vehicle body or underbody due to low ground clearance

The running boards are attached to the vehicle body via the underbody. This limits the ground clearance.

Drive over obstacles, such as curbs, particularly carefully and slowly.

### Cargo compartment

# Opening the tailgate

**DANGER** Risk of exhaust gas poisoning


Combustion engines emit poisonous exhaust gases such as carbon monoxide. Exhaust gases can enter the vehicle interior if the tailgate is open when the engine is running, especially if the vehicle is in motion.

- Always switch off the engine before opening the tailgate.
- Never drive with the tailgate open.
- NOTE Damage to the tailgate caused by obstacles above the vehicle

The tailgate swings rearwards and upwards when it is opened.

- Make sure that there is sufficient space behind and above the tailgate.
- Limit the opening angle of the tailgate (→ page 87).

- If the tailgate is unlocked, pull the tailgate handle and release it again immediately.
- Vehicles with HANDS-FREE ACCESS: Make a kicking movement with your foot below the bumper (→ page 85).



 Pull remote operating switch (1) until the tailgate opens.

or

- Press and hold the so button on the key.
- If the tailgate has stopped in an intermediate position, pull it upwards. Release it as soon as it begins to open.

If an obstacle obstructs the tailgate during the automatic opening process, blockage detection will stop the tailgate. The automatic blockage detection function is only an aid. It is not a substitute for you having to pay attention.

## Closing the tailgate

**WARNING** Risk of injury from unsecured items in the vehicle

If objects, luggage or loads are not secured or not secured sufficiently, they could slip, tip over or be thrown around and thereby hit vehicle occupants.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

Always stow objects in such a way that they cannot be thrown around. Before the journey, secure objects, luggage or loads against slipping or tipping over.

Observe the notes on loading the vehicle. **Notes on closing the tailgate:** your vehicle is equipped with automatic key recognition.

Note that the tailgate will not be locked in the following situation:

- You have locked the vehicle and closed the tailgate while a key belonging to the vehicle is inside the vehicle and is detected.
- A second key belonging to the vehicle is not detected outside the vehicle.

Automatic key recognition is only an aid and is not a substitute for your attentiveness.

- Before locking, ensure that at least one key belonging to the vehicle is outside the vehicle.
- To close the tailgate: pull the tailgate downwards slightly. Release it as soon as it begins to close.

**WARNING** Risk of becoming trapped during automatic closing of the tailgate


Parts of the body could become trapped. There may be people in the closing area.

Make sure that nobody is in the vicinity of the closing area during the closing process.


Use one of the following options to stop the closing process:

- Press the ্ব্র্যা button on the SmartKey.
- Press or pull the remote operating switch on the driver's door.
- Press the closing or locking button on the tailgate.
- · Pull the tailgate handle.

**Vehicles with HANDS-FREE ACCESS:** it is also possible to stop the closing process by making a kicking movement below the rear bumper.



- Switch on the power supply or the vehicle.
- Push remote operating switch ① until the tailgate is fully closed.



Press closing button ① on the tailgate.

### Vehicles with KEYLESS-GO

- Press locking button ② on the tailgate. If a key is detected outside the vehicle, the tailgate will close and the vehicle will be locked.
- Press and hold the ্রিয় button on the key.

  The key must be in the vicinity of the vehicle.

#### Vehicles with HANDS-FREE ACCESS

Make a kicking movement with your foot below the bumper (→ page 85).

# Automatic reversing function for the tailgate

The tailgate is equipped with automatic blockage detection with a reversing function. If an obstacle obstructs the tailgate during the automatic closing process, it will automatically open again slightly. Automatic blockage detection with the reversing function is only an aid and is not a substitute for your attentiveness.

During the closing process, make sure that no body parts are in the closing area.

# **WARNING** Risk of becoming trapped despite reversing function

The reversing function will not react:

- To soft, light and thin objects, e.g. fingers.
- Towards the end of the closing procedure.


In these situations in particular, the reversing function cannot prevent someone being trapped.

Make sure that no body parts are in the closing area.

If someone is trapped, either:

- Press the 🐒 button on the SmartKey.
- Press or pull the remote operating switch on the driver's door.
- Press the closing or locking button on the tailgate.
- Pull the tailgate handle.

#### HANDS-FREE ACCESS function



HANDS-FREE ACCESS allows you to open and close the tailgate, or even stop the opening and closing process at any point, by performing a kicking motion under the rear bumper. The transmission must be in position **P** for this function.

The kicking motion triggers the opening or closing process alternately.

- If you stop the tailgate opening process with a kicking motion, the tailgate is closed with the next kicking motion
- If you stop the tailgate closing process with a kicking motion, the tailgate is opened with the next kicking motion

In the following cases, the tailgate can be closed only with HANDS-FREE ACCESS:

- If the vehicle is switched on and the kev's unlock function has been set so that only the driver's door is unlocked when activated  $(\rightarrow page 74)$ .
- If the vehicle has been centrally locked from the inside ( $\rightarrow$  page 78).

Observe the notes when opening ( $\rightarrow$  page 82) and closing ( $\rightarrow$  page 83) the tailgate.

(i) Two warning tones sound when the tailgate is opening or closing.

# **WARNING** Risk of burns caused by a hot exhaust system

The vehicle exhaust system can become very hot. If you use HANDS-FREE ACCESS, you could burn yourself by touching the exhaust system.

Always ensure that you only make a kicking movement within the detection range of the sensors.


- I NOTE Vehicle damage due to unintentional opening of the tailgate or a door
- When using an automatic car wash
- When using a high pressure cleaner
- Deactivate the function of the SmartKey in these situations.

or

Make sure that the SmartKey is at a minimum distance of 10 ft (3 m) (power washer) or 20 ft (6 m) (automatic car wash) away from the vehicle. Ensure that you are standing firmly on the ground when performing the kicking motion. You could otherwise lose your balance, e.g. on ice.

Observe the following notes:

- The key is behind the vehicle.
   If the key is not recognized:
  - Take the key in your hand. or
  - Ensure that the function of the key is activated (→ page 74).
- Stand at least 12 in (30 cm) away from the vehicle when performing the kicking motion.
- Do not come into contact with the bumper when performing the kicking motion.
- Do not carry out the kicking motion too slowly.
- The kicking motion must be towards the vehicle and back again.
- Vehicles with trailer hitch: Perform the kicking motion to the left or right of the ball head.



Detection range of the sensors

If several consecutive kicking motions are not successful, wait ten seconds.

### System limits

The system may be impaired or inoperative in the following cases:

- The sensors are dirty, e.g. due to road salt or snow.
- The kicking motion is made using a prosthetic leg.

The tailgate can open or close unintentionally in the following situations:

- · A person's arms or legs are moving in the sensor detection range, e.g. when polishing the vehicle or picking up objects.
- · Objects are moved or placed behind the vehicle, e.g. the hose of a fuel dispenser, a charging cable or luggage
- Tension belts, tarps or other covers are pulled over the bumper.
- A protective mat with a length reaching over the loading sill down into the detection range of the sensors is used
- The protective mat is not secured correctly.
- Vehicles with trailer hitch: Work is being carried out on the trailer hitch, trailers or rear bicycle racks.

Deactivate the function of the key ( $\rightarrow$  page 74) or do not carry the key about your person in such situations.

## Limiting the opening angle of the tailgate

### Activating the opening angle limiter

You can limit the opening angle of the tailgate in the top half of its opening range up to a point shortly before the end position.

- > Stop the opening procedure of the tailgate at the desired position.
- Press and hold the closing button on the tailgate until you hear a short tone. The opening angle limiter will be activated. The tailgate will then stop in the stored position when opened.

# Fully opening the tailgate after it has stopped automatically

Pull the handle on the outside of the tailgate again.


# Deactivating the opening angle limiter

Press and hold the closing button on the tailgate until two short tones sound.

# Unlocking the tailgate with the emergency key

### Requirements:

- The rear seat backrest has been folded forward
- The cargo compartment cover has been removed.



Remove the emergency key ( $\rightarrow$  page 75).

Insert emergency key ② into opening ① in the trim and push it in the direction of the arrow.

The tailgate will be unlocked.

### Side windows

# Opening and closing the side windows

**WARNING** Risk of entrapment when opening a side window

When opening a side window, parts of the body could be drawn in or become trapped between the side window and window frame.

- When opening, make sure that nobody is touching the side window.
- If someone is trapped, release the button immediately or pull it in order to close the side window again.

**WARNING** Risk of becoming trapped when closing a side window

When closing a side window, body parts could be trapped in the closing area in the process.

- When closing, make sure that no body parts are in the closing area.
- If someone is trapped, release the button immediately or press the button in order to reopen the side window.


**WARNING** Risk of becoming trapped when children operate the side windows

Children could become trapped if they operate the side windows, particularly when unattended.

- Activate the child safety lock for the rear passenger compartment side windows.
- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.
- Never leave children unattended in the vehicle.

### Requirements:

The power supply or the vehicle has been switched on.



- Closing
- Opening

The buttons on the driver's door take precedence.

- ➤ To start automatic operation: press the ☐ button beyond the pressure point or pull and release it.
- To interrupt automatic operation: press or pull the 🔳 button again.

When the vehicle is switched off, you can continue to operate the side windows.

This function is available for around four minutes or until a front door is opened.

Automatic reversing function of the side windows If an obstacle impedes a side window during the closing process, the side window will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

During the closing process, make sure that no body parts are in the closing area.

▲ WARNING Risk of becoming trapped despite there being reversing protection on the side window

The reversing function does not react:

- To soft, light and thin objects, e.g. fingers.
- · During resetting.

The reversing function cannot prevent someone from becoming trapped in these situations.

- During the closing process, make sure that no body parts are in the closing area.
- If someone becomes trapped, press the abutton to open the side window again.

# Convenience opening (ventilating the vehicle before starting a journey)

A

**WARNING** Risk of entrapment when opening a side window

When opening a side window, parts of the body could be drawn in or become trapped between the side window and window frame.

- When opening, make sure that nobody is touching the side window.
- Release the button immediately if somebody becomes trapped.

#### Requirements

- The SmartKey is in the immediate vicinity of the vehicle.
- Press and hold the button on the Smart-Key.

The following functions will be performed:

- · The vehicle will be unlocked.
- · The side windows will be opened.

- The panoramic sliding sunroof will be opened.
- The driver's seat ventilation will be switched on
- i If the roller sunblind of the panoramic sliding sunroof is closed, the roller sunblind will be opened first.
- To interrupt convenience opening: release the ਰੂਹ button.
- ► To continue convenience opening: press and hold the ਰਿਹੀ button again.

# Convenience closing (closing the vehicle from outside)

WARNING Risk of entrapment due to not paying attention during convenience closing

When the convenience closing feature is operating, parts of the body could become trapped in the closing area of the side window and the sliding sunroof.

When the convenience closing feature is operating, monitor the entire closing process and make sure that no body parts are in the closing area.

### Requirements

- The SmartKey is in the immediate vicinity of the vehicle.
- Press and hold the button on the Smart-Key.

The following functions will be performed:

- · The vehicle will be locked.
- The side windows will be closed.
- The panoramic sliding sunroof will be closed.
- To interrupt convenience closing: release the button.
- (i) Convenience closing also functions with KEY-LESS-GO (→ page 78).

### Resolving problems with the side windows

A

WARNING Risk of becoming trapped or fatally injured if reversing protection is not activated

If you close a side window again immediately after it has been blocked, the side window will close with increased or maximum force. The reversing function is then not active and body parts may become trapped.

- Make sure that no parts of the body are in the closing area.
- To stop the closing process, release the button or press the button again to reopen the side window.

# A side window cannot be closed and you cannot see the cause.

- Check to see whether any objects are in the window guide.
- Adjust the side windows.

## Adjusting the side windows

If a side window is obstructed during closing and reopens again immediately:

Immediately after this, pull and hold the corresponding button again until the side window has closed and hold the button for at least one more second (re-adjustment).

The side window will be closed without the automatic reversing function.

If the side window is obstructed again and reopens again immediately:

Immediately after this, pull and hold the corresponding button again until the side window has closed and hold the button for at least one more second (follow-up adjustment). The side window will be closed without the automatic reversing function.

The side windows cannot be opened or closed using the convenience opening feature.

Possible causes are:

- The key battery is weak or discharged.
- Check the battery using the indicator lamp  $(\rightarrow page 73)$ .

Replace the key battery, if necessary  $(\rightarrow page 75)$ .

### Sliding sunroof

# Opening and closing the sliding sunroof

- The term "sliding sunroof" refers to the panorama roof with power tilt/sliding panel.
  - WARNING Risk of becoming trapped when the sliding sunroof is being opened and closed

Body parts may become trapped in the range of movement.

- During the opening and closing process, make sure that no body parts are in the sweep of the sliding sunroof.
- If someone is trapped, release the control panel immediately.

or

Touch the control panel during automatic operation.

The opening/closing process will be stopped.

WARNING Risk of becoming trapped if the sliding sunroof is operated by children

Children operating the sliding sunroof could get caught in the moving parts, particularly if unattended.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- WARNING Risk of becoming trapped when the roller sunblind is being opened and closed

Body parts may become trapped between the roller sunblind and frame or sliding roof.

- During the opening or closing process, make sure that no body parts are in the roller sunblind's range of movement.
- If someone is trapped, release the control panel immediately.

or

- Touch the control panel during automatic operation.
   The opening/closing process will be stopped.
- I NOTE Malfunction due to snow and ice

Snow and ice may cause the sliding sunroof to malfunction.


- Open the sliding sunroof only if it is free of snow and ice.
- NOTE Damage caused by protruding objects

Objects that protrude from the sliding sunroof may damage the seals.

- Do not allow anything to protrude from the sliding sunroof.
- NOTE Damage to panorama roof with power tilt/sliding panel caused by roof luggage rack

If the panorama roof with power tilt/sliding panel is opened when a roof luggage rack is installed, the panorama roof with power tilt/sliding panel may be damaged by the roof luggage rack.

Do not open the panorama roof with power tilt/sliding panel if a roof luggage rack is installed.



The sliding sunroof and the roller sunblind are operated using control panel ①.

The panorama roof with power tilt/sliding panel can be operated only when the roller sunblind is open.

To open: swipe backwards across control panel 1 and hold it.

- To close: swipe forwards across control panel and hold it.
- To raise or lower: press control panel 1 briefly.
- To start automatic operation: swipe forwards or backwards across control panel 1
- To cancel automatic operation: press control panel 
   again.

The opening/closing process will be stopped.

## Automatic reversing function of the sliding sunroof

If an obstacle obstructs the sliding sunroof during the closing process, the sliding sunroof will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

During the closing process, make sure that no body parts are in the closing area.

# **WARNING** Risk of becoming trapped despite reversing function

The reversing function will not react:

- To soft, light and thin objects, e.g. fingers.
- Towards the end of the closing procedure.
- During resetting.
- During the closing process, make sure that no body parts are in the closing area.
- If someone is trapped, release the control panel immediately.

or

Touch the control panel during automatic closing.

The closing process will be stopped.

# Automatic reversing function of the roller sunblind If an obstacle obstructs the roller sunblind during

the closing process, the roller sunblind will open again automatically. The automatic reversing function is only an aid and is not a substitute for your attentiveness.

When closing the roller sunblind, make sure that no body parts are in the range of movement.

**WARNING** Risk of becoming trapped despite reversing function

In particular, the reversing function does not react to soft, light and thin objects, e.g. fingers.

- When closing the roller sunblind, make sure that no body parts are in the range of movement.
- If someone is trapped, release the control panel immediately.

or

Touch the control panel during automatic closing.

The closing process will be stopped.

# Automatic functions of the sliding sunroof

(i) The term "sliding sunroof" refers to the panorama roof with power tilt/sliding panel.

Automatic lowering function Vehicles with a panorama roof with power tilt/ sliding panel: if the sliding sunroof is raised at the rear, it will automatically be lowered slightly at higher speeds. At low speeds, it will be raised again automatically.

**▲** ∨

**WARNING** Risk of becoming trapped by automatic lowering of the sliding sunroof

At higher speeds, the raised sliding sunroof will automatically be lowered slightly at the rear.

- Make sure that nobody reaches into the sliding sunroof's range of movement while the vehicle is in motion.
- If someone becomes trapped, touch the control panel.

# Rectifying problems with the sliding sunroof



**WARNING** Risk of becoming trapped or fatal injuries when the sliding sunroof is closed again

If you close the sliding sunroof again immediately after it has been blocked or reset, the sliding sunroof will close with increased or maximum force.

There is a risk of becoming trapped or even of fatal injuries!

- Make sure that no parts of the body are in the closing area.
- If someone is trapped, release the control panel immediately.

or

Touch the control panel during automatic closing.

The closing process will be stopped.

# The sliding sunroof cannot be closed and you cannot see the cause.

(i) The term "sliding sunroof" refers to the panorama roof with power tilt/sliding panel.

If the sliding sunroof is obstructed during closing and reopens again slightly:

- Immediately after automatic reversing, swipe forwards across the control panel
  - $(\rightarrow$  page 91) and hold it until the sliding sunroof is closed.

The sliding sunroof will be closed with increased force.

If the sliding sunroof is obstructed again and opens again slightly:

Repeat the previous step. The sliding sunroof will be closed again with increased force.

# The sliding sunroof or the roller sunblind is not operating smoothly.

Reset the sliding sunroof and the roller sunblind.

#### Resetting the sliding sunroof and the roller sunblind

- Swipe forwards across the control panel  $(\rightarrow)$  page 91) and hold it repeatedly until the sliding sunroof is completely closed.
- Swipe across the control panel and hold it for another second.
- Swipe across and hold the control panel until the roller sunblind is fully closed.
- Swipe across the control panel and hold it for another second.
- Use automatic operation to fully open and then close the sliding sunroof.

### Anti-theft protection

#### Function of the immobilizer

The immobilizer prevents your vehicle from being started without the correct kev.

The immobilizer is automatically activated when the vehicle is switched off, and deactivated when the vehicle is switched on.

When leaving the vehicle, always take the key with you and lock the vehicle. Anyone can start the vehicle if a valid key has been left inside the vehi-

(i) In the event that the engine cannot be started (vet the vehicle's starter battery is charged). the immobilizer may be defective. Contact an authorized Mercedes-Benz Center or call 1-800-FOR-MERCedes (in the USA) or 1-800-387-0100 (in Canada).

## ATA (anti-theft alarm system)


### Function of the ATA system

If the ATA system is armed, a visual and audible alarm is triggered in the following situations:

- When a door is opened
- · When the tailgate is opened
- When the hood is opened
- When interior protection is triggered  $(\rightarrow page 96)$
- When the tow-away alarm is triggered  $(\rightarrow page 96)$

The ATA system is armed automatically after approximately ten seconds in the following situations:

- After the vehicle is locked with the key
- After the vehicle is locked using KEYLESS-GO



Indicator lamp 

flashes when the ATA system is armed.

The ATA system is deactivated automatically in the following situations:

- After the vehicle is unlocked with the key
- After the vehicle is unlocked using KEYLESS-GO
- After the start/stop button is pressed with the key in the storage compartment (→ page 171)

#### Deactivating the ATA

Press the 📆, 🔕 or 🐒 button on the key.

(

Press the start/stop button with the key in the storage compartment (→ page 171)

# Deactivating the alarm using KEYLESS-GO:

Grasp the outside door handle with the key outside the vehicle.

# Function of the tow-away alarm

This function may not be available in all countries.

An audible and visual alarm is triggered if a change in your vehicle's angle of inclination is detected while the tow-away alarm is armed.

The tow-away alarm is automatically armed after about 60 seconds:

- After the vehicle is locked with the key
- After the vehicle is locked using KEYLESS-GO

The tow-away alarm is only armed when the following components are closed:

- Doors
- Tailgate

The tow-away alarm is automatically deactivated:

- After the ্র or ্র্যা button on the key is pressed
- After the start/stop button is pressed with the key in the storage compartment (→ page 171)
- After the vehicle is unlocked using KEYLESS-GO
- · When HANDS-FREE ACCESS is used

Information on collision detection for a parked vehicle ( $\rightarrow$  page 223).

### Arming/deactivating tow-away alarm

Multimedia system:

- → 🔝 >> Settings >> Vehicle
- ▶ Opening/closing ▶ Vehicle Protection
- Arm or deactivate Tow-away Protection.

Tow-away alarm is armed again in the following cases:

- · The vehicle is unlocked again.
- A door is opened.
- · The vehicle is locked again.

### Function of interior protection

This function may not be available in all countries.

When interior protection is armed, a visual and audible alarm is triggered if movement is detected in the vehicle interior.

Interior protection is armed automatically after approximately ten seconds:

- After the vehicle is locked with the key
- After the vehicle is locked using KEYLESS-GO

Interior protection is only armed when the following components are closed:

- Doors
- Tailgate

Interior protection is automatically deactivated:

- After the 🔒 or 🐒 button on the key is pressed
- After the start/stop button is pressed with the key in the storage compartment  $(\rightarrow page 171)$
- · After the vehicle is unlocked using KEYLESS-GO
- When HANDS-FREE ACCESS is used.

The following situations can lead to a false alarm:

· When there are moving objects such as mascots in the vehicle interior

- If a side window is open
- If the panoramic sliding sunroof is open

# Arming/deactivating interior protection

Multimedia system:

- → 🙀 >> Settings >> Vehicle
- ▶ Opening/closing ▶ Vehicle Protection
- Arm or deactivate Interior Protection.

Interior protection will be armed again in the following cases:

- The vehicle is unlocked again.
- A door is opened.
- The vehicle is locked again.

### Notes on the correct driver's seat position

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint. steering wheel and mirror, and fasten your seat belt.



Ensure the following when adjusting steering wheel 1, seat belt 2 and driver's seat 3:

- You are sitting as far away from the driver's air bag as possible, taking the following points into consideration:
- You are sitting in an upright position
- Your thighs are slightly supported by the seat cushion

- Your legs are not fully extended and you can depress the pedals properly
- The back of your head is supported at eve level by the center of the head restraint
- You can hold the steering wheel with your arms slightly bent
- You can move your legs freely
- You can see all the displays on the driver display clearly
- You have a good overview of the traffic conditions
- Observe the notes on correctly fastening the seat belt ( $\rightarrow$  page 42).

# Notes on grab handles

WARNING Risk of injury due to excessive load on the grab handles

If you apply your full body weight to the grab handle or pull it abruptly, the grab handle may be damaged or come loose from its anchorage. This may result in injuries.

Use the grab handles only to stabilize the seating position or to assist in getting in and out of the seat.

#### Seats

Adjusting the front seat with manual and electric seat adjustment

**WARNING** Risk of becoming trapped if the seats are adjusted by children

Children could become trapped if they adjust the seats, particularly when unattended.

- When leaving the vehicle, always take the SmartKey with you and lock the vehicle.
- Never leave children unattended in the vehicle.

You can adjust the seats when the vehicle is switched off.

**A** WARNING Risk of becoming trapped when adjusting the seat

When you adjust a seat, you or other vehicle occupants could become trapped, e.g. on the seat guide rail.

When adjusting a seat, make sure that no one has any part of their body within the sweep of the seat.

Observe the safety notes on "Air bags" and "Children in the vehicle".

WARNING Risk of accident due to the driver's seat not being engaged

The driver's seat may move unexpectedly while driving.

This could cause you to lose control of the vehicle.

Always make sure that the driver's seat is engaged before starting the vehicle.

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- . If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- · If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint. steering wheel and mirror, and fasten your seat belt.

**WARNING** Risk of becoming trapped if the seat height is adjusted carelessly

If you adjust the seat height carelessly, you or other vehicle occupants could be trapped and thereby injured.

### 100 Seats and stowing

Children in particular could accidentally press the electrical seat adjustment buttons and become trapped.

While moving the seats, make sure that hands or other body parts do not get under the lever assembly of the seat adjustment system.

★ WARNING Risk of injury due to head restraints not being installed or being adjusted incorrectly

If head restraints have not been installed or have not been adjusted correctly, there is an increased risk of injury in the head and neck area, e.g. in the event of an accident or when braking.

- Always drive with the head restraints installed.
- Before driving off, make sure for every vehicle occupant that the center of the head restraint supports the back of the head at about eye level.

Adjust the head restraint fore-and-aft position so that it is as close as possible to the back of your head.

**WARNING** Risk of injury or death due to an incorrect seat position

The seat belt does not offer the intended level of protection if you have not moved the seat backrest to an almost vertical position.

In particular, you could slip beneath the seatbelt and become injured.

- Adjust the seat properly before beginning your journey.
- Always ensure that the seat backrest is in an almost vertical position and that the shoulder belt is routed across the center of your shoulder.

WARNING Risk of potentially fatal injuries due to objects trapped under the front passenger seat

Objects trapped under the front passenger seat may interfere with the function of the

automatic front passenger air bag shutoff or damage the system.

- Do not stow any objects under the front passenger seat.
- When the front passenger seat is occupied, ensure that no objects have become trapped beneath the front passenger seat.


! NOTE Damage to the seats when adjusting

The seats may be damaged by objects when adjusting the seats.

- When adjusting the seats, make sure that there are no objects in the footwell, under or behind the seats.
- ! NOTE Damage to the headliner when making adjustments

The headliner may be damaged when adjusting the front seats.

Adjust the head restraints first before adjusting the height of the respective seat.




- Seat backrest inclination
- Seat height
- Seat cushion inclination

- Seat cushion length
- Seat fore-and-aft position
- To adjust the seat fore-and-aft position: lift lever (5) and slide the seat into the desired position.
- Make sure that the seat is engaged.

# Adjusting the front seat fully electrically

The switches for adjusting the seats do not move. You will therefore receive no direct feedback on the switch while pressing it. Feedback is provided only by the movement of the seat.




- Head restraint height
- Seat height
- Seat cushion inclination
- Seat cushion length
- Seat fore-and-aft position
- Seat backrest inclination
- Save the settings with the memory function  $(\rightarrow page 113)$ .

### 102 Seats and stowing

(i) The head restraint height will be adjusted automatically when you adjust the seat height or the seat fore-and-aft position.

# Adjusting the 4-way lumbar support



- Higher
- Softer

- 3 Lower
- Firmer
- Use buttons (1) to (4) to adjust the contour of the backrest.

#### Head restraints

Adjusting the head restraints on the front seats

**WARNING** Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:

- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint,

steering wheel and mirror, and fasten your seat belt.


**WARNING** Risk of injury due to incorrectly adjusted head restraints

If head restraints have not been adjusted correctly, there is an increased risk of injury in the head and neck area, e.g. in the event of an accident or sudden braking.

Before driving off, make sure for every vehicle occupant that the center of the head restraint supports the back of the head at about eye level.

Adjust the head restraint fore-and-aft position so that it is as close as possible to the back of your head.

### Seats with manual and electric seat adjustment



- Take hold of the head restraint on both sides and press release knob (1).
- To move forwards or backwards: pull the head restraint forwards or push it backwards.
- To move upwards or downwards: push the head restraint upwards or downwards.
- Let go of release knob 1.


### Seats with electric seat adjustment



- Take hold of the head restraint on both sides. and press release knob (1).
- To move forwards or backwards: pull the head restraint forwards or push it backwards.
- Let go of release knob 1.
- To move upwards or downwards: adjust the head restraint using the buttons on the door operating unit ( $\rightarrow$  page 101).

# Adjusting the head restraints of the rear seats manually

(i) Move all head restraints up at least to the first detent, even in the steeper seating position (cargo position) ( $\rightarrow$  page 121). If a head restraint is in the lowest, non-locked position, the respective seat must not be used.




#### 104 Seats and stowing

- ➤ To raise: push release knob 
   in the direction of the arrow and pull the head restraint up until it engages.
- ➤ To lower: press release knob in the direction of the arrow and push the head restraint down until it engages.

# Installing/removing the rear seat head restraints

### Removing



Release the rear seat backrest and fold it forwards slightly (→ page 118).

- Press release knob ② and pull the head restraint upwards as far as it will go.
   Release knob ③ will extend.
- Push both release knobs (1) and (2) at the same time in the direction of the arrow and pull out the head restraint.
- Fold the rear seat backrest back until it engages.

### Installing

- Release the rear seat backrest and fold it forwards slightly (→ page 118).
- Insert the head restraint such that the notches on the bar are on the left when viewed in the direction of travel.
- Push the head restraint down until it engages.
- Fold the rear seat backrest back until it engages.

## Configuring the seat settings

Multimedia system:

→ Comfort → Seat

### Adjusting the air cushions

In the corresponding menu, adjust the air cushions for Lumbar or Side Bolsters.

### Setting the seat heating balance

- Select Heating Settings.
- Select Seat Heating Balance.
- Adjust the heat distribution for the desired seat.

# Setting automatic seat adjustment

WARNING Risk of becoming trapped during adjustment of the driver's seat after calling up a driver profile

Selecting a user profile may trigger an adjustment of the driver's seat to the position saved under the user profile. You or other vehicle occupants could be injured in the process.

Make sure that when the position of driver's seat is being adjusted using the multimedia system, no people or body parts are in the seat's range of movement.

If there is a risk of someone becoming trapped, immediately stop the adjustment process by:

a) Pressing the warning message on the central display.

or

b) Pressing a position button of the memory function or a seat adjustment switch in the driver's door. The adjustment process is stopped.

### Multimedia system:

→ 🔝 >> Comfort >> Seat >> Automatic Seat Positioning

# Manually adjusting driver's seat and steering wheel position to body size

The vehicle calculates a suitable driver's seat and steering wheel position on the basis of the driver's body size and sets this directly.

- To set the unit of measurement: select cm or ft/in.
- Set the size using the scale.
- Select Start Positioning. The driver's seat and steering wheel position is adjusted to the body size that has been set.
- (i) You can also configure these settings via the Mercedes me user account for your user profile. By synchronizing the profiles in the vehicle and the Mercedes me connect profiles. vou can carry over these settings for your vehicle. Further information about synchronizing user profiles.
- (i) If the driver's seat and steering wheel position calculated by the vehicle is not practical or comfortable, it can be manually adapted at any time via the control buttons. The outside mirrors are not set via this function. Instead, they have to be set manually via the operating switches.

# Overview of massage programs

• Classic Massage: Relaxing back massage

#### 106 Seats and stowing

- Mobilizing Massage Mobilizing massage with upward-moving relaxing waves. Can promote slower, deeper respiration. This can improve the supply of oxygen to cells and the brain.
- Activating Massage: Activating massage with upward-moving relaxing waves
- Relaxing Massage: Relaxing back massage with increasing wave motions and then soothing movements
- Deep Waves: Wave-like movements in the cushion can promote blood flow and metabolic processes in the lower back and legs
- Deep Workout: Wave-like movements in the cushion are combined with wave movements from the backrest and can stimulate blood circulation and metabolism in the lower back, buttocks and legs
- (i) The Deep Waves and Deep Workout programs are only available on the driver's seat.

## Selecting the massage program for the front seats

Multimedia system:

- → 🔝 >> Comfort
- ► Select Massage.
- Select a massage program (→ page 105).
- Start the program for the desired seat .
- To set the massage intensity: switch Intensive on or off.
- ➤ To stop the massage: select ■.
- i The availability of this function is dependent on the vehicle's equipment.

### Resetting seat settings

Multimedia system:

- → 🔝 **>>** Comfort **>>** Seat
- Select Reset.
- Select for the desired seat.
  The settings for the selected seat are reset.

## Switching the seat heating on/off

A

**WARNING** Risk of burns due to repeatedly switching on the seat heating

Repeatedly switching on the seat heating can cause the seat cushion and seat backrest padding to become very hot.

In particular, the health of persons with limited temperature sensitivity or a limited ability to react to high temperatures may be affected or they may even suffer burn-like injuries.

Do not repeatedly switch on the seat heating.

To protect against overheating, the seat heating may be temporarily deactivated after it has been switched on repeatedly.

!


**NOTE** Damage to the seats caused by objects or documents when the seat heating is switched on

When the seat heating is switched on, overheating may occur due to objects or documents placed on the seats, e.g. seat cushions or child seats. This could cause damage to the seat surface.

Make sure that no objects or documents are on the seats when the seat heating is switched on.

## Requirements

• The power supply is switched on.




- Press button 1 for the respective seat repeatedly until the desired heating level is reached. Depending on the heating level, up to three indicator lamps will light up. If all indicator
- lamps are off, the seat heating is switched off. The seat heating will automatically switch down from the three heating levels after around 8, 10 and 20 minutes until the seat
- (i) If you switch the power supply off and on again within 20 minutes, the previous setting of the seat heating for the driver's seat will remain active.

# Switching the seat ventilation on/off

heating is switched off.

# Requirements

• The power supply is switched on.



Press button (1) for the respective seat repeatedly until the desired blower setting is reached.

Depending on the blower setting, up to three indicator lamps will light up. If all indicator lamps are off, the seat ventilation is switched off.

i If you switch the power supply off and on again within 20 minutes, the previous seat ventilation setting for the driver's seat will remain active.

## Steering wheel

## Adjusting the steering wheel manually

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:


- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten your seat belt.

**WARNING** Risk of entrapment for children when adjusting the steering wheel

Children could injure themselves if they adjust the steering wheel.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

# Unlocking



- Fold release lever 1 down as far as it will go.
- Adjust height **2** and distance **3** to the steering wheel.

# Locking

Fold release lever 1 up as far as it will go.

Check and make sure that the steering column is locked by moving the steering wheel.

# Adjusting the steering wheel electrically

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:


- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- ▶ Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten your seat belt.

**A** WARNING Risk of entrapment for children when adjusting the steering wheel

Children could injure themselves if they adjust the steering wheel.

- Never leave children unattended in the vehicle
- When leaving the vehicle, always take the key with you and lock the vehicle.

The steering wheel can be adjusted when the power supply is disconnected.



- 1 To move up
- To move back
- To move down
- To move forward
- Save the settings with the memory function  $(\rightarrow page 113).$

# Decoupling the steering wheel heater from the seat heating

## Requirements

- The power supply or the vehicle has been switched on.
- The steering wheel heater and the seat heating are linked.

#### Multimedia system:

→ 🔝 **>>** Comfort **>>** Seat

# ➤ Heating Settings

The function is active by default and the steering wheel heater is automatically activated and deactivated when the seat heating is switched on and off.

➤ Tap on Additional Steering Wheel Heating. The steering wheel heater will be decoupled from the seat heating.

When you switch the vehicle off, the steering wheel heater will switch off.

i The steering wheel heater can also be deactivated via the MBUX voice assistant.

# Easy entry and exit feature

# Using the easy entry and exit feature

WARNING Risk of accident when pulling away during the adjustment process of the easy entry and exit feature

You could lose control of the vehicle.

Always wait until the adjustment process is complete before driving off.



**WARNING** Risk of becoming trapped when adjusting the easy entry and exit feature

You and other vehicle occupants, particularly children, may become trapped.

Make sure that no one has any part of their body within the range of movement of the steering wheel and driver's seat.

If there is a risk of becoming trapped by the steering wheel:

Move the steering wheel adjustment lever.

The adjustment process is stopped.

If there is a risk of becoming trapped by the driver's seat:

- Press the switch for seat adjustment. The adjustment process is stopped.
- Never leave children unattended in the vehicle.
- ► When leaving the vehicle, always take the key with you and lock the vehicle.

**Vehicles with memory function:** you can stop the adjustment process by pressing one of the memory function position switches.



WARNING Risk of becoming trapped if children activate the easy entry and exit feature

Children could become trapped if they activate the easy entry and exit feature, particularly when unattended.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

In order to use the easy entry and exit feature, the automatic seat adjustment function must have been switched on ( $\rightarrow$  page 105).

When the easy entry and exit feature is active, the steering wheel and driver's seat will move as follows:

- The steering wheel will move upwards.
- . The driver's seat will move forward or backward to a position suitable for getting in or out of the vehicle.

This will occur in the following situations:

- You switch off the vehicle when the driver's door is open.
- · You open the driver's door when the vehicle is switched off.
- (i) The steering wheel will then move upwards only if it is not already as high as it will go.

The driver's seat will move forwards or backwards only if it is not already in the ideal position for getting in or out of the vehicle.

The steering wheel and the driver's seat will move back to the last driving position in the following cases:

- You switch the power supply or the vehicle on when the driver's door is closed
- You close the driver's door when the vehicle is switched on.

The last drive position will be saved when:

- If you switch off the vehicle.
- Vehicles with memory function: you call up the seat settings via the memory function.
- Vehicles with memory function: you save the seat settings via the memory function.

Vehicles with memory function: press one of the memory function position switches to stop the adjustment process.

## Setting the easy entry and exit feature

#### Requirements

- The automatic seat adjustment has been activated ( $\rightarrow$  page 105).
- The power supply or the vehicle has been switched on.

#### Multimedia system:

→ 🕝 >> Settings >> Vehicle >> Comfort >> Easy Entry And Exit Feature

#### Setting the easy entry and exit feature

- Select Steering Wheel & Seat, Steering Wheel Only or Off.
- (i) If you are using a custom user profile, this information will be used for the easy entry and exit feature. This will cause the driver's seat and steering wheel to move into the correct position automatically.

## Memory function

# Function of the memory function

**WARNING** Risk of an accident if the memory function is used while driving

If you use the memory function on the driver's side while driving, you could lose control of the vehicle as a result of the adjustments being made.

- Only use the memory function on the driver's side when the vehicle is stationary.
- ▲ WARNING Risk of entrapment when adjusting the seat with the memory function

When the memory function adjusts the seat, you and other vehicle occupants – particularly children – could become trapped.

During the adjusting process of the memory function, ensure that no body parts are in the area of movement of the seat or the steering wheel.

 If someone becomes trapped, press a preset position button or seat adjustment switch immediately.
 The adjustment process is stopped.

**WARNING** Danger of entrapment when memory function is activated by children

When children activate the memory function, they can get trapped, especially if they are unsupervised.

- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.

You can use the memory function when the vehicle is switched off.


Seat adjustments for up to three people can be stored and called up using the memory function.

You can save the following settings for the front seat:

- Seat, backrest, head restraint position and contour of the seat backrest in the lumbar region
- Seat heating: distribution of the heated sections of the seat cushion and seat backrest
- Driver's side: steering wheel position and position of the outside mirrors on the driver's and front passenger sides

## Operating the memory function

#### Storing



- Set the front seat, the steering wheel, the head-up display and the outside mirror to the desired position.
- Press the M button and then release it.

- Press one of the preset position buttons 1. 2 or 3 within three seconds. An acoustic signal sounds. The settings are stored.
- To call up: press the preset position button 1, 2 or 3. The seat will be moved to the stored position. After releasing the button, the front seat, outside mirror, head-up display and steering column will continue to move into the stored position automatically.

## Stowage areas

Notes on loading the vehicle

**DANGER** Risk of exhaust gas poisoning

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Exhaust gases can enter the vehicle interior if the tailgate is open when the engine is running, especially if the vehicle is in motion.

Always switch off the engine before opening the tailgate.

Never drive with the tailgate open.

Objects in the deployment area of an air bag may prevent the air bag from functioning correctly. Observe the notes on air bags ( $\rightarrow$  page 57).

WARNING Risk of injury from unsecured items in the vehicle

If objects, luggage or loads are not secured or not secured sufficiently, they could slip, tip over or be thrown around and thereby hit vehicle occupants.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects in such a way that they cannot be thrown around.
- Before the journey, secure objects, luggage or loads against slipping or tipping over.

**WARNING** Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open storage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or abrupt changes in direction.

- Always store objects such that they cannot be thrown around in such situations.
- Always make sure that objects do not protrude from storage spaces, parcel nets or storage nets.
- Close the lockable storage spaces before starting a journey.
- Stow and secure objects that are heavy, hard, pointed, sharp-edged, fragile or too large in the cargo compartment.

WARNING Risk of accident due to objects in the driver's and front-passenger footwell

Objects in the driver's and front-passenger footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating- and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's or front-passenger footwell.
- Always ensure that the pedals have sufficient free space.
- Always install the floor mats securely and as prescribed.
- Do not use loose floor mats and do not place floor mats on top of one another.

Vehicles with automatic front passenger air bag shutoff: objects trapped under the front passenger seat may interfere with the function of the automatic front passenger air bag deactivation or damage the system. Therefore please

observe the notes on the function of automatic front passenger air bag deactivation ( $\rightarrow$  page 47).

A

WARNING - Risk of accident or injury when using the cup holder while the vehicle is moving

The cup holder cannot secure containers while the vehicle is moving.

If you use a cup holder while the vehicle is moving, the container may be flung around and liquids may be spilled. The vehicle occupants may come into contact with the liquid and if it is hot, they could be scalded. You could be distracted from traffic conditions and you may lose control of the vehicle.

- Only use the cup holder when the vehicle is stationary.
- Only use the cup holder for containers of the right size.
- Close the container, particularly if the liquid is hot.

NOTE Damage to the cup holder

The cup holder can be damaged when folding back the rear armrest. When open, the cup holder can be damaged by body weight.

- The rear armrest can only be folded back when the cup holder is closed.
- Do not sit or support vourself on the cup holder when it is open.

WARNING Risk of injury due to an open cargo compartment floor

If you drive with the cargo compartment floor open, objects could be flung around and hit vehicle occupants as a result. There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

Always close the cargo compartment floor before a journey.

**A** WARNING Risk of burns from the tailpipe and tailpipe trims

The exhaust tailpipe and tailpipe trims can become very hot. If you come into contact with these parts of the vehicle, you could burn vourself.

- Always be particularly careful around the tailpipe and the tailpipe trims and supervise children especially closely in this area.
- Allow vehicle parts to cool down before touching them.
- NOTE Damage to the cargo floor caused by an unevenly distributed load or an abrupt application of load.

The cargo floor may be damaged by an unevenly distributed load or an abrupt application of load.

Distribute the load evenly.

- Drive carefully when the vehicle is laden. Avoid abrupt starts, braking and steering as well as rapid cornering.
- (i) Leather is a natural product. It has natural surface properties, such as differences in structure, marks caused by growth and injury or subtle color differences. These surface characteristics are particular to leather, and not material defects. Leather is also subject to a natural aging process which changes the surface characteristics.

The driving characteristics of your vehicle are dependent on the distribution of the load within the vehicle. You should bear the following in mind when loading the vehicle:

- Never allow the payload including occupants to exceed the maximum permissible gross mass or the gross axle weight rating for the vehicle. The values are specified on the vehicle identification plate on the vehicle's B-pillar.
- The load must not protrude above the upper edge of the seat backrests.


- Always place the load behind unoccupied seats if possible.
- Secure the load using the cargo tie-down rings and distribute the tension evenly.

#### Notes on carrying a roof load:


- Distribute the roof load and vehicle load evenly, and place heavy objects at the bottom.
   Also observe the notes on loading the vehicle.
- Drive with care. Avoid sudden starting, braking and steering maneuvers or fast cornering.
- (i) Further information on stowage compartments and stowage facilities can be found in the Digital Operator's Manual.

# Stowage spaces in the vehicle interior

Overview of the front storage compartments




- Stowage spaces in the doors
- Storage compartment under the armrest with multimedia and USB ports
- Storage compartment in the front center console with cup holders, USB ports and charging module for wireless charging of mobile phones
- Glove box



Under armrest ② there is also a sliding storage compartment ⑤, which can be used in the front or rear position. Push the compartment to the desired position until it engages.

For cleaning, the storage compartment can be moved to the middle position and removed. The rubber mat in the storage compartment can be removed for cleaning.



Depending on the vehicle version, there is a storage compartment in the rear center console (6). The rubber mat in the storage compartment can be removed for cleaning.

Opening and closing the storage compartment in the front center console

WARNING Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open storage spaces and mobile

phone brackets cannot always retain all objects they contain.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects in such a way that they cannot be thrown around in such situations.
- Always make sure that objects do not protrude from storage spaces, parcel nets or storage nets.
- Close the lockable storage spaces before starting a journey.
- Always stow and secure heavy, hard, pointed, sharp-edged, fragile or bulky objects in the trunk.


Observe the notes on loading the vehicle.



- To open: slide the cover of the storage compartment in the front center console all the way forwards in the direction of the arrow using handle 1.
- To close: briefly push handle (1) of the open cover of the storage compartment in the front center console forwards.

The cover will automatically close the storage compartment in the front center console.

# Locking/unlocking the glove box



Turn the emergency key a quarter turn clockwise 2 (to lock) or counter-clockwise 1 (to unlock).

# Through-loading feature in the rear bench seat (EASY-PACK Quickfold)

# Folding the rear seat backrests forward

**WARNING** Risk of becoming trapped when adjusting the seats

When you adjust a seat, you may trap yourself or a vehicle occupant.

When adjusting a seat, make sure that no one has any body parts in the sweep of the seat.

**WARNING** Risk of an accident because the seat backrest is not engaged

The seat backrest may fold forwards.

There is a risk of the following, in particular:

 The vehicle occupant may be pressed against the seat belt. The seat belt cannot protect as intended and could cause additional injury.

- A child restraint system is no longer properly supported or properly positioned and may no longer fulfill its function as intended.
- The seat backrest cannot restrain objects or goods in the trunk or cargo compartment.

Always ensure that the seat backrest is engaged, especially:

- After the seat has been adjusted.
- After the cargo compartment enlargement has been folded forwards

Prior to use, make sure that the red marking of the lock verification indicator is no longer visible. Otherwise, the seat backrest is not locked.


Always ensure that all vehicle occupants have their seat belts fastened correctly and are sitting properly. Particular attention must be paid to children.

## Requirements


- The rear seat backrest head restraints are fully inserted
- The rear armrest has been folded up.

If you no longer require the folded-down rear seat backrest as a load area, fold the backrest back into place.

Ensure that the center seat backrest is in an upright position and locked to the left seat backrest (→ page 120).



Press the seat belt tongue of seat belt 1 into marked position 2.



To fold the left seat backrest forward: briefly pull left button 1.

The left and center seat backrests fold forwards.

If the left seat backrest is not locked with the center seat backrest, this will be shown on the driver display.

- ➤ To fold the right seat backrest forward: briefly pull right button ①.
  The right seat backrest will fold forwards.
- Folding the rear seat backrest back
- NOTE Damage caused by trapping the seat belt when folding back the seat backrest

The seat belt could become trapped and thus damaged when the seat backrest is folded back.

Make sure that the seat belt is not trapped when folding back the seat backrest.




- Move the driver's or front passenger seat forwards, if necessary.
- Swivel seat backrest back until it engages. If the seat backrest is not engaged and locked in place, red lock verification indicator will be visible.

Locking the release catch of the center rear seat backrest

## Requirements:

 The left and center seat backrests are engaged and joined together.


You can lock the center seat backrest release catch if you want to secure the cargo compartment against unauthorized access. The center seat backrest can then be folded forwards only together with the left seat backrest.



- Fold the center and left seat backrests forwards.
- To lock or unlock: slide catch 1 upwards or downwards.

# Adjusting the angle of the rear seat backrests (cargo position)

To enlarge the cargo compartment, you can adjust the seat backrests so that they are 10 degrees steeper (cargo position).



- Fold the seat backrest forwards  $(\rightarrow page 118).$
- Move bracket 1 in the direction of the arrow.



Push seat backrest 2 back to bracket 1 until the backrest engages. If the seat backrest is not engaged and locked in place, red lock verification indicator (3) will be visible.

## Cargo compartment cover

# Extending/retracting the cargo compartment cover

**WARNING** Risk of injury or death due to poorly secured objects

The cargo compartment cover alone cannot secure or restrain heavy objects, items of luggage or heavy loads.

You could be hit by an unsecured load, particularly in the event of abrupt changes in direction, sudden braking or an accident.


- Always stow objects in such a way that they cannot be thrown around.
- Secure objects, luggage or loads against slipping or tipping over, e.g. by using tie downs, even if you are using the cargo compartment cover.

! NOTE Damage to the cargo compartment cover when loading the vehicle

The cargo compartment cover may be damaged when the vehicle is being loaded.

Do not place any objects above the lower edge of the side windows or on the cargo compartment cover.

The cargo compartment cover is attached behind the seat backrest of the rear bench seat.




➤ To extend: pull cargo compartment cover ①
back by grab handle ② and hook it into the
holders on the left and right.

- To retract: unhook cargo compartment cover
   from the holders on the left and right and
  guide it forwards by grab handle until it is
  fully retracted.
- Installing and removing the cargo compartment cover

#### Requirements

• The cargo compartment cover is retracted.

## Removing the cargo compartment cover



Press in the end cap of cargo compartment cover on the right- or left-hand side.


- Push cargo compartment cover 1 into recess 2 on the opposite side.
- Take cargo compartment cover (1) out by pulling it upwards.

## Installing the cargo compartment cover

- Press in the end cap of cargo compartment cover 1 on the opposite side and insert cargo compartment cover (1) into other recess 2.
- Slide the end cap outwards.

## Stowing the cargo compartment cover


Depending on the vehicle version, the cargo compartment cover can be stowed under the cargo floor.



- To insert: position cargo compartment cover 1 to the left under the trim and engage it in mounting 2.
- To remove: press the end cap of the cargo compartment cover inward and remove it from mounting 2.

## Overview of the tie-down eyes

Observe the notes on loading the vehicle  $(\rightarrow page 113).$ 



Tie-down eyes

# Overview of bag hooks

WARNING Risk of injury when using bag hooks with heavy objects


The bag hooks cannot restrain heavy objects or items of luggage.

Objects or items of luggage may be flung around and hit vehicle occupants.

- Only hang light objects on the bag hooks.
- Never hang hard, sharp-edged or fragile objects on the bag hooks.

Observe the notes on loading the vehicle ( $\rightarrow$  page 113).

The bag hook can bear a maximum load of 6.6 lbs (3 kg). Do not use it to secure a load.



Bag hook

## Attaching a roof luggage rack

A

**WARNING** Risk of accident due to exceeding the maximum roof load

The vehicle center of gravity and the usual driving characteristics as well as the steering and braking characteristics alter.

If you exceed the maximum roof load, the driving characteristics, as well as steering and braking, will be greatly impaired.

Never exceed the maximum roof load and adjust your driving style.

Vehicle-specific weight information can be found on the vehicle identification plate.

I N

**NOTE** Vehicle damage due to failure to observe the maximum permissible clearance height

If the vehicle height exceeds the maximum permissible clearance height, the roof and other vehicle parts may be damaged.

- Please observe the maximum clearance height indicated.
- If the vehicle exceeds the permissible clearance height, do not drive in.
- Take the modified vehicle height into account in the case of roof superstructures or other carrier systems.
- **NOTE** Damage to the panorama roof with power tilt/sliding panel due to nonapproved roof luggage racks

The panorama roof with power tilt/sliding panel may be damaged by the roof luggage rack if you attempt to open it when using a roof luggage rack not tested and approved for Mercedes-Benz.

When a roof luggage rack is installed. open the panorama roof with power tilt/ sliding panel only if this has been tested and approved for Mercedes-Benz.

The panorama roof with power tilt/sliding panel may be raised to allow ventilation of the vehicle interior.

- Secure the roof luggage rack to the roof railing.
- Observe the manufacturer's installation instructions

#### Cup holder

Installing or removing the cup holder in the center console

WARNING - Risk of accident or injury when using the cup holder while the vehicle is moving

The cup holder cannot secure containers while the vehicle is moving.

If you use a cup holder while the vehicle is moving, the container may be flung around and liquids may be spilled. The vehicle occupants may come into contact with the liquid and if it is hot, they could be scalded. You could be distracted from traffic conditions and you may lose control of the vehicle.

- Only use the cup holder when the vehicle is stationary.
- Only use the cup holder for containers of the right size.
- Close the container, particularly if the liquid is hot.

# WARNING Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open storage spaces and mobile phone brackets cannot always retain all objects they contain.


There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

Always stow objects in such a way that they cannot be thrown around in such situations.

- Always make sure that objects do not protrude from storage spaces, parcel nets or storage nets.
- Close the lockable storage spaces before starting a journey.
- Always stow and secure heavy, hard, pointed, sharp-edged, fragile or bulky objects in the trunk.

Observe the notes on loading the vehicle ( $\rightarrow$  page 113).


# Installing




► Insert two lugs ② into the recesses in the trim and swing cup holder ③ into the compartment until it engages.

# Removing

The cup holder can be removed for cleaning.



Push the side wall of rear beverage compartment (3) to the left until the cup holder releases and swing the cup holder out upwards.




Insert mats (4) in the cup holder beverage compartments can be removed for cleaning.

- To do so, use a suitable tool to push the insert mats out of their mounting from the rear of the removed cup holder.
- Reinsert the cup holder after cleaning.

# Using the cup holder

(i) Check whether the beverage container is held firmly by the cup holder. Some beverage containers will not be secured adequately in the cup holder due to their shape or size.

The side wall of the front beverage compartment can be retracted and extended manually.




Gently push a beverage container into the bottom 2 of the beverage compartment. The side panel will automatically extend to the left to secure the beverage container.

Alternatively, you can extend the side wall of the beverage compartment by pressing lightly on grooved surface 1.

# Retracting the side wall

When the front beverage compartment is not in use, the side panel can be retracted manually. The cup holder's holding function will then no longer be available.



 Push the side panel back in the direction of the arrow until it engages in correct position
 .

# Sockets


# Using the 12 V socket

# Requirements

• Connect only devices up to a maximum of 180 W (15 A).

Depending on the vehicle equipment, the vehicle has the following 12 V sockets:

- In the front passenger footwell
- In the cargo compartment



Example: 12 V socket in the front passenger footwell

- Fold up the cap of socket ①.
- Insert the plug of the device.

# Using the 115 V socket in the rear passenger compartment

**DANGER** Risk of fatal injuries due to a damaged connecting cable or a damaged socket

You could receive an electric shock if the connecting cable or the 115 V power socket is pulled out of the trim or is damaged or wet.

- Use only connecting cables that are dry and free of damage.
- When the vehicle is switched off, make sure that the 115 V power socket is dry.
- Immediately have the 115 V power socket checked or replaced at a qualified specialized workshop if it is damaged or has been pulled out of the trim.
- Never plug the connecting cable into a 115 V power socket that is damaged or has been pulled out of the trim.

**DANGER** Risk of death due to using the socket incorrectly

In particular, you could receive an electric shock:


- If you touch the inside of the socket
- If you insert unsuitable devices or objects into the socket
- Do not touch the inside of the socket.
- Only connect suitable devices to the socket.

Make sure that no liquids get into the 115 V socket.

When the 115 V socket is not in use, keep the socket flap closed.

#### Requirements

- Only connect devices with a suitable plug which conforms to the standards specific to the country you are in.
- · Only connect devices up to a maximum of 150 W.
- · Do not use multiple socket outlets.



- Open socket flap (3).
- Insert the plug of the device into 115 V socket

When the on-board electrical system voltage is sufficient, indicator lamp 2 lights up.

#### **USB** ports

Depending on its equipment, the vehicle has the following USB ports:

- In the storage compartment in the front center console
- In the storage compartment under the front armrest
- In the rear passenger compartment center console

Depending on the vehicle equipment, the vehicle has either one or two USB ports in the storage compartment in the front center console and beneath the front armrest.

Depending on the vehicle equipment, the vehicle has two USB ports in the rear passenger compartment center console.

You can charge a USB device, such as a mobile phone, at the USB ports using a suitable charging cable. Depending on the vehicle equipment, devices can be charged with up to 20 V (5 A) when the vehicle is switched on.

# Wireless charging of the mobile phone and connection with the exterior antenna

Notes on wirelessly charging a mobile phone

A

**WARNING** Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around and hit vehicle occupants. In addition, cup holders, open stowage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction.

- Always stow objects so that they cannot be thrown around in such situations.
- Always make sure that objects do not protrude from stowage spaces, parcel nets or stowage nets.
- Close the lockable stowage spaces before starting a journey.

 Always stow and secure heavy, hard, pointed, sharp-edged, fragile or bulky objects in the trunk/cargo compartment.

Observe the notes on loading the vehicle.

A

**WARNING** Risk of fire from placing objects in the mobile phone storage compartment

Placing other objects in the mobile phone storage compartment could constitute a fire hazard.

- Apart from a mobile phone, do not place any other objects in the mobile phone storage compartment, especially those made of metal.
- NOTE Damage to objects caused by placing them in the mobile phone storage compartment

If objects are placed in the mobile phone storage compartment, these may be damaged by electromagnetic fields.

- ▶ Do not place credit cards, storage media. ski passes or other objects sensitive to electromagnetic fields in the mobile phone storage compartment.
- NOTE Damage to the mobile phone stowage compartment caused by liquids

If liquids enter the mobile phone stowage compartment, the compartment may be damaged.

Ensure that no liquids enter the mobile phone stowage compartment.

Always observe the notes for persons with electronic medical aids ( $\rightarrow$  page 31).

- Depending on the vehicle equipment, the mobile phone is connected to the vehicle's exterior antenna via the charging module.
- · The charging function and wireless connection of the mobile phone to the vehicle's exterior antenna are available only if the vehicle is switched on.

- Small mobile phones may not be able to be charged in every position of the mobile phone stowage compartment.
- · Large mobile phones that do not rest flat in the mobile phone stowage compartment may not be able to be charged or connected with the vehicle's exterior antenna.
- The mobile phone may heat up during the charging process. This may also depend on the applications (apps) currently open in the background.
- To ensure more efficient charging and connection with the vehicle's exterior antenna. remove the protective cover from the mobile phone. Protective covers that are necessary for wireless charging are an exception.

# Wirelessly charging a mobile phone in the front

#### Requirements

• The mobile phone is suitable for wireless charging.

A list of compatible mobile phones can be found at: https://www.mercedes-benzmobile.com/



Place the mobile phone in the front storage compartment as centrally as possible with the display facing upwards on mat (1) next to the USB ports.

When the charging symbol is shown on the driver's display, the mobile phone is being charged. In addition, malfunctions when the mobile phone is being charged are shown on the central display.

(i) The mat can be removed for cleaning, e.g. using clean, lukewarm water.

# Installing/removing the floor mats


**WARNING** Risk of accident due to objects in the driver's footwell

Objects in the driver's footwell may impede pedal travel or block a depressed pedal.

This jeopardizes the operating and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Always install the floor mats securely and as prescribed in order to ensure that there is always sufficient room for the pedals.
- Do not use loose floor mats and do not place floor mats on top of one another.

# Installing floor mats



- Move the corresponding seat backwards and lay the floor mat in the footwell.
- Press studs ① onto holders ②.
- Adjust the corresponding seat.

# Removing floor mats

Pull the floor mat off holders 2.

Remove the floor mat.


# Exterior lighting

# Information about lighting systems and your responsibility

The various lighting systems of the vehicle are only aids. The driver of the vehicle is responsible for correct vehicle illumination in accordance with the prevailing light and visibility conditions, legal requirements and traffic situation.

# Light switch

# Operating the light switch



- **←P** Left-hand parking lights
- **P**≤→ Right-hand parking lights
- Standing lights and license plate lamp
- **AUTO** Automatic driving lights (preferred light switch position)

D Low beam/high beam

0\(\frac{1}{2}\) Activates or deactivates the rear fog light.

When low beam is activated, the [305] indicator lamp for the standing lights will be deactivated and replaced by the D low-beam indicator lamp.

- Always park your vehicle safely using sufficient lighting, in accordance with the relevant legal stipulations.
- **NOTE** Battery discharging by operating the parking lamps

Do not have the parking lamps switched on over a period of several hours.

If the battery is insufficiently charged, the standing lights or parking lights will be switched off automatically to facilitate the next engine start.

## 134 Light and visibility

The exterior lighting (except standing and parking lights) will switch off automatically when the driver's door is opened.

 Observe the notes on locator lighting (→ page 142).

## Switching on accident scene lighting

- Switch off the vehicle.
- Switch on the hazard warning lamps  $(\rightarrow page 135)$ .
- ► Turn the light switch from the AUTO position to the D position.

  The low beam will be switched on despite the vehicle being switched off.

The accident scene lighting will be switched off if:

- · you switch off the hazard warning lights.
- you turn the light switch back to AUTO.
- the battery is insufficiently charged.

# Automatic driving lights function

When the vehicle is switched on, the side lamps, low beam and daytime running lights will be

switched on automatically depending on the ambient light.



WARNING Risk of accident when the low beam is switched off in poor visibility

When the light switch is set to **AUTO**, the low beam may not be switched on automatically if there is fog, snow or other causes of poor visibility such as spray.

In such cases, turn the light switch to .

The automatic driving lights are only an aid. You are responsible for the vehicle lighting.


# Switching the rear fog light on/off

#### Requirements

- The light switch is in the or auto position.
- ► Press button 0 .

Please observe the country-specific laws on the use of rear fog lamps.

# Operating the combination switch for the lights



- High beam
- 2 Turn signal light, right
- Headlamp flashing
- Turn signal light, left
- Use the combination switch to select the desired function.

# Switching on high beam

- Turn the light switch to the or Auto position.
- Push the combination switch in the direction of arrow .

When high beam is activated, the indicator lamp for low beam will be deactivated and replaced by the indicator lamp for high beam **≣**□.

## Switching off high beam

Push the combination switch in the direction of arrow or pull it in the direction of arrow

## Headlamp flashing

Pull the combination switch in the direction of arrow 3.


## Turn signals

- To indicate briefly: push the combination switch briefly to the point of resistance in the direction of arrow 2 or 4. The corresponding turn signal light will flash three times.
- To indicate permanently: push the combination switch beyond the point of resistance in the direction of arrow or 4.

Vehicles with Active Lane Change Assist:

- · A turn signal indicator activated by the driver may continue to operate for the duration of the lane change.
- If the driver indicated directly beforehand but a lane change was not immediately possible, the turn signal indicator may activate automatically.

# Activating/deactivating the hazard warning lights



Press button ①

The hazard warning lights will switch on automatically if:

· the air bag has been deployed.

## **DIGITAL LIGHT adaptive functions**

# Function of dynamic low beam

With this system, the headlamps adapt to the driving and weather situation. It also provides extended functions for improved illumination of the road.

(i) The availability of the functions is countrydependent.

The system comprises the following functions:

- Active Headlamps (→ page 136)
- Topographical compensation (→ page 136)

The system will be active only when it is dark.

# Active headlamps function



- The headlamps will follow your steering movements.
- Relevant areas will be better illuminated during a journey.

The functions will be active when the low beam is switched on.

# Function of the topographical compensation

Based on available map data, the lighting system responds pre-emptively to different road heights. This means that the headlamp range will remain virtually constant when you are driving uphill or downhill.

- Only vehicles with a multimedia system with navigation have this function.
- Assistance functions of DIGITAL LIGHT


DIGITAL LIGHT visually expands on the driver assistance systems by projecting the assistant displays in front of the vehicle while it is in motion. DIGITAL LIGHT can therefore help the driver in critical situations

- i The availability of the functions is countrydependent.
- (i) The assistance functions of DIGITAL LIGHT may be an on-demand feature (→ page 24).

The system will remain active when Highbeam Assist is switched on.

① Depending on the country in which you are currently driving, certain functions may be disabled due to different legal requirements, even if they are enabled in the multimedia system. When you cross a border, the vehicle will automatically adapt to the applicable requirements.

# Spotlight




The spotlight function runs in the background and will flash the headlamps in four short bursts at persons detected within the lane markings. You will also be made aware of the position of the person by a projected symbol.

The function will be active in the following circumstances:

- · You are driving in an unlit area.
- The system detects a lane marking.

## Notes




If Traffic Sign Assist detects a roadworks zone, the system will provide support as follows:

• A corresponding symbol will be projected onto the road when you enter a roadworks zone.

Observe the system limitations of Traffic Sign Assist ( $\rightarrow$  page 260).

# Collision warning




If you fall below the safe distance at speeds of at least 19 mph (30 km/h), a collision warning symbol will be projected onto the road.

Observe the system limitations of Active Brake Assist ( $\rightarrow$  page 254).

#### 138 Light and visibility

## Lane change warning



During assisted lane changes at speeds of at least 19 mph (30 km/h), the course of the lane change will flash.

Observe the system limitations of Active Lane Change Assist ( $\rightarrow$  page 250).

## Lane keeping and blind spot warning



At speeds of at least 19 mph (30 km/h), a triangle that indicates a lane correction and its direction will be projected onto the road in the following cases:

- You leave the lane unintentionally.
   Observe the system limitations of Active Lane Keeping Assist (→ page 268).
- You switch on the turn signal light while an object or obstacle is in your blind spot.
   Observe the system limitations of Active Blind Spot Assist (→ page 264).

## Activating/deactivating dynamic low beam

## Requirements

• The vehicle is switched on.

Multimedia system:

- → 🔝 ➤ Settings ➤ Light
- >> DIGITAL LIGHT
- Activate or deactivate Dynamic Low Beam.

# Activating/deactivating enhanced assistance functions

- The availability of the functions is countrydependent.
- This function is an on-demand feature
   (→ page 24).
- Select Supporting Projections.
- Activate or deactivate the desired projections.
- Switch Projection for greeting/farewell on or off.

If the locator lighting or the exterior switch-off delay time is activated, a high-resolution greeting or farewell scene will be played back for a short period of time when the vehicle is

opened or switched off. You can choose between the Digital Rain and Star Wave sequences.

(i) More information on locator lighting  $(\rightarrow page 142)$ More information on the exterior switch-off delay time ( $\rightarrow$  page 142)

# Adaptive Highbeam Assist

# Adaptive Highbeam Assist function

WARNING Risk of accident despite Adaptive Highbeam Assist

Adaptive Highbeam Assist does not react to:

- · Road users without lights, e.g. pedestrians
- · Road users with poor lighting, e.g. cyclists
- · Road users whose lighting is obstructed, e.g. by a barrier

On very rare occasions, Adaptive Highbeam Assist may fail to recognize other road users with their own lighting, or may recognize them too late.

In these, or in similar situations, the automatic high beam will not be deactivated or will be activated despite the presence of other road users


Always observe the road and traffic conditions carefully and switch off the high beam in good time.

Adaptive Highbeam Assist cannot take into account road, weather or traffic conditions.

Detection may be restricted in the following cases:

- In poor visibility, e.g. fog, heavy rain or snow
- if there is dirt on the sensors or the sensors are obscured

Adaptive Highbeam Assist is only an aid. You are responsible for adjusting the vehicle's lighting to the prevailing light, visibility and traffic conditions.



Adaptive Highbeam Assist automatically switches between the following types of light:

- Low-beam headlamps
- · High beam

At speeds greater than 19 mph (30 km/h):

• If no other road users are detected, high beam will switch on automatically.

#### 140 Light and visibility

High beam will switch off automatically in the following cases:

- At speeds below 16 mph (25 km/h)
- If other road users are detected
- If street lighting is sufficient
- (i) The system's optical sensor is located behind the windshield near the overhead control panel.
- Switching Adaptive Highbeam Assist on/off

## Switching on

- Turn the light switch to the **AUTO** position.
- Switch on high beam using the combination switch.
  - If Adaptive Highbeam Assist is activated. the indicator lamp will light up on the driver's display.

## Switching off

Switch off high beam using the combination switch.

# Adaptive Highbeam Assist Plus

Adaptive Highbeam Assist Plus function (Canada)

WARNING Risk of accident despite Adaptive Highbeam Assist Plus

Adaptive Highbeam Assist Plus does not react to:

- Road users without lights, e.g. pedestrians
- Road users with poor lighting, e.g. cyclists
- Road users whose lighting is obstructed, e.g. by a barrier

On very rare occasions, Adaptive Highbeam Assist Plus may fail to recognize other road users with their own lighting, or may recognize them too late.

In these, or in similar situations, the automatic high beam will not be deactivated or will be activated despite the presence of other road users.


Always observe the road and traffic conditions carefully and switch off the high beam in good time.

Adaptive Highbeam Assist Plus cannot take into account road, weather or traffic conditions.

Detection may be restricted in the following cases:

- In poor visibility, e.g. fog, heavy rain or snow
- if there is dirt on the sensors or the sensors. are obscured

Adaptive Highbeam Assist Plus is only an aid. You are responsible for adjusting the vehicle's lighting to the prevailing light, visibility and traffic conditions.



Adaptive Highbeam Assist Plus automatically switches between the following types of light:

- Low beam
- · Partial high beam
- High beam
- ULTRA RANGE Highbeam

ULTRA RANGE Highbeam increases the brightness of the cone of light close to the legally permitted maximum

Partial high beam does not include other road users in the high beam area. It does not dazzle them but enables full high-beam illumination for the driver apart from the excluded vehicles. Highly reflective signs are also illuminated with reduced brightness.

At speeds below 16 mph (25 km/h) or when there is sufficient street lighting:

 Partial high beam and high beam will be switched off automatically.

At speeds above 19 mph (30 km/h):

- If no other road users are detected, high beam will be switched on automatically.
- If other road users are detected, partial high beam will be switched on automatically.

at speeds below 25 mph (40 km/h):

• ULTRA RANGE Highbeam will switch off automatically.

At speeds above 31 mph (50 km/h):

- If no other road users are detected, the road is straight and it is not raining heavily, ULTRA RANGE Highbeam will be switched on automatically.
- If other road users are detected, partial high beam will be switched on automatically.
- If highly reflective signs are detected, ULTRA RANGE Highbeam will be switched off automatically.
- The system's optical sensor is located behind the windshield near the overhead control panel.

# Switching Adaptive Highbeam Assist Plus on/off (Canada)

#### Switching on

- Turn the light switch to the AUTO position.
- Switch on high beam using the combination switch.

If Adaptive Highbeam Assist Plus is activated, the indicator lamp will light up on the driver's display. When partial high beam or

## 142 Light and visibility

high beam is active, the corresponding blue indicator lamp will also light up.

#### Switching off

Switch off high beam using the combination switch.

# Switching the daytime running lights on/off

Multimedia system:

- → Settings → Light
  → DIGITAL LIGHT
- ► Switch the Daytime Running Lights on or off.
- i In vehicles without DIGITAL LIGHT headlamps, the daytime running lights can be switched on or off on the driving lights menu.
- (i) Availability of the function is dependent on the respective country.

# Setting the exterior lighting switch-off delay time

Multimedia system:

- → 🔝 >> Settings >> Light
- ➤ Interior/Exterior Lighting
- >> External Lighting Display
- Set a switch-off delay time.

  After parking and locking the vehicle, the exterior lighting will be activated for the set time.

# Switching locator lighting on/off


Multimedia system:

- → 🔝 >> Settings >>> Light
- >> Interior/Exterior Lighting
- Activate or deactivate Locator Lighting.

When the function is activated, the exterior lighting will light up for 40 seconds after the vehicle is unlocked or the driver's door is opened when the vehicle is parked and not locked. When you start the vehicle, the locator lighting is switched off and automatic driving lights are activated.

# Interior lighting

## Adjusting the interior lighting



- Switches the front interior lighting on/ off.
- Switches the rear interior lighting on/ off.
- 3 Switches automatic interior lighting control on/off.
- To switch reading lamps on/off: hold your hand under the respective reading lamp (1) or

## Operating unit inside the grab handle (rear passenger compartment)



- 器 Rear reading lamp
- To switch on or off: press button ①.

## Adjusting the ambient lighting

Multimedia system:

→ Comfort → Ambient Light

## Setting the color

- Select Color.
- Select Monochrome or Multi-color.

Set the desired color or color scheme.

## Adjusting the brightness

- Select Brightness.
- Adjust the brightness.
- Depending on the ambient light, the ambient lighting will automatically switch between day and night modes.

## Activating the brightness for zones

- Select Brightness.
- Switch off Link Zones. The Direct, Indirect and Accents zones can be set separately.

# Activating effects

WARNING Risk of accident if ambient lighting and active ambient lighting effects are not switched on

The warning assistance effects will be fully active only when the relevant driving or driving safety systems are activated on the Driving Assistance menu.

- Make sure that the relevant driving or driving safety systems are activated.
- (i) Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).
- Select Effects.
- Activate the desired effect.
- Different effects will be available depending on the vehicle equipment.

## Operating feedback effects

· Climate: If changes are made to the temperature setting in the vehicle, the color of the ambient lighting will change briefly.

## Warning When Exiting

• If an object is detected in the blind spot while you are getting out of the vehicle, the ambient lighting in the affected door will flash red. Further information on the exit warning  $(\rightarrow page 264)$ .

#### 144 Light and visibility

#### Multi-color Animation

• The chosen color combination will change at predefined intervals.


# Switching the interior lighting switch-off delay time on/off

Multimedia system:

- → 🔝 >> Settings >> Light
- >> Interior/Exterior Lighting
- >> Internal Lighting Display
- Activate or deactivate Internal Lighting Display.

If this function is active, the interior lighting will be switched on for a short time after the end of the journey.


# Windshield wiper and windshield washer system Switching the windshield wipers on/off



- 1 0 Windshield wipers off
- 2 ••• Automatic wiping, normal
- 3 •••• Automatic wiping, frequent
- 4 Continuous wiping, slow
- 5 Continuous wiping, fast

- Turn the combination switch to the corresponding position 1 5.
- Single wipe: press button 
  as far as the pressure point.
- Wiping with washer fluid: press button beyond the pressure point.
- (i) Observe the notes on washing the vehicle in a car wash (→ page 377).

## Switching the rear window wiper on/off



- Single wipe/washing
- Single wipe: press button (1) as far as the point of resistance.
- Wiping with washer fluid: press button (1) beyond the point of resistance.

Switching intermittent wiping on/off: press button 2.

The symbol will appear on the driver's display when the rear window wiper is switched on

## Changing the windshield wiper blades

WARNING Risk of becoming trapped if the windshield wipers are switched on while wiper blades are being replaced

If the windshield wipers begin to move while you are changing the wiper blades, you can be trapped by the wiper arm.

Always switch off the windshield wipers and vehicle before changing the wiper blades.

## Moving the wiper arms into the replacement position


Switch the vehicle on and then off again immediately.

- ▶ Within around 15 seconds, press the 🍪 button on the combination switch for approximately three seconds ( $\rightarrow$  page 144). The wiper arms will move into the replacement position.
- (i) Depending on the production period of the vehicle, different variants of the wiper blades will have been installed.

## Removing the wiper blades (variant 1)

Fold the wiper arms away from the windshield.


## 146 Light and visibility



- Press release knob ②.
- Remove the wiper blade in the direction of arrow (3) away from the wiper arm.

## Removing the wiper blades (variant 2)


Fold the wiper arms away from the windshield.



- Slide catch ② in the direction of arrow ③
  until it engages in the removal position.

Remove the wiper blade from the wiper arm in the direction of arrow (4).

## Installing the wiper blades (variant 1)




- Insert the new wiper blade in to the wiper arm in the direction of arrow until release knob engages.
- Make sure that the wiper blade is seated correctly.

- Fold the wiper arms back onto the windshield.
- Switch on the vehicle.
- Press the button on the combination switch.

The wiper arms will return to their original positions.

Switch off the vehicle.


## Installing the wiper blades (variant 2)



- Insert the new wiper blade into the wiper arm in the direction of arrow 1.
- Slide catch 2 in the direction of arrow 3 until it engages in the locking position.
- Make sure that the wiper blade is seated correctly.
- Fold the wiper arms back onto the windshield.
- Switch on the vehicle.
- Press the button on the combination switch. The wiper arms will return to their original
  - positions.
- Switch off the vehicle.

### Maintenance display

A maintenance display can be found at the tip of the blade on the newly installed wiper blades.



Remove protective film (1) from the maintenance display.

When the color of the maintenance displays changes from black to yellow, you should replace the wiper blades.


## Replacing the rear window wiper blade

WARNING Risk of becoming trapped if the windshield wipers are switched on while wiper blades are being replaced

If the windshield wipers begin to move while you are changing the wiper blades, you can be trapped by the wiper arm.


Always switch off the windshield wipers and vehicle before changing the wiper blades.

## Removing the wiper blade



- Switch off the vehicle.
- Fold wiper arm ② away from the rear window until it engages in the replacement position.
- Unclip wiper blade 1 from wiper arm 2 and remove it in the direction of arrow 3.

## Installing the wiper blade



- Position wiper blade (1) with both lugs (3) on holder (2) on the wiper arm.
- Push wiper blade in the direction of arrow
   until it engages in holder .
- Make sure that wiper blade is seated correctly.

Fold the wiper arm from the replacement position back onto the rear window.

#### Mirrors

## Operating the outside mirrors

WARNING Risk of accident due to adjusting the vehicle settings while the vehicle is in motion

You could lose control of the vehicle in the following situations in particular:


- If you adjust the driver's seat, the head restraint, the steering wheel or the mirror while the vehicle is in motion
- If you fasten your seat belt while the vehicle is in motion
- Before starting the vehicle: in particular, adjust the driver's seat, head restraint, steering wheel and mirror, and fasten your seat belt.

WARNING Risk of accident due to misjudgment of distance when using the front-passenger mirror

The outside mirror on the front passenger side reflects objects on a smaller scale. The objects in view are in fact closer than they appear.

Therefore, always look over your shoulder to check the actual distance between you and the road users traveling behind you.

## Adjusting the outside mirrors



- Use button 2 or 4 to select the desired mirror.
- Use button 1 to adjust the position of the selected mirror.

# Folding the outside mirrors in/out (vehicles with electrically folding outside mirrors)

- Briefly press button 3.
- (i) If the battery has been disconnected or has discharged, the outside mirrors must be moved briefly using button (3). Only then will the automatic mirror folding function work properly.

## Engaging the outside mirrors

If an outside mirror has been forcibly disengaged, proceed as follows.

- Vehicles without electrically folding outside mirrors: move the outside mirror into the correct position manually, until it engages audibly.
- Vehicles with electrically folding outside mirrors: press and hold button (3).
  You will hear a click and the mirror will audibly engage. The outside mirror will now be set to the correct position.

## Automatic anti-glare mirrors function

A

**WARNING** Risk of acid burns and poisoning due to the anti-glare mirror electrolyte

Electrolyte may escape if the glass in an automatic anti-glare mirror breaks.

The electrolyte is hazardous to health and causes irritation. It must not come into contact with your skin, eyes, respiratory organs or clothing or be swallowed.

- If you come into contact with electrolyte, observe the following:
  - Immediately rinse the electrolyte from your skin with water and seek medical attention.
  - If electrolyte comes into contact with your eyes, immediately rinse them thoroughly with clean water and seek medical attention.
  - If the electrolyte is swallowed, immediately rinse your mouth out thoroughly. Do not induce vomiting. Seek medical attention immediately.

- Immediately change out of clothing which has been contaminated with electrolyte.
- If an allergic reaction occurs, seek medical attention immediately.

The inside rearview mirror and the outside mirror on the driver's side will automatically go into antiglare mode if light from a headlamp hits the sensor on the inside rearview mirror.

## System limits

The system will not go into anti-glare mode if:

- · The vehicle is switched off.
- · Reverse gear is engaged.
- · The interior lighting is switched on.

# Front-passenger outside mirror parking position function

The parking position makes parking easier.

The front-passenger outside mirror will swivel downwards in the direction of the rear wheel on the front passenger's side when:


- The parking position is stored ( $\rightarrow$  page 151).
- The front-passenger mirror is selected.
- · Reverse gear is engaged.

The front-passenger outside mirror will move back to its original position when:

- You shift the transmission to another transmission position.
- You are traveling at a speed greater than 9 mph (15 km/h).
- You press the button for the outside mirror on the driver's side.

## Storing the parking position of the frontpassenger outside mirror using reverse gear

## Storing



- Select the front-passenger outside mirror using button 2.
- Engage reverse gear.

Move the front-passenger outside mirror into the desired parking position using button 1.

## Calling up

- Select the front-passenger outside mirror using button 2.
- Engage reverse gear. The front-passenger outside mirror will move into the stored parking position.


## Activating/deactivating the automatic mirror folding function

Multimedia system:

- → Settings → Vehicle >> Open/Close
- Activate or deactivate Automatic Mirror Folding.

## 152 Light and visibility

# Area permeable to radio waves on the windshield



Radio-controlled equipment such as toll systems can be mounted only on areas 
one of the windshield that are permeable to radio waves.

Areas permeable to radio waves are best visible from outside the vehicle when the windshield is illuminated with an external light source.

Note this position for vehicles with:

· Windshield heater


## Overview of climate control systems

#### Notes on climate control

An interior air filter in combination with the prefilter in the engine compartment must always be used so that the air conditioning system, pollution level monitoring and the air filtration work correctly. Use filters recommended and approved by Mercedes-Benz. Always have maintenance work carried out at a qualified specialist workshop.

## Overview of the THERMATIC climate bar

The indicator lamps indicate that the corresponding functions are activated.




- Increases the temperature
- Output Description
  Output Descript examples of 4 switching climate control on/off (→ page 155) and **SYNC** synchronization function ( $\rightarrow$  page 158)
- Defrosts the windshield
- A/C Activates/deactivates the A/C function  $(\rightarrow page 156)$

- Switches the rear window defroster on/off
- Reduces the temperature
- Depending on vehicle equipment and settings: temperature display, defrost function display, display for pre-entry climate control or auxiliary heating
- Switches air-recirculation mode on/off  $(\rightarrow page 158)$
- EMENU Calls up the air conditioning menu  $(\rightarrow page 156)$
- AUTO Sets climate control to automatic mode  $(\rightarrow page 157)$
- \$\frac{1}{2} \text{ Increases the airflow or switches on cli- $\overline{\text{mate}}$  control ( $\rightarrow$  page 155)
- Reduces the airflow or switches off cli- $\overline{\text{mate}}$  control( $\rightarrow$  page 155)
- (i) The availability of individual functions depends on the country and equipment.

#### 154 Climate control

## Overview of THERMOTRONIC climate bar

The indicator lamps indicate that the corresponding function is activated.



Front climate bar on the central display (example)

- Increases the temperature
- SYNC Synchronization function (→ page 158)

- Switches off climate control  $(\rightarrow page 155)$
- Switches air-recirculation mode on/off (→ page 158)
- Opening the state of the sta
- A/c Activates/deactivates the A/C function
   (→ page 156)

Activates/deactivates residual heat utilization  $(\rightarrow page 158)$ 

- Switches the rear window defroster on/off
- Openating on vehicle equipment and settings:

Temperature display

Display for the defrost function


# Airflow

Pre-entry climate control or auxiliary heating

- Sets climate control to automatic mode, right ( $\rightarrow$  page 157)

- Menu Calls up the air conditioning menu (→ page 156)
- Reduces the airflow or switches off climate control  $(\rightarrow page 155)$
- (i) The climate bar is visible even when the vehicle is parked or the air conditioning is switched off (→ page 155).
- i The availability of individual functions is country- and equipment-dependent.

## Overview of the rear operating unit



Example: USA

- Sets the air distribution to the center air vents in the rear passenger compartment, left
- Sets the temperature in the rear passenger compartment, left

- Sets the airflow in the rear passenger compartment, left, or switches climate control on/off ( $\rightarrow$  page 156)
- Switches climate control on / off  $(\rightarrow page 156)$
- Sets the airflow in the rear passenger compartment, right, or switches climate control on/off ( $\rightarrow$  page 156)
- Sets the temperature in the rear passenger compartment, right
- Sets the air distribution to the center air vents. in the rear passenger compartment, right
- Sets rear passenger compartment climate control to automatic mode, right
- Sets the air distribution to the footwell vents. in the rear passenger compartment, right
- Synchronization is activated ( $\rightarrow$  page 158)
- Sets the air distribution to the footwell vents. in the rear passenger compartment, left
- Sets rear passenger compartment climate control to automatic mode. left

The settings for the second row of seats can be configured via the rear operating unit or the multimedia system (→ page 157) depending on the vehicle's equipment.

# Operating the climate control system

Switching climate control on/off

## Switching on climate control

Set the airflow to level 1 or higher via 4 on the climate bar on the central display

Press Auto. ▼ Or FMENU.

## Switching off climate control

Set the airflow to level 0 via so on the climate bar on the central display

or

or

Press Ca

If climate control is switched off, the windows may fog up more quickly. Switch climate control off only briefly.

(i) If you switch off climate control by pressing d, fragrancing, if enabled, will also be switched off automatically.

#### **156** Climate control

# Switching climate control on/off via the rear operating unit

## Switching on

Press button 4.

or

Set the airflow to level 1 or higher using buttons (3) and (5).

or

Press buttons 2, 6, 8 or 2.

## Switching off

Press button 4.

or

- Set the airflow to level 0 using buttons (3) and (5).
- i If rear climate control is switched off via button (a), OFF will be shown on the displays.

# Switching the A/C function on/off using the air conditioning control panel

The A/C function heats, cools and dehumidifies the vehicle's interior air.

- Press the A/c button.
- (i) Switch off the A/C function only briefly, otherwise the windows may fog up more quickly. Condensation may drip from the underside of the vehicle when cooling mode is active. This is not indicative of a malfunction.

# Calling up the air conditioning menu via the climate bar or the air conditioning control panel

The air conditioning menu can be called up via the climate bar. The climate bar is always shown on the lower edge of the central display.

- Select the Climate Menu entry in the air conditioning bar.
  - The First Row of Seats menu is opened.

## Defrosting the windshield via the climate bar

## Switching on

Press on the climate bar on the central display.

## Switching off

Press , Auto or on the climate bar on the central display.

or

- Set the airflow to 0.
- (i) When the defrost function is activated, some functions (e.g. the temperature setting) will automatically be deactivated.

# Activating/deactivating the A/C function via the air conditioning menu

Multimedia system:

## → Climate Menu ➤ First Row of Seats

Depending on the external conditions, support for improved cooling and dehumidification of the interior air will be provided when the A/C function is activated. If it is not possible to operate the A/C

function on the climate bar on the central display. switch the function on or off in the climate menu of the central display.

Select A/C (A/C).

## Setting climate control to automatic mode

In automatic mode, the set vehicle interior temperature is controlled automatically and maintained at a constant level by the air supply.

- Press AUTO on the climate bar on the central display.
- (i) You can increase or reduce the airflow by pressing \( \mathbb{\partial} \) on the climate bar on the multimedia system. The airflow will automatically be reduced in the event of an incoming call. You will still be able to adjust the airflow manually by pressing \\ \text{\formalfolds} \\ \text{ln automatic mode,} \end{array} five levels can be set via the controller and seven levels can be set without automatic mode.
- To switch to manual operation: switch off automatic mode or adjust the air distribution, e.g. 😼 .

## Setting air distribution via the air conditioning menu

Multimedia system:

- → Climate Menu
- Select First Row of Seats or Second Row of Seats.
- To set air distribution: select النها, المراة or . قر
- Set the airflow.
- When the air conditioning system is switched on, at least one zone is always active. However, several air distribution options can be selected at the same time, for example to set the climate control for the vehicle interior and the footwells simultaneously. The will climate control for the windshield can only be selected for the first seat row. When automatic mode is active, the buttons for setting the air distribution are deactivated automatically. If the air conditioning system is deactivated, the buttons remain operable and the last setting is saved.

## Setting rear climate control using the air conditioning menu

Multimedia system:

¬→ Climate Menu

## Setting the temperature

- Select Second Row of Seats.
- Set the temperature.

## Setting the airflow

- Select Second Row of Seats.
- Set the air flow with or .

### Controlling the rear climate control automatically

- Select AUTO.
- (i) When the defrost function is activated, some functions (e.g. the temperature setting) will automatically be deactivated. To deactivate the defrost function, press either WAX, AUTO or c set the air flow to level 0  $(\rightarrow page 156)$ .

#### 158 Climate control

# Switching the synchronization function on/off via the air conditioning menu

Multimedia system:

#### → Climate Menu → First Row of Seats

The synchronization function controls the climate control centrally. The driver's settings for temperature, airflow and air distribution are automatically adopted for each climate zone.

► Select SYNC (SYNC).

## Defrosting the windows

### Windows fogged up on the inside

- Press AUTO on the climate bar on the central display.
- If the windows remain fogged up: press was on the climate bar on the central display.

## Windows fogged up on the outside

Switch on the windshield wiper.

# Switching air-recirculation mode on/off via the air conditioning menu

#### Requirements

• The THERMOTRONIC air conditioning control panel is available.

#### Multimedia system:

- → Climate Menu ➤ First Row of Seats
- Press in the upper display area of the climate bar.

The interior air will be recirculated.

Air-recirculation mode will automatically switch to fresh air mode after a while.

(i) If air-recirculation mode is switched on, the windows may fog up more quickly. Switch on air-recirculation mode only briefly.

## Switching air-recirculation mode on/off

- Press on the climate bar on the central display.
  - The interior air will be recirculated.

Air-recirculation mode will automatically switch to fresh air mode after a while.

i If air-recirculation mode is switched on, the windows may fog up more quickly. Switch on air-recirculation mode only briefly.

# Switching residual heat mode on/off via the climate bar

#### Requirements

- The residual heat function is available.
- The vehicle is parked.
- · The coolant temperature is sufficiently high.

It is possible to make use of the residual heat from the engine to continue heating the front compartment of the vehicle for approximately 30 minutes, depending on the temperature set.

To switch on or off: select Residual Heat on the climate bar of the central display.

The residual heat function will automatically switch off after a while.

(i) If residual engine heat utilization is activated. the two buttons for setting the temperature and air distribution will automatically be deactivated.

## Activating/deactivating ionization

Multimedia system:

## ¬→ Climate Menu → Air Quality

When ionization is activated, the air inside the vehicle is enriched with negatively charged oxygen ions. These can promote the well-being of the occupants.

- Select Ionization.
- (i) The function can only be performed if AUTO mode is activated or the air distribution is set to the side air vent. The function is restricted if the side air vents on the driver's side are closed.

## Fragrance system

Activating/deactivating the fragrance system using the multimedia system

#### Requirements

- Automatic climate control is activated.
- The glove compartment will close.
- A flacon is inserted.

Multimedia system:

## → Climate Menu >> Air Quality

The fragrance system distributes a pleasant fragrance throughout the vehicle interior from a flacon located in the glove compartment.

- Navigate down until the climate control bar is active.
- Select Fragrance.
- Activate or deactivate fragrancing.
- Setting the fragrance system

## Requirements

- The climate control system is switched on.
- The glove compartment is closed.

A flacon is inserted.

Multimedia system:

→ Climate Menu ➤ Air Quality

- Select Fragrance.
- Keep pressing until the desired intensity is reached.
- Inserting or removing the flacon of the fragrance system

WARNING Risk of injury from liquid perfume

If children open the flacon, they could drink the liquid perfume or it could come into contact with their eves.

- Do not leave children unattended in the vehicle.
- Consult a doctor immediately if liquid perfume has been drunk.
- If liquid perfume comes into contact with your eyes or skin, rinse your eyes with clean water.

#### 160 Climate control


flacons

If symptoms continue, consult a doctor.



Full flacons must not be disposed of together with household waste.

Hand in full flacons at a pollutant collection point.



- ① Cap
- Placon
- To insert: slide the flacon into the holder as far as it will go.
- To remove: after opening the glove compartment, wait for approximately seven seconds and pull out the flacon.

If you do not use genuine Mercedes-Benz interior perfumes, observe the manufacturers' safety notices on the perfume packaging.

Dispose of the genuine Mercedes-Benz interior perfume flacon when it is empty and do not refill it

#### Refillable flacon

- Unscrew the cap of the empty flacon.
- Fill the flacon with a maximum of 0.5 fl. oz. (15 ml).
- Screw the cap back onto the flacon.

Always refill the empty refillable flacon with the same perfume. Observe the separate information sheet that comes with the flacon.

#### Information on the windshield heater

The windshield heater is switched on automatically if the  $[m]^{MX}$  button is activated.

After the vehicle is started, the windshield heater will be switched on automatically as required.

## Pre-entry climate control when the vehicle is unlocked

## Function of pre-entry climate control when the vehicle is unlocked

The seats can be briefly preheated or precooled before you get into the vehicle.

Depending on the vehicle's equipment, the following functions will be activated as needed during precooling:

- Automatic climate control
- Blower
- Seat ventilation

Depending on the vehicle's equipment, the following functions will be activated as needed during preheating:

- · Automatic climate control
- Blower
- Seat heating
- · Steering wheel heater
- Mirror heater
- Rear window defroster

Depending on the vehicle's equipment, the following functions will also be adjusted during preentry climate control if they have already been switched on during regular vehicle operation:

- Fragrancing
- Ionization
- Setting pre-entry climate control when the vehicle is unlocked in the multimedia system Multimedia system:
- → Climate Menu → Pre-entry Climate Ctrl.
- (i) This function is available only for plug-in hybrid vehicles.
- Activate or deactivate the function.

### Selecting seats

Select Driver, Passenger, Rear Left or Rear Right.

The seat-specific functions of pre-entry climate control (e.g. seat heating) will be performed for the selected seats.

When pre-entry climate control is enabled, an LED on the climate bar on the central display will light

up blue for a cooled vehicle and red for a heated vehicle.

Activating/deactivating pre-entry climate control when the vehicle is unlocked

## Requirements

- The high-voltage battery is charged sufficiently.
- The function has been activated via the multimedia system.
- To switch on: unlock the vehicle. The climate control functions are activated for up to five minutes for pre-heating and precooling.

Pre-entry climate control when the vehicle is unlocked cannot be activated more than twice when the vehicle is switched off.

To switch off: press sign on the climate bar on the central display.

#### 162 Climate control

Depending on the vehicle equipment, the following functions will remain active once the vehicle has been started:

- Seat heating
- Seat ventilation
- Fragrancing
- ionization

## Pre-entry climate control for departure time

■ Pre-entry climate control for departure time function



**WARNING** Risk of fatal injury due to exposure to extreme heat or cold in the vehicle

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold, there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.

# A

**WARNING** Risk of burns due to repeatedly switching on the seat heating

Repeatedly switching on the seat heating can cause the seat cushion and seat backrest padding to become very hot.

In particular, the health of persons with limited temperature sensitivity or a limited ability to react to high temperatures may be affected or they may even suffer burn-like injuries.

Do not repeatedly switch on the seat heating.

To protect against overheating, the seat heating may be temporarily deactivated after it has been switched on repeatedly.

(i) The pre-entry climate control for departure time function is available only for vehicles with 48 V on-board electrical systems.

The air inside the vehicle can be heated, ventilated or cooled to the set temperature when the vehicle is parked.

When the vehicle is connected to power supply equipment, priority will be given to charging the

48 V battery to a specified minimum state of charge.

The running time of pre-entry climate control may be reduced in the following circumstances:

- The vehicle is not connected to power supply equipment.
- The 48 V battery is not fully charged.

The running time of pre-entry climate control may be reduced in the following circumstances:

- The vehicle is not connected to power supply equipment.
- The high-voltage battery is not fully charged

With active pre-entry climate control, the state of charge of the 48 V battery may be reduced, even if the charging cable connector is connected.

If available, seat ventilation will be activated in the cooling and ventilation modes.

Depending on the vehicle's equipment, the following functions will be activated in heating mode, if available:

· Seat heating

- · Steering wheel heater
- Mirror heater
- · Rear window defroster

When the set temperature changes, climate control mode will automatically switch:

- From heating mode to ventilation or cooling mode, or
- from cooling mode to ventilation or heating mode, or
- from ventilation mode to heating or cooling mode
- Setting pre-entry climate control at departure time via the multimedia system

  Multimedia system:

→ Climate Menu → Pre-entry Climate Ctrl.

### Setting the departure time

 Plug-in hybrid: the set departure times are used for the vehicle's pre-entry climate control and for predictions regarding the approximate state of charge and range at the time selected. Additional information on the charging settings: ( $\rightarrow$  page 334).

- Select Edit Departure Time 🖊 .
- Select a departure time or set a new departure time.

#### Setting the repeat days

- Set the desired departure time and select the corresponding weekdays on which this departure time is to apply.
- Press OK to confirm.

## Selecting seats

- Select Driver, Passenger, Rear Left or Rear Right.
   Pre-entry climate control will take place for
- the selected seats.

  Activating/deactivating pre-entry climate con-

## Requirements

trol for departure time

 The 48 V battery or the high-voltage battery is charged sufficiently.

- The function has been activated via the multimedia system.
- To activate: set the departure time (→ page 163).
  Vehicles with 48 V on-board electrical system: Pre-entry climate control for departure time will switch on a maximum of 5 minutes before the selected departure time.
  - Plug-in hybrid: Pre-entry climate control for departure time will switch on a maximum of 55 minutes before the selected departure time. It will remain active for another five minutes if departure is delayed.
- To deactivate the pre-entry climate control for departure time early: press [ st ] on the climate bar on the central display or switch off the preselection of the time in the climate menu.

If present, the following functions will remain active once the vehicle has been started:

- Seat heating
- · Seat ventilation

#### 164 Climate control

Depending on the vehicle's equipment, the following functions will also be adjusted during preentry climate control if they have already been switched on during regular vehicle operation:

- Fragrancing
- Ionization

# Activating/deactivating immediate pre-entry climate control



**WARNING** Risk of fatal injury due to exposure to extreme heat or cold in the vehicle

If persons, particularly children, are subjected to prolonged exposure to intense heat or cold, there is a risk of severe injury or even death.

Never leave persons, particularly children, unattended in the vehicle.

# A

**WARNING** Risk of burns due to repeatedly switching on the seat heating

Repeatedly switching on the seat heating can cause the seat cushion and seat backrest padding to become very hot.

In particular, the health of persons with limited temperature sensitivity or a limited ability to react to high temperatures may be affected or they may even suffer burn-like injuries.

Do not repeatedly switch on the seat heating.

To protect against overheating, the seat heating may be temporarily deactivated after it has been switched on repeatedly.

## Requirements

• The vehicle is switched off.

Air conditioning of the vehicle interior can continue, e.g. if a journey is interrupted, for up to 50 minutes in the case of plug-in hybrids and up to 5 minutes in the case of some models with a 48 V on-board electrical system.

- - The red or blue indicator lamp below the climate bar on the central display will light up or go out.
- ➤ Set the temperature using the arrows ▼▲ on the climate bar on the central display.

The colors of the indicator lamp have the following meanings:

- Blue: stationary ventilation is switched on.
- Red: the stationary heater is switched on.
- Yellow: the departure time is preselected.

#### Air vents

Adjusting the front air vents



**WARNING** Risk of burns or frostbite due to being too close to the air vents

Very hot or very cold air can flow from the air vents.

- Make sure that all vehicle occupants always maintain a sufficient distance from the air vents.
- If necessary, direct the airflow to another area of the vehicle interior.

To guarantee the flow of fresh air through the air vents into the vehicle interior, note the following:

- Always keep the vents and ventilation grilles in the vehicle interior clear.
- Keep the air inlet free of residue build-up  $(\rightarrow page 377)$ .



- To open or close: hold the center of air vent 1 and turn it to the left (open) or right (closed) as far as it will go.
- To set the airflow direction: hold the center of air vent 1 and move it up or down or to the left or right.

## Adjusting the rear air vents



- To open or close: turn controller 1 to the left or right as far as it will go.
- To set the airflow direction: hold the center of controller 1 and move it up or down or to the left or right.

### 166 Driving and parking

## Driving

### Notes on Mercedes-AMG vehicles

Observe the notes on the following topics in the supplement. You may otherwise fail to recognize potential dangers.

- (i) Availability of some functions depends on the respective equipment and model.
- · Reduction of engine output and engine torque
- · AMG Real Performance Sound
- RACE START
- Boost strategy
- . AMG RIDE CONTROL
- AMG ACTIVE RIDE CONTROL
- AMG steering wheel buttons

## Notes on plug-in hybrids

## Notes on plug-in hybrid operation

A

WARNING Risk of chemical burns and poisoning from damaged high-voltage battery

If the housing of the high-voltage battery has been damaged, electrolyte and gases may leak out.

- Avoid contact with the skin, eyes or clothing.
- Immediately rinse electrolyte splashes off with water and seek medical attention straight away.
- A

 DANGER Risk of fire and explosion from excessive internal pressure of the highvoltage battery

In the event of a vehicle fire, flammable gas can escape and ignite.

If there is an unusual smell, smoke or burn marks, stop the charging process immediately.

- Leave the danger zone immediately.
   Secure the danger area at a sufficient distance.
- Call the fire service.

### ! NOTE Mercedes-AMG vehicles

Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The hybrid system combines a combustion engine with an electric motor.

Characteristics when the vehicle is at a standstill:

- The combustion engine is generally switched off.
- · Idle speed occurs only in certain instances.

Characteristics when the vehicle is started:

 If the high-voltage battery is sufficiently charged, the vehicle can be started with the electric drive system without the combustion engine (noiseless start).

- If the high-voltage battery for the electric drive system is not sufficiently charged or the vehicle conditions for a silent start are not met. the vehicle will start with the combustion engine.
- i Depending on the system, it may be that even though the high-voltage battery is charged, electric mode has restricted or no availability. When the combustion engine has run for long enough and the ambient conditions permit, electric mode will be available without restriction once more.

Characteristics with moderate power output requests:

- The combustion engine is switched off as often as possible during a journey.
- Depending on the drive program selected and the state of charge of the high-voltage battery, the vehicle can be accelerated electrically up to a speed of approximately 87 mph (140 km/h).

Characteristics with high power output requests:

- The electric motor supports the combustion engine (boost effect), e.g. when pulling away or accelerating.
- The high-voltage battery is discharging.

Characteristics when the accelerator pedal is released during the journey:

- The electric motor is operated as an alternator when in overrun mode and during braking.
- . The high-voltage battery is charging.

Notes on electric mode:

- · Vehicles with hybrid systems generate significantly less noise when stationary and when being driven than vehicles with combustion engines.
- In electric mode, the vehicle may not be heard by other road users due to the significantly reduced noise generated when the vehicle is in motion and when at a standstill.

It is for this reason that the vehicle is equipped with a sound generator, which serves as an acoustic vehicle alerting system (AVAS). This safety system is prescribed by law.

The external noise produced by the sound generator is perceptible in the vehicle interior when the vehicle is stationary and at low speeds and does not represent a malfunction.

- If not all of the vehicle conditions for electric mode are met, the combustion engine will be switched on.
- Performance restrictions in electric mode are possible as a result of the operating temperature of the high-voltage battery and drive system, the ambient temperature and aging of the high-voltage battery.
- In electric mode, the maximum power will not be permanently available and may drop to continuous output.

Notes on the acoustic vehicle alerting system:

· The sound generator produces idling and speed-dependent driving noises up to a speed of approximately 19 mph (30 km/h).

### 168 Driving and parking

- This will help other road users, particularly pedestrians and cyclists, to hear your vehicle better.
- From a speed of 13 mph (20 km/h), the acoustic vehicle alerting system gradually switches off.

## Manually disconnecting the high-voltage onboard electrical system

DANGER Risk of death and fire due to modified and/or damaged components of the high-voltage on-board electrical system

The vehicle's high-voltage on-board electrical system is under high voltage. If you modify component parts in the vehicle's high-voltage on-board electrical system or touch damaged component parts, you may be electrocuted. In addition, modified and/or damaged components may cause a fire.

In the event of an accident or impact to the underbody, components of the high-voltage electrical system may be damaged although the damage is not visible.


- Never make any modifications to the high-voltage on-board electrical system.
- Do not switch on or use the vehicle if its high-voltage on-board electrical system components have been modified or damaged.
- Never touch damaged components of the high-voltage on-board electrical system.
- After an accident, do not touch any components of the high-voltage on-board electrical system.
- After an accident, have the vehicle transported away.
- Have the components of the high-voltage on-board electrical system checked at a qualified specialist workshop and replaced if necessary.

## Requirements

Only disconnect the high-voltage on-board electrical system manually in the following situations:

- The restraint system warning lamp | Iights up in the driver display, e.g. after an accident.
- The vehicle is badly damaged, e.g. after an accident, and the restraint system components have not been triggered.

## Operating the high-voltage disconnect device



- Switch off the vehicle.
- Shift the transmission to position **P**.
- Apply the electric parking brake.
- Secure the vehicle against rolling away.
- Open the hood.

- Observe additional label (3) for high-voltage disconnect device 2.
- Press release tab 
  in the direction of the arrow and pull it out.
- Pull high-voltage disconnect device 2 in the direction of the arrow until it engages. The high-voltage on-board electrical system is switched off.

All work on the hybrid drive system -- (including after disconnecting the high-voltage on-board electrical system manually) may only be carried out in a qualified specialist workshop.

## Switching on the power supply or the vehicle

**A** WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle, they could, in particular:

· open doors, thereby endangering other persons or road users.

- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.


In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- · changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

## Requirements

- The key is in the vehicle and is detected.
- The brake pedal is not depressed.

## 170 Driving and parking



To switch on the power supply: press button once.

You can, for example, switch on the windshield wiper.

The power supply will be switched off again if the following conditions are met:

- You open the driver's door.
- You press button 1 twice more.

To switch on the vehicle: press button twice.

Indicator and warning lamps will light up on the driver's display.

The vehicle will be switched off again if one of the following conditions is met:

- You do not start the vehicle within 15 minutes and the transmission is in position P or the electric parking brake is applied.
- You press button 1 once.

## Starting the vehicle

Starting the vehicle with the start/stop button

**A** DANGER Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

- Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation.
- ▲ WARNING Risk of fire due to flammable materials in the engine compartment or on the exhaust system

Flammable materials may ignite.

Therefore, regularly check that there are no flammable foreign materials in the engine compartment or on the exhaust system.

#### Requirements

- The key is in the vehicle and is detected.
- $\triangleright$  Shift the transmission to position  $\boxed{P}$  or  $\boxed{N}$ .
- depress the brake pedal and press button once.
- If the vehicle does not start: switch off nonessential consumer equipment and press button once.
- If the vehicle still does not start and the Place the Key in the Marked Space See Operator's

Manual display message appears on the driver's display: start the vehicle with the key in the marked space (emergency operation mode) ( $\rightarrow$  page 171).

(i) You can switch off the vehicle while driving. To do this, press and hold button (1) for about three seconds or press button (1) three times within three seconds. Be sure to observe the safety notes concerning this under "Driving tips" ( $\rightarrow$  page 174).

Observe any information regarding display messages that may be shown on the driver's display.

Starting the vehicle with the key in the marked space (emergency operation mode) If the vehicle does not start and the Place the Key in the Marked Space See Operator's Manual display message appears on the driver's display, you can start the vehicle in emergency operation mode.



- Make sure that marked space (2) is empty.
- Remove key 1 from the key ring.
- Place key 1 on the symbol in marked space **2**.

The vehicle will start after a short time.

If you remove key 1 from marked space 2, the vehicle can still be driven. For further engine starts, however, key 10 must be located on the symbol in marked space 2 during the entire trip.

Have key (1) checked at a qualified specialist workshop.

#### If the vehicle does not start:

- Place key 1 in marked space 2 and leave it there.
- Depress the brake pedal and start the vehicle using the start/stop button.
- (i) You can switch on the power supply or the vehicle with the start/stop button.

Observe any information regarding display messages that may be shown on the driver's display.

## Starting the vehicle via Remote Online Services

## Cooling or heating the vehicle interior before starting the journey

Ensure the following before starting the engine:

- The legal stipulations in the area where your vehicle is parked allow engine starting via smartphone.
- It is safe to start and run the engine where your vehicle is parked.
- . The fuel tank is sufficiently full.
- The starter battery is sufficiently charged.

### 172 Driving and parking

# Charging the starter battery before starting the journey

You can receive a message on your smartphone when the state of charge of the starter battery is low. You can then start the vehicle with the smartphone to charge the battery. The vehicle is automatically switched off after ten minutes.

Ensure the following before starting the engine:

- The legal stipulations in the area where your vehicle is parked allow engine starting via smartphone.
- It is safe to start and run the engine where your vehicle is parked.
- The fuel tank is sufficiently full.
- Starting the vehicle (Remote Online)

**WARNING** Risk of crushing or entrapment due to unintentional starting of the engine

Limbs could be crushed or trapped if the engine is started unintentionally during service or maintenance work.

Always secure the engine against unintentional starting before carrying out maintenance or repair work.

#### Requirements

- Park position P is selected.
- The anti-theft alarm system is not activated.
- The panic alarm is not activated.
- The hazard warning lights are off.
- The hood is closed.
- The doors are closed and locked.
- The windows and sliding sunroof are closed.
- Start the vehicle using the smartphone. After every vehicle start, the engine runs for ten minutes.

You can carry out a maximum of two consecutive starting attempts. You must start the vehicle once with the key before starting the vehicle again with the smartphone.

You can turn off the vehicle at any time as follows:

• via the Mercedes me App

- by pushing the button 🔒 or 🔕 on the key
- i Further information can be found in the Mercedes me App.

# Securing the engine against starting before carrying out maintenance or repair work:

- Turn on the hazard warning lights or unlock the doors.
- Open a side window or the sliding sunroof.

## Breaking-in notes

To preserve the engine during the first 1000 miles (1500 km):

- Drive at varying road speeds and engine speeds.
- Do not drive faster than 85 mph (140 km/h).
- Drive the vehicle in drive program c or E.

**Plug-in hybrid:** use drive program [1], [H] or [B].

- Then shift to the next higher gear at the very latest when the needle reaches the last third before the red area in the tachometer
- Do not shift down manually in order to brake.
- · Avoid overstraining the vehicle, e.g. by driving at full throttle.
- Do not depress the accelerator pedal past the pressure point (kickdown).
- Increase the engine speed only gradually and accelerate the vehicle to full speed after 1000 miles (1500 km).

This also applies when the engine or parts of the drivetrain have been replaced.

Please also observe the following breaking-in notes:

- In certain handling and driving safety systems, the sensors adjust automatically while a certain distance is being driven after the vehicle has been delivered or after repairs. Full system effectiveness is reached only when this teaching-in process has concluded.
- · Brake pads, brake discs and tires that are either new or have been replaced achieve opti-

mum braking effect and grip only after the vehicle has been driven several hundred kilometers. Compensate for the reduced braking effect by applying greater force to the brake pedal.

## Notes on optimized acceleration

If all necessary requirements and activation conditions are fulfilled, the best possible acceleration can be achieved from a standstill.

Do not use optimized acceleration on public roads. Individual wheels could spin and you could lose control of the vehicle. There is an increased risk of skidding and/or accident.

Be sure to observe the safety notes and information on ESP® ( $\rightarrow$  page 228).

## Pulling away with optimized acceleration

WARNING Risk of skidding and accidents due to the wheels spinning

If you pull away using optimized acceleration, individual wheels can spin and the vehicle can skid.

There is an increased risk of skidding and accidents, especially when ESP® is switched off!

Make sure that there are no persons or obstacles in the vicinity of the vehicle.

#### Requirements

- the vehicle is broken in ( $\rightarrow$  page 172).
- · the vehicle and tires are in good condition.
- the roadway has a high-grip surface.
- the engine and transmission are at normal operating temperature.

## 174 Driving and parking

! NOTE Increased wear due to optimized acceleration

When pulling away with optimized acceleration, all components of the drivetrain are subjected to a very high load.

This can lead to increased component wear.

- Do not always pull away with optimized acceleration.
- ► Engage the  $\boxed{\mathbf{D}}$  drive position ( $\rightarrow$  page 194).
- Move the steering wheel to the straight-ahead position.
- ▶ Select the drive program  $\bigcirc$  (→ page 190).
- ▶ Deactivating ESP<sup>®</sup> ( $\rightarrow$  page 230).
- Depress and hold the brake pedal firmly with your left foot.
- With your right foot, fully depress the accelerator pedal.

After no more than five seconds, take your left foot quickly off the brake, but keep the accelerator pedal depressed.

The vehicle will pull away at maximum acceleration.

Switch on ESP® once the acceleration procedure is complete.

## Ending optimized acceleration

- Remove your foot from the accelerator pedal.
- Reactivate ESP®.
- After you pull away with optimized acceleration, components of the drivetrain can become very hot, which means that optimized acceleration values may only be reached again after a few minutes.

## Notes on driving

WARNING Risk of accident due to objects in the driver's footwell

Objects in the driver's footwell may impede pedal travel or block a depressed pedal.

This will jeopardize the operating- and road safety of the vehicle.

- Stow all objects in the vehicle securely so that they cannot get into the driver's footwell.
- Make sure that there is always sufficient clearance for the pedals.
- Always install the floor mats securely and as prescribed.
- Do not use loose floor mats and do not place floor mats on top of one another.

 WARNING Risk of accident due to incorrect footwear

Incorrect footwear includes, for example:

- · Shoes with platform soles
- · Shoes with high heels
- Slippers

There is a risk of an accident.

Always wear suitable footwear so that you can operate the pedals safely.

WARNING Risk of accident if the vehicle is switched off while driving

If you switch off the vehicle while driving, safety functions are restricted or no longer available.

This may affect the power steering system and the brake force boosting, for example,

You will need to use considerably more force to steer and brake, for example.

Do not switch off the vehicle while driving.

**DANGER** Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation.

**WARNING** Risk of skidding and of an accident due to shifting down on slippery road surfaces

If you shift down on slippery road surfaces to increase the engine braking effect, the drive wheels may lose traction.

▶ Do not shift down on slipperv road surfaces to increase the engine braking effect

**DANGER** Risk of fatal injury due to poisonous exhaust gases

If the tailpipe is blocked or sufficient ventilation is not possible, poisonous exhaust gases such as carbon monoxide may enter the vehicle. This is the case, for example, if the vehicle gets stuck in the snow.

Keep the tailpipe and the area around the vehicle free from snow when the engine or the stationary heater is running.

Open a window on the side of the vehicle facing away from the wind to ensure an adequate supply of fresh air.

WARNING Risk of accident and injury due to being under the influence of alcohol and drugs while driving

Drinking and driving and/or taking drugs and driving are very dangerous combinations. Even a small amount of alcohol or drugs can affect your reflexes, perceptions and judgment.

The possibility of a serious or even fatal accident are greatly increased when you drink or take drugs and drive.

Do not drink or take drugs and drive or allow anyone to drive who has been drinking or taking drugs.

WARNING Risk of accident due to the brake system overheating

If you leave your foot on the brake pedal when driving, the brake system may overheat.

## 176 Driving and parking

This increases the braking distance and the brake system can even fail.

- Never use the brake pedal as a footrest.
- Do not depress the brake pedal and the accelerator pedal at the same time while driving.
- I NOTE Engine damage due to excessively high engine speeds

The engine will be damaged if you drive with the engine in the overrevving range.

- Do not drive with the engine in the overrevving range.
- I NOTE Wearing out the brake linings by continuously depressing the brake pedal
- Do not depress the brake pedal continuously whilst driving.
- To use the braking effect of the engine, shift to a lower gear in good time.

- ! NOTE Damage to the drivetrain and engine when pulling away
- Do not warm up the engine while the vehicle is stationary. Pull away immediately.
- Avoid high engine speeds and driving at full throttle until the engine has reached its operating temperature.
- I NOTE Damage to the catalytic converter due to non-combusted fuel

The engine is not running smoothly and is misfiring.

Non-combusted fuel may get into the catalytic converter.

- Only depress the accelerator pedal slightly.
- Have the cause rectified immediately at a qualified specialist workshop.

I NOTE Reduced battery life due to frequent short-distance trips

The 12 V battery may not be sufficiently charged when the vehicle is used only for short-distance trips. This reduces the life of the battery.

- Drive longer distances regularly to charge the battery.
- NOTE Vehicle damage due to failure to observe the maximum permissible clearance height

If the vehicle height exceeds the maximum permissible clearance height, the roof and other vehicle parts may be damaged.

- Please observe the maximum clearance height indicated.
- If the vehicle exceeds the permissible clearance height, do not drive in.
- Take the modified vehicle height into account in the case of roof superstructures or other carrier systems.

(i) Please bear in mind that all the speed values stated in this Operator's Manual are approximate and are subject to a certain tolerance.

## Observe the notes on driving with a roof load, trailer or fully laden vehicle.

Driving with a loaded roof luggage rack or trailer. or with the vehicle fully loaded or occupied. changes the handling and steering characteristics of vour vehicle.

Therefore please observe the following notes:

- Do not exceed the permissible roof load and trailer load. Also observe the information in the technical data in this respect.
- Distribute the roof load and vehicle load evenly and place heavy objects at the bottom. Also comply with the notes on loading the vehicle.( $\rightarrow$  page 113)
- Drive carefully, avoiding abrupt starting, braking and steering as well as fast cornering.

## Notes on driving on roads treated with de-icing salt

The braking effect is limited on road surfaces treated with de-icing salt.

Please therefore bear in mind the following notes:

- Due to salt build-up on the brake discs and brake linings, the braking distance can increase considerably or braking may be onesided.
- Maintain a much greater safety distance to the vehicle traveling ahead.

Remove salt build-up as follows:

- Brake occasionally, paying attention to the traffic conditions
- Carefully depress the brake pedal at the end of the journey and when starting the next journev

### Notes on hydroplaning

Hydroplaning can take place if a certain depth of water has built up on the road surface.

Observe the following notes during heavy precipitation or in conditions in which hydroplaning may occur:

- Reduce speed.
- Avoid tire ruts.

- · Avoid sudden steering movements.
- Brake carefully.
- (i) Also observe the notes on regularly checking wheels and tires ( $\rightarrow$  page 412).

Notes on driving through water on the road Water ingress can damage the engine, electrics

and transmission Water can also enter the air intake of the engine

and cause engine damage.

Observe the following if you need to drive through water:

- Observe the maximum permissible fording depth ( $\rightarrow$  page 458).
- Drive at a walking pace at most, otherwise water may enter the vehicle interior or engine compartment.
- · Vehicles traveling ahead, or oncoming vehicles, can create waves that may exceed the maximum permissible depth of water.

The braking effect of the brakes is reduced after fording. Brake carefully, paying attention to the

### 178 Driving and parking

traffic conditions, until braking power has been fully restored.

## Function of rear axle steering

The rear axle steering is an electromechanical auxiliary steering on the rear axle which adjusts the steering of the rear wheels according to the position of the front wheels, depending on the speed. This results in greater maneuverability and improved driving stability for the vehicle.

Rear axle steering has the following characteristics:

- reduced steering effort and turning circle resulting in reduced parking effort
- more direct steering resulting in improved control of the vehicle
- improved cornering of the vehicle

Observe the notes on snow chains and snow chain mode ( $\rightarrow$  page 413).

## Notes on off-road driving

lack

**WARNING** Risk of accident if you do not keep to line of fall on inclines

If you drive at an angle or turn on an incline, the vehicle could slip sideways, tip and rollover.

Always drive on inclines in the line of fall (straight up or down) and do not turn.

**♠** ₩

**WARNING** Risk of fire caused by flammable material on hot exhaust system components

Flammable material such as leaves, grass or twigs may ignite if they come into contact with hot parts of the exhaust system.

- When driving on an unpaved road or offroad, check the vehicle underside regularly.
- In particular, remove trapped plant parts or other flammable material.
- If there is damage, consult a qualified specialist workshop immediately.

When you drive off road, sand, mud and water or water mixed with oil etc. may get into the brakes. This may lead to a reduction in braking performance or total brake failure as a result of increased wear. The braking characteristics will vary depending on the material that has entered the system. Clean the brakes after driving off road. If you then notice reduced braking performance or hear scraping noises, have the brake system checked at a qualified specialist workshop. Adapt your driving style to the changed braking characteristics.

! NOTE Damage caused by driving over obstacles

The vehicle can be damaged by:

- Driving onto high curbs or unpaved roads.
- Quickly driving over obstacles such as curbs, speed bumps or potholes.
- Heavy objects hitting the underbody or chassis components.
- Do not drive over obstacles that could damage the vehicle.

- Check the vehicle regularly for damage during off-road driving.
- Adjust the vehicle speed to suit the road surface conditions
- If there is damage, consult a qualified specialist workshop immediately.
- **ENVIRONMENTAL NOTE** Environmental damage due to non-observance of prohibition signs

Environmental protection has priority. Treat nature with respect.

Be sure to observe prohibition signs.

## Checklist before driving off road

Check the following points before driving off road:

- Fuel level
- Engine oil level: fill engine oil to the maximum level to ensure full gradeability ( $\rightarrow$  page 374).
- · Tire-change tool kit and spare wheel
- · Tires and wheels

Further information about special all-terrain tires for retrofitting can be obtained from a qualified specialist workshop.

The off-road menu in the multimedia system can assist you when you drive off road. Before driving off road, familiarize yourself with its displays and equipment-dependent settings ( $\rightarrow$  page 336).

### Off-road driving

Read this section before driving your vehicle off road. Practice by driving over more gentle off-road terrain first

- Observe the notes on off-road ABS  $(\rightarrow page 227)$ .
- Select drive program  $\bigcirc$  ( $\rightarrow$  page 190) before driving off road.
- Always keep the engine running and in gear when driving on inclines. Observe the notes on driving in mountainous terrain.
- Do not drive on unknown terrain that is not easily visible and stay on marked routes.
- · Always keep the doors and windows closed while the vehicle is in motion.

- Deactivate Active Distance Assist DISTRONIC or cruise control
- Adapt your driving style to the terrain.
- Do not use the HOLD function on steep gradients with slippery or loose surfaces.

# Driving on sand

When driving on sand, also observe the following instructions:

- · Select a higher vehicle level.
- · Shift to a lower gear.
- Drive quickly to overcome the rolling resistance. Otherwise, the vehicle may dig itself in.
- Drive in the tracks of other vehicles if possible. Make sure that the following prerequisites are met:
  - the tire ruts are not too deep
  - the sand is firm enough
  - the ground clearance is sufficient

# **Fording**

Also observe the following information when fording:

- Do not exceed 6 mph (10 km/h).
- Observe the maximum permissible fording depth (→ page 458).
- Switch off automatic climate control (→ page 157).
- Ensure that a bow wave does not form as you drive.
- Do not stop in the water and do not switch off the engine. Ensure the ECO start/stop function is switched off (→ page 181).

## Driving in mountainous terrain

Also observe the following information when driving in mountainous terrain:

- Observe the values for the angle of approach/ departure and of the maximum gradient-climbing ability (→ page 458).
- · Avoid high engine speeds.
- Use the braking power of the engine when driving downhill.

- Shift to a lower gear on uphill gradients and on long, steep downhill gradients.
- If necessary, activate DSR before driving downhill (→ page 245).

### Checklist after driving off road

Driving off-road places greater demands on your vehicle than driving on normal roads. Check the entire vehicle for damage and foreign bodies every time after driving off road. Foreign bodies in the wheels or drivetrain can lead to imbalances and therefore vibrations.

- If the drive program is selected: select another drive program.
- · Deactivate DSR.
- Lower the vehicle level again to a level suitable to the road conditions, e.g. to the normal level.
- Apply the brakes to dry them after fording.
- Check that the service brake is working normally after a long downhill stretch.
- Clean the following components every time after driving off road:

- license plate number
- headlamps and tail lamps
- tires, wheels and wheel arches
- underbody
- After driving through sand, mud, water or gravel, have the following components checked and cleaned:
  - brake discs and brake linings
  - tires and wheels
  - axle joints

## ECO start/stop function

- ECO start/stop function
- i Plug-in hybrid: the function is not available.
- (i) Depending on the engine, the ECO start/stop function is not available in all drive programs. Observe the status display in the driver's display for this.

The engine will be switched off automatically in the following situations if all vehicle conditions for an automatic engine stop are met:

- You brake the vehicle to a standstill in transmission position  $\mathbf{D}$  or  $\mathbf{N}$ .
- You depress the brake pedal when traveling at a low speed.

If the system has detected one of the following situations, the engine will not stop:

- · You stop at a stop sign and there is no vehicle in front of you.
- The vehicle that stopped in front of you sets off again.
- You maneuver, turn the steering wheel sharply or engage reverse gear.
- (i) If the system detects an intelligent stop inhibitor, e.g. a stop sign, the engine will not stop. If you activate the HOLD function or engage park position P, the engine can be switched off in spite of an intelligent stop inhibitor.

The engine will restart automatically in the following cases:

- You engage transmission position **D** or **R**.
- You depress the accelerator pedal.
- The vehicle requires an automatic engine start.
- You release the brake pedal.
- You release the brake pedal on a downhill gradient and the vehicle does not roll.
- The vehicle rolls on a downhill gradient and does not automatically enter glide mode at 15 mph (20 km/h).

ECO start/stop function symbols on the driver's display:

- The A symbol (green) appears when the vehicle is at a standstill: the engine was switched off by the ECO start/stop function.
- The symbol (yellow) appears when the vehicle is at a standstill: not all vehicle conditions for an engine stop have been met.
- Neither the A symbol nor the Symbol appears when the vehicle is at a standstill: an

intelligent stop inhibitor, e.g. a stop sign, has been detected

The symbol appears: the ECO start/stop function is deactivated or there is a malfunction.

If the engine was switched off by the ECO start/ stop function and you leave the vehicle, a warning tone will sound and the engine will not be restarted. In addition, the following display message will appear on the driver's display:


## Vehicle is Ready to Drive Switch Off Vehicle Before Exiting

If you do not switch off the vehicle, it will automatically be switched off after three minutes.

Switching the ECO start/stop function on/off

**NOTE** Mercedes-AMG vehicles

Observe the notes in the Supplement. You could otherwise fail to recognize dangers.



- Press button ①.

  A display will appear on the driver's display when you switch the ECO start/stop function on/off.
- (i) (A<sup>prr</sup> will be continuously shown on the driver's display while the ECO start/stop function is deactivated.

## ECO display function



The ECO display shows an evaluation of your driving style on the driver display depending on the situation. This enables you to check the efficiency of your driving style and adjust it if necessary. The ECO Display menu shows a ball ② that will roll forwards or backwards in the direction of travel on a stylized road according to the driving characteristics.

Above and below the road, lines mark the area for an efficient driving style ③. Ball ② will light up in green if it is rolling within these lines. Outside the lines, the ball will light up in orange.

The ECO display assesses the following criteria for an economical driving style:

- · Coasting at the right times
- Consistent speed
- Moderate acceleration

The overall assessment of your driving style "from start" is indicated using stars ①. It starts with five empty stars, which you can fill one after the other if you drive efficiently. When all five stars are filled, a glow will appear in the background.

(i) You can call up the ECO Display function via the Classic menu (→ page 306).

# ECO Assist function (vehicles with 48 V on-board electrical system)

For plug-in hybrids, note the ECO Assist information ( $\rightarrow$  page 185).

(i) ECO Assist is active only in drive programs [E] and [C].

ECO Assist analyzes data for the vehicle's expected route. This allows the system to optimally adjust the driving style for the route ahead, save

fuel and recuperate. If the system detects an event ahead and the vehicle nears the event, ECO Assist will calculate the optimum speed for maximum fuel economy and recuperative energy based on the distance, speed and downhill gradient.

If the deceleration provided by ECO Assist is not sufficient, you must also brake with the service brake. This is especially the case if, for example. vou pull away again in slow-moving traffic and the distance to the vehicle in front is very short.



- "Foot off the accelerator" recommendation
- Route event ahead

If a route event ahead or a vehicle driving in front is detected which requires an adjustment to your driving style to ensure greater efficiency, corresponding symbol 2 and the symbol will be displayed in gray.

If you release the accelerator pedal, the symbol will turn green and recuperation in overrun mode will be initiated. If the deceleration is not sufficient, also apply the service brake. If ECO Assist intervenes for a route event ahead (not for a vehicle in front) and you then press the accelerator pedal again, you end ECO Assist's control.

The ECO Assist display is hidden again in the following cases:

- You do not react to the ECO Assist recommendation for a long time.
- You press the accelerator pedal while ECO Assist is intervening for a route event ahead (not for a vehicle in front).
- ECO Assist cannot identify any further recommendations from the route ahead.

In addition to a vehicle in front [ , ECO Assist can detect the following route events 2 depending on the vehicle's equipment:

Traffic circle Sharp bend

Intersection

Т T-intersection

Downhill gradient

Speed limit

(i) In drive program [C], ECO Assist reacts only to the "Vehicle in front" route event .

### System limits

If the calculated route is adhered to when route guidance is active, ECO Assist will operate with greater accuracy. The basic function is also available without active route guidance. Not all information and traffic situations can be foreseen. The quality depends on the map data.

ECO Assist is only an aid. The driver is responsible for keeping a safe distance from the vehicle in front, for vehicle speed and for braking in good time.

The system may be impaired or may not function in the following situations:

- If there is poor visibility, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog or heavy spray.
- If there is glare, e.g. from oncoming traffic, direct sunlight or reflections.
- If the windshield is dirty in the vicinity of the multifunction camera.
- If the multifunction camera is fogged up, damaged or obscured.
- If road signs are hard to detect, e.g. due to dirt, snow or insufficient lighting, or because they are obscured.
- If the digital road map of the navigation system has incorrect or outdated information.
- If signs are ambiguous, e.g. road signs in roadworks or in adjacent lanes.
- If the radar sensors are dirty or obscured.
- When you drive on roads with steep uphill or downhill gradients.

• If there are narrow vehicles in front, such as bicycles or motorcycles.

# Recuperative brake system (plug-in hybrid)

# Function of the recuperative brake system

The recuperative braking system converts the vehicle's kinetic energy into electrical energy during overrun and braking.

Depending on the selected recuperation level, the electric motor is operated as an alternator when in overrun mode and during braking in order to charge the high-voltage battery while driving. As soon as you take your foot off the accelerator while driving in transmission position  $\boxed{\mathbf{D}}$ , recuperation starts in overrun mode.

The higher the recuperation, the more sharply the vehicle is braked when coasting and the more electrical energy is fed into the high-voltage battery.

The deceleration in overrun mode may not be sufficient depending on the driving situation. There is no deceleration to a standstill. Also brake with the service brake if necessary. Always adapt your

speed to the driving situation and keep sufficient distance.

(i) If you brake heavily, the mechanical brake is also used. This means that the maximum recuperation energy cannot be recovered. The more proactively you accelerate and brake, the more efficiently energy can be recuperated.

# System limits


With recuperation in overrun mode, the braking effect of the electric motor is only reduced or non-existent in the following situations:

- when the high-voltage battery charge level increases
- if the high-voltage battery is not yet at a normal operating temperature

# Manually setting recuperative deceleration

- **NOTE** Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

(i) You can use the steering wheel paddle shifters to adjust the intensity of recuperation in drive programs [H], [B] and [EL].



The following recuperation levels are available:

- **D AUTO** Intelligent, anticipatory recuperation with ECO Assist (→ page 185)
- **D** + No recuperation: the vehicle rolls freely
- **D** Normal recuperation
- **D** Increased recuperation: Strong vehicle deceleration in overrun mode, e.g.for driving on a downhill gradient

Default setting:

- DAUTO: If the ECO Assist function in the mul- $\overline{\text{timedia}}$  system is switched on ( $\rightarrow$  page 187).
- **D**: If the ECO Assist function in the multimedia system is switched off.
- **D AUTO** is only available if the ECO Assistant function in the multimedia system is switched on and if the function of the radar sensors is not impaired. Please also note the information on the vehicle sensors and cameras  $(\rightarrow page 225)$ .
- **Increase recuperation:** Pull the paddle shifter briefly.
- Reduce recuperation: Pull the paddle shifter priefly.
- Default setting: Pull long on the paddle shifter 1 or 2 engage the transmission position **D** again.
- (i) When the vehicle is started again, the standard setting is also set.

The driver display shows the currently set recuperation level next to the transmission position display.

# ECO Assist (plug-in hybrid)

### ECO Assist function

(i) The following function depends on the equipment and the country.

ECO Assist analyzes data for the vehicle's expected route. This allows the system to help optimally adjust your driving style for the route ahead, save fuel and recuperate. If the system detects an event ahead and the vehicle nears the event. ECO Assist will calculate the optimum speed for maximum fuel economy and recuperative energy based on the distance, speed and downhill gradient.

If the deceleration provided by ECO Assist is not sufficient, you must also brake with the service brake. This is especially the case if, for example, you pull away again in slow-moving traffic and the distance to the vehicle in front is very short.

The function is active under the following conditions:

 The function is activated in the multimedia. system ( $\rightarrow$  page 187).

- The D AUTO recuperation level is selected
   (→ page 184).
- **M** manual gearshifting is not activated.
- Drive program s or so is not selected.



- "Foot off the accelerator" recommendationRoute event ahead
- If a route event that can be dealt with more efficiently by adjusting your driving style is detected ahead, corresponding symbol ② and the symbol will be displayed in gray.

If you release the accelerator pedal, the symbol will turn green and recuperation in over-

run mode will be initiated. If the deceleration is not sufficient, also apply the service brake.

If ECO Assist makes adjustments for a route event ahead and you step on the accelerator pedal, ECO Assist control is terminated. This does not apply in the case of a vehicle in front.

The ECO Assist display is hidden again in the following cases:

- You do not react to the ECO Assist recommendation for a long time.
- You press the accelerator pedal while ECO
   Assist is intervening for a route event ahead.
   This does not apply in the case of a vehicle in front.
- ECO Assist cannot identify any further recommendations from the route ahead.

In addition to a vehicle in front [A], ECO Assist can detect the following route events ② depending on the vehicle's equipment:

♣ Traffic circle

Sharp bend

▶ Intersection

T-intersection

Downhill gradient

Speed limit

## System limits

If the calculated route is adhered to when route guidance is active, ECO Assist will operate with greater accuracy. The basic function is also available without active route guidance. Not all information and traffic situations can be foreseen. The quality depends on the map data.

ECO Assist is only an aid. The driver is responsible for keeping a safe distance from the vehicle in front, for vehicle speed and for braking in good time.

The system may be impaired or may not function in the following situations:

- If there is poor visibility, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog or heavy spray.
- If there is glare, e.g. from oncoming traffic, direct sunlight or reflections.

- If the windshield is dirty in the vicinity of the multifunction camera
- If the multifunction camera is fogged up, damaged or obscured.
- If road signs are hard to detect, e.g. due to dirt, snow or insufficient lighting, or because they are obscured.
- If the digital road map of the navigation system has incorrect or outdated information.
- If signs are ambiguous, e.g. road signs in roadworks or in adjacent lanes.
- If the radar sensors are dirty or obscured.
- When you drive on roads with steep uphill or downhill gradients.
- If there are narrow vehicles in front, such as bicycles or motorcycles.

## Activating and deactivating ECO Assist Multimedia system:

- → Settings → Assistance Driving
- Activate or deactivate the function.

# Function of the route-based operating strategy (plug-in hybrid)

(i) The following function is country-dependent and available only in conjunction with an integrated navigation system.

The route-based operating strategy will be active in the following circumstances:

- Driving mode H is selected.
- The Route Based option is selected for driving mode H in the DYNAMIC SELECT menu  $(\rightarrow page 190)$ .
- · Route guidance is active.
- The state of charge of the high-voltage battery is sufficient

When the function is active, data on the further route will be analyzed. This includes e.g. road type, speed limits and elevation data.

The hybrid system will then adapt the operating strategy to the further course of the route:

· Use of electrical energy and the combustion engine will be adapted.

- The state of charge of the high-voltage battery will be controlled accordingly.
- Electrical energy will be reserved especially for electric mode, e.g. urban route sections or green zones.
- The vehicle will automatically select the operating mode.

# Function of the haptic accelerator pedal (plug-in hybrid)

The haptic accelerator pedal has an additional pressure point followed by increased pedal resistance to help you drive in all-electric mode.

Characteristics of the additional pressure point:

- Available only in the 🔳 drive program
- is used when the electric drive support power availability display is full (POWER)
- Indicates the maximum available electric performance

The subsequent increased pedal resistance indicates that the journey is being continued with the combustion engine.

### DYNAMIC SELECT

## Function of DYNAMIC SELECT

- I NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

DYNAMIC SELECT allows a driving mode to be selected quickly according to the current driving conditions or the desired vehicle characteristics. You can select the following driving modes.

i Depending on the engine and equipment, the vehicle will have different driving modes.

The selected driving mode appears on the driver display.

## Individual

- Custom settings (→ page 190)
- Custom settings (plug-in hybrid)

# s Sport

• Maximum output is available

- · Sporty driving
- · Sporty, but with an emphasis on stability
- Enables a sporty driver to adopt a more active driving style
- Only suitable for good road conditions, a dry road surface and a clear stretch of road

# H Hybrid (plug-in hybrid)

- Comfortable and economical driving
- · Balance between traction and stability
- · Recommended for all road conditions
- Full range of all intelligent hybrid functions
- Adjustable recuperation in overrun mode
- The selection of the appropriate drive type by the hybrid system depends on the driving conditions and the route

## **C** Comfort

- · Comfortable and economical driving
- · Balance between traction and stability
- · Recommended for all road conditions

## EL Electric (plug-in hybrid)

- Electric mode Driving without the combustion engine is possible up to approx. 87 mph (140 km/h)
- · Adjustable recuperation in overrun mode
- Adaptation of Active Distance Assist DISTRONIC for electric mode
- Depending on the equipment, the maximum set speed for cruise control and Active Distance Assist DISTRONIC can be limited to the maximum speed possible in electric mode
- Activation of the combustion engine via the pressure point of the accelerator pedal (kickdown)

# B Battery Hold (plug-in hybrid)

- Prioritizes maintaining the state of charge of the high-voltage battery, e.g. for subsequent journeys in the inner city/green zones
- The selection of the appropriate drive type by the hybrid system depends on the driving conditions and the route
- · Adjustable recuperation in overrun mode

- Particularly economical driving
- Balance between traction and stability
- Recommended for all road conditions

## Offroad

- · For driving off-road, e.g. on dirt roads, loose surfaces, gravel or sand, as well as on difficult. uneven terrain, off paved roads and on rocky terrain
- Intervenes later if there is oversteer or understeer, thus improving traction
- Not suitable for use on public roads
- Can be selected up to 62 mph (100 km/h)
- From 68 mph (110 km/h): Switches to C

# · Plug-in hybrid:

- From 68 mph (110 km/h): Switches to H and lowers the vehicle to standard level
- Driving in hybrid or electric mode, depending on a sufficient state of charge of the

high-voltage battery having and the setting in the multimedia system ( $\rightarrow$  page 190)

i The ESP® settings in driving modes and are designed for stability. Therefore, choose one of these driving modes especially when transporting roof loads, in trailer operation and when the vehicle is fully laden or fully occupied.

Plug-in hybrid: This also applies to driving modes H, EL and B.

Depending on the driving mode, the following systems will change their characteristics:

- Drive system
  - Engine and transmission management
  - Active Distance Assist DISTRONIC
  - Availability of Gliding mode
- FSP®
- Steering

# Notes on the roof load display


Certain drive programs and ESP® settings are unsuitable for transporting a roof load.

If one of these drive programs is set or selected, the symbol is shown as a warning. When this symbol is shown, the selected drive program is not suitable for transporting a load on the roof.

The following drive programs are affected:

- Drive program S Sport
- Drive program I Individual with the ESP® setting Sport

## Selecting the drive program



- Press DYNAMIC SELECT button (1) on the left or right.
- The drive program selected appears in the driver's display.
- i In drive program , some driving systems are restricted in their function or not available. When selecting drive program , a

- confirmation prompt therefore appears on the central display before the drive program is activated.
- Plug-in hybrid: in drive program , you can switch between hybrid and electric mode via the multimedia system (→ page 190).

# Configuring DYNAMIC SELECT in the multimedia system

Multimedia system:

- → 🔝 >> Settings >> Vehicle
- **▶> DYNAMIC SELECT**

# Setting drive program I

- ▶ Select Individual.
- Select and set a category.
- (i) A sporty ESP mode can be set in conjunction with a sporty suspension mode.

## Setting the H drive program (plug-in hybrid)

Select Hybrid.

Select Route Based or Standard.
If route guidance is active and the Route
Based option has been activated, the electrical energy is distributed intelligently over the entire route. In built-up areas, electric mode is preferred, while on the freeway the combustion engine is used.

With the Standard option, the vehicle drives in its standard drive program ( Electric or Hybrid). There is no distribution of electrical energy over the entire route. The high-voltage battery is exhausted and the vehicle is then driven by the combustion engine.

## Switching the reset display on/off

- Activate or deactivate Request at Start.
- (i) This function must be activated for each user profile separately. Only when this function is activated will the drive program and ECO start/stop setting for the previous journey be saved for the respective user profile.

**Function on:** the next time the vehicle is started a prompt appears asking whether the last active drive program should be restored. If the ECO start/stop function was deactivated, an additional

prompt appears asking if the function should remain deactivated

(i) The prompt appears only if the previously active settings deviate from the standard settings.

**Function off:** the next time the vehicle is started the c drive program is set automatically. The ECO start/stop function is activated automatically.

## Switching the reset display on/off (plug-in hybrid)

- Activate or deactivate Request at Start.
- (i) This function must be activated for each user profile separately. The drive program for the respective user profile of the last driver is only stored if this function is activated.

**Function on:** the next time the vehicle is started a prompt appears asking whether the last active drive program should be restored.

(i) The prompt appears only if the previously active settings deviate from the standard settings.

Function off (plug-in hybrid): if the drive program was the last one active, and all requirements for the drive program are fulfilled, it will be selected automatically the next time the vehicle is started. If another drive program was active, then the H drive program is set automatically.

## Displaying vehicle data

Multimedia system:

¬→ 🔝 >> Info

Select Vehicle.

The vehicle data is displayed.

## Displaying engine data

Multimedia system:

☐ ► Info

Select Engine.

The engine data is displayed.

The actual maximum values that can be achieved for engine output and engine torque may deviate from the certified values within the country-specific guidelines for permissible tolerances (basis: UN-ECE No. 85 or countryspecific guidelines).

Influencing variables include:

- Sea level
- Fuel quality
- Outside temperature
- Operating temperature of the engine

Adjust your driving style accordingly. The warning lamp in the driver display is on until the engine has reached operating temperature.

- (i) The values displayed serve only as guidance. The values for engine output and engine torque shown on the central display may deviate from the actual values.
- (i) The warning lamp to show the power output limitation after starting the vehicle is not available in all vehicle models.

## Calling up the fuel consumption indicator

Multimedia system:

- → 🔝 » Info
- Select Consumption.
   The current and average fuel consumption will be displayed.

### Automatic transmission

**DIRECT SELECT lever** 

■ Function of the DIRECT SELECT lever

**WARNING** Risk of accident due to incorrect gearshifting

If the engine speed is higher than the idle speed and you engage the transmission position  $\boxed{\mathbf{D}}$  or  $\boxed{\mathbf{R}}$ , the vehicle may accelerate sharply.

If you engage the transmission position
D or R when the vehicle is at a stand-still, always depress the brake pedal

firmly and do not accelerate at the same time.

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- releasing the parking brake.
- changing the gearbox position.
- starting the vehicle.
- Never leave children unattended in the vehicle.

- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.

▲ WARNING Risk of accident- and injury when the transmission position is not engaged

The current transmission position will be highlighted on the driver display.

If the selected transmission position is not highlighted, the vehicle may pull away in the wrong direction or roll away.


After changing the transmission position, always check the transmission position indicator on the driver display.

If the transmission position is not highlighted on the driver display even after a short time:

- Pay attention to the display messages.
- Pull away carefully and check the engaged transmission position.

- ► When parking, engage the parking brake and secure the vehicle against rolling awav.
- Have the transmission checked immediately at a qualified specialist workshop.

Use the DIRECT SELECT lever to switch the transmission position. The current transmission position will be highlighted on the driver display.



- P Park position
- R Reverse gear
- Neutral
- Drive position

# Engaging reverse gear R

Depress the brake pedal and push the DIRECT SELECT lever upwards past the first point of resistance.

## Engaging neutral N

- Depress the brake pedal and push the DIRECT SELECT lever up or down to the first point of resistance.
- (i) To shift into neutral N with the vehicle switched on, push the selector lever up or down for several seconds to the first point of resistance.

Subsequently releasing the brake pedal will allow you to move the vehicle freely, e.g. to push it or tow it away.

Proceed as follows if you want the automatic transmission to remain in neutral N, even if the vehicle is switched off or the driver's door is opened:

- Depress the brake pedal and engage neutral N when the vehicle is at a standstill.
- Release the brake pedal.
- Switch off the vehicle.

The Risk of Vehicle Rolling Away N Activated Manually No Automatic Change to P message appears in the driver's display.

(i) If you then exit the vehicle leaving the key in the vehicle, the automatic transmission remains in neutral [N].

The park position **P** is automatically re-engaged as soon as one of the following conditions is met:

- You switch to transmission position **D** or **R**.
- You press the button P.

# Engaging park position P

NOTE Damage due to engaging park position P while the vehicle is rolling

If you shift the transmission into park position  $\boxed{\mathbf{P}}$  while the vehicle is rolling, the transmission may be damaged.

- If the vehicle is rolling, do not open a door.
- Only engage park position **P** when the vehicle is stationary.
- Observe the notes on parking the vehicle (→ page 216).

- Depress the brake pedal until the vehicle comes to a standstill.
- When the vehicle is stationary, press button P.

When the transmission position display shows [P], the park position is engaged. If the transmission position display [P] is not shown, apply the parking brake and secure the vehicle to prevent it from rolling away.

 Depending on the situation, it may take a short time until P is engaged. Therefore, always pay attention to the transmission position display.

Park position **P** will be engaged automatically if one of the following conditions is met:

- You switch the stationary vehicle off in transmission position D or R.
- You open the driver's door when the vehicle is stationary in transmission position D or R.
- When the vehicle is rolling, you switch if off in transmission position D or R and bring it to a standstill.

- When the vehicle is rolling, you shift to transmission position N, bring the vehicle to a standstill and open the driver's door when the vehicle is stationary.
- Engaging park position **P** automatically is required by the vehicle.
- (i) To maneuver with an open driver's door, open the driver's door while the vehicle is stationary and engage transmission position D or R again.

# Engaging drive position D


 Depress the brake pedal and push the DIRECT SELECT lever down past the first point of resistance.

When the automatic transmission is in transmission position  $\boxed{\textbf{D}}$ , it will shift gears automatically. This depends, among other things, on the following factors:

- The selected drive program
- · The position of the accelerator pedal
- · The driving speed

# Manual gearshifting

- **NOTE** Mercedes-AMG vehicles
  - Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- (i) For plug-in hybrids, observe the information regarding the regenerative brake system  $(\rightarrow page 184)$ .



When the automatic transmission is shifted to position D, you can shift it manually with the steering wheel paddle shifters. If permitted, the automatic transmission will shift to a higher or

lower gear depending on the steering wheel paddle shifter pulled.

You have two options for manually shifting the automatic transmission:

- Temporary setting
- Permanent setting

The gears are shifted automatically when manual shifting is deactivated.

## Temporary setting:

- To activate: pull steering wheel paddle shifter or o.
  - Manual shifting will be activated for a short time. The transmission position display will show **M** and the current gear.
- How long manual shifting stays activated depends on various factors.

Manual shifting can be deactivated automatically in the following cases:

- When the drive program is changed
- When the vehicle is restarted.

- When transmission position **D** is engaged again
- Driving style
- To shift up: pull steering wheel paddle shifter 2.
- To shift down: pull steering wheel paddle shifter 1
- To deactivate: pull and hold steering wheel paddle shifter 2.

The transmission position display will show D.

(i) You can activate or deactivate manual shifting permanently in the multimedia system.

# Permanently activating or deactivating manual gearshifting

Multimedia system:

- → 🚡 >> Settings >> Vehicle >> Driving
- Permanently switch the function on or off.

## Gearshift recommendation

The gearshift recommendation assists you in adopting an economical driving style.



When gearshift recommendation appears on the driver's display, shift to the recommended gear.

# Using kickdown

Maximum acceleration: depress the accelerator pedal beyond the point of resistance.

To protect against engine overrev, the automatic transmission will shift up to the next gear when maximum engine speed has been reached.

#### Glide mode function

- I NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

Glide mode helps you to reduce fuel consumption when you employ an anticipatory driving style.

Glide mode is characterized by the following:

- The internal-combustion engine is switched off depending on the driving situation. All the vehicle functions remain active.
- The transmission position display D is shown in green.

Glide mode is activated if the following conditions are met:

• Drive program 🔳 is selected.

- · The speed is within a suitable range.
- The road's course is suitable, e.g. no steep inclines or tight bends.
- There is no trailer coupled up to the trailer hitch, and there is no bicycle rack installed.
- The state of charge of the battery is sufficient.
- You do not depress the accelerator or brake pedal (except for light brake applications).
- (i) Glide mode can also be activated if you have selected the "Eco" setting for the drive in the drive program .

Glide mode will be deactivated again if one of the conditions is no longer met.

Glide mode can also be prevented by the following parameters:

- Incline
- Downhill gradient
- Temperature
- Altitude
- Speed
- Operating condition of the engine

Traffic situation

## Function of the 4MATIC

4MATIC ensures that all four wheels are driven. Together with ESP® and 4ETS, 4MATIC improves the traction of your vehicle whenever a driven wheel spins due to insufficient traction.

If you fail to adapt your driving style, 4MATIC can neither reduce the risk of an accident nor override the laws of physics. 4MATIC cannot take account of road, weather and traffic conditions, 4MATIC is only an aid. You are responsible especially for maintaining a safe distance from the vehicle in front, for vehicle speed, for braking in good time and for staving in lane.

(i) In wintry driving conditions, the maximum effect of 4MATIC can only be achieved if you use winter tires (M+S tires), with snow chains if necessary.

## Refueling

# Refueling the vehicle

WARNING Risk of fire or explosion from fuel

Fuels are highly flammable.

- Fire, open flames, smoking and creating sparks must be avoided.
- Before refueling, switch off the vehicle and, if installed, the stationary heater, and leave them switched off during refueling.

# WARNING Risk of injury from fuels

Fuels are poisonous and hazardous to your health.

- Do not swallow fuel or let it come into contact with skin, eyes or clothing.
- Do not inhale fuel vapor.
- Keep children away from fuel.

Keep doors and windows closed during the refueling process.

If you or other people come into contact with fuel, observe the following:

- Immediately rinse fuel off your skin with soap and water.
- If fuel comes into contact with your eyes, immediately rinse them thoroughly with clean water. Seek medical attention immediately.
- If you swallow fuel, seek medical attention immediately. Do not induce vomiting.
- Change immediately out of clothing that has come into contact with fuel.

WARNING Risk of fire and explosion due to electrostatic charge

Electrostatic charge can ignite fuel vapor.

- Before you open the fuel filler cap or take hold of the pump nozzle, touch the metallic vehicle body.
- To avoid creating another electrostatic charge, do not get into the vehicle again during the refueling process.
- I NOTE Damage caused by the wrong fuel

Vehicles with a gasoline engine:

Even small amounts of the wrong fuel could result in damage to the fuel system, the engine and the emission control system.

Refuel only with low-sulfur spark-ignition engine fuel.

This fuel may contain up to 10% ethanol. Your vehicle is suitable for use with E10 fuel.

Never refuel with one of the following fuels:

- Diesel
- Gasoline with more than 10% ethanol by volume (e.g. E15, E85, E100)

- Gasoline with more than 3% methanol by volume (e.g. M15, M30, M85, M100)
- · Gasoline with metallic additives

If you have accidentally refueled with the wrong fuel:

- Do not switch on the vehicle.
- Consult a qualified specialist workshop.
- I NOTE Do not use diesel to refuel vehicles with a gasoline engine

If you have accidentally refueled with the wrong fuel:

- Do not switch on the vehicle. Otherwise fuel can enter the engine.
  - Even small amounts of the wrong fuel could result in damage to the fuel system and the engine. The repair costs are high.
- Consult a qualified specialist workshop.
- Have the fuel tank and fuel lines drained completely.

- NOTE Damage to the fuel system due to overfilling the fuel tank
- Only fill the fuel tank until the pump nozzle switches off.


If too much fuel has been added due, for example, to a faulty filling pump:

- Do not switch on the vehicle.
- Consult a qualified specialist workshop.
- ! NOTE Fuel may spray out when you remove the fuel pump nozzle
- Only fill the fuel tank until the pump nozzle switches off.

#### Requirements

- · The vehicle is unlocked.
- Plug-in hybrid with gasoline engine: the fuel tank was bled before refueling (→ page 199).


Observe the notes on service fluids and fuel. Refuel only with fuel that has at least the octane number specified in the information label in the fuel filler flap. Otherwise, engine output may be reduced and fuel consumption increased.



- Fuel filler flap
- Bracket for the fuel filler cap
- Tire pressure table
- QR code for rescue card
- Fuel type

- (i) Plug-in hybrid with gasoline engine: the fuel filler flap opens automatically after the fuel tank has been bled ( $\rightarrow$  page 199).
- Press in the center on the back area of fuel filler flap 1.
- Turn the fuel filler cap counter-clockwise and remove it
- Insert fuel filler cap from above into bracket 2.
- Completely insert the pump nozzle into the tank filler neck, hook in place and refuel.
- Fill the fuel tank only until the pump nozzle switches off.
- Replace the cap on the filler neck and turn clockwise until it engages audibly.
- Close fuel filler flap (1).

# Depressurizing the fuel tank (plug-in hybrid with gasoline engine)



Pull switch (1) once briefly. Indicator lamp (2) will flash and the Please Wait Depressurizing Fuel Tank message will appear on the driver's display.

When the fuel tank is depressurized, indicator lamp 2 will light up steadily.

The Fuel Tank Is Depressurized Ready for Refueling message will appear on the driver display and the fuel filler flap will open automatically.

(i) Depressurizing the fuel tank may take several minutes.

The fuel tank can only be depressurized if the conditions described above are fulfilled. Otherwise, drive the vehicle at least 1/3 mile (0.5 km) and repeat the process.

- i In the following situations, there is a malfunction:
  - Indicator lamp ② flashes initially and then goes out.
  - The yellow engine diagnostics warning lamp lights up.
- NOTE Damage to the fuel filler flap when opening it

If an attempt is made to open a fuel filler flap that is not unlocked, the fuel filler flap or the opening mechanism may be damaged. Only refuel when the fuel filler flap has opened automatically.

# Charging the high-voltage battery (plug-in hybrid)

## Notes on charging the high-voltage battery

NOTE High-voltage battery damage due to leaving the vehicle idle for lengthy periods of time

Lithium-ion batteries experience a natural self-discharge.

Exhaustive discharging can therefore occur if the vehicle is idle for several months. This can damage the high-voltage battery.

To avoid damage, please observe the following recommendations when handling the high-voltage battery. NOTE Accelerated aging of the high-voltage battery due to not observing the following recommendations

As a result of its basic characteristics, the storage capacity of and the amount of energy available from the high-voltage battery decreases over the course of its life. Due to this, both the maximum electrical range that can be achieved by the vehicle and its maximum electrical output can be impaired.

The following factors could accelerate the aging of the high-voltage battery:

- A high condition of charge, especially if the vehicle is idle for a lengthy period of time
- Frequent rapid charging with direct current (mode 4)
- Leaving the vehicle idle for lengthy periods at high ambient temperatures
- To avoid accelerated aging, please observe the following recommendations when handling the high-voltage battery.

**NOTE** Damage to the drive system when the high-voltage battery is charged at extreme altitudes

The drive system may be damaged if you charge the high-voltage battery at extreme altitudes more than 13123.36 ft (4000 m) above sea level.

Continuing the journey may then no longer be possible.

Avoid charging processes at extreme altitudes.


Recommendations when handling the high-voltage battery:

- Rapid-charge the high-voltage battery with direct current (Mode 4) only when required.
- If the vehicle is to be idle for a longer period, park it with the high-voltage battery at a charge level between 25 % and 30 %. Do not permanently connect the high-voltage battery to a power supply.

- If leaving the vehicle idle for lengthy periods. avoid high outside temperatures wherever possible.
- · Check the charge level of the high-voltage battery every six weeks ( $\rightarrow$  page 215).
- Be sure to charge the high-voltage battery if the charge level is below 15 %.
- Do not disconnect the 12 V battery even if the vehicle is left unused for a lengthy period. Otherwise the condition of the vehicle's high-voltage battery cannot be monitored.
- When only using the high-voltage battery with low states of charge, fully charge the high-voltage battery twice a year.

Depending on the equipment, your vehicle is equipped with one of the following vehicle sockets:

- Type 1 for charging with alternating current (mode 2/3)
- Type Combo 1 for charging with alternating current (mode 2/3) and charging with direct current (mode 4)



Example: type Combo 1 vehicle socket

- AC charging port
- Socket extension for DC charging
- (i) When using a CCS charging cable (Combined Charging System) for charging with direct current, both areas of the vehicle socket are covered by the charging cable plug.

Charging options for the high-voltage battery (mode 2, 3 or 4):

- While the vehicle is in motion by means of recuperation
- Stationary alternating current charging:
  - At a mains socket (mode 2)
  - At a wallbox or charging station (mode 3)
- Stationary DC charging:
  - At a rapid-charging station (mode 4)

Depending on the country-specific vehicle equipment and your vehicle's charging cable, single phase AC charging is also possible.

Observe the different grid requirements of your current location when charging. Only use charging cables which conform to the grid requirements. Consult a qualified electrician or your local grid operator if you have any questions.

It is recommended that you charge the high-voltage battery at a wallbox or charging station due to the improved charging power and better charging efficiency offered.

## System limits

The power output of the high-voltage battery may be impaired by the following:

- high or low outside temperatures
- Electrical auxiliary consumers in the vehicle being switched on, e.g. operating the air conditioning system
- · extended periods without charging

The charging time or the charging power of the high-voltage battery may be increased by the following:

- high or low outside temperatures
- a low or high state of charge of the high-voltage battery
- The maximum available charge current of the charging device

# Stowing the charging cable

Always stow the vehicle's charging cable in the charging cable bag provided, and secure the charging cable bag in the trunk or cargo compart-

ment with the included retaining strap. Otherwise, the charging cable bag with the charging cable will not be sufficiently secured.




Example: charging cable bag in the trunk/cargo compartment

As delivered, charging cable bag ① with retaining strap ② is located in the trunk or cargo compartment. To secure the charging cable bag, the

retaining strap must be attached to cargo tiedown ring 3. Do not use bag hooks to attach the retaining strap.



- Feed the loop end of retaining strap (2) through cargo tie-down ring (3) into the trunk or cargo compartment.
- Feed the end with the snap hook through the loop of retaining strap (2).



- Tighten retaining strap 2 so that the knot around cargo tie-down ring (3) is tight and secure.
- Hook the snap hook of retaining strap 2 in a tie-down eye of charging cable bag 1.

# Notes on charging the high-voltage battery at a mains socket (Mode 2)

**DANGER** Risk of fatal injury from incorrectly installed component parts

Connecting the charging cable to a mains socket using incorrectly installed component parts could cause a fire or an electric shock, for example.

- Only connect the charging cable to a mains socket that:
- has been properly installed and
- has been inspected by a qualified electrician
- For safety reasons, only use the charging cable supplied with the vehicle or an original Mercedes-Benz charging cable.
- Purchase these parts at an authorized Mercedes-Benz Center and obtain advice there.

Mercedes-Benz thoroughly tests these original charging cables for their suitability for high-voltage charging of your vehicle.

- Never use a damaged charging cable.
- Do not use:
- extension cables
- extension reels
- · multiple sockets
- Never use socket adapters to connect the charging cable to the mains socket. The only exception being if the adapter has been tested and approved by the manufacturer for charging the high-voltage battery of an electric vehicle.
- Observe the safety notes in the operating instructions for the socket adapter.

Only the following charging cables may be used:

- The charging cable supplied with the vehicle.
- A charging cable that has been approved for the vehicle.

The charging process can vary depending on the power supply equipment. The charging times when charging the high-voltage battery at the mains socket are considerably longer than when charging at a wallbox or charging station.

When doing so, always observe the local information.

Do not leave the charging cable controls hanging loose from a mains socket.

Do not lift the controls by the following component parts:

- the charging cable connector
- · the mains plug

When charging, protect the charging cable control element from excessive heat such as direct sunlight. Otherwise the charging process may be aborted.

# Notes on charging the high-voltage battery at a wallbox or charging station (mode 3)

A

**DANGER** Risk of fatal injury from incorrectly installed component parts

Connecting the charging cable to the vehicle using incorrectly installed components could cause a fire or an electric shock, for example.

- Only connect the charging cable to a wallbox if:
- The wallbox has been properly installed
- The wallbox has been inspected by a qualified electrician
- · The charging cable is not damaged
- Do not extend the charging cable.
- Do not use adapters.
- Observe the safety notes in the operating instructions for the wallbox.

DANGER Risk of fatal injury due to damaged components

Connecting the vehicle to a charging station using damaged component parts could cause a fire or an electric shock, for example.

- Perform a visual check of the charging station for obvious defects, for example damage to the housing or charging cable connection
- Never use damaged charging cables.
- Do not use an extension for the charging cable.
- Do not use adapters.
- Always observe the safety instructions on the charging station.

Most charging stations must be activated before the charging process, e.g. using an RFID card or via Plug-and-Charge. Observe the on-site operator's instructions for the charging station and the notes on Mercedes me Charge (see the vehicle's Digital Operator's Manual).

The amount of energy dispensed for the charging process, shown by the charging station, may be higher than the amount of energy actually absorbed by the high-voltage battery. This is the result of different levels of charging losses and is described as recharge efficiency. Charging losses occur, for example, due to heat that builds up when the vehicle is charging or from auxiliary consumers that are switched on. Further information on recharge efficiency can be obtained at a qualified specialist workshop.

Notes on charging the high-voltage battery at a rapid charging station (mode 4)

DANGER Risk of fatal injury due to damaged components

Connecting the vehicle to a charging station using damaged component parts could cause a fire or an electric shock, for example.

Perform a visual check of the charging station for obvious defects, for example

- damage to the housing or charging cable connection
- Never use damaged charging cables.
- Do not use an extension for the charging cable.
- Do not use adapters.
- Always observe the safety instructions on the charging station.

**DANGER** Risk of fatal injuries when carrying out maintenance work during the charging process

During the charging process, the high-voltage on-board electrical system is under high voltage.

Do not perform any maintenance work during the charging process.

Most charging stations must be activated before the charging process, e.g. using an RFID card or via Plug-and-Charge. Observe the on-site operator's instructions for the charging station and the

notes on Mercedes me Charge (see the vehicle's Digital Operator's Manual).

The amount of energy dispensed for the charging process, shown by the charging station, may be higher than the amount of energy actually absorbed by the high-voltage battery. This is the result of different levels of charging losses and is referred to as charging efficiency. Charging losses occur, for example, due to heat that builds up when the vehicle is charging or from auxiliary consumers that are switched on. Further information on charging efficiency can be obtained at a qualified specialist workshop.

# Maximum permissible charging current for charging at a mains socket

! NOTE Overloading the mains socket due to excessive charging current

If the charging current is too high, the fuse could be tripped or the external mains supply could overheat.

- Ensure that the external mains supply has been designed to handle the charging current provided.
- For safety reasons, only use the charging cable supplied with the vehicle or an original Mercedes-Benz charging cable. Mercedes-Benz thoroughly tests these original charging cables for their suitability for high-voltage charging of your vehicle.
- Purchase these parts at a Mercedes-Benz service center and obtain advice there.
- Check the maximum charging current using the charging capacity shown on the driver's display.

The charging cable supplied is set to a countryspecific maximum charging current value. When charging abroad, the maximum value may exceed the permitted value for that country.

Before charging at a mains socket, have the maximum permissible charging current for the

- relevant mains socket or the building checked by a qualified electrician.
- When abroad, observe the country-specific laws when charging.

If you have questions concerning the charging current or if there is a malfunction, please contact a qualified specialist workshop.

# Overview of the charging cable control panel

The charging cable control panel described below shows the current status of the charging process.




- Supply voltage indicator
- Charging process indicator
- Temperature monitor indicator
- Safety system indicator


# Supply voltage indicator

Display	Meaning
Lights up white	The supply voltage is connected.

# Charging process indicator (2)



# Temperature control indicator (3)



# Safety system indicator (1)

, ,	
Display	Meaning
Flashes red	Charging cable mal- function – cannot carry out the charging process, reset the charging cable control panel.
Lights up red	White LED is off: power supply malfunction – cannot carry out the charging process, replace the mains socket. White LED is on: vehicle malfunction – cannot carry out the
	charging process, reset the charging cable control panel.


When all four displays light up, the charging cable control panel is performing a self-test.

If the temperature monitor ③ indicates a malfunction, it may help to protect the charging cable from direct sunlight.

To reset the charging cable control panel: if safety system indicates a charging cable malfunction or a vehicle malfunction, first reset the charging cable operating unit. To do this, disconnect the charging cable from the vehicle and from the mains socket and wait for approximately five seconds. If the malfunction persists after the charging cable is reconnected, charging at the mains socket is not possible. The charging cable must be replaced or the vehicle plug must be checked at a qualified specialist workshop, depending on the indicator.

# Functions of the indicator lamps on the vehicle socket

The socket flap is centrally locked and unlocked together with the vehicle.



Example: type Combo 1 vehicle socket

- Socket lamp
- Charging process indicator lamp
- 3 Locking status indicator lamp

The upper curve of he socket lamp ① is used for the lighting and flashes or lights up as with indicator lamp ②. The lower curve is used for the sta-

tus display and flashes or lights up as with indicator lamp ②.

The color and signaling of the indicator lamps and have the following meaning.

Locking status 🕡 3

- Lights up white: vehicle socket unlocked; insert or remove charging cable
- Flashes white: malfunction during locking or unlocking

- Lights up green (for approx. 60 s): charging process completed
- · Flashes green: charging; active energy flow
- Lights up orange (for approx. 60 s): charging break
- Flashes orange: connection is being established
- Flashes red (for approx. 90 s): malfunction in vehicle; charging not possible

DANGER Risk of death when charging at a damaged socket

The charging process uses high voltage.

If the charging cable, the vehicle socket or the mains socket are damaged, you could receive an electric shock.

- Only use an undamaged charging cable.
- Avoid mechanical damage such as crushing, abrading or driving over the cable.
- Have a damaged vehicle socket replaced at a qualified specialist workshop as soon as possible.
- Never connect the charging cable to a damaged vehicle socket.
- **NOTE** Damage due to overheating of charging cable and charge port

During the charging process, the charging cable and charge port can heat up within the permissible limits.

The permissible limit values are influenced by the following factors:

- the power supply system and the charging cable are not damaged
- the instructions for handling the charging cable and the control element on the charging cable have been observed
- If the charging cable or charge port becomes too hot, have the power supply system checked.
- **NOTE** Damaged or dirty vehicle socket when the socket flap is open
- Always keep the socket cover and the socket flap closed when there is no charging cable connected. This protects the vehicle socket from dirt and damage.
- Make sure that the socket cover is closed properly before closing the socket flap. This can otherwise result in damage which may prevent the socket flap from being opened again.

NOTE Damage to the vehicle socket or the charging cable connector due to incorrect handling

Do not use excessive force (maximum 67.4 lbf (300 N)) to fully insert the charging cable connector into the vehicle socket. You may otherwise damage the vehicle socket, the charging cable connector or their contacts.

If you feel there is increased resistance. pull the charging cable connector out of the socket and reinsert it.


# Requirements

- The transmission is in position **P**.
- The vehicle is unlocked, or the vehicle is locked and the distance between the key and the vehicle does not exceed 3 ft (1 m).
- The charging cable is not taut.

Depending on the equipment, your vehicle is equipped with one of the following vehicle sockets.

• Type 1 for AC charging (Mode 2/3)

• Type Combo 1 for AC charging (Mode 2/3) and DC charging (Mode 4)



Type Combo 1 vehicle socket (example)

Press the center rear of the socket flap and swing it forwards to open.

The indicator lamp and upper status display light up white.

- (i) The socket flap (1) can also be opened via the multimedia system (→ page 334). If the socket flap (1) cannot be opened despite the vehicle being unlocked, the charge socket flap can be opened by emergency release (→ page 214).
- Press catch to the right and fold up socket cover .
- (i) Only connector (i) is required for the charging cable connector in vehicles with a Combo vehicle socket. Only open the upper section of the socket cover (ii).
- To charge at a mains socket, fully insert the mains plug into the mains socket of the external power source.
- Fully insert the charging cable connector into vehicle socket (a). If the wallbox/charging station is not equipped with a charging cable, fully insert the plug of the vehicle's charging cable into the wallbox/charging station socket.

Make sure that the charging cable is not taut when inserted.

The indicator lamp (s) [ and lower status display (4) flash orange, and green as soon as the high-voltage battery is being charged.

When the charging cable is connected to the vehicle, the vehicle cannot be started or moved.

At the start of the charging process, the charge level display is shown in the driver display with an estimated completion time. The completion time is the time when the high-voltage battery will be fully charged.

- (i) Depending on the temperature, the fan and battery cooling system may audibly switch on during the charging process.
- (i) If the vehicle is idle for lengthy periods and connected to the mains supply, the high-voltage battery will be recharged automatically as needed or when electrical consumers are activated (e.g. the pre-entry climate control).


The vehicle is equipped with an electric safety mechanism to protect against overvoltages in the power grid. This device may be triggered during severe thunderstorms, for example. and may lead to the building's circuit breaker being tripped and an interruption in the power supply. These functions serve to protect the vehicle.

After switching the building fuse back on again the charging process is automatically continued. During a charge interruption without triggering the building fuse it may take up to ten minutes for the charging process to continue automatically.

# Ending the alternating current charging process (mode 2/3)

### Requirements

 The vehicle is unlocked or the vehicle is locked. and the distance between the key and the vehicle does not exceed 3 ft (1 m).



Example:Type Combo 1 vehicle socket

(i) Vehicles equipped with a Type 1 vehicle socket for AC charging have no charging interruption button 3.

- Type Combo 1 vehicle socket: press the charging interruption button (3). The charging process is ended. The indicator lamp 1 lights up white. The vehicle socket is unlocked.
- As an alternative, and only if the charging interruption button (3) is not working, you can unlock the vehicle using the vehicle key or centrally from inside to end the charging process. If the indicator lamp 1 then lights up white, the vehicle socket is unlocked for around 30 seconds.
- (i) The charging process can also be ended via the multimedia system ( $\rightarrow$  page 334).
- Type 1 vehicle socket: unlock the vehicle with the vehicle key or centrally from inside. The charging process is ended. The indicator lamp 1 lights up white. The vehicle socket is unlocked.
- Press and hold button 2 on the charging cable plug and remove the charging cable plug from the vehicle socket.

- i If you cannot remove the charging cable plug, repeat the unlocking procedure. If the charging cable plug is still locked, contact a qualified specialist workshop.
- Close the socket cover and the socket flap.
- (i) The indicator lamp (ii) (iii) on the vehicle socket remains lit for some time before going out.

# Starting the direct current charging process (mode 4)

**A** DANGER Risk of death when charging at a damaged socket

The charging process uses high voltage. If the charging cable, the vehicle socket or the mains socket are damaged, you could receive an electric shock.

- Only use an undamaged charging cable.
- Avoid mechanical damage such as crushing, abrading or driving over the cable.

- Have a damaged vehicle socket replaced at a qualified specialist workshop as soon as possible.
- Never connect the charging cable to a damaged vehicle socket.
- I NOTE Damage due to overheating of charging cable and charge port

During the charging process, the charging cable and charge port can heat up within the permissible limits.

The permissible limit values are influenced by the following factors:


- the power supply system and the charging cable are not damaged
- the instructions for handling the charging cable and the control element on the charging cable have been observed
- If the charging cable or charge port becomes too hot, have the power supply system checked.

- NOTE Damaged or dirty vehicle socket when the socket flap is open
- Always keep the socket cover and the socket flap closed when there is no charging cable connected. This protects the vehicle socket from dirt and damage.
- Make sure that the socket cover is closed properly before closing the socket flap. This can otherwise result in damage which may prevent the socket flap from being opened again.
- NOTE Damage to the vehicle socket or the charging cable connector due to incorrect handling

Do not use excessive force (maximum 67.4 lbf (300 N)) to fully insert the charging cable connector into the vehicle socket. You may otherwise damage the vehicle socket, the charging cable connector or their contacts.

If you feel there is increased resistance, pull the charging cable connector out of the socket and reinsert it.

- The transmission is in position **P**.
- The vehicle is unlocked or the vehicle is locked and the distance between the key and the vehicle does not exceed 3 ft (1 m).
- The charging cable is not taut.



- Push on the center rear of the socket flap (1) and swing the socket flap forwards. The indicator lamp (3) and upper status display 4 light up white.
- The socket flap (1) can also be opened via the multimedia system ( $\rightarrow$  page 334). If socket flap (1) cannot be opened despite the vehicle being unlocked, the charge socket flap can be opened with the emergency release ( $\rightarrow$  page 214).
- Push latch 7 to the right and flip up socket cover 2.
- The connections (6) and (8) are required for the CCS charging cable plug. Both sections of the socket cover must therefore be opened
- Fully insert the CCS charging cable plug into the vehicle socket.

Make sure that the charging cable is not taut when inserted.

The indicator lamp (5) [ 7 and lower status display (4) flash orange, and green as soon as the high-voltage battery is being charged.

When the charging cable is connected to the vehicle, the vehicle cannot be started or moved.


At the start of the charging process, the state of charge indicator is shown on the driver display with a predicted completion time. The predicted completion time either refers to the predicted state of charge at the set departure time, or the time at which the high-voltage battery will be fully charged.

- (i) Depending on the temperature, the fan and battery cooling system may audibly switch on during the charging process.
- (i) If the vehicle is idle for lengthy periods and connected to the power grid, the high-voltage battery will be recharged automatically as needed or when electrical consumers are activated (e.g. the pre-entry climate control).

# Ending the direct current charging process (mode 4)

## Requirements

 The vehicle is unlocked or the vehicle is locked and the distance between the key and the vehicle does not exceed 3 ft (1 m).




- Press charging interruption button (3).
  The charging process is ended. The 
  cator lamp (1) lights up white. The vehicle socket is unlocked.
- (i) As an alternative, and only if the charging interruption button (a) is not working, you can unlock the vehicle using the vehicle key or centrally from inside to end the charging process. If the indicator lamp (a) then lights up white, the vehicle socket is unlocked for around 30 seconds.
- (i) The charging process can also be ended via the multimedia system (→ page 334).
- Press and hold button ② on the charging cable plug and remove the charging cable plug from the vehicle socket.
- If you cannot remove the charging cable plug, unlock the vehicle and repeat the unlocking procedure. If the charging cable plug is still locked, contact a qualified specialist workshop.
- Close the socket cover and the socket flap.

After the charging cable plug has been disconnected, the left findicator lamp on the vehicle socket remains lit for some time before going out.

# Emergency release of the socket flap

If the socket flap cannot be opened due to a malfunction, an emergency release of the socket flap can be performed for the charging process.




- Press in the catch spring of interior lamp (1) with a suitable object, e.g. a screwdriver, and carefully prise the interior lamp out of the load compartment trim.
- Pull emergency release 2 in the direction of the arrow. The socket flap of the vehicle socket swings open.

- Guide the connecting cables of interior lamp back behind the load compartment trim, laterally position interior lamp (1) and snap it into the load compartment trim.
- Start the alternating current charging process  $(\rightarrow page 209)$ .

Start the direct current charging process  $(\rightarrow page 212)$ .

# Function of the charge level display in the driver display



- Remaining range at current charge level
- Current charge level of the high-voltage bat-
- Maximum charge level (as per the setting)
- Remaining time until fully charged (up to the selected maximum charge level)
- Openamic charge level display
- Current charging power
- (i) The indicated remaining range (1) may vary due to various factors, e.g.driving style or topography.

When the vehicle is switched off and connected to the mains supply, the driver display shows the charge level display for approximately two minutes.

i The value of current charging power can differ from the display on the charging station.

Mercedes-AMG vehicles: the prediction for the remaining range ① and the maximum state of charge ③ are not displayed.

## Parking

# Parking the vehicle



WARNING Risk of accident and injury caused by an insufficiently secured vehicle rolling away

If the vehicle is not securely parked sufficiently, it can roll away in an uncontrolled way even at a slight downhill gradient.

On uphill or downhill gradients, turn the front wheels so that the vehicle rolls towards the curb if it starts moving.

- Apply the parking brake.
- Switch the transmission to position **P**.



WARNING Risk of fire caused by hot exhaust system parts

Flammable materials such as leaves, grass or twigs may ignite.

- Park the vehicle so that no flammable material can come into contact with hot vehicle components.
- In particular, do not park on dry grassland or harvested grain fields.



**WARNING** Risk of accident and injury due to children left unattended in the vehicle


If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.

• operate vehicle equipment and become trapped, for example.

In addition, the children could also set the vehicle in motion by, for example:

- · releasing the parking brake.
- changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- When leaving the vehicle, always take the key with you and lock the vehicle.
- Keep the key out of reach of children.
- ! NOTE Damage to the vehicle due to it rolling away
- Always secure the vehicle against rolling away.



- Bring the vehicle to a standstill by depressing the brake pedal.
- On uphill or downhill gradients, turn the front wheels so that the vehicle rolls towards the curb if it starts moving.
- Apply the electric parking brake.

- Engage transmission position | P | in a stationary vehicle with the brake pedal applied  $(\rightarrow page 194)$ .
- Switch off the vehicle by pressing button ①.
- Release the service brake slowly.
- Get out of the vehicle and lock it.
- When you park the vehicle, you can still operate the side windows and the panoramic sliding sunroof for approximately four minutes if the driver's door is closed

# Automatic vehicle shut-off when locking

Your vehicle is equipped with automatic engine shut-off.

When you leave the vehicle ready to drive, the vehicle will be turned off when locked under the following conditions:

- The ignition is switched on or the engine is running.
- Transmission position **P** is engaged.
- . The driver's door is closed.
- . In addition, one of the following conditions must be fulfilled:

- The vehicle is locked using the vehicle kev.
- Vehicles with KEYLESS-GO: the vehicle is locked with KEYLESS-GO on the door handle of a closed door
- Vehicles with KFYLESS-GO: the vehicle is locked via the locking button in the tailgate.
- (i) The engine will continue to run if the vehicle is not locked as described after it has been left. In this case, switch off the vehicle manually.

## Automatic switch-off of the vehicle after a period of time (depending on equipment)

When the engine is running, the following display message appears in the driver's display when leaving the vehicle or after a certain time stopped in transmission position P: Vehicle Ready to Drive Shutdown Occurs When Locked or Automatically in XX Mins

The vehicle will then automatically switch off after a total of 20 minutes of time stopped.

(i) To avoid automatic switch-off after the time has elapsed, confirm the corresponding message in the central display of the multimedia system.

In the following cases, the engine continues to run:

- if the vehicle is not locked as described after leaving it
- if the automatic switch-off is not displayed by the display message
- if, once the time has elapsed, the automatic switch-off has been deactivated via the corresponding message in the central display

In this case, switch off the vehicle manually.

# Garage door opener

Programming buttons for the garage door opener



**DANGER** Risk of death caused by exhaust gases

Combustion engines emit poisonous exhaust gases such as carbon monoxide. Inhaling these exhaust gases is hazardous to health and leads to poisoning.

Never leave the engine or, if present, the auxiliary heating running in an enclosed space without sufficient ventilation.



WARNING Risk of injury by becoming trapped when opening and closing a garage door

When you operate or program a garage door with an integrated garage door opener, persons can become trapped or struck by the garage door if they stand within its range of movement.

Always make sure that nobody is within the range of the garage door's movement.


Only operate the following doors using the garage door opener:

- · Doors with a safety stop and reversing feature
- Doors which conform to the current U.S. safety standards

Before programming the garage door opener, park the vehicle outside the garage. Make sure that the vehicle is switched on but not started.

#### Requirements

- The vehicle has been parked outside the garage or outside the range of movement of the door.
- The vehicle is switched on.
- · The vehicle has not been started.
- i The garage door opener function is always available when the vehicle is switched on.



Check if the transmitter frequency of the remote control has the frequency range of 280 to 868 MHz.

Radio equipment approval number:

- NZLMUAHL5 (USA)
- 4112A-MUAHL5 (Canada)

- Press and hold button (1), (2) or (3) that you wish to program. Indicator lamp (4) flashes yellow.
- It can take up to 20 seconds before the indicator lamp flashes yellow.
- Release the previously pressed button. Indicator lamp (a) continues to flash yellow.
- Point remote control (5) from a distance of 0.4 in (1 cm) to 3 in (8 cm) towards button
- Press and hold button (6) of remote control (5) until one of the following signals appears:
  - Indicator lamp (4) lights up green continuously. Programming is complete.
  - Indicator lamp (4) flashes green. Programming was successful. Additionally, synchronization of the rolling code with the door system must be carried out.
- If indicator lamp (4) does not light up or flash green: repeat the procedure.
- Release all of the buttons.

(i) The remote control for the door drive is not included in the scope of delivery of the garage door opener.

# Synchronizing the rolling code

### Requirements

- The door system uses a rolling code.
- The vehicle must be within range of the garage door or door drive
- The vehicle as well as persons and objects are located outside the range of movement of the door.
- Press the program button on the door drive Initiate the next step within approximately 30 seconds.
- Press previously programmed button 1. 2 or (3) repeatedly until the door closes. When the door closes, programming is completed.
- (i) Please also read the operating instructions for the door drive.

# ■ Troubleshooting when programming the remote control

- Check if the transmitter frequency of remote control (5) is supported.
- Replace the batteries in remote control 6.
- ► Hold remote control ⑤ at various angles from a distance of 0.4 in (1 cm) to 3 in (8 cm) front of the inside rearview mirror. You should test every position for at least 25 seconds before trying another position.
- Hold remote control (§) at the same angles at various distances in front of the inside rearview mirror. You should test every position for at least 25 seconds before trying another position.
- On remote controls that transmit only for a limited period, press button (a) on remote control (b) again before transmission ends.
- Angle the antenna line of the garage door opener unit toward the remote control.
- (i) It is possible that older garage doors cannot be operated using the remote control in the inside rearview mirror even after you have

successfully performed the measures described above. If this is the case, contact the Homel ink® Hotline.

- Support and additional information on programming:
  - on the toll free HomeLink<sup>®</sup> Hotline on 1-800-355-3515
  - on the Internet at https:// www.homelink.com/mercedes

# Opening or closing the garage door

#### Requirements

- The corresponding button is programmed to operate the door.
- Press and hold buttons (1), (2) or (3) until the door opens or closes.

## Clearing the garage door opener memory

- Press and hold buttons (1) and (3). Indicator lamp (4) lights up yellow.
- If indicator lamp (a) flashes green: release buttons (a) and (a).
   The entire memory has been deleted.

# Electric parking brake

# ■ Function of the electric parking brake (applying automatically)

WARNING Risk of accident and injury due to children left unattended in the vehicle

If you leave children unattended in the vehicle, they could, in particular:

- open doors, thereby endangering other persons or road users.
- get out and be struck by oncoming traffic.
- operate vehicle equipment and become trapped, for example.

- · releasing the parking brake.
- · changing the gearbox position.
- · starting the vehicle.
- Never leave children unattended in the vehicle.
- ▶ When leaving the vehicle, always take the kev with you and lock the vehicle.
- Keep the key out of reach of children.

# The electric parking brake is applied if the transmission is in position [P] and one of the following conditions is fulfilled:

- · The vehicle is switched off
- The seat belt tongue is not inserted in the seat belt buckle of the driver's seat and the driver's door is opened.
- (i) To prevent application: pull the handle of the electric parking brake ( $\rightarrow$  page 222).

## In the following situations, the electric parking brake is also applied:

- The HOLD function is keeping the vehicle stationary.
- Active Parking Assist is keeping the vehicle stationary.
- Active Distance Assist DISTRONIC is bringing the vehicle to a standstill
- . In addition, one of the following conditions must be fulfilled:
  - The vehicle is switched off.
  - The seat belt tongue is not inserted in the seat belt buckle of the driver's seat and the driver's door is opened.
  - There is a system malfunction.
  - The power supply is insufficient.
  - The vehicle is stationary for a lengthy period.

When the electric parking brake is applied, the red PARK (USA) or (Canada) indicator lamp lights up in the driver's display.

(i) The electric parking brake is not automatically applied if the vehicle is switched off by the ECO start/stop function.

# Function of the electric parking brake (releasing automatically)

The electric parking brake is released when the following conditions are fulfilled:


- · The driver's door is closed.
- The vehicle has been started.
- The transmission is in position **D** or **R** and vou depress the accelerator pedal or vou shift from transmission position P to D or R when on level ground.
- If the transmission is in position **R**, the tailgate must be closed.
- . The seat belt tongue is inserted into the seat belt buckle of the driver's seat.
  - If the seat belt tongue is not inserted into the seat belt buckle of the driver's seat, one of the following conditions must be fulfilled:
  - You shift from transmission position **P**.

- You have previously driven at speeds greater than 2 mph (3 km/h).

When the electric parking brake is released, the red PARK (USA) or (©) (Canada) indicator lamp in the driver's display goes out.

# Applying/releasing the electric parking brake manually

# **Applying**



Push handle (1).
The red PARK (USA) or (6) (Canada) indicator lamp lights up in the driver's display.

(i) The electric parking brake is only securely applied if the red PARK (USA) or (D) (Canada) indicator lamp is lit continuously.

## Releasing

- Switch on the vehicle.
- Pull handle (i).
  The red PARK (USA) or (iii) (Canada) indicator lamp in the driver's display goes out.

# Emergency braking

Press and hold handle .
As long as the vehicle is in motion, the Release Parking Brake message is displayed and the red PARK (USA) or (Canada) indicator lamp flashes.

When the vehicle has been braked to a standstill, the electric parking brake is applied. The red PARK (USA) or (Canada) indicator lamp lights up in the driver's display.

## Information on collision detection on a parked vehicle

If a collision is detected on the locked vehicle when the tow-away alarm is activated and collision detection is switched on, you will receive a message in the multimedia system when the vehicle is switched on

You will receive information about the following points:

- The area of the vehicle that may have been damaged.
- The force of the impact.

The following situation can lead to inadvertent activation:

- The parked vehicle is moved, for example, in a two-story garage.
- (i) Deactivate the tow-away alarm in order to prevent inadvertent activation. If you deactivate the tow-away alarm, collision detection will also be deactivated.

You can permanently deactivate collision detection via the multimedia system  $(\rightarrow page 223)$ .

(i) If the battery is severely discharged, the function for detecting a collision on a parked vehicle is automatically deactivated to facilitate the next engine start.

### System limits

Detection may be restricted in the following situations.

- the vehicle is damaged without impact, for example, if an outside mirror is torn off or the paint is damaged by a key
- an impact occurs at low speed
- the electric parking brake is not applied
- (i) You are responsible for your vehicle. Convince yourself that your vehicle is free of damage and roadworthy.

## Setting collision detection for a parked vehicle

Multimedia system:

- → 🔝 >> Settings >> Vehicle ➤ Open/Close ➤ Vehicle Protection
- Activate or deactivate the function via Collision Notification.
- (i) A maximum of three incidents can be registered. Up to 15 photos are taken for every incident. In the event of another incident, the photos of the first incident will be overwritten if they have not been deleted already.

## Activating or deactivating the collision photos function

Please note that legal restrictions regarding automatic recording of the vehicle surroundings may be in place in certain countries.

Activate or deactivate Collision Photos.

# Transferring the collision photos with the Mercedes me app

Select Upload Collision Photos.

or

- Select Upload Automatically.
- Scan the generated QR code on the central display with the Mercedes me app. The encrypted collision photos will then be uploaded to Mercedes me.
- (i) Any device that can scan QR codes can be used to view the collision photos in the Mercedes me app.

#### Copying the collision photos to a USB flash drive

- Connect a USB flash drive.
- Select Manage Collision Photos.
- Select Copy (USB).
   All collision photos are copied to the USB flash drive.
- i Use only FAT32 or exFAT-formatted USB storage devices to ensure secure operation.

## Deleting collision photos

- Select Manage Collision Photos.
- Select Delete.
   All collision photos are deleted.

# Notes on parking the vehicle for an extended period

If you leave the vehicle parked for longer than six weeks, it may suffer damage through disuse.

The 12 V battery may also be impaired or damaged by heavy discharging.

(i) Further information can be obtained at a qualified specialist workshop.

# Standby mode (extension of the starter battery's period out of use)

# Standby mode function

i This function is not available for all models.

If standby mode is activated, energy loss will be minimized during extended periods of non-operation.

Standby mode is characterized by the following:

- · The starter battery is preserved.
- The maximum non-operational time appears in the driver's display.

The connection to online services is interrupted.

If the following conditions are fulfilled, standby mode can be activated or deactivated using the multimedia system:

- · The vehicle is switched on.
- · The vehicle has not been started.

Exceeding the vehicle's displayed non-operational time may cause inconvenience; i.e. it cannot be guaranteed that the starter battery will reliably start the vehicle.

Charge the starter battery in the following situations:

- The vehicle's non-operational time has to be extended.
- The starter battery charge level is insufficient for standby mode.
- (i) Standby mode is automatically deactivated when the vehicle is switched on.

# Activating/deactivating standby mode (parking up the vehicle)

## Requirements

- The power supply is switched on.
- The vehicle is not switched on.

#### Multimedia system:

- → Settings → Vehicle > Other Functions
- Activate or deactivate Standby Mode.

# Driving and driving safety systems

## Driving systems and your responsibility

Your vehicle is equipped with driving systems that assist you in driving, parking and maneuvering the vehicle. The driving systems are only aids. They are not a substitute for you paying attention to your surroundings and do not relieve you of your responsibility pertaining to road traffic law. The driver is always responsible for maintaining a safe distance to the vehicle in front, for vehicle speed, for braking in good time and for staying in lane.


Pay attention to the traffic conditions at all times and intervene when necessary. Be aware of the limitations regarding the safe use of these systems.


Driving systems can neither reduce the risk of an accident if you fail to adapt your driving style nor override the laws of physics. They cannot always take into account road, weather or traffic conditions.

(i) Some driving systems can regulate or limit the speed to a previously set value. Draw attention to the stored speed when changing drivers.

#### Information on vehicle sensors and cameras

Some driving and driving safety systems use cameras as well as radar or ultrasonic sensors to monitor the area in front of, behind or next to the vehicle.





- Multifunction camera
- Cameras in the outside mirrors
- Front radar
- Front camera

- 6 Corner radars
- O Ultrasonic sensors
- Rear view camera

WARNING Risk of accident due to restricted detection performance of vehicle sensors and cameras

If the area around vehicle sensors or cameras is covered, damaged or dirty, certain driving and safety systems cannot function correctly. There is a risk of an accident.

- Keep the area around vehicle sensors or cameras clear of any obstructions and clean.
- Have damage to the bumper, radiator grille or stone chipping in the area of the front and rear windows repaired at a qualified specialist workshop.

In particular, keep the areas around the sensors and cameras free of dirt, ice or slush ( $\rightarrow$  page 382). The sensors and cameras must not be covered and the detection ranges around them must be kept free. Do not attach additional

license plate brackets, advertisements, stickers or foils – including those that protect against stone chippings – in the detection range of the sensors and cameras. Make sure that there are no overhanging loads protruding into the detection range.

If there is damage to a bumper or the radiator grille, or after an impact, have the function of the sensors checked at a qualified specialist workshop. Have damage or stone chipping in the area of the cameras on the windshield and rear window repaired at a qualified specialist workshop.

(i) The rear view camera can extend and retract automatically for the purpose of calibration, even though there is no camera image in the display.

# Overview of driving systems and driving safety systems

- ABS (→ page 227)
- BAS (→ page 228)
- ESP® ( $\rightarrow$  page 228)
- ESP<sup>®</sup> Crosswind Assist (→ page 229)

- ESP<sup>®</sup> trailer stabilization (→ page 229)
- EBD (→ page 230)
- STEER CONTROL (→ page 230)
- HOLD function (→ page 230)
- Hill Start Assist (→ page 232)
- Valet Service Mode (→ page 232)
- Beginner Driver Mode (→ page 233)
- ATTENTION ASSIST (→ page 233)
- Cruise control (→ page 235)
- Traffic Sign Assist (→ page 260)

# Driving Assistance Package

The availability of some functions or partial functions of the Driving Assistance Package depends on the equipment or country. The functions of your Driving Assistance Package may differ from the functions listed here. The functions Active Distance Assist DISTRONIC, Active Blind Spot Assist, Active Brake Assist, Active Lane Keeping Assist and Active Emergency Stop Assist are, with restricted functions, also available without Driving Assistance Package.

- Active Distance Assist DISTRONIC  $(\rightarrow page 237)$
- Active Speed Limit Assist (→ page 242)
- Route-based speed adaptation (→ page 242)
- DSR (→ page 245)
- Active Brake Assist (→ page 254)
- Active Steering Assist (→ page 246)
- Active Emergency Stop Assist (→ page 248)
- Active Lane Change Assist (→ page 250)
- Active Stop-and-Go Assist (→ page 244)
- Blind Spot Assist and Active Blind Spot Assist with exit warning ( $\rightarrow$  page 264)
- Active Lane Keeping Assist (→ page 268)
- PRE-SAFE<sup>®</sup> Impulse Side (→ page 50)

# Parking Package

- (i) The availability of individual functions depends on country and equipment.
- Rear-view camera (→ page 271)
- 360° Camera (→ page 273)
- Parking Assist PARKTRONIC (→ page 280)

- Active Parking Assist (→ page 283)
- Memory Parking Assist (→ page 292)
- Trailer Maneuvering Assist (→ page 296)

## Function of ABS

The Anti-lock Brake System (ABS) regulates the brake pressure in critical driving situations:

- During braking, for instance, at maximum fullstop braking or if there is insufficient tire traction, the wheels are prevented from locking.
- Vehicle steerability while braking is ensured.

If ABS intervenes when braking, you will feel a pulsing in the brake pedal. The pulsating brake pedal can be an indication of hazardous road conditions and can serve as a reminder to take extra care while driving.

## System limits

- ABS is active from speeds of approx. 3 mph (5 km/h).
- ABS may be impaired or may not function if a malfunction has occurred and the yellow

ABS warning lamp lights up continuously after the vehicle is started.

#### Function of off-road ABS

(i) Off-road ABS is activated automatically when you select the drive program.

Off-road ABS is specially adapted for driving offroad:

- The front wheels lock cyclically during braking.
- The braking distance is shortened due to the digging-in effect.

#### System limits

- Off-road ABS functions at speeds below 25 mph (40 km/h).
- If off-road ABS intervenes, the ability to steer may be restricted.

# Function of BAS

**WARNING** Risk of an accident caused by a malfunction in BAS (Brake Assist System)

If BAS is malfunctioning, the braking distance in an emergency braking situation is increased.

Depress the brake pedal with full force in emergency braking situations. ABS prevents the wheels from locking.

The Brake Assist System (BAS) supports your emergency braking situation with additional brake force.

If you depress the brake pedal quickly, BAS is activated:

- BAS automatically boosts the brake pressure.
- BAS can shorten the braking distance.
- · ABS prevents the wheels from locking.

The brakes will function as usual once you release the brake pedal. BAS is deactivated.

### Function of ESP®

A

**WARNING** Risk of skidding if ESP® is deactivated

If you deactivate  $\mathsf{ESP}^{\$}$ ,  $\mathsf{ESP}^{\$}$  cannot carry out vehicle stabilization.

- ESP® should only be deactivated in the following situations.
- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The Electronic Stability Program (ESP®) can monitor and improve driving stability and traction in the following situations within physical limits:

- When you pull away on wet or slippery road surfaces.
- When braking.

If the vehicle deviates from the direction desired by the driver,  $\mathsf{ESP}^{\otimes}$  can stabilize the vehicle by intervening in the following ways:

- · One or more wheels are braked.
- The engine output is adapted according to the situation.

When ESP® is deactivated, the Figure 1 warning lamp lights up continuously:

- · Driving stability will no longer be improved.
- The drive wheels could spin.
- ETS/4ETS traction control is still active.
- (i) When ESP® is deactivated, you are still assisted by ESP® when braking.

When the warning lamp flashes, one or more wheels have reached their grip limit:

- Adapt your driving style to suit the current road and weather conditions.
- Do not deactivate ESP<sup>®</sup>.
- Only depress the accelerator pedal as far as is necessary when pulling away.

Deactivate ESP® in the following situations to improve traction:

- · When using snow chains.
- In deep snow.
- On sand or gravel.
- (i) Spinning the wheels results in a cutting action, which enhances traction.

If the swarning lamp lights up continuously, FSP® is not available due to a malfunction.

Observe the following information:

- Warning and indicator lamps (→ page 534)
- Display messages (→ page 461)

#### ETS/4ETS

ETS/4ETS (Electronic Traction System) traction control is part of ESP® and makes it possible to pull away and accelerate on slippery roads.

If you select the drive program, a special ETS/4ETS system specifically suited to off-road terrain will automatically be activated.

ETS/4ETS can improve the vehicle's traction by intervening in the following ways:

- The drive wheels are braked individually if they spin.
- More drive torque is transferred to the wheel or wheels with traction.

# Influence of drive programs on ESP®

The drive programs enable ESP® to adapt to different weather and road conditions as well as the driver's preferred driving style. Depending on the selected drive program, the appropriate ESP® mode will be activated ( $\rightarrow$  page 190).

## Function of ESP® Crosswind Assist

ESP® Crosswind Assist detects sudden gusts of side wind and helps the driver to keep the vehicle in the lane:

 ESP® Crosswind Assist operates at vehicle speeds between approximately 50 mph (80 km/h) and 125 mph (200 km/h) when you are driving straight ahead or cornering slightly.

 The system stabilizes the vehicle by applying the brakes to specific wheels on one side.

#### Function of FSP® trailer stabilization

WARNING Risk of accident in poor road and weather conditions

In poor road and weather conditions, the trailer stabilization cannot prevent lurching of the vehicle/trailer combination. Trailers with a high center of gravity may tip over before ESP® detects this.

Always adapt your driving style to suit the current road and weather conditions.

When you are driving with a trailer, ESP® can stabilize your vehicle if the trailer begins to swerve from side to side:

- ESP® trailer stabilization will be active at speeds above 40 mph (65 km/h).
- Slight swerving is reduced by means of a targeted, individual brake application on one side.

• In the event of severe swerving, the operating energy output will also be reduced and the brakes will be applied to all wheels.

ESP® trailer stabilization may be impaired or may not function if:

• The trailer is not connected correctly or is not detected properly by the vehicle.

# Activating/deactivating ESP® (Electronic Stability Program)

Multimedia system:









- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- Select FSP.
- Select On or Off.

ESP® is deactivated if the ESP® OFF warning lamp lights up continuously on the driver's display.

Observe any information on warning lamps and display messages which may be shown on the driver's display.

#### Function of EBD

Electronic Brakeforce Distribution (EBD) is characterized by the following:

- Monitoring and regulating the brake pressure on the rear wheels
- Improved driving stability when braking, especially on bends.

#### **Function of STEER CONTROL**

STEER CONTROL assists you by transmitting a noticeable steering force to the steering wheel in the direction required for vehicle stabilization.

This steering recommendation is given in the following situations:

- · both right wheels or both left wheels are on a wet or slippery road surface when you brake
- the vehicle starts to skid.

#### System limits

STEER CONTROL may be impaired or may not function in the following situations:

- FSP® is deactivated.
- ESP<sup>®</sup> is malfunctioning.
- The steering is malfunctioning.

If ESP® is malfunctioning, you will be assisted further by the power steering.

#### **HOLD function**

## HOLD function

The HOLD function holds the vehicle at a standstill without requiring you to depress the brake pedal, e.g. while waiting in traffic.

The HOLD function is only an aid. The responsibility for the vehicle safely standing still remains with the driver

#### System limits

The HOLD function is only intended to provide assistance when driving and is not a sufficient means of safeguarding the vehicle against rolling away when stationary.

• The incline must not be greater than 30%.

# Activating/deactivating the HOLD function

WARNING Risk of an accident due to the HOLD function being active when you leave the vehicle

If the vehicle is only braked with the HOLD function it could, in the following situations, roll awav:

- If there is a malfunction in the system or in the power supply.
- If the HOLD function is deactivated by depressing the accelerator pedal or brake pedal, e.g. by a vehicle occupant.

Always secure the vehicle against rolling away before you leave it.

## Requirements

- The vehicle is stationary.
- The driver's door is closed or the seat belt on. the driver's side is fastened.
- The vehicle has been started or has been. automatically switched off by the ECO start/ stop function.
- The electric parking brake is released.
- Active Distance Assist DISTRONIC is deactivated
- The transmission is in position **D**, **R** or **N**.

## Activating the HOLD function

- Depress the brake pedal, and after a short time quickly depress further until the HOLD display appears in the driver's display.
- Release the brake pedal.

## Deactivating the HOLD function

Depress the accelerator pedal to pull away. or

Depress the brake pedal until the HOLD display disappears from the driver's display.

The HOLD function is deactivated in the following situations:

- Active Distance Assist DISTRONIC is activated
- The transmission is shifted to position **P**.
- The vehicle is secured with the electric parking brake.

In the following situations, the vehicle is held by transmission position P and/or by the electric parking brake:

- The seat belt is unfastened and the driver's. door is opened.
- · The vehicle is switched off.
- · There is a system malfunction.
- The power supply is insufficient.

In addition, the Brake Immediately message may appear in the driver's display and a horn tone may sound at regular intervals.

- Immediately depress the brake pedal firmly until the warning message disappears. The HOLD function is deactivated.
- Additionally secure the vehicle against rolling away.

#### **Function of Hill Start Assist**

WARNING Risk of accident and injury due to the vehicle rolling away

After a short time, Hill Start Assist no longer holds the vehicle.

Swiftly move your foot from the brake pedal to the accelerator pedal. Do not leave the vehicle when it is being held by Hill Start Assist.

Hill Start Assist will hold the vehicle for a short time when you pull away on a hill in the following circumstances:

- The transmission is in position **D** or **R**.
- The electric parking brake is released.

This will give you enough time to move your foot from the brake pedal to the accelerator pedal and depress it before the vehicle begins to roll away.

#### Valet service mode

## Function of the valet service mode

(i) This function is an on-demand feature (→ page 24).

In valet service mode, the vehicle acceleration is limited to reduce the risk of damage to and improper use of the vehicle when it is handed over to third parties.

Valet service mode is characterized by the following:

- · Power output is reduced.
- In principle, a maximum speed of 81 mph (130 km/h) can be reached.
- The sporty drive programs and the program are not available.
- ESP® cannot be deactivated.
- Profiles that are still logged in are logged out and unprotected profiles are secured.

#### Switch valet service mode on or off

#### Requirements

- For activation: the vehicle is at a standstill.
- For deactivation: the park position P is selected.

#### Multimedia system:

# → 🙀 **>>** Apps **>>** Valet service mode

- Activate or deactivate the function. If the valet service mode is activated an indicator lamp lights up in the driver display.
- Alternatively the valet service mode can be switched on or off via the Mercedes me connect App.
   Further information on Mercedes me connect (→ page 355)
- The valet service mode is only protected against deactivation by a third party in conjunction with Mercedes me connect. If the vehicle is linked to Mercedes me connect, only the profile that has activated the mode or the specified main user can deactivate it again.

(i) The valet service mode remains active in case of a profile change or if the vehicle is switched on or off and must be consciously switched off by the authorized users.

## Beginner driver mode

# Function of the beginner driver mode

(i) This function is an on-demand feature  $(\rightarrow page 24)$ .

In beginner driver mode, the vehicle acceleration is limited to increase safety for inexperienced drivers

Beginner driver mode is characterized by the following:

- Power output is reduced.
- In principle, a maximum speed of 81 mph (130 km/h) can be reached.
- The sporty drive programs and the drive program are not available.
- ESP® cannot be deactivated.

## Switch Beginner Driver Mode on or off

#### Requirements

- For activation: the vehicle is at a standstill.
- For deactivation: the park position **P** is selected

#### Multimedia system:

→ Apps → Beginner Driver Mode

- Activate or deactivate the function. If Beginner Driver Mode is activated an indicator lamp lights up in the driver display.
- Alternatively, Beginner Driver Mode can be switched on or off via the Mercedes me connect App. Further information on Mercedes me connect  $(\rightarrow page 355)$
- (i) Beginner Driver Mode is protected against deactivation by a third party only in conjunction with Mercedes me connect. If the vehicle is linked to Mercedes me connect, only the profile that has activated the mode or the specified main user can deactivate it again.

(i) Beginner Driver Mode remains active in case of a profile change or if the vehicle is switched on or off and must be consciously switched off by the authorized users.

#### ATTENTION ASSIST

#### ■ Function of ATTENTION ASSIST

ATTENTION ASSIST helps you on long, monotonous journeys, e.g. on highways and trunk roads. If indicators of fatigue or increasing lapses in concentration on the part of the driver are detected. the system will suggest taking a break.

ATTENTION ASSIST is only an aid. It cannot always detect fatigue or lapses in concentration in time. The system is not a substitute for a well-rested and attentive driver. On long journeys, take regular breaks in good time that allow for adequate recuperation.

You can choose between two settings:

- Standard: normal system sensitivity.
- **Sensitive:** higher system sensitivity. The driver is warned earlier and the attention level detec-

ted by ATTENTION ASSIST is adapted accordingly.

If drowsiness or increasing lapses in concentration are detected, the ATTENTION ASSIST: Take a Break! warning appears on the driver's display. You can acknowledge the message and take a break where necessary. If you do not take a break and ATTENTION ASSIST continues to detect increasing lapses in concentration, you will be warned again after a minimum of 15 minutes.



The following information is displayed on the driver's display:

• The length of the journey since the last break

The attention level determined by ATTENTION ASSIST.

The more segments ① of the circle displayed, the higher the detected attention level. Fewer segments ① are displayed in the circle as the attention level decreases.

If ATTENTION ASSIST is unable to calculate the attention level and cannot issue a warning, the System Suspended message appears.

If a warning is shown on the driver's display, the MBUX multimedia system offers to search for a rest area. You can select a rest area and start navigation to this rest area.

When you restart the vehicle, ATTENTION ASSIST is automatically switched on. The last selected sensitivity level remains stored.

## System limits

ATTENTION ASSIST is active in the speed range between 37 mph (60 km/h) and 124 mph (200 km/h).

If the system is not available due to a fault, the ATTENTION ASSIST warning lamp will light up permanently on the driver's display

Particularly in the following situations, ATTENTION ASSIST only functions in a restricted manner and warnings may be delayed or not occur:

- If you have been driving for less than approximately 30 minutes.
- If the road condition is poor (uneven road surface or potholes).
- · If there is a strong crosswind.
- If you adopt a sporty driving style (high cornering speeds or high rates of acceleration).
- If the Steering Assist function of Active Distance Assist DISTRONIC is active.
- If the clock is set to the incorrect time.
- If you change lanes and vary your speed frequently in active driving situations.

Also observe any information regarding display messages that may be displayed on the driver's display.

The ATTENTION ASSIST drowsiness or alertness assessment is reset and restarted when continuing the journey in the following situations:

· You switch off the vehicle.

• You unfasten your seat belt and open the driver's door (e.g. to change drivers or take a break).

# Setting ATTENTION ASSIST

Multimedia system:

→ Settings → Assistance

➤ Assistance ➤ ATTENTION ASSIST

## Setting the sensitivity

- Select next to ATTENTION ASSIST.
- Select Standard or Sensitive.

# Speed control cruise control

# Function of cruise control

Cruise control regulates the speed to the value selected by the driver.

If you accelerate to overtake, for example, the stored speed is not deleted. If you remove your foot from the accelerator pedal after overtaking, cruise control will resume speed regulation back to the stored speed.

You can store any speed from 15 mph (20 km/h) up to the maximum design speed.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

Mercedes-AMG vehicles: cruise control is available up to a maximum speed of 155 mph (250 km/h).

### Displays on the driver's display

Grav: cruise control is selected but not yet active, or temporarily passive.

Green: cruise control is active.

A stored speed is shown under the display and is indicated in the speedometer.

## System limits

Cruise control may be unable to maintain the stored speed on uphill gradients. The stored speed is resumed when the gradient evens out.

Change to a lower gear in good time for long and steep downhill gradients. Take particular note of this when driving a laden vehicle. By doing so, you will make use of the braking effect of the engine.

This relieves the load on the brake system and prevents the brakes from overheating and wearing too quickly.

Do not use cruise control in the following situations:

- In traffic situations which require frequent changes of speed, e.g. in heavy traffic, on winding roads
- On slippery roads. Accelerating can cause the drive wheels to lose traction and the vehicle could then skid.
- When visibility is poor

# Operating cruise control


WARNING Risk of accident due to stored speed

If you call up the stored speed and this is lower than your current speed, the vehicle decelerates.

Take into account the traffic situation. before calling up the stored speed.

#### Requirements

- Cruise control is selected.
- ESP® must be activated, but not intervening.
- The vehicle speed is at least 15 mph (20 km/h).
- The transmission is in position **D**.



Steering wheel control panel for cruise control

RES/P CANCEL

SET + SET -

Adopts the stored/detected speed Deactivates cruise control Control panel for increasing/

decreasing speed

Activates cruise control

(S) OFF

Deactivates cruise control

Activating cruise control

► Press 📆.

## Activating cruise control

Press SET + or SET - on control panel 1. The current speed will be stored and maintained by the vehicle.

or

Press RESI®.

The last stored speed will be called up and maintained by the vehicle.

If the last stored speed has previously been deleted, the current vehicle speed will be stored.

(i) When you switch off the vehicle, the last speed stored will be deleted.

# Increasing/decreasing the stored speed

- To increase the stored speed: swipe upwards from the bottom of control panel 1.
  - The stored speed will be increased by 1 mph (1 km/h).

- To decrease the stored speed: swipe downwards from the top of control panel 1.
  - The stored speed will be decreased by 1 mph (1 km/h).

Briefly press SET+ or SET- on control panel

The stored speed will be increased or decreased to the following values depending on the unit:

- mph: the next value ending in 5
- km/h: the next value ending in 0

- Accelerate the vehicle to the desired speed.
- Press SET + on control panel 1.

# Adopting a detected speed

If cruise control is activated and Traffic Sign Assist has detected a traffic sign with a maximum permissible speed and this is displayed on the driver's display:

► Press RES/♥].

The maximum permissible speed shown by the traffic sign will be stored and the vehicle will maintain that speed.

## Deactivating cruise control

Press CANCEL.

## Deactivating cruise control

- ► Press 📆.
- (i) If you brake or deactivate ESP® or if ESP® intervenes, cruise control will be deactivated.

#### Active Distance Assist DISTRONIC

- Function of Active Distance Assist DISTRONIC
- The Active Distance Assist DISTRONIC described for vehicles without the Driving Assistance Package is an on-demand feature (country-dependent) ( $\rightarrow$  page 24).

Active Distance Assist DISTRONIC maintains the set speed in free-flowing traffic. If vehicles are detected ahead the set distance is maintained, if necessary until the vehicle comes to a standstill.

The vehicle accelerates or brakes depending on the distance to the vehicle in front and the set speed. The speed and distance to the vehicle in front are set and saved using the steering wheel.

Available speed range:

- · Vehicles without Driving Assistance Package: 15 mph (20 km/h) - 100 mph (160 km/h)
- · Vehicles with Driving Assistance Package: 15 mph (20 km/h) - 130 mph (210 km/h)


Other features of Active Distance Assist DISTRONIC:

- · Adjusts the driving style depending on the selected drive program (energy-saving, comfortable or dynamic) (→ page 188)
- Initiates acceleration to the stored speed if the turn signal indicator is switched on to change to the overtaking lane
- · Vehicles with Driving Assistance Package:
  - Reacts to stationary vehicles detected in urban speed ranges (except bicycles and motorcycles)

- Takes one-sided overtaking restrictions into account on highways or multi-lane roads with separate roadways (countrydependent)
- (i) In the DYNAMIC SELECT menu, it is possible to set the driving mode of Active Distance Assist DISTRONIC. Depending on the selected drive program, the driving behavior is energy-saving, comfortable or dynamic. In the Active Distance Assist menu, the driving style can be permanently set to comfortable or dynamic (→ page 244).

Vehicles with Active Parking Assist and Driving Assistance Package: if Active Distance Assist DISTRONIC has braked the vehicle to a standstill, it can automatically follow the vehicle in front when driving off again within 30 seconds if the system detects that the driver is touching the steering wheel. If a critical situation is detected in the surrounding area when driving off, such as a person in the vehicle path, a visual and acoustic warning indicates that the driver must now take control of the vehicle. The vehicle is not accelerated any further.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize potential dangers ( $\rightarrow$  page 225).



Display in the driver display in the menuAssistance

- Vehicle in front
- ② Distance indicator
- Specified distance set

The vehicle detected in front ① is highlighted in green. It may also be in the lane to the right of your vehicle in situations where it is not permitted to overtake on the left, for example, on UK highways.

#### Permanent status display

- Gray: Active Distance Assist DISTRONIC selected but not yet active
- Green speedometer, gray vehicle: Active Distance Assist DISTRONIC active, speed set
- Green: Active Distance Assist DISTRONIC active and vehicle detected

The stored speed is shown under the permanent status display and highlighted on the speedometer. Active Distance Assist DISTRONIC's status display is grayed out when in passive mode.

If the speed of the vehicle in front or the ascertained target speed due to the route event ahead is less than the stored speed, the segments in the speedometer light up.

The display appears briefly if you increase or decrease the specified distance (3).

i The green vehicle symbol si displayed cyclically when the vehicle is ready to pull away.

(i) The system is switched to passive mode if you depress the accelerator pedal beyond the Active Distance Assist DISTRONIC setting. The following message appears briefly in the driver display Suspended.

### System limits

The system may be impaired or inoperative in the following instances, forexample:

- In snow, rain, fog, heavy spray, if there is glare, in direct sunlight or in greatly varying ambient light.
- The windshield in the camera's area is dirty, fogged up, damaged or covered.
- If the radar sensors are dirty or covered.
- · In parking garages or on roads with steep uphill or downhill gradients.
- If there are narrow vehicles in front, such as bicycles or motorcycles.

In addition, on smooth or slippery roads, one or more wheels may lose grip due to braking or acceleration, and the vehicle may begin skidding.

Do not use Active Distance Assist DISTRONIC in these situations.

WARNING Risk of accident from acceleration or braking by Active Distance Assist DISTRONIC

Active Distance Assist DISTRONIC may accelerate or brake in the following cases, for example:

- If the vehicle pulls away using Active Distance Assist DISTRONIC.
- If the stored speed is called up and is considerably faster or slower than the currently driven speed.
- If Active Distance Assist DISTRONIC no. longer detects a vehicle in front or does not react to relevant objects.
- Always carefully observe the traffic conditions and be ready to brake at all times.
- Take into account the traffic situation before calling up the stored speed.

WARNING Risk of accident due to insufficient deceleration by Active Distance Assist DISTRONIC

Active Distance Assist DISTRONIC brakes your vehicle with up to 50% of the possible deceleration. If this deceleration is not sufficient. Active Distance Assist DISTRONIC alerts you with a visual and acoustic warning.

- Adjust your speed and maintain a suitable distance from the vehicle in front
- Brake the vehicle yourself and/or take evasive action.

WARNING Risk of accident if detection function of Active Distance Assist DISTRONIC is impaired

Active Distance Assist DISTRONIC does not react or has a limited reaction:

· when driving on a different lane or when changing lanes

- to pedestrians, animals, bicycles or stationary vehicles, or unexpected obstacles
- · to complex traffic conditions
- · to oncoming vehicles and crossing traffic

As a result, Active Distance Assist DISTRONIC may neither give warnings nor intervene in such situations.


Always observe the traffic conditions carefully and react accordingly.

# Operating Active Distance Assist DISTRONIC

## Requirements

- The electric parking brake is released.
- ESP<sup>®</sup> is activated and is not intervening.
- The transmission is in position **D**.
- · All the doors are closed.
- The check on the radar sensor system has been completed successfully.
- Snow Chain Mode is not active (→ page 413).
- DSR is deactivated (→ page 245).

Drive program is deactivated (→ page 188).



RES/

Adopts the stored/detected speed Deactivates Active Distance Assist DISTRONIC

SET + SET -

Control panel for increasing/ decreasing speed



Increases/decreases the specified distance



Activates/deactivates Active Distance Assist DISTRONIC

To operate Active Distance Assist
DISTRONIC: press the respective button with
only one finger or swipe on the control panel.

# Activates/deactivates Active Distance Assist DISTRONIC

Press .

## **Activating Active Distance Assist DISTRONIC**

► To activate without a stored speed: press

SET+ on the upper section or SET- on the lower section of control panel (1) or press

RESI(\*\*). Remove your foot from the accelerator pedal.

or

To activate with a stored speed: press RESIP.
Remove your foot from the accelerator pedal.
The last stored speed will be called up and maintained by the vehicle.

If the stored speed has been deleted, the current vehicle speed will be stored.

## Increasing or reducing the speed

- To increase the stored speed: swipe upwards from the bottom of control panel .
  - The stored speed will be increased by 1 mph (1 km/h).
- To decrease the stored speed: swipe downwards from the top of control panel 1.
  - The stored speed will be decreased by 1 mph (1 km/h).

Briefly press SET + on the upper section or set- on the lower section of control panel

The stored speed will be increased or reduced by 5 mph (10 km/h).

or

- Accelerate the vehicle to the desired speed.
- Press SET + on the upper section of control panel 1

## Adopting the limit speed shown on the driver's display

- To activate Active Distance Assist DISTRONIC: press set+, set- or RES/.
- To accept the displayed speed limit: press RES/P

The limit speed shown on the driver's display will be adopted as the stored speed. The vehicle will adapt its speed to that of the vehicle in front, but only up to the stored speed, or will limit its speed accordingly.

(i) A speed limit shown on the driver's display will be adopted only during travel, not when the vehicle is stationary.

## Pulling away with Active Distance Assist DISTRONIC

- Activate Active Distance Assist DISTRONIC and remove your foot from the brake pedal. ► Press RES/

  Press RES/

  • .
- or

Depress the accelerator pedal briefly and

The functions of Active Distance Assist DISTRONIC will still be active.

## Reducing or increasing the specified distance from the vehicle in front

Press ক্লি.

The 🚊 indicator will appear. The specified distance will be reduced by one level.

If the lowest level is already selected, the selection will jump to the highest level.

### Deactivates Active Distance Assist DISTRONIC

WARNING Risk of an accident due to Active Distance Assist DISTRONIC being active when you leave the driver's seat

If you leave the driver's seat while the vehicle is being braked by Active Distance Assist DISTRONIC only, the vehicle can roll away.

Always deactivate Active Distance Assist DISTRONIC and secure the vehicle to

- prevent it from rolling away before you leave the driver's seat
- Press CANCEL.
- (i) If you brake or deactivate ESP® or if ESP® intervenes. Active Distance Assist DISTRONIC will be deactivated.

# ■ Function of Active Speed Limit Assist

If a change in speed limit is detected and the automatic adoption of speed limits is switched on, this will automatically be adopted as the stored speed (→ page 244). Speed limits below 12 mph (20 km/h) will not be adopted.

The vehicle's speed will be adjusted when the vehicle is level with the traffic sign at the latest. In the case of signs indicating entry into an urban area, the speed will be adapted according to the speed permitted within the urban area. The speed limit indicator on the driver's display will always be updated when the vehicle is level with the traffic sign.

If you are driving on a German freeway and there is no speed limit, the system will use the speed stored for a stretch of road with no speed limit as the set speed. If you do not alter the stored speed on a stretch of road with no speed limit, the recommended speed of 80 mph (130 km/h) will be adopted.

If Active Distance Assist DISTRONIC has been put into passive mode by pressing the accelerator pedal, only speed limits which are higher than the set speed are adopted.

The maximum permissible speed does not take the road condition or current weather and traffic conditions into account. Adjust your speed accordingly as and when necessary.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

# System limits

The system limits of Traffic Sign Assist apply to the detection of traffic signs ( $\rightarrow$  page 260).

Speed limits below 12 mph (20 km/h) will not automatically be adopted by the system as the stored speed. Temporary speed restrictions (e.g. for a certain time or due to weather conditions) cannot be properly detected by the system.

Adjust your speed in these situations.

**A** WARNING Risk of accident due to adjustment of speed by Active Speed Limit Assist.

The speed adopted by the Active Speed Limit Assist may be too high or incorrect in individual cases:

- At limit speeds below 12 mph (20 km/h)
- In wet or foggy conditions
- Ensure that the speed being driven always complies with the traffic laws.
- Adjust the speed being driven to the current traffic and weather conditions.

# Function of route-based speed adaptation

When Active Distance Assist DISTRONIC is activated, the vehicle speed will be adapted accordingly to the route events ahead. Depending on the drive program selected, the vehicle will negotiate a route event ahead in an energy-saving, comfortable or dynamic manner. When the route event has been passed, the vehicle will accelerate again to the stored speed. The set distance to the vehicle

in front, vehicles detected ahead and speed restrictions ahead will be taken into account.

Route-based speed adaptation can be activated in the multimedia system ( $\rightarrow$  page 244).

The following route events will be taken into account:

- Bends
- Traffic circles
- T-intersections
- Turns and exits
- Traffic jams ahead (only with Live Traffic)

Also, the speed will be reduced if the turn signal indicator is switched on and one of the following situations is detected:

- · Turning off at intersections
- Driving in slowing-down lanes
- Driving in lanes adjacent to slowing-down lanes

The driver is responsible for choosing the right speed and observing other road users. This applies in particular to intersections, traffic circles and traffic lights, as route-based speed adaptation does not brake the vehicle to a standstill.

When route guidance is active, the first speed adjustment will be carried out automatically. If the turn signal indicator is switched on, the selected route will be confirmed and further speed adjustment will be activated.

Speed adjustment will be canceled in the following cases:

- · If the turn signal indicator is switched off before the route event and it is therefore assumed that the route event is not relevant to the driver
- If the driver depresses the accelerator or brake pedal during the process


## System limits

Route-based speed adaptation does not take right of way regulations into account. The driver is responsible for complying with road traffic regulations and driving at a suitable speed.

In difficult conditions, the speed selection made by the system may not always be suitable. This applies to the following situations, for example:

- The road's course is not clearly visible
- Road narrowing
- · Varying maximum permissible speeds in individual lanes, e.g. at toll stations
- · Wet road surfaces, snow or ice
- If transport equipment, such as a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection has been correctly established.

The driver will need to intervene accordingly in these situations.



Route-based speed adaptation can malfunction or be temporarily unavailable in the following situations:

- If the driver does not follow the calculated route
- If map data is not up-to-date or available
- . In the event of roadworks
- · In bad weather or road conditions
- If the accelerator pedal is depressed
- In the event of electronically displayed speed limitations
- Adapt the speed to the traffic situation.

# Setting Active Distance Assist DISTRONIC driving styles

## Requirements

Active Distance Assist DISTRONIC is activated.

#### Multimedia system:

- → Settings → Assistance
- ▶ Driving ▶ Active Distance Assist

### Selecting a driving style

- Select Based on DYNAMIC SELECT, Dynamic or Comfortable.
- Further information about Active Distance Assist DISTRONIC (→ page 240).

# Setting speed adjustment

Select Adopt Speed Limit or Route-based Speed Adaptation.

When these functions are active, the vehicle speed will be adjusted depending on the route events ahead.

- (i) If one of the following systems is activated, the detected speed can be manually adopted as the speed limit:
  - Active Distance Assist DISTRONIC
  - Variable limiter
- i) Further information on speed adjustment
   (→ page 242).

## ■ Function of Active Stop-and-Go Assist

Active Stop-and-Go Assist helps you when in traffic jams on multi-lane roads with separate roadways by automatically pulling away within up to 60 seconds and with moderate steering maneuvers. It orients itself using the vehicle in front and lane markings. Active Stop-and-Go Assist automatically maintains a safe distance from the vehicle in front and vehicles cutting in.

Active Stop-and-Go Assist requires you, as the driver, to keep your hands on the steering wheel at all times so that you are able to intervene at any time to correct the course of the vehicle and keep it in lane.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

Active Stop-and-Go Assist activates automatically when all the following conditions are met:

- You are in a traffic jam on a highway or highspeed major road.
- Active Distance Assist DISTRONIC is activated and active (→ page 240).

- · Active Steering Assist is activated and active  $(\rightarrow page 248)$ .
- You are traveling no faster than 35 mph (60 km/h).

When Active Stop-and-Go Assist is active the status display appears on the driver's display.

#### System limits

The system limitations of Active Distance Assist DISTRONIC and Active Steering Assist apply to Active Stop-and-Go Assist (→ page 246).

# DSR (Downhill Speed Regulation)

#### Function of DSR

DSR is an aid to assist you when driving downhill. It keeps the speed of travel at the selected target speed. The steeper the downhill gradient, the greater the DSR braking effect on the vehicle. On flat stretches of road and uphill gradients, DSR brakes the vehicle minimally or not at all.

When DSR is activated and the transmission is in position D, R or N, DSR controls the driving

speed. The target speed can be set to a value between 1 mph (2 km/h) and 11 mph (18 km/h). By braking or accelerating, you can drive at a higher or lower speed than the target speed at any time.

DSR will be switched off automatically

- if you are driving at a speed greater than 28 mph (45 km/h)
- if you change the drive program

The Off message will appear on the driver's display. The status indicator on the driver's display will go out. You will also hear a warning tone.

(i) DSR will remain active in drive program .

### ■ Information on DSR

WARNING Risk of skidding and accident when DSR is activated on slippery road surfaces

If the driven speed and the target speed differ, the wheels may lose traction.

Take into account the road surface and the difference between the driving speed and target speed before activating DSR.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

You are always responsible for keeping control of the vehicle and for assessing whether the downhill gradient can be negotiated. Depending on road surface and tires. DSR may not always be able to keep to the target speed. Select a target speed suitable for the environmental conditions and also apply the brakes yourself if required.

# Activating or deactivating DSR (Downhill Speed) Regulation)

## Requirements

• You are driving at 24 mph (40 km/h) or slower.

If the vehicle speed is too high, the Max. speed 40 km/h message appears in the driver's display.

Active Distance Assist DISTRONIC, cruise control and the variable limiter are switched off.

## Multimedia system:

- → Settings → Assistance
- ► Select ssr .

A status display appears in the driver's display when the function is activated.

## Changing the target speed



- To increase the target speed: swipe upwards from the bottom of control panel 1.
  - The target speed will be increased by 1 mph (1 km/h).

Or

Press and hold set at the top of control panel n.

The target speed will be increased in 1-mph (1-km/h) increments.

- To reduce the target speed: swipe downwards from the top of control panel .
  - The target speed will be reduced by 1 mph (1 km/h).

or

Press and hold set— at the bottom of control panel .

The target speed will be reduced in 1-mph (1-km/h) increments.

The set target speed will be shown and next to the status display on the driver's display.

## **Active Steering Assist**

# ■ Function of Active Steering Assist

Active Steering Assist is available up to a speed of 130 mph (210 km/h). The system helps you to stay in the center of the lane by means of moderate steering interventions. Depending on the vehicle's speed, Active Steering Assist uses the vehicles ahead and lane markings as a reference.

(i) Depending on the country, Active Steering Assist can use the surrounding traffic as a reference in the lower speed range. If necessary, Active Steering Assist can then also provide assistance outside the center of the lane.

If the detection of lane markings and vehicles ahead is impaired, Active Steering Assist will switch to passive mode. The system will provide no support in this case.

## Permanent status display on the driver's display

Gray: activated and passive

Green: activated and active

Red, flashing: prompt to the driver to actively confirm or transition from active to passive status, system limit detected

(i) During the transition from active to passive status, the symbol will be shown as enlarged and flashing. Once the system is passive, the symbol will be shown as gray on the driver's display.

#### Touch detection

The driver is required to keep their hands on the steering wheel at all times and be able to intervene at any time to correct the course of the vehicle and keep it in lane. The driver must expect a change from active to passive mode or vice versa at any time.



If the system detects that the driver has not steered the vehicle for a considerable period of time or has removed their hands from the steering wheel, an optical warning will be given first. Display 1 will appear on the driver's display. If the driver still does not steer the vehicle, or gives no confirmation to the system, a warning tone will sound in addition to the visual warning message.

If the driver does not react to this warning for a considerable period, an emergency stop may be initiated ( $\rightarrow$  page 248).

The warning will not be issued or will be stopped as soon as the system detects that the driver has touched the steering wheel.

Touch detection may be limited or may not function if there is no direct contact between hand and steering wheel, e.g. if you are wearing gloves or if there is a steering wheel cover on the steering wheel.

If Active Steering Assist detects that a system limit has been reached, a visual warning will be issued and a warning tone will sound.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

#### System limits

Active Steering Assist has a limited steering torque for lateral guidance. In some cases, the steering intervention will not be sufficient to keep the vehicle in the lane.

The system may be impaired or may not function in the following instances:

- Visibility is poor, e.g. due to snow, rain, fog, heavy spray, greatly varying ambient light or strong shadows on the road.
- There is glare, e.g. from oncoming traffic, direct sunlight or reflections.
- There is insufficient illumination of the road.
- The windshield is dirty, fogged up, damaged or covered in the vicinity of the camera, e.g. by a sticker.
- No lane markings or several unclear lane markings are present for one lane, or the markings change quickly, for example, in a construction area or at intersections.
- The lane markings are worn away, dark or covered up, e.g. by dirt or snow.

- The distance to the vehicle in front is too short and the lane markings cannot be detected as a result.
- The road is narrow and winding.
- There are obstacles in the lane or projecting out into the lane, such as object markers.
- Transport equipment such as a trailer or bicycle rack is attached to the trailer hitch and the electrical connection has been correctly established.

The system will not provide assistance in the following conditions:

- · On very tight bends and when turning.
- · When crossing intersections.
- · At traffic circles or toll stations.
- When actively changing lane without switching on the turn signal indicator.
- When the tire pressure is too low.

# **WARNING** Risk of accident if Active Steering Assist unexpectedly stops functioning

If the system limits of Active Steering Assist are reached there is no guarantee that the system will remain active or will keep the vehicle in lane.

- Always keep your hands on the steering wheel and observe the traffic carefully.
- Always steer the vehicle paying attention to traffic conditions.

# WARNING Risk of accident if Active Steering Assist unexpectedly intervenes

The detection of lane markings and objects may malfunction and cause unexpected steering interventions.

Steer according to traffic conditions.

# Activating/deactivating Active Steering Assist

## Requirements

ESP<sup>®</sup> is activated, but is not intervening.

Active Distance Assist DISTRONIC is activated.

Multimedia system:

Activate or deactivate Active Steering Assist.

## **Function of Active Emergency Stop Assist**

Active Emergency Stop Assist monitors the steering wheel as well as the accelerator and brake pedals. If the system detects a lack of driver activity or the vehicle is in danger of leaving the lane, a warning can be issued and an emergency stop initiated.

Vehicles without Driving Assistance Package: The system is available from a speed of approx. 37 mph (60 km/h).

Vehicles with Driving Assistance package: If Active Steering Assist is switched off, the system is available from a speed of approx. 37 mph (60 km/h).

If the system detects that the vehicle is in danger of leaving the lane, a warning can be issued and an emergency stop initiated.

- The driver has not touched the steering wheel for a certain while, or no steering movement is detected for a lengthy period (depending on the vehicle equipment).
- Neither the accelerator nor the brake pedal is depressed.
- (i) Vehicles with Driving Assistance package: if Active Steering Assist is switched on and active, the system monitors only the steering wheel. If the driver has not touched the steering wheel for a certain while, a warning may be issued despite pedal actuation. Observe also the instructions on the touch detection of Active Steering Assist  $(\rightarrow page 246)$ .



Active Emergency Stop Assist issues the following warnings in order:

- Display message ① appears in the driver displav.
- In addition to display ①, a warning tone sounds.
- The Initiating Emergency Stop message appears in the driver display, a continuous warning tone sounds and the vehicle will no longer accelerate. Additionally, a slight tensioning of the belt will be generated as required.

- The vehicle speed is reduced in increments until the vehicle comes to a standstill. Sharp brake impulses are also effected.
- i Vehicles with Driving Assistance Package: If Active Distance Assist DISTRONIC is active and the driver unfastens the seat belt and opens the driver's door, an emergency stop can be initiated immediately.

Vehicles with Driving Assistance package: If possible, a lane change to the adjacent lane is performed (country-dependent). It is possible to change lanes across one lane and only to the outside lane, not to the hard shoulder.

When automatic braking is initiated, Active Distance Assist DISTRONIC is deactivated. Depending on the respective country, the hazard warning light system is switched on.

When the vehicle has come to a standstill:

- · the vehicle is secured with the electric parking brake.
- the vehicle is unlocked.
- if possible, an emergency call is made to the Mercedes-Benz emergency call center.

Before automatic braking is initiated, you can cancel Active Emergency Stop Assist by turning the steering wheel.

You can cancel an intervention by Active Emergency Stop Assist after automatic braking is initiated by performing one of the following actions:

- Accelerating or braking: the emergency stop is canceled, but the warning message, warning tone and electric power steering remain active
- Steering: electric power steering is canceled, the warning message and warning tone remain active, and the vehicle continues to be braked
- Active Emergency Stop Assist can initiate an emergency stop a maximum of three times within a driving cycle. After that, Active Steering Assist and Active Emergency Stop Assist are disabled until the vehicle has been restarted.

## System limits

For the detection of vehicles and other obstacles, observe the system limits of the following functions:

- Active Distance Assist DISTRONIC
   (→ page 237)
- Active Steering Assist (→ page 246)
- Active Lane Change Assist (→ page 250)
- Active Lane Keeping Assist (→ page 268)
- Active Brake Assist (→ page 254)

### Vehicles without Driving Assistance Package:

Active Emergency Stop Assist is inactive in the following cases:

- Active Lane Keeping Assist has reached a system limit.
- \( \overline{\nabla\_{is}} \) Active Lane Keeping Assist is switched off (white status display).
- 7:1 Active Lane Keeping Assist is not ready (gray status display).


# **Active Lane Change Assist**

# ■ Function of Active Lane Change Assist

Active Lane Change Assist helps the driver with changing lanes by applying steering torque and is activated when the driver indicates briefly.

For this, the following conditions must be fulfilled:

- You are driving on a highway or high-speed major road.
- The vehicle's speed is between approximately 40 mph (65 km/h) and 110 mph (180 km/h).
- The adjacent lane is separated by a broken lane marking.
- No vehicle or obstacle is detected in the adjacent lane.
- Active Lane Change Assist is selected in the multimedia system.
- Active Distance Assist DISTRONIC and Active Steering Assist are switched on and active.



Display in the driver's display in the menuAssistance

- Green arrow: lane change initiated
- 2 Red arrow: lane change canceled

When Active Lane Change Assist is available, the indicator will appear along with green arrows on the driver's display. If the system has been activated but is not currently available, the indicator will appear along with gray arrows on the driver's display.

If no vehicle or obstacle is detected in the adiacent lane and a lane change is permitted, the lane change will begin after the driver has indicated briefly. The lane change will be shown to the driver with a flashing green arrow next to the steering wheel symbol. Green arrow 1 will be displayed in the appropriate adjacent lane on the driver's display on the Assistance menu. A message reading Lane Change to the Left, for example, will also appear.

If a lane change is not possible directly after the driver has activated the turn signal indicator because e.g. an obstacle has been detected, the arrow will also flash in green next to the steering wheel symbol . The neighboring lane will continue to be monitored. When the lane becomes clear, a lane change will be carried out and a message reading e.g. Lane Change to the Left will appear on the driver's display. When the green arrows stop flashing, activate the lane change again.

Active Lane Change Assist can be canceled in various situations, including the following:

- · Change in the surrounding conditions (e.g. detected obstacle).
- The driver steers too sharply or in the opposite direction.
- The driver moves the turn signal indicator in the opposite direction.
- Active Distance Assist DISTRONIC or Active Steering Assist is deactivated.
- The vehicle cannot make the lane change as planned.

Cancellation of Active Lane Change Assist will be displayed as follows:

- The arrow in the selected direction of travel turns red.
- A corresponding message will also appear in the driver's display.
- In certain circumstances, a warning tone will sound.

## A

WARNING Risk of accident when changing lane to an occupied adjacent lane

Lane Change Assist cannot always clearly detect if the adjacent lane is free.

The lane change might be initiated although the adjacent lane is not free.

- Before changing lanes, make sure that the neighboring lane is free and there is no danger to other road users.
- Monitor the lane change.

# **WARNING** Risk of accident if Lane Change Assist unexpectedly stops functioning

If the system limitations for Lane Change Assist have been reached, there is no guarantee that the system will remain active.

Lane Change Assist cannot then assist you by applying steering torque.

Always monitor the lane change and keep your hands on the steering wheel. Observe the traffic conditions and steer and/or brake if necessary.

### Automatic Lane Change

Automatic Lane Change is a sub-function of Active Lane Change Assist. It can assist the driver in deciding when a lane change is appropriate and in executing it.

## A

**WARNING** Risk of accident due to incorrectly triggered lane change

The system cannot always clearly recognize all situations in which a lane change is appropriate.

The system can initiate a lane change even though the traffic situation is not suitable or the neighboring lane is not available, not usable or occupied.

- Always monitor the traffic situation.
- If necessary, cancel the lane change by holding the steering wheel or countersteering slightly and return the vehicle to its own lane.

You can cancel a lane change initiated by the system at any time by holding the steering wheel or

countersteering slightly and returning the vehicle to its own lane.

For an Automatic Lane Change, the following conditions must be met:

- The conditions for activating Active Lane Change Assist are fulfilled.
- Automatic Lane Change is activated in the multimedia system.
- You are driving on a freeway in a country where the function is available.
- The road you are currently driving on allows lane changes (e.g. there are no tight bends).
- The vehicle speed is between approximately 40 mph (65 km/h) and 85 mph (140 km/h).

Active Lane Change Assist can initiate an automatic lane change in various situations, including the following:

 The set desired speed of Active Distance Assist DISTRONIC cannot be reached due to a slower vehicle in front.

- There is little traffic and the set desired speed of Active Distance Assist DISTRONIC can also be reached in a slower lane
- A lane change is necessary to follow the set route in the navigation system or the road you are currently driving on. The lane change may take place before the request to do so appears in the navigation system.
- · The system detects that the lane you are driving in will end soon.
- You are in the lane furthest to the right.

In particular, Active Lane Change Assist will not execute Automatic Lane Change in the following situations:

- If the vehicle is already in a lane that it should use to follow the set route in the navigation system.
- On some route sections, no lane change will be made to the lanes furthest to the right.
- The system detects that the neighboring lane will end soon.

- If Automatic Lane Change has been canceled by the driver, no lane change in that direction will be initiated for a certain time
- If the driver has initiated a lane change in one direction or has changed lanes manually, no lane change in the opposite direction will be initiated for a certain time.

The same abort conditions apply to Automatic Lane Change as to driver-initiated lane changes with Active Lane Change Assist.

In addition, Automatic Lane Change can be canceled in the following circumstances in particular:

- The system detects a road work site marked off by traffic cones in the vehicle's own lane or in the neighboring lane during the lane change.
- The system detects that the reason for the lane change no longer exists.

## Display in the driver's display

When Automatic Lane Change is turned on, the Automatic Lane Change On message will appear. When Automatic Lane Change is available, the ASA indicator will appear in green instead of the

indicator. If Automatic Lane Change is available but not all conditions to activate the function are currently met, the A symbols will be shown in gray. If the system deems it advisable to change lanes and needs to adjust the traveled speed to do so, the green A will flash on the side to which a lane change is to be made.

When Automatic Lane Change starts, for example, the Lane Change to the Left message will appear and a warning tone will sound.

When Automatic Lane Change is canceled, the A on the side to which a lane change should be made will turn red. Additional warning messages may also appear and another warning tone may sound in certain situations.

#### System limits

The system limits of Active Steering Assist apply to Active Lane Change Assist ( $\rightarrow$  page 246).

The system may also be impaired or may not function in the following situations:

- The sensors are damaged, covered or dirty  $(\rightarrow page 225).$
- The exterior lighting shows a defect.

- The system does not detect a suitable road, such as on tight bends.
- . The vehicle is at a road work site.

Automatic Lane Change may not function or may be impaired in the following situations in particular and could lead to lane changes being initiated incorrectly:

- The vehicle is at a road work site and/or the system has detected a road work site marked off by traffic cones.
- The system can no longer detect the lane marking correctly.
- It is raining heavily.
- Another vehicle changes to the same lane at the same time (e.g. when the vehicle is passing an on-ramp).
- (i) The Active Lane Change Assist sensors adjust automatically while a certain distance is being driven after the vehicle has been delivered. Active Lane Change Assist will be unavailable during this teach-in process, and no arrows will be displayed next to the Active Steering Assist symbol .

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

## Setting Active Lane Change Assist

Multimedia system:

- → Settings → Assistance → Driving → Active Lane Change Assist
- Select Active Lane Change Assist.
- Choose between the On and Off setting options.
- Choose between the On, Also Automatically and Off setting options.

The Also Automatically setting option can also be switched on and off on the quick-access menu.

(i) If Active Steering Assist has been switched off, it will not be possible to operate Active Lane Change Assist.

#### **Active Brake Assist**


#### ■ Function of Active Brake Assist

Active Brake Assist consists of the following functions:

- Collision warning
- · Autonomous braking function
- · Situation-dependent brake force boosting
- Vehicles with Driving Assistance Package and Active Steering Assist: Evasive Steering Assist
- Vehicles with Driving Assistance Package: Evasive Steering Assist
- Vehicles with Driving Assistance Package: intersection start-off function

Active Brake Assist can help you to minimize the risk of a collision with vehicles, cyclists or pedestrians or to reduce the effects of such a collision.

If Active Brake Assist has detected a risk of collision, a warning tone will sound and the distance warning lamp will light up.



Display on the driver's display in the Assistance menu

- Insufficient distance
- Red radar waves

In the Assistance menu, an insufficient distance to the vehicle in front 1 will be displayed in red. If you further reduce the distance, the vehicle in front will also be highlighted in red. When the system detects a risk of collision, red radar waves 2 will appear in front of your vehicle.

i Vehicles with PRE-SAFE®: depending on the country, an additional haptic warning will occur in the form of slight, repeated tensioning of the seat belt on the driver's side.

Vehicles with active ambient lighting: if Warning Support is activated, the Active Brake Assist warning will also be accompanied by ambient lighting ( $\rightarrow$  page 143).

If you do not react to the warning, autonomous braking can be initiated in critical situations. In particularly critical situations, Active Brake Assist can also initiate autonomous braking directly. In this case, the warning tone and the distance warning lamp | will occur at the same time as the brake application.

If you apply the brakes yourself in a critical situation or apply the brakes during autonomous braking, situation-dependent brake force boosting will occur. The brake pressure will increase up to maximum full-stop braking if necessary.



If autonomous braking or situation-dependent brake force boosting has occurred, pop-up 1 will appear on the driver's display and then automatically disappear after a short time.

If the autonomous braking function or situationdependent brake force boosting is triggered, preventive measures for occupant protection (PRE-SAFE®) may also be initiated.

WARNING Risk of an accident caused by limited detection performance of Active Brake Assist

Active Brake Assist cannot always clearly identify objects and complex traffic situations.

In such cases, Active Brake Assist might:

- Give a warning or brake without reason
- Not give a warning or not brake

Active Brake Assist is only an aid. The driver is responsible for maintaining a sufficiently safe distance to the vehicle in front, vehicle speed and for braking in good time.

- Always pay careful attention to the traffic situation; do not rely on Active Brake Assist alone.
- Be prepared to brake or swerve if necessary.

If Active Brake Assist is deactivated or the functions are restricted, e.g. due to activation of another driving system, the Active Brake Assist warning lamp will appear on the driver's display.

If the system is unavailable due to dirty or damaged sensors or due to a malfunction, or if the functions are restricted, the Active Brake Assist warning lamp will appear on the driver's display.

Also observe the system limits of Active Brake Assist.

The individual subfunctions are available in the following speed ranges:

### Collision warning

The collision warning can assist you in the following situations from approximately 4 mph (7 km/h) with an intermittent warning tone and the distance warning lamp 🔼.

Vehicles without Driving Assistance Package:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 50 mph (80 km/h) when approaching stationary vehicles, pedestrians walking in the direction of travel and cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching crossing pedestrians and cyclists
- At speeds up to approximately 37 mph (60 km/h) when approaching stationary pedestrians and cyclists

Vehicles with Driving Assistance Package:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 75 mph (120 km/h) when approaching crossing vehicles, pedestrians and cyclists
- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching stationary pedestrians and cyclists

## Autonomous braking function

From a speed of approximately 4 mph (7 km/h), the autonomous braking function may intervene in the following situations:

Vehicles without Driving Assistance Package:

 At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead

- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead, pedestrians walking in the direction of travel and stationary vehicles
- At speeds up to approximately 43 mph (70 km/h) when approaching crossing pedestrians and cyclists

#### Vehicles with Driving Assistance Package:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 75 mph (120 km/h) when approaching crossing vehicles, pedestrians and cyclists
- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching stationary pedestrians and cyclists

## Situation-dependent brake force boosting

From a speed of approximately 4 mph (7 km/h), situation-dependent brake force boosting may intervene in the following situations.

Vehicles without Driving Assistance Package:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead. pedestrians walking in the direction of travel and stationary vehicles
- At speeds up to approximately 43 mph (70 km/h) when approaching crossing pedestrians and cyclists
- At speeds up to approximately 37 mph (60 km/h) when approaching stationary pedestrians and cyclists

Vehicles with Driving Assistance Package:

- At speeds up to approximately 155 mph (250 km/h) when approaching vehicles ahead
- At speeds up to approximately 75 mph (120 km/h) when approaching crossing vehicles, pedestrians and cyclists

- At speeds up to approximately 62 mph (100 km/h) when approaching stationary vehicles
- At speeds up to approximately 50 mph (80 km/h) when approaching cyclists ahead
- At speeds up to approximately 43 mph (70 km/h) when approaching stationary pedestrians and cyclists

## Canceling a brake application by Active Brake Assist

You can cancel a brake application by Active Brake Assist at any time:

- by fully depressing the accelerator pedal or with kickdown.
- by releasing the brake pedal.

Active Brake Assist may cancel the brake application when one of the following conditions is fulfilled:

- You maneuver to avoid an obstacle.
- There is no longer a risk of collision.

 An obstacle is no longer detected in front of your vehicle.

# Reaction to oncoming road users (only vehicles with Driving Assistance Package)

Active Brake Assist can also react to detected oncoming road users:

- Reaction up to a speed of approximately 62 mph (100 km/h)
- Warning regarding oncoming road users via warning tone and distance warning lamp
- Autonomous brake application in order to reduce the severity of an accident

# Intersection start-off function (vehicles with Driving Assistance Package only)



If a risk of collision with crossing traffic is detected when you are pulling away or driving at walking pace, three red arrows pointing in the direction of the crossing road user will light up one after the other on the driver's display together with the distance warning lamp  $\boxed{\mathbb{A}}$ . If the situation is particularly critical, the arrows will flash. A warning tone will also sound. If you do not react to the warning in critical situations, acceleration may be restricted or autonomous braking may be initiated. Autonomous braking can also prevent the vehicle from pulling away and hold it at a

standstill. In particularly critical situations, Active Brake Assist can also initiate autonomous braking directly. In this case, the distance warning lamp and the warning tone will occur at the same time as the brake application.

If autonomous braking or situation-dependent brake force boosting has occurred, a pop-up will appear on the driver's display and then automatically disappear after a short time.

In the Late setting of Active Brake Assist, the purely visual warning level and the limitation of possible acceleration will be deactivated. If the situation is particularly critical, it is still possible for a visual warning to be issued, a warning tone to be emitted and autonomous braking to be initiated.

## **Evasive Steering Assist**



**WARNING** Risk of accident despite Evasive Steering Assist

Evasive Steering Assist cannot always recognize objects or complex traffic situations clearly.

Moreover, the steering support provided by Evasive Steering Assist is not sufficient to avoid a collision.

- Always pay careful attention to the traffic situation: do not rely on Evasive Steering Assist alone.
- Be prepared to brake or swerve if necessarv.
- ► End the support by actively steering in non-critical situations.
- Drive at an appropriate speed if there are pedestrians close to the path of your vehicle.

Evasive Steering Assist has the following characteristics:

- Detection of pedestrians, cyclists and vehicles.
- · Assistance through power-assisted steering if a swerving maneuver is detected.
- · Activation by an abrupt steering movement during a swerving maneuver.

- Assistance during swerving and straightening of the vehicle
- Reaction from a speed of approximately 12 mph (20 km/h) up to a speed of approximately 68 mph (110 km/h).

The support of Evasive Steering Assist can be canceled at any time by counter steering.

#### System limits

Full system performance will not yet be available for a short time after switching on the vehicle or after driving off. As long as the functions are restricted, the Active Brake Assist warning lamp may also be shown on the driver's display. Depending on the environmental conditions. it may take a few minutes before full system performance is available.

The system may be impaired or may not function, particularly in the following situations:

- In snow, rain, fog, heavy spray, direct sunlight or greatly varying ambient light, or if there is glare.
- If the sensors are dirty, fogged up, damaged or covered. ( $\rightarrow$  page 225)

- If the sensors are impaired due to interference from other radar sources, e.g. strong radar reflections in parking garages.
- If a loss of tire pressure or a defective tire has been detected and displayed.
- In complex traffic situations where objects cannot always be clearly identified.
- If pedestrians, cyclists or vehicles move quickly into the sensor detection range.
- If road users are hidden by other objects or are located close to other objects.
- If the typical outline of a pedestrian or cyclist cannot be distinguished from the background.
- If a pedestrian or cyclist is not detected as such, e.g. due to special clothing or other objects.
- If the driver's seat belt is not fastened.
- · On bends with a tight radius.

## Setting Active Brake Assist

#### Requirements

The vehicle is switched on.

Multimedia system:

- Activate or deactivate the function.
- i It is recommended that you always leave Active Brake Assist activated.

Switching off Active Brake Assist also switches off the distance warning function, the collision warning, the autonomous braking function and Active Evasive Steering Assist (with Driving Assistance Package - country-dependent).

i If Active Brake Assist is deactivated, the symbol appears in the status bar of the driver display. When the vehicle is next started, the system is activated again.

#### Setting warning timing

- ► Select alongside Active Brake Assist.
- Select Early, Medium or Late.

## Traffic Sign Assist

## Function of Traffic Sign Assist

Traffic Sign Assist detects the traffic signs with the multifunction camera and compares them with the information on the digital road map of the navigation system. It supports you by showing detected speed restrictions and overtaking bans on the driver display.

Maximum permissible speeds can also be shown on the head-up display.

The system can issue a warning when you exceed the maximum permissible speed.

In some countries, the system can provide you with further functions and can warn you when you are approaching pedestrian crossings or when you are about to drive past stop signs or red lights unintentionally.

The camera also detects and analyzes traffic signs with a restriction indicated by an additional sign (e.g. in wet conditions).

Traffic Sign Assist portrays only selected signs on the driver display. Actual traffic signs and speed

restrictions have priority over traffic signs and speed restrictions shown on the driver display.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize potential dangers ( $\rightarrow$  page 225).

#### Notes on trailer operation

Observe also the notes on trailer operation
 (→ page 299).

If a trailer or bicycle rack is connected correctly, the central display shows the query about the type of trailer and its maximum permissible speed ( $\rightarrow$  page 303).

The driver must manually adjust the maximum permissible speed in the small or large trailer category.

In particular, the country-specific laws must be taken into account, e.g. on:

- maximum design speed or speed restriction for which the vehicle is approved
- permissible gross mass with or without towing vehicle

- required number of years with a corresponding driving license
- type and condition of the road used
- the weather conditions

The maximum permissible speed adapted to the vehicle/trailer combination can be transferred to the manual or automatic speed transfer during the journey (depending on the equipment).

On the system side, relevant additional signs for speed restrictions and clear road category traffic rules can be considered for the vehicle combination (depending on the country).

No maximum permissible speed can be selected for a bicycle rack in the multimedia system. When using a bicycle rack, observe the specifications for the maximum permissible speed in the Operator's Manual

Observe also the following information:

- · select a speed adapted to the traffic, surroundings and weather conditions
- · observe actual traffic signs
- observe applicable traffic rules and regulations

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize potential dangers ( $\rightarrow$  page 225).

### Displays on the driver display



- Permissible speed
- Permissible speed when there is a restriction
- Additional sign with restriction

The system can show up to two traffic signs on the driver display simultaneously. The system always prioritizes displaying speed restrictions. The head-up display shows only one traffic sign with a maximum permissible speed. If two speed signs are shown on the driver display, forexample, when speed limits are detected, the value of the left-hand speed restriction (1) is always transmitted to the cruise control or Active Distance Assist DISTRONIC for acceptance and shown on the head-up display.

Important information from other systems can cause traffic signs to be hidden for a short time.



Examples of traffic signs which can be displayed

Traffic Sign Assist can detect and display the following traffic signs (1):

- · speed restrictions
- end of the speed restriction
- overtaking restrictions

- play streets
- · recommended speeds

Traffic Sign Assist can detect the following additional signs ⓐ and, if necessary, analyze the relevance of the restrictions using other vehicle sensors:

- · in wet conditions
- slippery road surfaces
- in fog
- · temporary restrictions
- exits
- restrictions for car/trailer combinations

Traffic Sign Assist also uses data from the digital street map on the navigation system. When you leave or enter a municipality or change roads, on a highway exit or slip road forexample, or after you turn at a intersection, the display on the driver display can thus be updated without a traffic sign having been detected.

(i) Regularly update the digital road map of the navigation system to ensure optimum functioning of Traffic Sign Assist. If Traffic Sign Assist cannot determine the currently applicable maximum permissible speed (e.g. due to a lack of signage), the following display appears in the driver display:



Traffic Sign Assist is not available in all countries. This display is shown permanently in the vehicle when you are traveling in countries that do not support Traffic Sign Assist.

If the system is temporarily or permanently unavailable due to a technical malfunction or soiling of the windshield, a corresponding display message appears in the driver display. The Traffic Sign Assist warning lamp also lights up in the driver display in certain countries.

 Please also note the information on the display messages from Traffic Sign Assist (→ page 461).

## Warning when the maximum permissible speed is exceeded

The system can warn you if you unintentionally exceed the maximum permissible speed. Depending on the country, you can set how much the maximum permissible speed may be exceeded on the multimedia system before a warning is issued. You can switch off the warning, or select in the settings whether the warning should be issued optically, with the traffic sign flashing in the driver display, or as a combination of optic and acoustic warning. Selection of the type of warning is confirmed via an indication in the driver display, depending on the respective country of use.



- Optical warning only
- WARNING off
- (i) The type, duration and deployment stages of the speed limit warning, as well as the option of setting the timing of the deployment stages upon which the warning is issued, are subject to legislation valid for the respective country in which the vehicle is delivered.

## Additional functions of Traffic Sign Assist (country-specific)

Warning for no-entry signs: Traffic Sign Assist can warn you if you drive the wrong way down a sec-

tion of road, forexample, on highway slip roads or one-way streets.

Warning at pedestrian crossings: if you approach pedestrian crossings, provided that pedestrians are in the danger zone or are moving towards it, Traffic Sign Assist can warn you up to a speed of approximately 44 mph (70 km/h).

Warning at stop signs: Traffic Sign Assist can warn you up to a speed of approximately 44 mph (70 km/h) if you are about to drive past a stop sign unintentionally. For this to be possible, the signs must be clear. For example, if the system detects more than one stop sign, a stop sign can be confirmed using the digital navigation map. No warning can be issued if several different signs are detected.

Warning at red lights: Traffic Sign Assist can warn vou up to a speed of approximately 44 mph (70 km/h) if you are about to drive through a red light unintentionally.

The following conditions must be fulfilled:

- · Several traffic lights have been detected.
- · All traffic lights detected are red.

- · At least one of the red traffic lights detected is on the front passenger side beside the vehicle's lane
- The traffic lights are in the following sequence (from top to bottom): red, yellow, and green.
- (i) Where available, you can turn the warnings on and off in the Traffic Sign Assist menu under Further Warnings( $\rightarrow$  page 264).

### System limits

The system may be impaired or inoperative in the following situations in particular:

- If visibility is poor, e.g. due to insufficient illumination of the road, highly variable shade conditions, rain, snow, fog, swirling dust or heavy spray.
- If there is glare, e.g. from oncoming traffic. direct sunlight or reflections.
- if there is soiling on the windshield in the vicinity of the multifunction camera or if the camera is fogged up, damaged or obscured.
- If the traffic signs are difficult to see because, forexample, they are dirty, obscured, faded,

iced over, damaged, inconveniently positioned, insufficiently illuminated or askew.

- Active traffic signs with LED displays may not be detected correctly, or even at all due to technical factors such as transmission frequency.
- If the information on the navigation system's digital map is incorrect, incomplete or out of date.
- If the signs, road markings or road layout are ambiguous, e.g. traffic signs at road works, at exits and slip roads, adjacent lanes or parallel roads, and pedestrian crossing markings at traffic lights.
- If the signage or road markings do not comply with the standard.
- If the signage, road markings, or road guidance is country-specific and deviates from the navigation system's route guidance, e.g. at or after road works.
- After sharp turns and tight bends, if traffic signs are outside the camera's field of vision.
- If you overtake vehicles with traffic signs affixed or attached to them.

 If you use transport equipment secured to the vehicle with a trailer coupling, suchas a bicycle rack, restrictions for vehicle/trailer combinations may be considered valid if applicable.

## Setting Traffic Sign Assist

Multimedia system:

→ Settings → Assistance → Assistance → Traffic Sign Assist

### Activating or deactivating the speed warning

Switch off Speed Limit Warning. Following country-specific legislation, the speed warning will remain off until the next time the vehicle is switched on or off and the driver's door is opened (depending on the equipment).

#### Change the type of speed warning

Change the warning to Visual or Visual & Audible.

## Setting the warning threshold

This value determines the speed at which a warning is issued when exceeded.

Set the desired speed under Warning Threshold.

## Activating or deactivating further functions of Traffic Sign Assist

Switch Further Warnings on or off.
The available functions are switched on or off.

### Set the type of warning for other functions

Select Visual or Visual & Audible.

## Blind Spot Assist and Active Blind Spot Assist

# Function of Blind Spot Assist and Active Blind Spot Assist with exit warning

Blind Spot Assist and Active Blind Spot Assist use radar sensors to monitor the area up to 130 ft (40 m) behind and 10 ft (3 m) next to your vehicle.

The system can detect vehicles from a speed of approximately 8 mph (12 km/h) and issue a warning if they move into the monitoring range.

Status display on the driver's display

**Gray:** the system is activated but not operational.

Green: the system is activated and operational.



Display on the driver's display in the Assistance menu

- Warning lamp in the outside mirror
- Red radar waves

If a vehicle is detected from approximately 8 mph (12 km/h) and this vehicle enters the warning range immediately afterwards, the warning lamp in the corresponding outside mirror will light up red. In the Assistance menu, the lamp in outside mirror 
will also light up red, and the lane in which the vehicle is detected will be hatched out. If a vehicle is detected in the warning range and you switch on the turn signal indicator in the corresponding direction, a double warning tone will sound once and the warning lamp in the corresponding outside mirror will flash red. Red radar waves 2 will be displayed next to your vehicle on the assistant display.

If the turn signal indicator remains on, the display in the outside mirror will flash for all other detected vehicles, but no further warning tone will sound. If you overtake a vehicle quickly, no warning will be given.

(i) Vehicles with active ambient lighting: if Warning Support is activated, the warning will also be highlighted by the ambient lighting  $(\rightarrow page 143)$ .

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize dangers ( $\rightarrow$  page 225).

▲ WARNING Risk of accident despite Blind Spot Assist

Blind Spot Assist does not react to vehicles approaching and overtaking you at a greatly different speed.

Blind Spot Assist cannot warn drivers in this situation.

Always pay careful attention to the traffic situation and maintain a safe distance at the side of the vehicle.

**A** WARNING Risk of accident despite Active Blind Spot Assist

Active Blind Spot Assist does not react to the following:

- if you overtake a vehicle too closely so that it is in the blind spot area
- · if vehicles traveling at a much faster speed approach and then overtake

Active Blind Spot Assist may not give warnings or intervene in such situations.

Always pay careful attention to the traffic situation and maintain a safe distance at the side of the vehicle.

## Exit warning

The exit warning is an additional function of Blind Spot Assist and Active Blind Spot Assist and can warn vehicle occupants attempting to leave a stationary vehicle about approaching vehicles.

**WARNING** Risk of accident despite exit warning

The exit warning neither reacts to stationary objects nor to persons or road users approaching you at a greatly differing speed.

The exit warning cannot warn drivers in these situations.

Always pay particular attention to the traffic situation when opening the doors and make sure there is sufficient clearance. If a vehicle is detected in the monitoring range, the warning lamp in the corresponding outside mirror will light up red.

If a vehicle occupant pulls the door handle on the side for which the warning is issued, a warning tone will sound twice and the ambient lighting in the respective door and the warning lamps in the corresponding outside mirror will flash red.

- (i) Vehicles with ambient lighting or active ambient lighting: the Warning Support provided by the ambient lighting can be activated and deactivated (→ page 143).
- (i) The warning assistance can differ depending on the equipment and may vary according to the setting.

The exit warning is available only when Blind Spot Assist or Active Blind Spot Assist is active.

After the vehicle is switched off, the exit warning continues to function for a few minutes. When the outside mirror warning lamp flashes three times, the exit warning is no longer available.

The exit warning is only an aid and not a substitute for the attention of vehicle occupants. The

responsibility when opening the doors and leaving the vehicle remains with the vehicle occupants.

#### System limits

Blind Spot Assist and Active Blind Spot Assist may be limited in the following situations in particular:

- If there is dirt on the sensors or the sensors are obscured
- In poor visibility, e.g. due to fog, heavy rain or snow
- If there are narrow vehicles, e.g. bicycles or motorbikes
- If the road has very wide or narrow lanes
- If vehicles are not driving in the middle of their lane

Warnings may be issued in error when you drive close to crash barriers or similar structural lane borders. Always make sure that there is sufficient distance at the sides for other traffic or obstacles.

Warnings may be interrupted when you drive alongside long vehicles, such as trucks, for a prolonged time.

Blind Spot Assist and Active Blind Spot Assist are not operational when reverse gear is engaged.

Blind Spot Assist and Active Blind Spot Assist will not be operational if transport equipment, for example a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection has been correctly established.

Additionally, the exit warning may be limited in the following situations:

- · When the sensors are covered by adjacent vehicles in narrow parking spaces
- When people approach the vehicle
- · In the event of stationary or slow moving objects

## Function of braking intervention by Active Blind Spot Assist

(i) The brake application function is available only for vehicles with a Driving Assistance Package.

If Active Blind Spot Assist detects a risk of a side impact in the monitoring range, a course-correct-

ing brake application is carried out. This is designed to help you avoid a collision.

The course-correcting brake application is available in the speed range between approximately 20 mph (30 km/h) and approximately 125 mph  $(200 \, \text{km/h}).$ 

WARNING Risk of accident despite brake application of Active Blind Spot Assist

A course-correcting brake application cannot always prevent a collision.

- Always steer, brake or accelerate yourself, especially if Active Blind Spot Assist warns you or makes a course-correcting brake application.
- Always maintain a safe distance at the sides.



If a course-correcting brake application occurs, the red warning lamp flashes in the outside mirror and a warning tone sounds. In addition, a display

1 indicating the danger of a side collision appears in the driver display.

In rare cases, the system may make an inappropriate brake application. This brake application may be interrupted at any time if you steer slightly in the opposite direction or accelerate.

## System limits

Note the system limitations of Active Blind Spot Assist; you may otherwise not recognize the dangers ( $\rightarrow$  page 264).

Either a course-correcting brake application appropriate to the driving situation, or none at all, may occur especially in the following situations:

- Vehicles or obstacles, e.g. crash barriers, are located on both sides of your vehicle.
- A vehicle approaches too closely on the side.
- You have adopted a sporty driving style with high cornering speeds.
- You brake or accelerate significantly.
- A driving safety system intervenes, e.g. ESP<sup>®</sup> or Active Brake Assist.
- ESP<sup>®</sup> is deactivated.
- A loss of tire pressure or a defective tire is detected.
- Transport equipment, e.g. a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection has been correctly established.

## Activating/deactivating Blind Spot Assist or Active Blind Spot Assist

Multimedia system:

- → Settings → Assistance
- >> Collision Avoidance
- Switch Active Blind Spot Assist on or off.

## **Active Lane Keeping Assist**

## Function of Active Lane Keeping Assist

Active Lane Keeping Assist monitors the area in front of your vehicle by means of a multifunction camera, ( $\rightarrow$  page 225) and can protect you from leaving your lane unintentionally. The system can guide you back into your lane by course-correcting steering intervention, and warn you with tangible steering wheel feedback.

Active Lane Keeping Assist is available in the speed range between 37 mph (60 km/h) and 124 mph (200 km/h).

The system can intervene if the following conditions are met:

- Active Lane Keeping Assist detects a lane marking.
- One of your front wheels moves onto this lane marking.

If you activate the direction indicators, there is no steering intervention on that side.

There is no steering intervention if you leave your lane without activating the direction indicators but there is a risk of collision with a moving obstacle in your own lane.

Vehicles with Blind Spot Assist or Driving Assistance Package: If the system detects an obstacle, e.g. another vehicle, in the adjacent lane, there is steering intervention despite the direction indicators.



In the following cases a warning (1) appears in the driver display and a warning tone is sounded:

- a steering intervention by Active Lane Keeping Assist has a duration longer than approximately ten seconds.
- there are two or more steering interventions by the systems within approximately three minutes, without steering action by the driver.

You can set the sensitivity of the system in the Active Lane Keeping Assist settings, to determine the level of assistance. You can also determine whether the system is to react to interrupted lane markings or only to solid lane markings  $(\rightarrow page 271)$ .

If ATTENTION ASSIST has detected signs of drowsiness, the most sensitive setting is automatically selected ( $\rightarrow$  page 233).

## Status displays of Active Lane Keeping Assist

White: Active Lane Keeping Assist is switched off

> If ESP® is switched off or a tire pressure loss warning is given, Active Lane Keeping Assist is automatically switched off.

- Yellow: There is a malfunction. Also note any display messages.
- 7: \ Gray: Active Lane Keeping Assist is switched on but not ready.
- **Green:** Active Lane Keeping Assist is switched on and ready. If the system is ready only on one side, only the lane marking on that side is shown in green.
- Red: Active Lane Keeping Assist has guided you back into your lane by course-correcting steering intervention. If a tangible warning is also given at the steering wheel, the status display flashes. Only the lane

marking on the warning side is shown in red

Vehicles without Driving Assistance Package: If both lane markings are shown in red in the status display at the same time, Active Lane Keeping Assist has initiated an emergency stop ( $\rightarrow$  page 248).



Display in the driver display in the menu Assistance

If one of your front wheels moves onto a recognized lane marking, this is highlighted in red in the Assistance menu in the driver display.

 Vehicles with active ambient lighting: If Warning Support is switched on, the warning by Active Lane Keeping Assist is reinforced by the ambient lighting (→ page 143).

## System limits

In the following situations, there may be no course-correcting steering intervention but a warning may be given at the steering wheel depending on the situation:

- if you clearly and actively steer, brake or accelerate.
- if a driving safety system is intervening, e.g. ESP® or Active Brake Assist
- if you have adopted a sporty driving style with high cornering speeds or high rates of acceleration.
- if transport equipment, for example a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection has been correctly established.

The system may be impaired or inoperative in the following situations in particular:

- if there is poor visibility, e.g. owing to insufficient road illumination, highly variable shade conditions, rain, snow, fog or heavy spray.
- if there is glare, e.g. from oncoming traffic, direct sunlight or reflections.
- if there is dirt on the windshield in the vicinity of the multifunction camera, or if the camera is fogged up, damaged or obscured.
- if the bumper is dirty in the area of the radar sensors, or if these are damaged or obscured
- if there are no lane markings, or several unclear lane markings are present for one lane, e.g. around roadworks.
- if the lane markings are worn, dark or covered.
- If the distance to the vehicle in front is too short and the lane markings cannot therefore be detected.
- if the lane markings change quickly, e.g. lanes branch off, cross one another or merge.
- if the road is very narrow and winding.

Observe the notes on driving systems and your responsibility; you may otherwise fail to recognize potential dangers ( $\rightarrow$  page 225).

## Activating/deactivating Active Lane Keeping Assist

Multimedia system:

- → Settings → Assistance
- >> Collision Avoidance
- ➤ Active Lane Keeping Assist
- Activate or deactivate the function.

Alternatively, Active Lane Keeping Assist can be activated and deactivated via the quick vehicle access :

i The settings after the vehicle is started are country-specific.

## Setting Active Lane Keeping Assist

Multimedia system:

- → Settings → Assistance
- > Collision Avoidance
- >> Active Lane Keeping Assist

#### Setting the sensitivity

- Select 🔼.
- Select Early, Med. or Late.

The last selected setting will be adopted the next time the vehicle is started

(i) The standard setting of this function is country-dependent.

## Activating or deactivating assistance with dashed lane markings

Select Advanced Support.

The last selected setting will be adopted the next time the vehicle is started.

(i) The standard setting of this function is country-dependent.

This function must be activated in vehicles without the Driving Assistance Package so that Emergency Stop Assist is fully available. Further information on Emergency Stop Assist  $(\rightarrow page 248)$ 


#### Rear view camera

#### ■ Function of the rear-view camera

The rear-view camera serves solely as an aid. It is not a substitute for you having to pay attention to your surroundings. The responsibility for safe maneuvering and parking remains with you. Ensure that no persons, animals, objects, etc. are in the maneuvering area while maneuvering and parking.

(i) The area behind the vehicle is displayed as a mirror image, as it would appear in the inside rearview mirror.

The following camera perspectives are available in the central display:



Menu Camera Views (Top View)

- Menu Parking Assistance
- Rear-view camera with Top View
- Wide-angle view
- Activate / deactivate Parking Assist PARKTRONIC (→ page 282)
- Warning display of Parking Assist PARKTRONIC (→ page 280)

- Guide lines at a distance of approximately 1.6 ft (0.5 m), 3.3 ft (1.0 m), 5 ft (1.5 m) and 9.9 ft (3.0 m) from the rear area
- Lane marking the course the tires will take with the current steering angle (dynamic)
- Driven surface depending on the current steering angle (dynamic)
- Guide line at a distance of approximately1.0 ft (0.3 m) from the rear area
- (i) When Active Parking Assist is active, paths  $\bigcirc$  are displayed in green ( $\rightarrow$  page 283).



Wide-angle view

Warning display of Parking Assist PARKTRONIC (→ page 280)

#### System limits

If the system is not ready for operation, the System Inoperative message appears on the central display.

The rear-view camera will not function or will function only partially in the following situations:

- You are driving forwards at a speed greater than approximately 10 mph (16 km/h).
- The tailgate is open.
- The weather conditions are poor, e.g. heavy rain, snow, fog, storm or spray.
- The ambient light is poor, e.g. at night or if a light is shining into the camera.
- The camera lens is obstructed, dirty or fogged up. Observe the notes on cleaning the rearview camera (→ page 382).
- The camera or rear of your vehicle is damaged. In this case, have the camera and its position and setting checked at a qualified specialist workshop.
- (i) Do not use the rear-view camera in these types of situations. You could otherwise injure others or collide with objects when parking the vehicle.

The field of vision and other functions of the camera system may be restricted due to additional

vehicle attachments (e.g. license plate bracket or bicycle rack).

- (i) The contrast of the display may be impaired by direct sunlight or by other light sources, e.g. when driving out of a garage. Particular attention must be afforded in this case.
- (i) Have the display repaired or replaced if, forexample, its use is considerably restricted due to pixel errors.

Observe also the information on vehicle sensors and cameras ( $\rightarrow$  page 225).

#### 360° camera

#### ■ Function of the 360° camera

The 360° camera is a system comprising four cameras which cover the immediate vehicle surroundings. The cameras support you, for example, when parking or when exits are difficult to see.


The 360° camera includes the following cameras and evaluates their images:

- Rear-view camera
- Front camera

Two outside mirror cameras

The cameras serve solely as aids and may show a distorted view of obstacles, show them incorrectly or even omit them altogether. They are not a substitute for you having to pay attention to your surroundings. The responsibility for safe maneuvering and parking remains with you. Ensure that there are no persons, animals, objects, etc. in the maneuvering area while maneuvering and parking.


The following camera perspectives are available in the central display:



Overview of menu Camera Views

- Menu Parking Assistance
- 2 Top view with image from the front camera
- 3 Top view with image from the rear-view cam-
- 3D view left side of the vehicle
- 3D view right side of the vehicle
- 3D auto view


- Activating/deactivating Parking Assist PARKTRONIC (→ page 282)
- (a) Set the GPS activation point ( $\rightarrow$  page 279)
- Switch between standard and wide-angle view
- The warning display of the Parking Assist PARKTRONIC is shown in all views (→ page 280).



#### Function of the guide lines

- Guide lines at a distance of approximately 1.6 ft (0.5 m), 3.3 ft (1.0 m), 5 ft (1.5 m) and 9.9 ft (3.0 m) from the rear area
- Lane marking the course the tires will take with the current steering angle (dynamic)

- Driven surface depending on the current steering angle (dynamic)
- Guide line at a distance of approximately 1.0 ft (0.3 m) from the rear area
- (i) When Active Parking Assist is active, lanes and guidelines are displayed in green instead of yellow (→ page 283).



Top view with the image from the front or rear-view camera

- Warning display of Parking Assist PARKTRONIC (→ page 280)
- Your vehicle from above
- 3 Lane indicating the route the vehicle will take at the current steering angle

WARNING Risk of accidents due to objects not being displayed or being displayed in a distorted manner

Due to the projection of the cameras, objects in the 3D views may be strongly distorted or not displayed at all.

Make sure that there are no persons, animals or objects etc., in the maneuvering area while maneuvering and parking.



3D view, left/right-hand side of the vehicle

Display of Parking Assist PARKTRONIC  $(\rightarrow page 280)$ 

In the 3D view, left/right-hand side of the vehicle, the virtual camera moves to the respective side of the vehicle. When you change the transmission position, the view is automatically adapted.

(i) The area behind the vehicle is **not** displayed as a mirror image as is usual in the 3D views.



3D auto view

- Display of Parking Assist PARKTRONIC  $(\rightarrow page 280)$
- Quide lines

In the 3D auto view, the virtual camera moves to the standard perspective, facing forward from the rear above the roof. The view changes automatically when approaching obstacles.


If you touch the touchscreen, the view changes to a 3D view with free rotation. You can turn, tilt and zoom the views by touch.



Wide-angle view

- Display of Parking Assist PARKTRONIC  $(\rightarrow page 280)$
- Switch between standard and wide-angle view

If you select the trailer view and no trailer is coupled to the vehicle, the following display appears:



#### Trailer view

- Switch between standard and trailer view
- Yellow guide line, locating aid
- Ball head of the trailer hitch
- Red guide line at a distance of approximately 1.0 ft (0.3 m) from the ball head of the trailer hitch
- i In trailer mode, the guide lines are shown at the level of the trailer hitch.

When the electrical connection is established between the vehicle and the trailer, the display changes to the side camera view.



Side view of outside mirror cameras in trailer view

 Switch to the side view of the outside mirror cameras

## System limits

If the system is not ready for operation, the System Inoperative message appears on the central display.

A

WARNING Risk of accident due to restrictions in the function of the 360° camera

If the function of the  $360^{\circ}$  camera is restricted, there is a risk of collision with people or objects.

- Do not use the 360° camera in the event of function restrictions.
- Make sure that there are no persons, animals or objects etc., in the maneuvering area while maneuvering and parking.

The 360° camera will not function or will only partially function in the following situations:

- You are driving forwards at a speed greater than approximately 10 mph (16 km/h).
- · The doors are open.
- · An outside mirror is not completely extended.
- · The tailgate is open.
- The weather conditions are poor, e.g. heavy rain, snow, fog, storm or spray.
- The ambient light is poor, e.g. at night or if a light is shining into the camera.
- The camera lens is obstructed, dirty or fogged up. Refer to the notes on cleaning the 360° camera (→ page 382).
- If cameras or vehicle components in which the cameras are installed are damaged. In this

event, have the cameras, their positions and their setting checked at a qualified specialist workshop.

For technical reasons, the standard height of the vehicle may be altered if the vehicle is carrying a heavy load and can result in inaccuracies in the guide lines and in the display of the generated images.

The field of vision and other functions of the camera system may be restricted due to additional vehicle attachments (e.g. license plate bracket or bicycle rack).

- (i) Contrast of the display may be impaired by abrupt, direct sunlight or other light sources, e.g. when driving out of a garage. Particular attention must be afforded in this case.
- (i) Have the display repaired or replaced if, forexample, its use is considerably restricted due to pixel errors.

Observe also the information on vehicle sensors and cameras ( $\rightarrow$  page 225).

#### Off-road function of the 360° camera

The 360° camera can assist you with different views when you drive off road.


The following views are available:

- Transparent hood
- Front view
- Rear view

To call up the function, call up the off-road menu in the multimedia system ( $\rightarrow$  page 336).

(i) Active Parking Assist, Parking Assist PARKTRONIC and the maneuvering assistant functions are not available in the addrive program. Please also note the system limits of the respective functions.

### Transparent hood



Transparent hood display (example)

- Cardinal point
- Switch camera perspective on/off
- 3 Activate/deactivate Parking Assist PARKTRONIC (→ page 280)
- Positions of the wheels
- Area under the hood


- Lane indicating the route the vehicle will take at the current steering angle
- Flevation above sea level

If the off-road menu is open on the central display and button ② is switched on, the transparent hood view will automatically be displayed in transmission position  $\boxed{\textbf{D}}$ .

The transparent hood view shows a virtual image of the area directly in front of the bumper, in front of the tires and under the hood. The current lane is also displayed. The transparent hood can assist you when you drive over difficult terrain, e.g. on rocky or uneven ground.

The front camera captures and records the shaded area under the hood ③. This area will then be shown as soon as it has been traversed by the vehicle. If the vehicle has not moved for some time, the recorded area will be displayed in gray-scale and faded out.

#### Front and rear view



Front and rear view display (example)

- Cardinal point
- Switch camera perspective on/off
- Activate / deactivate Parking Assist PARKTRONIC (→ page 280)
- Opening Pitch indicator

- Second the state of the stat
- 6 Roll indicator
- Elevation above sea level
- Note that the area between the vehicle and up to approximately 40 in (1 m) in front of the vehicle is not displayed.

The pitch and roll indicators are shown only in the front view.

If the vehicle is traveling faster than approximately 5 mph (8 km/h), the view will automatically change from transparent hood to front view. The camera image will be closed if the vehicle is traveling faster than approximately 12 mph (20 km/h) - 19 mph (30 km/h) (depending on the drive program).

The rear-view camera image will automatically be displayed when you engage reverse gear.

### System limits


The area under the hood may not be displayed correctly in the following situations:

· in the rain

- in the dark
- when shadows fall on the area recorded by the camera

Observe the instructions on the 360° camera's function and its system limits. Otherwise, you may fail to recognize potential dangers ( $\rightarrow$  page 273).

## ■ Calling up the 360° camera views using the button



- Press button 

  .
- Select Camera Views menu.
- Select the desired view in the multimedia system ( $\rightarrow$  page 273).

## Selecting a view for the 360° camera (reverse) gear)

- Engage reverse gear.
- Select the desired view in the multimedia system ( $\rightarrow$  page 273).

## ■ 360° Camera with GPS - managing activation positions

Multimedia system:

→ Settings → Assistance

Camera

## Renaming an activation position

- (i) You can determine activation positions in the Camera Views menu. ( $\rightarrow$  page 273)
- Select for the desired activation position.
- Select Edit.

Enter a name and confirm. The activation position is saved under the new name.

### Deleting an activation position

- Select for the desired activation position.
- Select Delete Entry.
- Confirm the prompt. The activation position is deleted.

## Opening the camera cover

Multimedia system:

→ Settings → Assistance

- Camera
- Select Open Camera Cover.
- (i) The camera cover closes automatically after some time, or after the vehicle is switched on or off.

## Parking Assist PARKTRONIC

## ■ Function of Parking Assist PARKTRONIC

Parking Assist PARKTRONIC is an electronic parking assistance system that monitors your vehicle's surroundings. The distance between your vehicle and a detected obstacle is displayed visually and acoustically.

The passive side impact protection also warns you of obstacles to the sides. These must be detected beforehand by the sensors in the front or rear bumper while you are driving by them. If you steer in the direction of a detected obstacle and there is a risk of a lateral collision, a warning will be issued.

Passive side impact protection can be activated and deactivated via the multimedia system ( $\rightarrow$  page 283).

In order for front or rear obstacles to the side to be displayed, the vehicle must first travel a distance of at least half a vehicle length. Once the vehicle has traveled one vehicle length, obstacles on all sides can be shown.

Parking Assist PARKTRONIC is only an aid. It is not a substitute for your attention to the surround-

ings. The responsibility for safe maneuvering and parking remains with you. Ensure that there are no persons, animals or objects in the maneuvering area while maneuvering and parking in / exiting parking spaces.

#### Indicators on the central display



Vehicles with 360° camera

Vehicles with rear-view camera

- 1 Front and rear ready for display
- All sides ready for display
- 3 All sides ready for display and obstacles detected

As soon as Parking Assist PARKTRONIC is ready for display, respective areas 
to 
for the display will be shown in blue.

The color of the display will change depending on the distance to the detected obstacle:

- Blue: > 3.3 ft (1 m) (no obstacles detected)
- Yellow: approximately 3.3 ft (1 m) 2.3 ft (0.7 m)
- Orange: approximately 2.3 ft (0.7 m) 1.3 ft (0.4 m)
- **Red:** < 1.3 ft (0.4 m)

Vehicles with 360° camera: the boundary line will shift dynamically depending on the position and distance of the obstacles detected.

An intermittent warning tone will also sound depending on the distance to the obstacle detected. You can set the timing of the warnings in the multimedia system. In the Warn Early setting, the system will warn you from a distance of 3.3 ft (1 m). In the standard setting, it will do so from a shorter distance of 1.3 ft (0.4 m).



Vehicles with 360° camera



Vehicles with rear-view camera

If you are not on the Camera & Parking menu and an obstacle in the vehicle path is detected, popup window (1) will appear on the central display if the following requirements are met:

· Vehicles without Active Parking Assist: when you are driving at a speed no greater than 8 mph (12 km/h).

• Vehicles with Active Parking Assist: when you are driving at a speed no greater than 11 mph (18 km/h).



Head-up display (example)

Optionally, obstacles detected by Parking Assist PARKTRONIC from a distance of approximately 3.3 ft (1.0 m) in front 2 and 2.3 ft (0.7 m) at the sides (3) can also be shown on the head-up display.

#### System limits

Parking Assist PARKTRONIC will not necessarily take into account the following obstacles:

- Obstacles below the detection range, e.g. persons, animals or objects.
- Obstacles above the detection range, e.g. overhanging loads, overhangs or loading ramps of trucks.
- Pedestrians or animals approaching the vehicle from the side.
- · Objects placed next to the vehicle

Obstacles at the sides will not be shown in the following situations, for example:

- You park the vehicle and switch it off.
- You open the doors.

After the vehicle is restarted, you will need to drive past obstacles to detect them again before a new warning can be issued.

Also observe the system limits of the following systems:

Rear-view camera (→ page 271)

• 360° camera (→ page 273)

Observe the information on vehicle sensors and cameras; otherwise, the system will not be able to function properly ( $\rightarrow$  page 225).

**Vehicles with trailer hitch:** if transport equipment, e.g. a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection is correctly established, Parking Assist PARKTRONIC will be deactivated for the rear zone.

#### Problems with Parking Assist PARKTRONIC

If the Parking Assist PARKTRONIC display lights up red for approximately three seconds and then goes out, and the <code>park</code> symbol appears on the driver display, the system may have been deactivated due to signal interference. Start the vehicle again and check whether Parking Assist PARKTRONIC works in a different location.

If a warning tone also sounds, the causes may be as follows:

- (→ page 382)The sensors are dirty: clean the sensors.
- Parking Assist PARKTRONIC has been deactivated due to a malfunction: restart the vehi-

cle. If the problem persists, consult a qualified specialist workshop.

# Activating/deactivating Parking Assist PARKTRONIC

NOTE Vehicle damage during parking or maneuvering due to objects at close range

Parking Assist PARKTRONIC may not detect certain objects close to the vehicle.

When parking or maneuvering, look out in particular for objects that are underneath or above the sensors, e.g. flower pots or drawbars. Otherwise, the vehicle or other objects could be damaged.

## Requirements

- The camera menu is open.
- Or: the Parking Assist PARKTRONIC pop-up window is displayed.
- ► Tap Pv on the central display.

If the indicator lamp is lit, Parking Assist PARKTRONIC is active. If the indicator lamp does not light up or the symbol pin is displayed, Parking Assist PARKTRONIC is not active.

(i) Parking Assist PARKTRONIC is automatically activated when the vehicle is started.

Alternatively, Parking Assist PARKTRONIC can be activated or deactivated in the quick-access menu.

## Setting the warning tones of Parking Assist PARKTRONIC

Multimedia system:

→ Settings → Assistance **▶** Parking **▶** PARKTRONIC

## Adjusting warning tones

- Select Set Warning Tones.
- Set the desired level under Volume or Tone Pitch.

#### Activating/deactivating audio fadeout

Select Audio Fadeout and switch Audio Fade for Warnings on / off.

The volume of the current media source will be reduced when a Parking Assist PARKTRONIC warning tone is sounding.

Select Audio Fadeout and switch Audio Fadeout When in R on/off.

The volume of the currently media source will be reduced when reverse gear is engaged.

## Setting warning times

- Select Time of Warning.
- Set the desired warning time for Front or Rear.
- Switch Side Warning on or off.

## **Active Parking Assist**

## Function of Active Parking Assist

Active Parking Assist is an electronic parking assistance system that uses ultrasound with the assistance of the rear-view camera and 360°

camera. When you are driving forwards up to approximately 22 mph (35 km/h), the system will automatically measure parking spaces on both sides of the vehicle.

Active Parking Assist serves solely as an aid. It is not a substitute for you having to pay attention to your surroundings. The responsibility for safe maneuvering and parking remains with you. Ensure that no persons, animals or objects etc. are in the maneuvering area.

Active Parking Assist offers the following functions:

Vehicles with rear-view camera

- Parking in parking spaces parallel to the road-
- · Backing up into parking spaces perpendicular to the roadway

The parking space can be freely selected. The vehicle will be parked in reverse.

Vehicles with 360° camera

· Parking in parking spaces parallel to the roadway

- Parking in parking spaces perpendicular to the roadway (either forwards or backing up as desired)
- Parking in parking spaces that can be detected as such only from markings (at the roadside, for example)
- Exiting parking spaces if you have parked using Active Parking Assist

The parking space can be freely selected. The parking direction (forwards or backing up) can also be freely selected, depending on the orientation of the parking space.

If Active Parking Assist is available, the message will appear on the driver's display. When the system detects parking spaces, will appear. The arrows show the side of the roadway on which available parking spaces are located. These will then be shown on the central display.

When Active Parking Assist is activated, the turn signal indicator will be activated based on the calculated path of your vehicle. The procedure will be assisted by acceleration, braking, steering and gear changes when you enter or exit a parking space.

To start the parking procedure, press the button ( $\rightarrow$  page 285) or select Active Parking Assist ( $\rightarrow$  page 314) in the navigation view (e.g. when near the destination).

Active Parking Assist will be canceled in the following situations:

- You press the hutton again.
- · You begin steering.
- You select park position P.
- You engage the electric parking brake.
- FSP® intervenes.
- You open the driver's door.

#### System limits

Active Parking Assist will not be available in the address drive program or if the exterior lighting is malfunctioning.

Also observe the system limits of the following systems:

- Rear-view camera (→ page 271)
- 360° camera (→ page 273)

Objects that are above or below the detection range of Active Parking Assist, e.g. protruding loads, overhangs or loading ramps of trucks or boundaries of parking spaces, will not be detected when the parking space is measured. These will also not subsequently be taken into account when the parking procedure is calculated. In some circumstances, Active Parking Assist may therefore guide you into the parking space prematurely or brake too late.

Certain environmental conditions, such as snowfall or heavy rain, may lead to a parking space being measured incorrectly. Parking spaces that are partially occupied by trailer drawbars may not be identified as such or may be measured incorrectly. Use Active Parking Assist only on level road surfaces with adequate grip. WARNING Risk of accident due to objects located above or below the detection range of Active Parking Assist

If there are objects above or below the detection range, the following situations may arise:

- · Active Parking Assist may steer too early.
- The vehicle may not stop in front of these objects.

There is a danger of collision!

In these situations, do not use Active Parking Assist.


Active Parking Assist can also display unsuitable parking spaces, e.g. parking spaces in which parking is not permitted or parking spaces on unsuitable surfaces.

Do not use Active Parking Assist in the following situations:


- In extreme weather conditions, such as ice. packed snow or heavy rain.
- When transporting a load that protrudes beyond the vehicle.

- If the parking space is on a steep incline.
- When snow chains are installed
- · When a trailer or bicycle rack is attached
- Directly after a tire change or when spare tires are installed.
- If the tire pressure is too low or too high.
- On steep inclines of more than approximately 15%.
- If the vehicle level has been offset, curb mounted on one side (vehicles with level control)

## Parking with Active Parking Assist




Press button ①.



Parking Assistance menu (example)

Select menu Parking Assistance ②.

Parking spaces (3) detected by the system will be shown on the central display.



Parking Assistance menu (example)

When the vehicle is stationary, indicated vehicle path (a) into currently selected parking space (5) will also appear.

- If a parking space is displayed: stop the vehicle.
- If necessary, select another parking space.

- Vehicles with 360° camera: to change the parking direction, tap the selected parking space again.
- To start the parking procedure: press button again.

or

- Depress the brake pedal and select Start Parking Procedure (a) (depending on equipment).
- Take your hands off the steering wheel.
  The vehicle will drive into the selected parking space.

The turn signal indicator will be switched on automatically when the parking procedure begins. You are responsible for selecting the turn signal indicator in accordance with the traffic conditions. If necessary, select the turn signal indicator accordingly.

WARNING Risk of accident due to vehicle swinging out while parking or pulling out of a parking space

While parking or exiting a parking space, the vehicle swings out and can drive onto areas of the oncoming lane.

This could cause you to collide with objects or other road users.

- Pay attention to objects and other road users.
- Where necessary, stop the vehicle or cancel the parking procedure with Active Parking Assist.

On completion of the parking procedure, the Active Parking Assist Finished display message will appear.

- Secure the vehicle against rolling away. When necessitated by legal requirements or local conditions: turn the wheels towards the curb.
- (i) You can stop the vehicle and change the transmission position during the parking procedure. The system will then calculate a new

vehicle path. If no new vehicle path is available, the transmission position can be changed again or the process can be canceled.




Immediate parking via the Camera Views menu

- Select the Camera Views menu.
  - When the vehicle is stationary and in transmission position R, and symbol 7 appears in the camera image: press button (1) again. The parking procedure will be initiated for the detected parking space.
- The parking space and parking direction cannot be changed in immediate parking.

## Exiting a parking space with Active Parking Assist

## Requirements

- The vehicle is equipped with a 360° camera.
- The vehicle has been parked with Active Parking Assist.
- Start the vehicle.



Press button ①.



Parking Assistance menu (example)

- Select menu Parking Assistance 2.
- If necessary, change direction of exit 3.
- To initiate the unparking procedure: press button again.

- Depress the brake pedal and select Start Unparking Procedure (a) (depending on equipment).
- If necessary, change the transmission position. Observe any messages displayed on the driver display and central display.

The vehicle will move out of the parking space.

The turn signal indicator will automatically be switched on when the process of exiting a parking space begins and switched off when it is completed. You are responsible for selecting the turn signal indicator in accordance with the traffic conditions. If necessary, select the turn signal indicator accordingly.

After the parking space has been exited, a warning tone and the Active Parking Assist Finished: Take Control of Vehicle message will prompt you to take control of the vehicle. You will have to accelerate, brake, steer and change gear yourself again.

If you do not react to the prompt to take control of the vehicle, the system will brake the vehicle to a standstill.

## Pausing Active Parking Assist

You can interrupt the parking or unparking procedure of Active Parking Assist by performing one of the following actions. forexample:

- Depress the brake pedal.
- Open the front passenger door, a rear door, the tailgate or the hood.
- Apply the electric parking brake or activate the HOLD function.
- To resume the parking or unparking procedure: gently depress the accelerator pedal.
- (i) If the electric parking brake was applied before Active Parking Assist was activated, depress the accelerator pedal gently to start the parking or unparking procedure.

Check the area around your vehicle again before resuming a paused parking procedure. Ensure that persons, animals or objects are no longer in the maneuvering range. Observe also the system limits of Active Parking Assist.



## Automatic braking function of Active Parking Assist

Persons or objects detected in the maneuvering range could cause the vehicle to brake sharply and interrupt the parking or exiting procedure. The vehicle will then be held at a standstill. If you depress the accelerator pedal, the parking or exiting procedure is resumed.

Check the area around your vehicle again before resuming the parking or exiting procedure. Check again that there are no persons, animals or objects in the maneuvering range. Also observe the system limitations of Active Parking Assist.

## Maneuvering assistance

## Function of Drive Away Assist

Drive Away Assist can reduce the severity of an impact when the vehicle is pulling away. If the system detects an obstacle in the direction of travel. the vehicle's speed will briefly be reduced to approximately 1 mph (2 km/h).

A risk of a collision may arise in the following situations, for example:

- · If the driver mixes up the accelerator and brake pedals.
- If the driver engages an incorrect gear.
- If the driver depresses the accelerator pedal with too much force

Drive Away Assist will be active under the following conditions:

- · If the vehicle was stationary and the transmission position was changed to R or D.
- If the vehicle has rolled less than approximately 3.3 ft (1.0 m) since being at a standstill.
- If the detected obstacle is less than approximately 3.3 ft (1.0 m) away.

The Drive-away Assist can be deactivated or activated on the Maneuvering Assistance menu  $(\rightarrow page 292).$ 

If a critical situation is detected, the symbol will appear in red in the selected view on the Camera & Parking menu.

i) If Drive Away Assist is not available, the symbol will appear in grey. If the Camera & Parking menu is not opened on the central display, the symbol and pop-up of Parking Assist PARKTRONIC will both appear.

Drive Away Assist is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals, objects etc. are in the maneuvering area.

WARNING Risk of accident caused by limited detection performance of Drive Away Assist

Drive Away Assist cannot always clearly identify objects and traffic situations.

- Always pay careful attention to the traffic situation; do not rely on Drive Away Assist alone.
- Be prepared to brake or swerve as necessary, provided the traffic situation permits and that it is safe to take evasive action.

#### System limits

Drive Away Assist is not available in drive program

The system limits of Active Parking Assist apply  $(\rightarrow page 283)$ .

The performance of Drive Away Assist will be restricted on uphill gradients.

If a transport device (e.g. trailer or bicycle carrier) is attached to the hitch and the electrical connection is correctly established, Drive Away Assist will not be available when the vehicle is backing up.

## Cross traffic warning function

The cross traffic warning can warn you of crossing traffic when you are exiting a parking space. The radar sensors in the bumper also monitor the area adjacent to the vehicle.

The cross traffic warning will be active in the following circumstances:

- Warning for Cross Traffic, Rear: the vehicle is backing up at a speed slower than approximately 6 mph (10 km/h).
- Warning for Cross Traffic, Front: the vehicle is driving forwards at a speed slower than

approximately 6 mph (10 km/h) and the camera image is shown on the central display ( $\rightarrow$  page 279).

The Warning for Cross Traffic, Front can be deactivated or activated on the Maneuvering Assistance(→ page 292) menu.

If a critical situation is detected, the <u>A</u> symbol will appear in red in the selected view on the Camera & Parking menu.

## Warning for Cross Traffic, Rear

- The vehicle brakes can be applied automatically when crossing traffic is detected.
- If the Camera & Parking menu is not open and a critical situation is detected, a warning will appear on the central display together with the PARKTRONIC Parking Assist pop-up.

## Warning for Cross Traffic, Front

 If Active Parking Assist is active, the vehicle brakes can be applied automatically when crossing traffic is detected.

- If Active Parking Assist is not active but the Camera & Parking menu is open, a warning will appear.
- If the Camera & Parking menu is not open, the system will not be able to react to crossing traffic.

The cross traffic warning is only an aid and not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals, objects etc. are in the maneuvering area.

A

WARNING Risk of accident caused by limited detection performance of the cross traffic warning

The cross traffic warning cannot always clearly identify objects and traffic situations.

- Always pay careful attention to the traffic situation; do not rely on the cross traffic warning alone.
- Be prepared to brake or swerve as necessary, provided the traffic situation per-

mits and that it is safe to take evasive action.

#### System limits

(i) If the cross traffic warning is not available, the symbol will appear in grey.

The cross traffic warning is not available in drive program .

The system limits of Active Parking Assist apply  $(\rightarrow page 283)$ .

If the radar sensors are obstructed by vehicles or other objects, detection will not be possible.

The cross traffic warning will not be available in the following situations:

- · On inclines
- Warning for Cross Traffic, Rear: if transport equipment (e.g. trailer or bicycle rack) is attached to the hitch and the electrical connection is correctly established.

## Function of close-range braking

The close-range braking function can prevent collisions with pedestrians when the vehicle is backing up at slow speeds. If the rear-view camera detects a person in the vehicle's path, the brakes can be applied to bring the vehicle to a standstill.

The close-range braking function may intervene in the following circumstances:

- The vehicle is backing up at a speed slower than 6 mph (10 km/h).
- The camera image is shown on the central display ( $\rightarrow$  page 279).

Close-range braking can be deactivated or activated on the Maneuvering Assistance menu (depending on the country) ( $\rightarrow$  page 292).

If the close-range braking function is triggered, the symbol will appear in red in the selected view on the Camera & Parking menu.

(i) If close-range braking is not available, the symbol will appear in gray.

The close-range braking function is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals, objects, etc. are in the maneuvering range.

WARNING Risk of accident caused by limited detection by the maneuvering brake function

The maneuvering brake function cannot always clearly detect people. Other obstacles are not detected by the function.

In these cases, the function may brake unnecessarily or not brake at all.

- Always pay careful attention to the traffic situation; do not rely on the maneuvering brake function alone
- Be ready to brake.

#### System limits

Close-range braking is not available in drive program 🔝.

Observe the system limits of the following functions:

- Active Parking Assist (→ page 283)
- 360° camera (→ page 273)
- Rear-view camera (→ page 271)

The close-range braking function will not be available in the following situations:

- On inclines
- If transport equipment (e.g. a trailer or bicycle rack) is attached to the trailer hitch and the electrical connection has been correctly established.
- Activating/deactivating maneuvering assistant Multimedia system:
- i) This function is an on-demand feature  $(\rightarrow)$  page 24).
- (i) Activating/deactivating the maneuvering assistant function is not available in all countries.
- ▶ Select Maneuvering Assistance.
- Activate or deactivate the desired maneuvering assistant.

## **Memory Parking Assist**

## Function of Memory Parking Assist

Memory Parking Assist can park your vehicle in a previously stored parking space. You can store parking procedures with a total distance of up to 550 yds (500 m) (110 yds (100 m) per parking or exiting procedure).

During parking or exiting, the system can cover a previously stored path of up to approximately 110 yds (100 m) to or out of the desired parking space, for example, from the driveway entrance into the garage.

Within a radius of approximately 165 yds (150 m), only one parking or exiting procedure can be recorded.

Only use Memory Parking Assist on private property. Use on public roads, e.g. in public parking areas, is not permitted.

Memory Parking Assist is only an aid. It is not a substitute for your attention to the surroundings. The responsibility for safe maneuvering and parking remains with you. Make sure that no persons, animals or objects etc. are in the vehicle's path.

#### System limits

Observe the system limits of Active Parking Assist ( $\rightarrow$  page 283).

A

WARNING Risk of accident due to objects located above or below the detection range of Memory Parking Assist

If there are objects above or below the detection range, the following situations may arise:

- Memory Parking Assist may steer too early.
- The vehicle may not stop in front of these objects.

This result in a collision.

In these situations, do not use Memory Parking Assist.

Objects located above or below the detection range of Memory Parking Assist may not be detected during the parking procedure.

Objects including drawbars of parked trailers that protrude into the parking space may not be detected.


Do not use Memory Parking Assist in the following situations, for example:

- In extreme weather conditions such as ice. packed snow or in heavy rain.
- When transporting a load that protrudes beyond the vehicle.
- If the parking space is on a steep downhill or uphill gradient.
- · When snow chains are installed.

## ■ Recording a parking procedure using Memory Parking Assist

#### Requirements

- The entire route is within the bounds of your own property, for example, and not on public roads.
- The system needs reference points in the surrounding area to orient itself, such as fences, walls or trees. Therefore, after you start the vehicle, you will need to drive for a certain distance first. If not enough reference points are detected in the surrounding area, no new route can be recorded.



Press button ①. The Camera & Parking view will open on the central display.




- Select the Memory Parking Assist menu.
- Brake the vehicle to a standstill at the desired starting point of the assisted parking procedure, e.g. a driveway entrance.
- To start recording: tap on 3.
- (i) If not all conditions for a recording are met, symbol 3 will be grayed out.

- Park the vehicle in the desired parking space. Do not exceed 5 mph (8 km/h).
- To stop recording: stop the vehicle and tap on again.
  - The recording will be stored.
- You can delete and rename stored parking procedures in the Memory Parking Assist settings.
- Parking with Memory Parking Assist

## Requirements

• A parking procedure has been recorded.



Press button ①.
The Camera & Parking view will open on the central display.




- Select Memory Parking Assist menu ②.
- Prake the vehicle to a standstill at the starting point of the stored parking procedure.
- To start the parking procedure: press .
- Select the stored parking procedure from the list.

- Follow the instructions on the central display. The vehicle will drive into the selected parking space.
- (i) The turn signal indicator will not be switched on automatically. You are responsible for selecting the turn signal indicator in accordance with the traffic conditions
- Once the parking procedure is complete, secure the vehicle against rolling away.

## Exiting a parking space with Memory Parking Assist

#### Requirements

- The unparking procedure was recorded together with the respective parking procedure and stored separately within one driving cycle.
- · The vehicle was parked using Memory Parking Assist.



Press button ①. The Camera & Parking view will open on the central display.



Select Memory Parking Assist menu 2.

## Starting the unparking procedure

- Press D.
- Confirm the saved unparking procedure.
- Follow the instructions on the central display. The vehicle will drive the recorded route.

- (i) The turn signal indicator will not be switched on automatically. You are responsible for selecting the turn signal indicator in accordance with the traffic conditions.
- Take control of the vehicle after the unparking procedure has been completed.

## Setting Memory Parking Assist

Multimedia system:

- → 🔝 ➤ Settings ➤ Assistance
- ▶ Parking ▶ Memory Parking Assist

## Renaming a recording

- Select Memory Parking Assist.
- Select next to the desired recording.
- ► Enter a name and confirm with OK.

## Deleting a recording

- Select Memory Parking Assist.
- Select next to the desired recording. The selected recording will be deleted.

## Deleting all recordings

Select Memory Parking Assist.

- Select Delete All Tracks.
- (i) Alternatively, you can delete all data in Memory Parking Assist by resetting the multimedia system (→ page 328).

## **Trailer Maneuvering Assist**

- Function of Trailer Maneuvering Assist
- This function is an on-demand feature
   (→ page 24).
- ▲ WARNING Risk of accident due to unsuitable trailers

Trailers with a steered axle or a fifth wheel cannot be used with Trailer Maneuvering Assist.

Due to this, the trailer cannot be maneuvered in the desired direction and you can cause a collision or the trailer can rollover.

Only use Trailer Maneuvering Assist with trailers with fixed drawbars and axles.

# WARNING Risk of accidents due to unsuitable hitching devices

Trailer hitches without a ball head, such as a Hensley hitch or a pintle hitch, as well as any hitch adapters or multiple hitch ball mounts, **cannot** be guided by Trailer Maneuvering Assist.

This will prevent the trailer from maneuvering in the desired direction and you may cause a collision or the trailer may roll over.

- Use Trailer Maneuvering Assist only with a trailer hitch with a ball head.
- Use Trailer Maneuvering Assist only with a trailer hitch without additional attachments, such as a weight distribution system or sway control.
- Use Trailer Maneuvering Assist only with a trailer with a drawbar that has no additional attachments or superstructures.
- Use Trailer Maneuvering Assist only with a hitch ball mount. The use of an additional hitch adapter or hitch ball mount is not permitted.

If after changing the trailer, ball neck or changing the ball head position the values for the ball head position are **not** reset and a calibration drive is carried out again, Trailer Maneuvering Assist will not function properly.

This will prevent the trailer from maneuvering in the desired direction and you may cause a collision.

- After changing the trailer, the ball neck or the ball head position, do not use Trailer Maneuvering Assist without carrying out a calibration drive again.
- After changing the trailer, the ball neck or the ball head position, reset the taught-in values.
- Then, carry out a calibration drive to teach in the values of the new ball head position.

Information on resetting the taught-in values for the ball head position and on the calibration drive  $(\rightarrow page 303)$ .

**NOTE** Damage due to overhanging loads in front or drawbar installations

The vehicle and the trailer may be damaged during maneuvering due to overhanging loads at the front of the trailer or drawbar installations.

Pay attention to overhanging loads or drawbar installations while maneuvering.

Trailer Maneuvering Assist assists you with backing up with a trailer. The rear-view camera monitors the articulation angle between the vehicle and the trailer and adjusts it to a specified value. Trailer Maneuvering Assist also limits your speed.

For Trailer Maneuvering Assist to function properly, a calibration drive must be carried out for the trailer and ball neck used and if the ball head position is changed. The current ball head position will be taught in during the calibration drive  $(\rightarrow page 303)$ .

Trailer Maneuvering Assist serves solely as an aid. It is not a substitute for you having to pay attention to your surroundings. The responsibility for safe maneuvering and parking remains with you. Ensure that there are no persons, animals or objects in the maneuvering area while maneuvering and parking in/exiting parking spaces.

You can enter the articulation angle value directly via the multimedia system, or use a straightening or 90° maneuver. When carrying out a straightening maneuver, the system calculates the articulation angle automatically and straightens the vehicle/trailer combination to the trailer's current direction

Observe the notes regarding trailer operation  $(\rightarrow page 299).$ 

#### System limits

Observe the system limits of the following functions:

- Active Parking Assist (→ page 283)
- 360° camera (→ page 273)
- Rear-view camera (→ page 271)

The system may be impaired or inoperative in the following situations:


- The gradient is greater than approximately 15%.
- The height of the ball head above even ground is less than 13.8 in (0.35 m) or greater than 21.6 in (0.55 m).

## Using Trailer Maneuvering Assist

#### Requirements


- The vehicle has been started and is stationary.
- A trailer is selected in the Vehicle menu
   (→ page 303).
- · A trailer has been detected.
- A calibration drive was carried out using the trailer, ball neck and current ball head position (→ page 303).
- A straight travel maneuver was carried out to calibrate Trailer Maneuvering Assist, observing the instructions in the central display (→ page 303).
- The gradient is less than approximately 15 %.
- The tailgate is closed.

- The electric parking brake is not applied.
- The driver's seat belt is fastened.
- (i) To ensure that the Trailer Maneuvering Assist functions correctly, reset the taught-in values for the ball head position after each change of trailer and ball neck as well as when changing the ball head position. Then perform a calibration drive again. Information on resetting and calibration drive (→ page 303).



- Engage reverse gear R.
- Press button 

   The camera image is shown on the central display.
- Take your hands off the steering wheel.



(i) This image is shown as an example and is without trailer.

You can select various maneuvers in the Trailer Maneuvering Assist menu. The maneuvers available depend on the trailer's current articulation angle and length.

To adjust the articulation angle: select **(4)**. To change the articulation angle, swipe to the left

or right in the central display in the entire area of the camera image.

To activate the straightening maneuver: select

The system calculates the articulation angle in such a way that the direction of the trailer at the time of activation is maintained. There is a short countersteering movement of the trailer while the vehicle is backing up to guide it back to the desired line. This allows the vehicle to align with the trailer, while at the same time maintaining the trailer's direction.

- To activate the 90° maneuver:
  - Align the vehicle in the same direction (line) as the trailer.
  - Select (3) (left or right).

The system calculates the articulation angle so that a trailer can be maneuvered into a driveway at the most acute angle possible when it is perpendicular to its own vehicle.

After the maneuver, the vehicle is aligned again in the trailer's direction.

- Accelerate and brake as required.
- (i) The maximum articulation angle depends on the length of the trailer. The system calculates this by driving the vehicle forwards, including cornering. Before the trailer length has been calculated, the maximum articulation angle is approximately 23°. The longer the trailer, the greater the maximum articulation angle (max. approximately 60°).
- (i) Be aware of all surroundings and always remain ready to brake.

#### Trailer hitch

Notes on trailer operation



Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

WARNING Risk of accident due to unsuitable ball neck

If you install an unsuitable ball neck, the trailer hitch and the rear axle may be overloaded.

This can significantly impair the driving characteristics and the trailer may become loose. There is a risk of fatal injury.

- Only install a ball neck that complies with the permissible dimensions and is designed for the requirements of trailer operation.
- Do not modify the ball neck or the trailer hitch.

The values approved by the manufacturer can be found on the identification plates and in the "Technical data" section under "Trailer hitch" for the towing vehicle ( $\rightarrow$  page 459).

# **WARNING** Risk of accident due to vehicle/trailer combination swerving

If you drive too fast in trailer operation, the vehicle/trailer combination may start to swerve.

This could cause you to lose control of the vehicle/trailer combination. The vehicle/trailer combination may even rollover.

- Under no circumstances should you try to straighten the vehicle/trailer combination by increasing your speed.
- Reduce the speed and do not countersteer.
- Brake if necessary.
- I NOTE Damage to the engine resulting from overheating
- If you subsequently have a trailer coupling retrofitted, depending on the vehicle type, changes to the engine cooling system may be required.

In the case of retrofitting a trailer coupling, please observe the attachment points on the vehicle frame.

The installation of a trailer hitch is only permissible if a trailer load is specified in your vehicle documents. If this is not the case, the vehicle is not approved for trailer operation.

Further information can be obtained at a qualified specialist workshop.

Please observe the manufacturer's operating instructions for the trailer coupling if a detachable trailer coupling is used.

Couple and uncouple the trailer carefully. If you do not couple the trailer to the towing vehicle correctly, the trailer could become detached.

Observe the following notes on the tongue weight:

- do not use a tongue weight that exceeds or falls below the permissible tongue weight
- use a tongue weight as close as possible to the maximum tongue weight

Do not exceed the following values:

- · Permissible trailer load
- Permissible rear axle load of the towing vehicle
- · Permissible gross mass of the towing vehicle
- · Permissible gross mass of the trailer
- Maximum permissible speed of the trailer

Ensure the following before starting a journey:

- the tire pressure on the rear axle of the towing vehicle is set for a maximum load
- the lighting of the connected trailer is operational

In the event of increased rear axle load, the vehicle/trailer combination may not exceed a maximum speed of 62 mph (100 km/h) for reasons concerning the operating permit. This also applies in countries in which the permissible maximum speed for car/trailer combinations is above 62 mph (100 km/h).


## Attaching the ball neck

WARNING Risk of accident and injury due to incorrectly installed ball neck

If the ball neck is not properly mounted and secured, it may come loose along with the trailer while the vehicle is in motion and endanger other road users. There is a risk of fatal injuries.

- Mount and secure the hall neck as described in the installation instructions of the ball neck manufacturer.
- ▶ With the ball neck mounted, always make sure it is properly secured before commencing a journey.

## Attaching the ball neck



- Secure the vehicle against rolling away.
- Remove cover cap (1) from the ball neck mount in the direction of the arrow
- Store cover cap 1 such that it cannot move around.
- Comply with the installation instructions of the ball neck manufacturer.

Observe the notes on loading the vehicle.

(i) To ensure that the Trailer Maneuvering Assist functions properly, the taught-in values for the ball head position must be reset after each change of trailer, ball neck, or ball head position. A calibration drive must then be performed again. Information on resetting and the calibration drive ( $\rightarrow$  page 303).

## Coupling up/uncoupling a trailer

The trailer will only be correctly detected by the vehicle if the following conditions are fulfilled:

- the trailer is connected correctly
- the trailer lighting system is in working order
- (i) Before using Trailer Maneuvering Assist and after each change of trailer, a calibration drive must be carried out with the ball neck being used ( $\rightarrow$  page 303).

A correctly connected trailer influences, among other things, the functions of the following systems:

- FSP® trailer stabilization.
- · Trailer Maneuvering Assist
- · Active Lane Keeping Assist
- Parking Assist PARKTRONIC
- · Active Parking Assist

- Blind Spot Assist
- Active Blind Spot Assist
- · Drive Away Assist
- Cross traffic warning
- Maneuvering brake function
- Rear view camera
- 360° camera

Vehicles without level control system: the ball head height will change depending on the vehicle's load. In this case, use a trailer with a height-adjustable drawbar.

## Coupling up a trailer

NOTE Damage to the starter battery due to full discharge

Charging the trailer battery using the power supply of the trailer can damage the starter battery.

Do not use the vehicle's power supply to charge the trailer battery. Information about a suitable ball neck for Mercedes-Benz vehicles can be obtained from a qualified specialist workshop, e.g. an authorized Mercedes-Benz Center.

- Secure the vehicle against rolling away.
- Remove the cover cap from the ball neck mount and store it in a safe place (→ page 301).
- Position the trailer on a level surface behind the vehicle and couple it up to the vehicle.
- Establish the electrical connection between the vehicle and the trailer.
- Accessories can be connected to the permanent power supply up to 180 W, and to the power supply that is switched on via the ignition lock.

## Decoupling a trailer

A

**WARNING** Risk of being crushed and becoming trapped when uncoupling a trailer

When uncoupling a trailer with an engaged inertia-activated brake, your hand may become trapped between the vehicle and the trailer drawbar.

- Do not uncouple trailers with an engaged overrun brake.
- NOTE Damage during uncoupling with an engaged overrun brake

The vehicle may be damaged if you uncouple with an engaged overrun brake.

- Do not uncouple trailers with an engaged overrun brake.
- Secure the vehicle against rolling away.
- Disconnect the electrical connection between the vehicle and the trailer.
- Uncouple the trailer.

- Remove the ball neck and, in doing so. observe the installation instructions from the ball neck manufacturer.
- Place the cover cap on the ball neck mount.

## Selecting a trailer type

Multimedia system:

→ Settings → Vehicle → Driving >> Trailer Type

#### Configuring settings for a trailer

The settings on this menu make it possible to calculate a route suitable for the selected trailer and optimize the calculated arrival time. Depending on the vehicle equipment, the maximum speed displayed on the instrument cluster will also be adjusted accordingly and taken into account in the context of speed acceptance.

- Select the desired trailer type.
- Select the maximum permissible speed of the selected trailer.
- (i) No maximum speed can be entered for a bicycle rack.

- To save changes: select Confirm.
- When contact with the trailer socket is established (trailer/rear bicycle rack), a menu will automatically appear on the display.

The following options are available:

- · Bicvcle rack
- Small trailer
- · Large trailer

## Calibrating a trailer coupling

- Select Trailer coupling has been changed to start calibration for the new ball head position.
- To save changes: select Confirm.
- Activate Trailer Maneuvering Assist and follow the corresponding instructions on the central display.

When the Activated: Trailer Maneuvering Assist message is displayed, calibration is complete and Trailer Maneuvering Assist can be used.

## Vehicle towing instructions

The vehicle is not suitable for the use of tow bar systems that are used for flat towing or dinghy towing, for example. Attaching and using tow bar systems may result in damage to the vehicle. When you are towing a vehicle with tow bar systems, safe driving characteristics cannot be guaranteed for the towing vehicle or the towed vehicle. The vehicle-trailer combination may swerve from side to side.

**NOTE** Mercedes-AMG E Performance

Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

The Mercedes-AMG E Performance model is not available in all countries.

Observe the following information:

- Permitted towing methods (→ page 403)
- Plug-in hybrid: permitted towing methods  $(\rightarrow page 403)$

• The notes on towing the vehicle with both axles on the ground (  $\rightarrow$  page 404)

## Notes on the driver display

WARNING Risk of accident if the driver's display fails

If the driver's display fails or malfunctions, you may not be aware of any functional limitations to safety-critical systems. This may affect the operating safety of the vehicle.

Park the vehicle safely as soon as possible and notify a qualified specialist workshop.

#### **NOTE** Mercedes-AMG vehicles

Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

If the operating safety of your vehicle is impaired, park the vehicle immediately and safely. Contact a qualified specialist workshop.

The driver display shows the following basic information:

· Speed and engine speed

- Fuel level and coolant temperature
- Indicator and warning lamps

Additional functions available include the following:

- Various menus, such as Assistance and Navigation
- Status displays for the driving systems
- Display messages
- Information on speed, Consumption and Range
- · Power meter level and state of charge of the high-voltage battery
- Indicator and warning lamps

Some menu content and settings can be changed.

## Operating the driver display

WARNING Risk of distraction from information systems and communications equipment


If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

Observe the legal requirements for the country in which you are currently driving when operating the driver display.

#### 306 Driver's display

## Scrolling on the menu bar



- Back button
- Main menu button
- 3 Touch Control

You can manage the content of the driver display with the controls on the left of the steering wheel. You can navigate the content by swiping vertically and horizontally with one finger on Touch Control

- Press the Touch Control to confirm your selection.
- (i) To operate Touch Control (3) in the most effective way, use the tip of your thumb if possible. You can also set the sensitivity of the Touch Control on the central display.
- Briefly press main menu button ②.
- Select a menu by swiping to the left or right on Touch Control 3.
- ► To confirm: press Touch Control ③.

## Driver display menus

Notes on menus on the driver display

★ WARNING Risk of distraction from information systems and communications equipment

If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

Observe the legal requirements for the country in which you are currently driving when operating the driver display.

The following menus can be called up via the menu bar on the driver display:

- Understated
- Sport
- Classic
- Navigation
- Assistance
- Offroad (vehicles with 4MATIC)
- Service

On some of these menus, you can choose from a range of information for the center display content.

On most of the menus, you can use Options to configure further settings for the menu-specific display content.

You can find further information about the possible settings and selections on the menus in the Digital Operator's Manual.

## Sport menu (plug-in hybrid)

Driver display:

¬→ Sport

The Sport menu provides additional information about the operating energy as well as the recuperated power of the vehicle.

- (i) When you call up the Sport menu on the menu bar of the driver display, the menu color setting will automatically be applied to the MBUX multimedia system.
- To call up the menu: press the Touch Control.



- Display area for recuperated power (recuperation)
- Display area for output
- 3 Additional display area for output

## Head-up Display

## Function of the head-up display

The head-up display projects various content into the driver's field of vision, for example.

You can use the head-up display menu bar to select various contexts, e.g.:


Minimal

- Sport
- Standard
- Offroad (vehicles with 4MATIC)
- · ECO display (depending on model and equipment) ( $\rightarrow$  page 182)
- Settings
- Head-up display on/off

The following image shows an example of the head-up display. You can choose what content is displayed ( $\rightarrow$  page 308).

#### 308 Driver's display

## Head-up display content with navigation (9x3°)



- Navigation instructions
- Navigation instructions (distance to the next route event)
- Steer Assist status
- Current speed
- Set speed in the driving system (e.g. cruise control)
- Detected traffic signs (Traffic Sign Assist)

When you receive a call, the Call Waiting message will appear on the head-up display and the driver's display.

## System limits

Visibility is particularly influenced by the following conditions:

- Seat position
- · Image position setting
- Ambient light
- · Wet road surfaces
- · Objects on the display cover
- Polarization in sunglasses

## Operating the head-up display

Selecting display content of the head-up display via the menu bar of the driver display

- Press the main menu button 🔝.
- To select the menu bar of the head-up display: swipe upwards on the Touch Control.



## Switching between display content on the headup display

- Swipe to the left or right on the Touch Control.
   A preview of the selected display content will appear on the head-up display.
- ► To confirm: press the OK button.

Switching back to the driver display

▶ Press the or button.

## Setting the position and brightness

 Swipe to the left or right on the Touch Control and select Settings on the menu bar of the head-up display.

- Press the Touch Control. The current position and brightness settings will be displayed as graphics on the head-up display as well as on the driver display.
- To adjust the position: swipe upwards or downwards on the Touch Control.
- To adjust the brightness: swipe to the left or right on the Touch Control. The settings configured for position and brightness will be saved automatically.
- Press the or ok button to exit the settings.

## Switching the head-up display on/off

Driver display:



#### Switching on

- Swipe upwards on the Touch Control.
- Press Touch Control OK.

## Switching off

Swipe upwards on the Touch Control.

- Swipe on the Touch Control and select Headup Display.
- Press Touch Control OK.

## Setting the head-up display in the multimedia system


Multimedia system:



## Switching the head-up display on/off

Select Head-up Display. The head-up display is activated or deactivated.

## Vehicles with a 48 V on-board electrical system



- Electric drive support
- Recuperation behaviour of the electric motor
- i Due to various system limits, the values displayed may temporarily differ slightly from the actual value.

#### 310 Driver's display

## Function of the power meter



- Start of the POWER display range
- End of the POWER display range
- Current state of charge of the high-voltage battery
- Maximum recovered energy
- Start of the display range of the recovered energy

The power meter has the following functions:

 mode, the electrical power assistance of the drive is displayed.

- The area (4) (5) shows the recuperation and charging behavior using the combustion engine.
- (i) Due to various system limits, displayed value (a) may temporarily differ slightly from the actual value.

# Overview of status indicators on the driver display

The status indicators for the driving and driving safety systems are shown in the 
 and 
 areas.



- Pedestrian detection (on assistant display only) (→ page 136)
- Active Parking Assist is available (→ page 285)
- Active Parking Assist has detected a parking space (→ page 285)
- Parking Assist PARKTRONIC deactivated (→ page 282)

Cruise control (→ page 235)

Active Distance Assist DISTRONIC
(→ page 237)

Specified distance for Active Distance Assist DISTRONIC (→ page 237)

Active Brake Assist switched off  $(\rightarrow page 259)$ 

Active Brake Assist impaired or not functioning (→ page 259)

Active Steering Assist (→ page 246)

Active Lane Change Assist (→ page 250)

 $\nearrow: \checkmark$  Active Lane Keeping Assist ( $\rightarrow$  page 268)

Active Blind Spot Assist (on assistant display only) ( $\rightarrow$  page 267)

Blind Spot Assist (on assistant display only)
(→ page 267)

READY Plug-in hybrid operation activated

Haptic accelerator pedal (→ page 185, 187, 182)

A ECO start/stop function (→ page 180)

**HOLD** HOLD function (→ page 230)

Adaptive Highbeam Assist (→ page 139)

Adaptive Highbeam Assist Plus

(→ page 140)

Active Stop-and-Go Assist (→ page 244)

★ Slippery road surface warning

Vehicles with Traffic Sign Assist: detected instructions and traffic signs (→ page 260)
Important information from other driving systems

Important information from other driving systems may briefly appear in front of the displayed traffic signs.

## Overview and operation

## Notes on the MBUX multimedia system

▲ WARNING Risk of distraction from information systems and communications equipment

If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

You must observe the legal requirements for the country in which you are currently driving when operating the multimedia system.

Depending on the equipment, the scope of function and product designation of your MBUX multimedia system may differ from the description and

images in this Operator's Manual. For example, route guidance with augmented reality is not available in all equipment variants.

- i The functions of your MBUX multimedia system may differ and depend on the following factors:
  - Market
  - National version
  - Technical conditions

Functions, services and service aspects provided by Mercedes-Benz and/or third-party providers may no longer be available when the contractual period expires or due to technical conditions. There is therefore no entitlement to the continuous provision of functions and services.

The described functions may be modified, optimized and adapted after the time of going to press.

Mercedes-Benz therefore reserves the right to introduce changes in the following areas:

Features

- Services
- Service aspects


For these reasons, descriptions and depictions relating to the MBUX multimedia system may, in some cases, differ for your vehicle.

! NOTE Increased surface temperature due to direct sunlight on the central display

The surface of the central display is very dark. If the display is exposed to direct sunlight, the surface can become very hot.

If the central display has been exposed to direct sunlight, allow it to cool down before touching it for a long time.

## Overview of the MBUX multimedia system



Touch Control and control panel for the MBUX multimedia system

MBUX stands for Mercedes-Benz User Experience.

- Operating Touch Control
- Central display with touch functionality
  - · Home screen overview
  - Operating the touchscreen
- Switch panel with:
  - Fingerprint sensor
  - (b) Switches the MBUX multimedia system on or off

Switches sound on or off → Adjusts the volume

Further operating options:

- · Conducting a dialog with the MBUX Voice Assistant.
- (i) You can find further information about operation as well as about applications and services in the Digital Operator's Manual.

## Anti-theft protection

This device is equipped with technical provisions to protect it against theft. Further information on anti-theft protection can be obtained at an authorized Mercedes-Benz Center.

## Zero layer

## Function of the zero laver

(i) Your software can be upgraded to a more current version at a later date.

The zero layer provides you with dynamic content from the MBUX multimedia system and is used to quickly access and control the applications you

use. When you select on the central display, the digital map with the applications appears in the lower display area. Compared to the home screen with a classic menu, the steps required to call up the applications are reduced. You can switch between the zero laver and the home screen with a classic menu.

The applications can be hidden from the display area and shown again.

The zero layer provides the following modules and applications:

· Navigation module

displayed.

- In the expanded view you can, for example, display the route overview, switch on the display of traffic information and make settings for View (map), Messages & Acoustic Signals, Route.
- Entertainment (media, radio) and telephone When the lower display area is shown, the entertainment sources are always displayed. A mobile phone must be connected to the MBUX multimedia system for the phone to be

#### 314 MBUX multimedia system

· Active applications

The lower display area shows an active massage program, for example.

Suggestions

Suggestions are displayed on the lower display area based on context and your user behavior. Here are a few examples:

- Latest calls
- Active massage programs
- Vehicle functions
- Online voice applications

The applications are first displayed in a reduced view. By tapping on them, you can operate them or open the associated menu (expanded view).

A long press on a suggestion opens a context menu in which further functions are available.

The learning function can be switched on and off for the options .

## Overview of the zero layer

Digital map and user-specific applications (example)



- Navigation module (reduced view)
- Enters a destination Searching for a parking space, in the vicinity for example

- Calls up the Control Center (pull the bar down)
- Status line
- Calls up user profile settings
- Content sharing menu (if available)
- Telephone Requirement for phone: the mobile phone is connected to the MBUX multimedia system.
- Entertainment sources (media, radio)
- 9

Press briefly: shows all applications  $(\rightarrow page 316)$ 

Press and hold: calls up the home screen with classic menu

Route monitor e.g. route list, lane recommendations, toll stations, 3D image of the upcoming driving maneuver

The zero layer shows the digital map and the userspecific applications.

The following user-specific applications are displayed in the lower display area:

- Suggestions Requirement: suggestions are activated  $(\rightarrow page 322)$ .
- Active applications e.g. a massage program e.g. Active Parking Assist
- Telephone 7
- Entertainment sources (8)
- Online voice applications

The lower display area can be hidden and shown  $(\rightarrow page 316)$ .

#### Information about entertainment sources

You can operate the applications in the reduced view or in the menu (expanded view)  $(\rightarrow page 316)$ .

#### Examples:

 Control a media source, e.g. pause/play, next track, set a station

- Select tracks from the current playlist or stations from the station list
- · Select a media source The media source must be connected to the MBUX multimedia system.

#### Information about the telephone

To use the functions, the mobile phones must be connected to the MBUX multimedia system.

Requirement for suggestions: the Calls & Messages option is activated in the suggestions.

## Examples:

- Answer a call and call a missed call The missed calls are displayed for the mobile phones connected to the MBUX multimedia system.
- · Display contacts and call list and call a contact
- Use voice functions
- Suggest contacts

The contacts are suggested for the mobile phones connected to the MBUX multimedia system. No contacts are suggested for the

mobile phones that are linked to another user profile.

- Write messages to contacts (suggestion)
- Connect a device via the device manager (suggestion)

## Information about active applications

The following functions are available:

- Operating a massage program
- · Raising or lowering the vehicle level

## Suggestions for comfort and vehicle functions as well as navigation

Requirement: the Comfort, Vehicle and Navigation options are activated in the suggestions.

- Operating a massage program For example, the multimedia system suggests a program at a certain time.
- Opening the tailgate Requirement: the vehicle is equipped with trunk lid convenience closing.
- · Setting the vehicle level
- Making heating settings

#### 316 MBUX multimedia system

- Activating/deactivating Parking Assist PARKTRONIC
- Selecting previous destinations and destinations from favorites

## Suggestions for online voice applications

Requirement: the Online Voice Services option is activated in the suggestions.

The suggested voice applications are made available online and are based on your previous voice inputs.

#### Examples:

- · What will the weather be like tomorrow?
- Play the messages.
- · Start geoquiz.
- Open the garage door.

## Calling up and operating the zero layer

#### Calling up the zero layer

When the vehicle has been switched on, the zero layer is displayed with the digital map. Navigation is active.

From another application: press the http://doi.or.in.

or

► Tap on 🞧.

# Operating applications in the reduced view (examples)

- Media: to play the previous or next track, tap
- To answer a call or call a missed call: tap on the contact.

After the connection has been established, the call functions are available.

- To end a call: tap on the contact again.
- To reply to a message: tap on a message and dictate the message via the MBUX Voice Assistant.
- ➤ To start a massage program: tap on the application and start the massage program.
- To select a previous destination: tap on the application and select one of the previous destinations.

To select a destination from the favorites: tap on the application and select the destination.

## Hiding and showing the display area with applications

- To hide: pull the applications down.
- ➤ To show: pull the bar above upwards.

or

Select 🚡.

or

Press the button on the steering wheel on the right.

## Navigation module (expanded view)



Example: route guidance is active

- Destination
- Searches for a gas station
- Switches traffic information display on or off
- Tap on the navigation module ( $\rightarrow$  page 314).
- Select Route in the lower menu bar.

## Operating a menu in the lower display area (example: active massage program)



- Selects a massage program
- Starts/stops a massage program for the driver
- Starts/stops a massage program for the front passenger
- Sets the relaxation intensity for the driver's or front passenger seat
- Tap on the application. The expanded view of the application is displayed.
- To close the menu: select

## Opening and closing the context menu for a suggestion

- Press and hold on a suggestion. The context menu opens and shows the No Longer Suggest option, for example.
- To close: swipe downwards.

## Removing a suggestion from the display area

Swipe the suggestion upwards.

## Showing all applications


- Briefly press 🛕. Available applications are displayed. The global search is available.
- To hide applications: briefly press again.

#### Switching between the zero layer and home screen with classic menu.

- ▶ Press and hold on 🚡. The home screen with classic menu is shown.
- To return to the zero layer: press and hold on

#### 318 MBUX multimedia system

#### Home screen overview



- Status line
- Calls up user profile settings and switches user
- Uses the global search
- Calls up the Control Center: pull the bar down
- 6 Calls up favorites
- O Displays in the status line


- Calls up applications
- Quick-access to application
- Global menu
  - Salls up previous menu
  - Press and hold: switches between home screen and zero layer
  - Previous track or previous radio station
  - Next track or next radio station
- (i) During a telephone call, the call duration is displayed in global menu (o).

The following functions are called up in the Control Center:

- · Notifications Center
- Favorites
- Vehicle quick-access

## Operating the MBUX multimedia system

## **Using Touch Control**




- 1 Shows the home screen
- 2 Touch Control
  - **▲ ▶ ▼** swipe in the direction of the arrow (navigate)
  - OK Press (confirm)
- Returns to the previous display
- Makes or accepts a call
- Rejects or ends a call
- To increase volume: swipe upwards To reduce volume: swipe down

- To switch off the sound: press
- ★ Calls up favorites
- Starts the MBUX voice assistant

You can navigate through menus and lists via the touch-sensitive surface of Touch Control (2) using a single-finger swipe, e.g.:

- To enter a character: select a character using the keyboard and press on Touch Control 2.
- To select a menu option: scroll in a list and press Touch Control 2.
- To move the digital map: swipe in any direction.

#### Using the touchscreen



Example: Control elements under the central display

- Fingerprint sensor
- Switches the MBUX multimedia system on or off
- Switches the mute function on / off

- Adjusts the volume Press - or + or swipe over the button
- To select a menu item or entry: tap on a symbol or an entry.
- To increase the map scale: tap twice quickly with one finger.
- To reduce the map scale: tap with two fingers.
- To enter characters with the keypad: tap on a button.
- To navigate in menus: swipe up, down, left or right.
- To use handwriting to enter characters: write the character with one finger on the touchscreen.
- To zoom in and out of the map: move two fingers together or apart.
- To enlarge or reduce the size of a section of a website: move two fingers together or apart.
- To turn the digital map: turn counter-clockwise or clockwise using two fingers.

#### 320 MBUX multimedia system

- To move the digital map: touch the touchscreen and move your finger in any direction.
- To save the destination in the digital map: touch the touchscreen and hold until a message is shown.
- To set the volume on a scale: touch the touchscreen and move the finger to the left or right.
- To call up a global menu in the applications: touch the touchscreen and hold until the Options menu appears.

#### Function of the MBUX Voice Assistant

▲ WARNING Risk of distraction from information systems and communications equipment

If you operate information systems and communication devices integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

For your own safety, always observe the following points when operating mobile communications equipment and especially your voice control system:

- Observe the legal requirements for the country in which you are driving.
- If you use the voice control system in an emergency your voice can change and your telephone call, e.g. an emergency call, can thereby be delayed.
- Familiarize yourself with the voice control system functions before starting the journey.

Using the MBUX Voice Assistant, vehicle functions and various areas of the MBUX multimedia system can be operated by voice input. The MBUX Voice Assistant is operational approximately half a minute after switching on the vehicle and can be

operated from all seats. Further information and examples of voice commands can be found in the Digital Operator's Manual.

You can use the MBUX Voice Assistant to operate the following functions depending on the vehicle equipment:

- Telephone
- · Text messages and e-mails
- Navigation
- · Radio and media
- Vehicle functions
- Online functions

Full functionality of the voice control system is only available for you with activation of online voice control.

## Conducting a dialog

## Starting a dialog

Say "Hey Mercedes" to activate the MBUX Voice Assistant. Voice activation must be switched on in the multimedia system. or

Press the button on the multifunction steering wheel.

A blue line appears in the MBUX multimedia system. The dialog can be started.

For the dialog with the MBUX Voice Assistant, you can use complete sentences of colloquial language as voice commands. Voice activation can also be directly combined with a voice command. e.g. "Hey Mercedes, how fast can I drive?"

## Calling up help

- For information about the MBUX Voice Assistant: say "Hey Mercedes, what can you do?"
- Digital Operator's Manual: "Show me the Operator's Manual". The full extent of the Digital Operator's Manual is available when the vehicle is stationary.

## Operating functions (examples)

- To operate the navigation: "Search for an Asian restaurant, but not Japanese, in South Manhattan."
- To operate the phone: "Call my father."

- To change the system language to English (short command): "Change language to English"
- To operate the radio: "Show me the list of radio stations."
- To operate media: "Switch on random playback."
- To operate vehicle functions: "Switch the seat heating to level 2."
- To operate online functions: "What's the time in Sydney?"
- To ask a question about the vehicle: "Do I have Blind Spot Assist?"

## Information on users, suggestions and favorites

WARNING Risk of becoming trapped dur-

ing adjustment of the driver's seat after calling up a driver profile

Selecting a user profile may trigger an adjustment of the driver's seat to the position saved under the user profile. You or other vehicle occupants could be injured in the process.

Make sure that when the position of driver's seat is being adjusted using the multimedia system, no people or body parts are in the seat's range of movement.

If there is a risk of someone becoming trapped, immediately stop the adjustment process by:

a) Pressing the warning message on the central display.

or

b) Pressing a position button of the memory function or a seat adjustment switch in the driver's door. The adjustment process is stopped.

The driver's seat is equipped with an anti-entrapment feature.

If the driver's door is open, the driver's seat will **not** be set after calling up the driver's profile.

## User profiles and user-specific content

Prerequisites for the vehicle owner:

You have a Mercedes me user account.

#### 322 MBUX multimedia system

- · You have a Mercedes me PIN.
- · You have agreed to the terms of use.
- The vehicle is linked to a Mercedes me user account.
- (i) If one of the pre-requisites listed is missing or if no user profile has been selected, the data described in the following section will be saved in the vehicle as the standard setting. Standard settings can be changed by all vehicle users.

User profiles save personal settings. If the vehicle is used by several people, a person can change their profile settings without changing the settings of other users.

You can individualize a user profile in the vehicle using the set-up assistant or using the settings in your user profile. Some settings, e.g. the Mercedes me PIN and a profile photo are made in the Mercedes me App or in the Mercedes me Portal.

User-specific content and applications with personal data are protected by different levels of security. To access protected content, the

Mercedes me PIN and, depending on the vehicle equipment, biometric sensors can be used.

- i The security level is set by the multimedia system and calculated from the combination of all sensor inputs. Some security levels cannot be turned off.
- When a user profile is activated, the following personalized comfort systems, for example, can be adjusted or their settings loaded:
  - Seat
  - Ambient light
  - · Outside mirrors
  - Roller sunblinds
  - Climate control settings

If the user profile is activated when driving, the driver's seat position will not be adjusted.

Depending on the vehicle equipment you can, as a user, save the following settings, for example:

- Driver's seat, steering wheel and mirror settings
- Climate control

- · Ambient lighting
- Radio (including station list)
- Suggestions and favorites

## Suggestions

The vehicle can learn the habits of the driver. It then makes suggestions regarding navigation destinations, phone numbers and music preferences. The requirements for that are the selection of a user, your consent to the recording of data and sufficient collected data.

#### **Favorites**

Favorites offer you quick access to frequently used applications. 100 favorites are available in total.

## Configuring users, suggestions and favorites

#### Requirements:

• The vehicle is stationary.

#### Multimedia system:



# Adding a user

- ▶ Select (+) Add User. A QR code is loaded.
- Scan the displayed QR code with the Mercedes me App or any QR code scanner on a mobile device. If the Mercedes me App is not vet installed on your mobile device, you will be directed to the store of your mobile device.
- Follow the directions in the app. The vehicle is connected with your Mercedes me user account. This automatically creates your user profile in the vehicle.

You will be informed when your user profile is available.

When the vehicle is stationary, the set-up assistant starts automatically after user selection.

#### Protecting user-specific content and applications

If you add a new user, access protection is already activated for the user profile. The Mercedes me PIN and, depending on the vehicle equipment, biometric sensors are available for access. Biometric sensors in the vehicle must be taught in. The authentication process then takes all taught-in and available sensors into account.

The following user-specific content and applications are protected, for example:

- User selection and user profile settings
- Biometric sensors

The teaching-in of biometric sensors is protected.

Suggestions

The data and determination of the most probable navigation destinations, media sources. radio stations, contacts and messages are protected.

- ENERGIZING COACH
  - The recorded health data and their evaluation are protected.
- · Mercedes me connect store

The purchase of services is protected.

- Switch Protect Content on or off.
- Switch Access Protection on or off.
- (i) When access protection is switched off, your user profile can be accessed and changed from every vehicle seat.
- (i) Access protection is switched on or off on a vehicle-specific basis.

## Setting up, editing and deleting biometric recognition

The biometric data models are saved in the sensors in the vehicle. If recognition has been taughtin, this sensor serves as a contributory factor for authentication on the multimedia system.

- Select Protect Content.
- Select Fingerprint Recognition or Voice Recognition.
- (i) If necessary, authenticate yourself on the multimedia system.

### Setting up fingerprint recognition

Place and lift your finger several times on the fingerprint sensor under the touchscreen. The finger is scanned. If the scanning procedure is successful, a message appears on the central display. You can unlock your user profile and protected applications with your finger print.

### Setting up voice recognition

Speak the sentence shown on the central display and follow the voice assistant's instructions.

If the voice recognition was successful, a message appears on the central display. You can unlock your user profile.

i Avoid background or disturbing noises during voice recognition.

## Deleting biometric data

- Tap on , for example, behind Fingerprint Recognition.
- Select Yes.

### Selecting a user

- (i) When you call up your driver profile, the driver's seat and the steering wheel can be set.
  - You can cancel the setting process with the following actions:
  - Press Tap Here to Cancel message on the central display.
  - Press one of the seat operating buttons in the driver's door.
- Select Change User.
- Select a user.
- When requested to do so, authenticate with the Mercedes me PIN or a taught-in biometric characteristic.

The user profile is loaded and activated.

 If you select Continue Without Selecting a User, no specific settings for the user profile are loaded.

# Configuring and deleting suggestions

- ➤ Select 🞧.
- Select Settings.

- Select System.
- Select Suggestions.
- ▶ Select 🔯 .
- Switch the options on or off individually. If an option is switched on and sufficient data has been gathered, personalized suggestions based on your user behavior will be offered to you on the zero layer. These are, for example, navigation destinations visited, phone numbers dialed as well as suggestions based on your music preferences.
- ➤ To delete collected suggestions: select [

ect	<b>S</b>	

Select Yes.

The suggestions are reset.

# Adding favorites from categories

- Select 🞧.
- ➤ Select ★
- ➤ Select >
- Select + Create New Favorite.
- Select the category.
- Select a favorite.

### System settings

# Overview of the system settings menu

In the system settings menu, you can make settings in the following menus and control elements:

- Display
  - Display brightness
- · Control elements
  - Keyboard language and handwriting recognition
  - Sensitivity of Touch Control
- MBUX Voice Assistant
- MBUX Interior Assistant
- Sound
  - Entertainment
  - Navigation and traffic announcements
  - Telephone
- Data protection
- Connectivity
  - Wi-Fi, Bluetooth®

- Time & date
- Language
- Units for distance
- System PIN
- Suggestions
- Software update
- System reset

# Overview of software updates

Important software updates may be necessary for the security of your multimedia system's data. Install these updates, or else the security of your multimedia system cannot be ensured.

The multimedia system displays a corresponding message when a software update is available.

If the Automatic Online Update option is active, software updates are downloaded automatically. If the option is deactivated, you will be informed of new software updates once. The software updates are available for downloading for a limited period of time.

Carrying out a software update:

- · You can start software updates via the communication module.
- You can start software updates via a Wi-Fi hotspot.
- You can start map updates from an external medium.
- (i) Online software updates cannot be performed via external Wi-Fi hotspots that are encrypted via TKIP.
- (i) If the Wi-Fi hotspot requires logging in via the browser, once the connection is successfully established the browser will open in order to start the update. To start the download follow the instructions in the browser.
- (i) To complete software updates via the communication module, the vehicle must be connected with the Internet and a Mercedes me user account.
- (i) To complete software updates via Wi-Fi, the vehicle must be connected to an external Wi-Fi hotspot.

A software update consists of three steps:

- Downloading or copying of the data required for installation
- Installation of the downloaded software update
- Activation of the downloaded software update
- i It may be necessary to restart the MBUX multimedia system after completion of a software update.
- (i) While some software updates are being downloaded, the multimedia system cannot be operated and the vehicle functions may be restricted.
- (i) Some software updates require a safe vehicle status for the installation to be completed. They can only be carried out in a safely parked vehicle with the vehicle switched off.

For software updates requiring a safe vehicle status: when the last installation step is reached, a message appears on the central display after the vehicle is switched off. Follow the step-by-step instructions on the central display to complete the installation.

There are software updates that can only be installed when the vehicle is safely parked, there are no more people in the vehicle and the vehicle is locked.

### Availability of the driver and central display

During the installation of software updates, it is not possible to use the vehicle, central display and driver display. You may receive the following display message when an installation is running:



(i) The display message does not appear every time a software update is installed.

In rare cases, an error can occur during the installation. The multimedia system automatically attempts to restore the previous version. If it is not possible to restore the previous version, the display message shown above appears every time the vehicle is started

#### Failure of the driver display

If the driver display fails or there is a malfunction, you may not recognize limitations in the functions of systems relevant to safety or the speed display, for example. This may impair the operating safety of the vehicle. Park the vehicle safely as soon as possible and notify a qualified specialist workshop. ( $\rightarrow$  page 482)

Further information about software updates can be found at https://me.secure.mercedes-benz.com

## Failure of the central display

If the central display fails or the display message shown above is shown continuously, several systems such as the rear view camera, Parking Assist PARKTRONIC or climate control are no longer available. Drive on carefully and consult a specialist workshop as soon as possible.

### Setting up a Wi-Fi hotspot

#### Requirements

- The Wi-Fi function is activated on the multimedia system and the communication device to be connected
- The communication device to be connected supports at least one of the types of connection described.

The connection types shown depend on the device to be connected. The function must be supported by the multimedia system and by the device to be connected. The type of connection must be selected on the multimedia system and on the device to be connected.

- (i) Some functions may first need to be activated on the communication device being connected. More detailed information can be found in the manufacturer's operating instructions.
- (i) The use of the vehicle data tariff by external devices is not available in all countries.

Multimedia system:

- → Settings → System
- > Internet and Bluetooth
- (i) The availability of the functions is dependent on the country.
- Select Wi-Fi.

The controller is to the right: Wi-Fi is switched on.

When the Wi-Fi function is switched on, you can connect the multimedia system with external hotspots or make it available as a hotspot for external devices.

When the Wi-Fi function is switched off, it is not possible to establish a hotspot connection.

(i) Depending on the vehicle equipment, you can purchase a data package directly from a mobile phone network provider via the Mercedes me Store. To be able to use the data package, you conclude a separate contract with a mobile phone network provider via the Mercedes me Store, which can be terminated at any time and for which there are no costs. This contract is a prerequisite for

using the services from the previously purchased package. The availability of this option is dependent on the country. If the data package option is not available or can be upgraded, you can purchase data volume directly from the mobile phone network provider for a fee.

(i) The use of the vehicle data tariff by external devices is not available in all countries.

# Using the multimedia system as a Wi-Fi hotspot

- Select MBUX Hotspot.
- Select one of the following connection options.

#### Connecting using a QR code

Requirement: an app for scanning the QR code is installed on the device being connected.

Alternatively: the device being connected has an integrated QR code scanner (see the manufacturer's operating instructions).

Scan the QR code shown. The Wi-Fi connection is established.

# Connecting using a security key

- Select the vehicle from the device to be connected. The vehicle is displayed with the MBUX XXXXX network name.
- Enter the security key shown on the device to be connected.
- Confirm the entry.

### Generating a new security key

- Select the Generate New Security Key option in the MBUX Hotspot menu.
- Confirm the prompt with Yes.
   A new security key is generated.

A connection will be established with the newly created security key.

(i) When a new security key is generated, all existing Wi-Fi connections are then disconnected. If the Wi-Fi connections are re-established, the new security key must be entered.

# Using a mobile communication device as a Wi-Fi hotspot (tethering)

i This function is country-dependent.

- Select the Manage Internet Access option in the Internet and Bluetooth menu.
- The Wi-Fi function on the mobile phone and Internet access via Wi-Fi must be activated (see the manufacturer's operating instructions).
- Select Search for Access.
- Select the network.
- Log in to the Wi-Fi network.

or

- Select the mobile phone with the Wi-Fi symbol.
- (i) With external Wi-Fi hotspots, which are encrypted via TKIP, online software updates cannot be carried out via the external Wi-Fi hotspot.

# System language

# Notes on the system language

This function allows you to determine the language for the menu displays and the navigation announcements. The selected language affects the characters available for entry. The navigation announcements are not available in all languages. If a language is not available, the navigation announcements will be in English.

# Setting the language

Multimedia system:

# Setting the system language

A list of the available system languages is shown.

Select a language. The system language is switched to the selected language.

# Resetting the multimedia system (reset function)

**WARNING** Risk of accident due to failure of central display functions

While the multimedia system is reset, its functions, such as the rear view camera, are not available.

Only reset the multimedia system when the vehicle is stationary.

#### Requirements

- The vehicle is switched on.
- The vehicle is stationary.

Multimedia system:



When resetting the system, personal data and settings are deleted, for example:

- · Connected devices
- Individual user profiles
- Biometric data
- (i) The data used and saved in the multimedia system by the driver assistance systems is deleted.
- Select Reset.

A guery appears asking if the system should really be reset.

Select Yes.

The multimedia system is reset to the factory settings. The multimedia system is restarted after the system reset.

Due to data protection, as well as the function of individual driving systems and driving safety systems, it is a requirement to carry out a complete system reset before selling the vehicle or transferring it to a third party, or after use as a hire car.

#### AMG TRACK PACE

#### Function of AMG TRACK PACE

This function is an on-demand feature and can be activated via Mercedes me after you purchase your vehicle. The Digital Operator's Manual contains further information on Mercedes me and on-demand features.

With AMG TRACK PACE, the driving characteristics on race tracks can be analyzed and optimized. You can drive previously saved race tracks (e.g. the Hockenheimring), or record and save new tracks. The lap times set will be stored for

every track. These can be analyzed and compared with other lap times to achieve the best possible race results. Additionally, acceleration and braking operations can be measured and stored.

Note: Use AMG TRACK PACE only on closed circuits away from public roads. Adapt your driving style to your personal skill level and environmental conditions. As the driver, you are solely responsible for driving your vehicle. Park your vehicle safely before operating the application.

### **Setting Track Race**

Multimedia system:

TRACK PACE ➤ Track Race

#### Recording a new track

- ► Select New Track .
- Select Start Record, at the desired starting point.

The track recording starts at this point.

During track recording, sectors can be set to divide up the track.

- Select Set Sector.
- Select Stop Recording to end track recording or cross the start line again.
- Confirm the prompt with Yes.
- Select the weather.
- (i) The temperature will be determined automatically.
- Enter a name.
- Press OK to confirm. The track will be saved under the name entered.

#### Searching by track name

- Select Search.
- Enter the track name.
  Tracks with the searched name are displayed.

## Measuring time on a saved track

- ► Select All tracks.
- Select the desired track.

Select Start Time Recording if you are already at the start line.

or

Select Navigate to to navigate to the start line.

Timekeeping begins automatically when the starting line has been crossed.

- (i) When AR is selected, the track display can be switched to AR. In addition, it is possible to switch to the telemetry display by selecting
- Select Stop timekeeping to end timekeeping.
- Confirm the prompt with OK.
- Select the weather.
- Select Yes to save the times set for this track.

# Showing readings during Track Race

The following readings can be shown:

- Tire temperature
- Miniature map
- · Sector overview

- · Engine data
- G-force display
- Lap overview
- Select Start Time Recording.
- Drag the desired display from the grid to the left or right edge of the central display. The readings will be shown during Track Race.

You can deactivate this by selecting  $\boxed{\times}$  on the active display.

## Displaying the analysis

- Select All tracks.

  An overview of all the driven tracks appears.
- Select a track.
- Select a session.

The following data is displayed:

- Lap and sector times
- · average and maximum permissible speed
- driver
- Vehicle

- Date
- Weather
- Select Add Recording to use a different session as a reference value.
- Select \_\_\_\_ to return to the overview.
- Select Diagram.
- Set the desired parameters.
  - The analysis is displayed.



- Lap overview
- Parameter overview
- Editing parameters
- Deleting parameters
- Adding new parameters
- i) The following values can be set for the parameters, for example:
  - Speed

- longitudinal/lateral acceleration
- Steering angle
- engine speed
- engine oil/tire temperature

Based on the analysis, you can check and optimize driving characteristics for any position on the track.

# Exporting tracks (USB)

- Select ∑ Tracks. An overview of all stored tracks will appear.
- Select the desired track.
- Select options for the desired track.
- Select Export Track to.... The selected track can be exported to a USB storage device connected to the vehicle.

#### Editing tracks and recordings

- Select Tracks.
- Select the desired track.
- Select options of for the desired track.
- Select Rename or Delete.

or

- Select a track.
- Highlight the desired recording.
- ► Select ••• Options.
- Select Export to... or Delete.

# **Setting Drag Race**

Multimedia system:

→ TRACK PACE → Drag Race

#### Measuring acceleration

- Select Drag race options.
- Select Acceleration.
- Set a starting speed or select Automatic.
   Measurement will begin as soon as the specified starting speed has been reached.
- Set a target speed. Measurement will stop as soon as the specified target speed has been reached.
- Start off and begin the measurement.
   Measurement will begin when the vehicle accelerates.

You can stop measurement early by interrupting the acceleration procedure.

#### Quarter-mile race

- Select Drag race options.
- Select Quarter Mile.
- Set a target distance.
   Measurement will stop as soon as the specified target distance has been reached.
- Start off and begin the measurement.
   Measurement will begin when the vehicle accelerates. Timing will run until the target distance or a maximum of one mile has been traveled.

You can stop measurement early by interrupting the acceleration procedure.

# Measuring braking

- Drag Race options
- Select Braking.
- Set a starting speed or select Automatic.
- Start off and begin the measurement.

Brake to a standstill.

Measurement is incremental, in steps of 6 mph (10 km/h) to a standstill. If the braking procedure is started e.g. at a speed of 98 mph (157 km/h), measurement will start as soon as 93 mph (150 km/h) has been reached

# Storing and calling up measured values

If a measurement is completed or canceled, a prompt will appear asking whether the measurement should be saved.

Confirm the prompt with OK to save.

#### Calling up saved measurements

- Select History.
- Select Acceleration, Quarter Mile or Braking.
- Select a measurement.
   The desired measurement will be displayed in detail.

or

Delete a measurement.

# Calling up the telemetry display

#### Multimedia system:

# → TRACK PACE → Telemetry

The telemetry display shows current vehicle data as a digital value and as a diagram. Up to four parameters can be selected to be shown on the display.

#### For example:

- Engine speed
- Wheel angle
- Speed
- Steering angle
- Set the desired parameters.
- Set the time.

The set parameters will be evaluated for the selected time on the diagram.

# Configuring AMG TRACK PACE

# Requirements

To connect a mobile device to the TRACK PACE app:

- the TRACK PACE app is installed on the mobile end device
- the mobile end device is connected to the multimedia system via Wi-Fi.

#### Multimedia system:

TRACK PACE ▶> 🌣

# Connecting a mobile device via the TRACK PACE app

The TRACK PACE app makes it possible to record videos and to synchronize them with stored tracks.

- Select TRACK PACE App.
- Select Authorize a New Device.
- Start the TRACK PACE app on the device to be connected.
- Select Continue and confirm the authorization prompt.

A four-digit code will be shown on the central display.

Enter the code on your smartphone. The device is authorized.

#### De-authorizing the mobile device

- Select TRACK PACE App.
- Select a device.
- Confirm the message prompt with Yes. The device is de-authorized

# Setting the TRACK PACE display on the head-up display and driver's display

- Select IC and HUD Contents.
- Activate or deactivate the desired contents. The content on the head-up display and the driver's display will be adapted.
- (i) Further information about the head-up display  $(\rightarrow page 307)$ .
- (i) Further information about the driver's display  $(\rightarrow page 305)$ .

# Setting acoustic feedback

- Select Acoustic Feedback.
  - A scale with values from 0 to 10 is shown.
- Select a setting.

### Displaying statistics

Select TRACK PACE Statistics.

Statistics on the current user profile will be displayed.

The following data is displayed:

- · Driving time
- · track driven
- · tracks recorded
- · Track Races recorded
- laps recorded
- Drag Races recorded
- maximum design speed

#### Activating the ambient light

If this function is active, the vehicle interior is lit red or green depending on Delta Time.

- Select Ambient Light.
- Activate or deactivate the function.

#### Adjusting the dashcam

If the vehicle is equipped with a dashcam, it can be used in AMG TRACK PACE.

- Select Dashcam.
- Select Track Race or Drag Race and apply Activate Recording.
- You can set which overlay is to be used in the recorded video under Video Overlay Content.

#### Activating boost strategy

This function is used to increase performance on a race track and is available only in the drive program.

- Select boost strategy.
- Activate or deactivate the function.
- i The function is not available for all vehicle models.

# Plug-in hybrid settings

# Configuring the charging settings

Multimedia system:

→ 🔝 **>>** Hybrid **>>** Charging

## Setting the charging program

Select Home, Work or Standard.

 The standard charging program is automatically activated when the vehicle is switched on or off.

### Opening the socket flap

Press Open socket flap.

The socket flap opens and can be closed again by hand. When the socket flap is open and a vehicle plug is inserted and locked in place, charging can be stopped by pressing the End charging and unlock button, which will be available at that time.

i The availability of this function is equipmentdependent.

# Unlocking the charging cable (mode 3 or 4)

When the function is active, the charging cable is unlocked when the maximum charge level is reached.

- Select Home or Work.
- Activate or deactivate Unlock Charging Cable.

# Activating or deactivating location-based charging

Select Charging Program, Home or Charging Program, Work. Activate or deactivate Select Based on Location.

When the function is activated, the vehicle's current position is saved as one of the selected options. When the address is reached again, a brief query appears as to whether the respective charging program should be selected.

# Setting the departure time

Select Next Departure Time.

The following charging times can be selected:

- individual charging times
- a Week Profile

# Setting an individual departure time

Select Add New Time and set the desired departure time.

Select and adapt an existing departure time.

### Setting repeat days

Select Add New Time and set the desired departure time.

Mark the relevant weekdays for which the departure time will apply and confirm with OK .

Select and edit existing repeat days.

# Setting the maximum charge level

- Select Maximum State of Charge.
- Set the desired percentage. The high-voltage battery is charged up to the set percentage as a maximum.
- The percentage can be set in increments of 10 %.
- As soon as the full charge level is reached, a notification is shown in the central display that the charging process is completed and the journey may be continued. The maximum charge level can be saved in the Home and Work charging programs. In the Standard charging program, the setting is automatically reset to a charge level of 100 % after the vehicle is switched on or off.

# Overview of the energy flow display in the multimedia system

The active components of the hybrid system are highlighted on the energy flow display. The energy flow between the individual components is shown in color

The components displayed are:

- State of charge of the high-voltage battery
- · Combustion engine
- Energy flow
- High-voltage battery

The energy flow is shown in different colors depending on the operating status:

- . White: constant energy flow
- Red: high energy flow (boost effect)
- Green: low-emission energy flow in the case of recuperation, electric mode and charging the high-voltage battery

# Calling up the energy flow display

Multimedia system:



Select Energy Flow.

The energy flow in the vehicle will be displayed.

Information on the status of the hybrid system and the current state of charge of the high-voltage battery will be displayed in addition to the energy flow.

#### Off-road menu

# Overview of the Offroad menu in the MBUX multimedia system

The Offroad menu provides an overview of the most important, relevant data for off-road driving, as well as functions to assist driving off-road and the possibility to record tracks for subsequent reuse or for sharing with other drivers.

#### Cockpit

This tab provides an overview of the most important data. Content is displayed in different tiles that can be changed using directional arrows or swipes. In addition, this menu contains buttons for quick-access to certain vehicle functions relevant to off-road operation.

Displayed data are, for example:

- Artificial horizon
- Compass
- Altitude
- Steering angle of the front and rear wheels
- Torque and power
- Tire pressure and temperature
- Transparent hood

Further information on the Cockpit tab  $(\rightarrow page 336)$ .

# Setting the off-road menu in the multimedia system

Multimedia system:

¬→ 🙀 >> Offroad >> Cockpit

## Setting displays in the central display

Press , p or on the display itself to jump to the next display.

# Quick-access: activating or deactivating Parking Assist PARKTRONIC

- Press P<sub>W</sub> to switch the function on or off.
- (i) Further information on Parking Assist PARKTRONIC (→ page 280).

# Quick-access: activating or deactivating ESP® (Electronic Stability Program)

- ▶ Press 🐉 to switch the function on or off.
- $\bigcirc$  Further information on ESP ( $\rightarrow$  page 228).

# Quick-access: activating or deactivating manual shifting

Press M to switch the function on or off.

(i) Additional information on manual gearshifting  $(\rightarrow page 195)$ .

# Quick-access: activating or deactivating DSR (Downhill Speed Regulation)

- Press to switch the function on or off.
- (i) Further information on DSR ( $\rightarrow$  page 245).

# Navigation and traffic

Notes on navigation

## Route guidance with augmented reality

WARNING Risk of accident and injury as a result of distraction, incorrect depiction or wrong interpretation of the display

The camera image of the augmented reality display is not suitable as a guide for driving.

- Always keep an eye on the actual traffic situation.
- Avoid extended observation of the camera image.

WARNING Risk of accident and injury due to imprecise positioning of additional information

The additional information from the augmented reality display may be inaccurate and is not a substitute for observing and assessing the actual driving situation.

Always keep an eye on the actual traffic situation when carrying out all driving maneuvers.

## Switching navigation on

Multimedia system:

- **→** 🔝
- Alternatively, press the fin button on the steering wheel on the right ( $\rightarrow$  page 318). The zero laver with the digital map is displayed.

### Navigation overview

# Digital map



Navigation module (reduced view) Route guidance active:

The navigation module shows the information relevant to the route in the zoomed-out view. e.g. the destination or a traffic delay

(x) Ends the current route guidance Tapping opens the navigation module in the expanded view with the Route

- Destination entry
- 3 Searches for a parking space
- Map orientation and set map type
- Current vehicle position (vehicle symbol or arrow)
- Display area with entertainment sources, phone, active applications and suggestions
- Navigation window shows the next driving maneuver (zoomed out view) or the route monitor (zoomed in view)

Route guidance active: route monitor shows, e.g. route sections, upcoming driving maneuvers with lane recommendations, destination, traffic delays, toll stations, 3D images at freeway exits, online content

Switches off navigation announcements

Switches on navigation announcements

The following map orientations 4 are available:

• 2D and to the north

- · 2D and direction of travel
- · 3D and direction of travel
- · Map with complete route
- i If the map is moved, the map switches between 3D direction of travel and 2D north orientation.

The following map types 4 are available:

- · Daytime display
- · Night-time display
- · Satellite map
- i If you notice a problem with the digital map you can report this under https:// mapfeedback.here.com/#/report.

#### Navigation module (expanded view)



Example: route guidance is active

- ① Destination
- Searches for a gas station
- Switches traffic information display on or off

#### Overview of the toll system

(i) The toll system is optional equipment and is not available in all vehicles.

Debiting of toll charges at freeway toll gates is facilitated with an electronic payment system.

The toll system uses RFID (Radio Frequency Identification) for data transfer between the control unit and the toll station.

The toll system is initially switched off at the factory.

The control unit is in the vehicle glove box.

In order to be able to use the toll system, it must have been registered by the customer and activated by the service provider:

- · Activate the toll system in the settings of the MBUX multimedia system or on the control unit.
- There are two ways to register and activate:
  - In the Mercedes me App, register the unit identification number of the control unit and activate the toll system.

Alternatively, you can register and activate via the Toll Service app.

Activation of the toll system can take up to 48 hours after registration.

When the toll system is activated, the automatic detection of the number of vehicle occupants is initially switched off at the factory. The number of vehicle occupants is preset with one person.

The following applies for roads on which toll charges are dependent on the number of vehicle occupants:

 If the automatic detection of the number of vehicle occupants is switched off, the number of vehicle occupants must be selected manually. This ensures correct toll accounting.

• The number of vehicle occupants can be

transmitted automatically. In the process, the number of seat belts worn is determined. If the number of detected persons does not correspond with the number of persons actually in the vehicle, the number of persons must be manually selected.

The standard setting of one person does not need to be changed for roads which require toll payment regardless of the number of vehicle occupants.

The toll system enables the payment of toll charges in many states of the USA.

(i) In Mexico, for example, the toll system can be registered and activated for journeys to the USA.

#### Notes on use

- · You can only use the toll system once registration and activation are complete.
- Drive at the prescribed vehicle speed in the toll lane.
- Mercedes-Benz recommends operation using the MBUX multimedia system. Alternatively. this can also be done on the control unit in the glove box.
- For safety reasons, entries should be made while the vehicle is stationary.
- For further information, please consult the Mercedes me App or an authorized Mercedes-Benz Center.

Or call 1-800-FOR-MERCedes (in the USA) or 1-800-387-0100 (in Canada).

For information on how to register and activate the toll system, see the Digital Operator's Manual.


# **Destination entry**

# Requirements:

- For the online search:
  - There is an Internet connection.
  - Mercedes me connect is available.
  - You have set up a user account in the Mercedes me Portal.
  - The vehicle is connected with the user account and you have accepted the terms of use.
  - Further information can be found at: https://www.mercedes.me
  - The service is available.
  - The service has been activated at an authorized Mercedes-Benz Center.

#### Multimedia system:





Example: entering a POI or address

- Input line with current entry
- Search result
- Selects destination input, displays further destination inputs with double arrow
- Oeletes an entry

- 6 Adopts the search result in the input line and continues the search
- O Deletes the last character entered
- Hides the keypad
- Switches to handwriting recognition
- Starts the MBUX voice assistant
- Sets the written language
- Switches to digits and special characters
- Switches to upper-case or lower-case letters
- ► Enter the destination in **(1)**. The entries can be made in any order.

  The search results are displayed in a list.
- Online search results for POIs may contain additional information, for example opening times and prices. The information is provided by an online map service.

  This online function is not available in all countries.
- You can enter a destination as a three-word address from what3words. This option is not available in all countries.
- Hide the keyboard with OK.

- Select the destination in the list. The route is calculated.
- (i) Observe the notes on the MBUX multimedia system ( $\rightarrow$  page 312).

# Calculating a route and using settings for route guidance



Detailed display with a route (example)

- Calls up alternative routes
- Adds an intermediate destination to the route and recalculates the route
- Sets intermediate destination as new destination and calculates new route

- Selects a point of interest in the vicinity of the destination
- 6 Address of the intermediate destination

After selection of a destination the route is be calculated.

Select one of the options.

## Calling up alternative routes

- Select Routes.
- Select an alternative route.

#### Starting route guidance (there is no route yet)

► Select Let's Go!.

#### Calling up the detailed display with destination address

Pull the bar between 2 and 3 upwards. Depending on the destination selection and availability, online content, for example ratings and weather information, is shown.

If the destination is in a different time zone, a message is displayed.

- To share a destination: select Share.
  This option allows you to scan the displayed OR code.
- To call up an Internet address: if a web address is available, select www.
- ► To call the destination: if a telephone number is available, select Call.

# Searching for POIs in the vicinity of the destination shown

- Select In The Vicinity.
- Search using categories, enter a search entry or search for a personal POI.

### Selecting a route type

- In the navigation module (expanded view), select  $\bigcirc$  ( $\rightarrow$  page 337).
- Select Route. The route is calculated as a fast route with a short journey time. Trailer mode is available if a trailer has been coupled with the vehicle. If available, you can select online routes. Traffic

- announcements for the route are taken into account via Reroute Based on Traffic \( \).
- (i) Trailer mode and online routes are not available in all countries and for all vehicles.

#### Calculating alternative routes

- In the navigation module (expanded view), select
- Select View.
- Activate Route Overview after Start.
   Alternative routes are calculated for every route.

# Selecting alternative routes

- i If Route Overview after Start has been switched on and a route has been calculated, the function is available.
- In the navigation module (expanded view), select Alternative Routes.
- When the alternative routes have been calculated, display the route in the navigation window by swiping to the right or left.
- Select Start.

## Activating a commuter route

- (i) A user profile has been created and Allow Destination Suggestions has been activated in the user options (→ page 322). Route guidance is not active.
- In the navigation module (expanded view), select 👸.
- Select Route.
- Activate Commuter Route.

  The navigation system automatically detects that the vehicle is on a commuter route.
  - For the daily commuter route, traffic incidents on the route are also reported when driving without active route guidance.
- To select or delete a commuter route: select Start or .

# Avoiding or using route sections, e.g. freeways or ferries

- In the navigation module (expanded view), select .
- Select Route.

- Select Avoid Options.
- Activate or deactivate the avoid option.

# Activating route guidance with augmented reality

- In the navigation module (expanded view), select 🔼.
- Select View
- Select Augmented Reality Video.
- Activate or deactivate Augmented Reality Video. The camera's video image is shown on the central display before a turning maneuver. The video image includes additional information.

# Showing property information for route guidance with augmented reality

Route guidance with augmented reality is activated.

- In the navigation module (expanded view), select 🔼 .
- Select View.
- Select Augmented Reality Video.

Activate Street Names and House Numbers. During route guidance, the activated options are shown as additional information in the camera image.

# Using map functions

Multimedia system:

**→** 🔝

# Increasing map scale

► When the map is shown, tap twice quickly with one finger on the central display.

or

Move two fingers apart on the central display.

#### Decreasing map scale

- Tap with two fingers on the central display.
- Move two fingers together on the central display.

### Moving the map

- When the map is displayed, swipe in any direction with one finger on the central display.
- To reset the map to the current vehicle posi-

### Selecting map orientation

Tap repeatedly on the occupass symbol on the map.

The map orientations changes in this order:

- The 2D map view is displayed so that north is always at the top.
- The 2D map view is aligned to the direction of travel.
- The 3D map view is aligned to the direction of travel.
- The map shows the complete route.

# Using services

#### Requirements

- There is an Internet connection.
- Mercedes me connect is available.

- You have set up a user account in the Mercedes me Portal.
- The vehicle is connected to a user account and you have accepted the conditions of use for the service.

Further information can be found at: https://www.mercedes.me

- · The service is available.
- The service has been activated at an authorized Mercedes-Benz Center.

#### Multimedia system:



#### Showing traffic information

- In the navigation module (expanded view), select  $\bigcirc$  ( $\rightarrow$  page 337).
- Select View.
- Activate Traffic.
- Activate Traffic Incidents and Free Flowing Traffic.

Traffic incidents, for example roadworks, local area reports (e.g. fog) and warning messages, are shown on the route.

The traffic delay is displayed for the current route. The smallest value for the display for traffic delays is a minute.

# Displaying hazard warnings

If hazard warnings are available these can be shown as symbols on the map. The display depends on the settings for the Traffic Incidents option.

- In the navigation module (expanded view), select (→ page 337).
- Activate or deactivate Traffic Incidents. If the option is activated, all of the symbols are shown.

If the option is deactivated, the symbols are only shown when there is a hazard warning.

The following hazards may be shown on the map:

- · Accidents and breakdowns
- Slippery roads, fog, crosswinds and heavy rain
- · Hazards reported manually
- Vehicle with active hazard warning light

- Roadworks
- Additional hazards (if available)

## Displaying online map contents

- In the navigation module (expanded view), select .
- Select View.
- Switch on an online service, e.g. Weather. Current weather information is displayed on the navigation map, e.g. temperature or cloud cover.

The service information is not shown in all map scales, e.g. weather symbols.

## Parking service

NOTE Vehicle damage due to failure to observe the maximum permissible clearance height

If the vehicle height exceeds the maximum permissible clearance height, the roof and other vehicle parts may be damaged.

- Please observe the maximum clearance height indicated.
- If the vehicle exceeds the permissible clearance height, do not drive in.
- Take the modified vehicle height into account in the case of roof superstructures or other carrier systems.
- NOTE Vehicle damage due to failure to observe local information and parking conditions

The data is based on the information provided by the respective service providers.

Mercedes-Benz does not guarantee the accuracy of the information provided in relation to the car park or parking area.

- Always observe the local information and conditions.
- This service is not available in all countries.
- In the navigation module (expanded view), select and switch on Parking.

Tap on **P** the map.

or

- In the route overview, select P Parking Spaces.
- Select the search position and search filter. e.g. Near Destination and Parking Garage. The map shows car parks suited to the selected settings.
- Select a parking option. The map shows the parking options in the vicinity.

The following information is displayed (if available):

- Destination address, distance from current vehicle position and arrival time
- Information on the parking garage/car park

For example, opening times, parking charges, current occupancy, maximum parking time, maximum access height.

The maximum access height shown by the parking service does not replace the need for observation of the actual circumstances.

- Available payment options (Mercedes pay. coins, bank notes, cards)
- Details on parking tariffs
- Number of available parking spaces
- Payment method (e.g. at parking meters)
- Services/facilities at the parking option
- Telephone number
- Calculate the route ( $\rightarrow$  page 341).

#### Notes on the dashcam

NOTE Risk of legal consequences due to violation of legal regulations and data protection provisions

You are legally responsible for operation and use of the dashcam functions.

The legal requirements relating to operation and use of the dashcam can vary depending

on the country in which the dashcam is operated.

This function is not permitted in all countries.

- Before using the dashcam, read up on the content of the legal regulations, in particular the data protection requirements in the respective country of use.
- Observe the legal regulations, in particular the data protection requirements.
- (i) Observe the following instructions for safe operation:
  - Only use FAT32 or exFAT formatted USB storage devices.
  - Use USB-IF certified USB storage devices.
     USB-IF is a non-profit corporation and stands for USB Implementers Forum.
     Based on the USB specification, USB-IF certifies, for example, USB versions, corresponding cables and plugs as well as energy supply processes via the USB interface.

- USB storage devices may be damaged if often or permanently overwritten at high speed. Mercedes-Benz recommends a high-quality external SSD drive.
  - The abbreviation SSD stands for Solid State Drive.
- (i) The file size and therefore the duration of single recording is limited by the limitations of the USB flash drive format. So FAT32 formatted USB flash drives do not allow files larger than 4 GB, for example.
  - When the file size is reached, the recording stops and you receive a notification.
- i The following functions are available in the Gallery app:
  - · Switching write protection on or off
  - · Deleting video files

# Selecting a USB device for a video recording with the dashcam

# Requirements:

 At least one USB device is connected with the multimedia system.

#### Multimedia system:

- → 🔝 **>>** Apps **>>** Dashcam
- Select the USB symbol.
- Select the USB device.
- (i) When USB devices contain multiple partitions, recorded video files are not always displayed in the recording list.

  Mercedes-Repz recommends that you use
  - Mercedes-Benz recommends that you use USB devices with one partition.

# Starting or stopping a loop recording with the dashcam

# Requirements:

- For recording and saving a video file: a USB device is connected with the multimedia system.
- · The vehicle is switched on.

#### Multimedia system:

# → 🔝 >> Apps >> Dashcam

If several USB devices are connected with the multimedia system, select a USB device  $(\rightarrow page 346)$ .

If no USB device is selected, a selection is made automatically when recording starts.

To select recording mode: select Loop Recording.

Loop Recording continuously records short video files. When the memory is full, recording is continued automatically. In doing so, the oldest video file is written over.

- To start: select Start Recording. The length of the recording is shown. The Do not remove the storage medium during recording. Before removing the storage medium, eject it first, message appears. The video file is stored on the USB device.
- To end: select End Recording.
- (i) In some countries, geo-coordinates (longitude and latitude) are shown in the video image. For technical reasons, the geo-coordinates may show greater inaccuracies.

A message may appear in the following cases:

 The camera is not functional, the Camera Unavailable message appears.

Have the camera checked in an authorized Mercedes-Benz Center.

- If the country border indication has been switched on.
- · If an outdoor recording is started with the camera app during a dashcam recording, the dashcam recording pauses and resumes automatically after the camera recording is finished. A notification to this effect is displayed.

## Starting or stopping an individual recording with the dashcam

#### Requirements:

- For recording and saving a video file: a USB device is connected with the multimedia system.
- · The vehicle is switched on.

#### Multimedia system:

- ► Apps ➤ Dashcam
- If several USB devices are connected with the multimedia system, select a USB device  $(\rightarrow page 346)$ . If no USB device is selected, a selection is

made automatically when recording starts.

- To select the recording mode: select Individual Recording. Individual Recording stops recording when the memory limit is reached. An individual recording is automatically protected against being overwritten.
- To start: select Start Recording. The length of the recording is shown. The Do not remove the storage medium during recording. Before removing the storage medium, eject it first, message appears. The video file is stored on the USB device.
- To end: select End Recording.
- (i) In some countries, geo-coordinates (longitude and latitude) are shown in the video image. For technical reasons, the geo-coordinates may show greater inaccuracies.

A report may appear in the following cases:

 Individual Recording: the memory is full or there are only a few minutes recording time available. The video recording stops or will be stopped imminently.

Change the USB device or delete a video file.

• The camera is not functional, the Camera Unavailable message appears.

Have the camera checked in an authorized Mercedes-Benz Center.

- If the country border indication has been switched on.
- If an outdoor recording is started with the camera app during a dashcam recording, the dashcam recording pauses and resumes automatically after the camera recording is finished. A notification to this effect is displayed.

#### Telephone

## Telephony

Notes on telephony



WARNING Risk of distraction from operating integrated communication equipment while the vehicle is in motion

If you operate communication equipment integrated in the vehicle when driving, you could be distracted from the traffic situation. This could also cause you to lose control of the vehicle.

- Only operate this equipment when the traffic situation permits.
- If you cannot be sure of this, stop the vehicle whilst paying attention to road and traffic conditions and operate the equipment with the vehicle stationary.

WARNING Risk of accident from operating mobile communication equipment while the vehicle is in motion.

Mobile communication devices distract the driver from the traffic situation. This can also cause the driver to lose control of the vehicle.

- As a driver, only operate mobile communication devices when the vehicle is stationary.
- As a vehicle occupant, use mobile communication devices only in the designated area, e.g. in the rear passenger compartment.

You must observe the legal requirements for the country in which you are currently driving when operating the multimedia system and mobile communication equipment in the vehicle.



**WARNING** Risk of injury due to objects being stowed incorrectly

If objects in the vehicle interior are stowed incorrectly, they can slide or be thrown around

and hit vehicle occupants. In addition, cup holders, open stowage spaces and mobile phone receptacles cannot always retain all objects within.

There is a risk of injury, particularly in the event of sudden braking or a sudden change in direction

- Always stow objects so that they cannot be thrown around in such situations.
- Always make sure that objects do not protrude from stowage spaces, parcel nets or stowage nets.
- Close the lockable stowage spaces before starting a journey.
- Always stow and secure heavy, hard. pointed, sharp-edged, fragile or bulky objects in the trunk/cargo compartment.

Observe the additional information on stowing mobile communications devices correctly:

 Loading the vehicle (→ page 113) Bluetooth® connection:

The menu view and the available functions in the telephone menu are in part dependent on the Bluetooth® profile of the connected mobile phone. If the mobile phone supports all the following Bluetooth® profiles, the full range of features is available.

- PBAP (Phone Book Access Profile)
  - The contacts on the mobile phone are shown automatically on the multimedia system.
- MAP (Message Access Profile)
  - The mobile phone message functions can be used on the multimedia system.
- HFP (hands-free profile)
  - Wireless telephony is available on the multimedia system.
- SAP (SIM Access Profile)
  - The car telephone has access to the SIM card data and dials into the mobile phone network via the exterior antenna.

Irrespective of this, Bluetooth® audio functionality can by used with any mobile radio unit.

For information on the range of functions of the mobile radio unit to be connected, see the manufacturer's operating instructions.

#### Network connection:

The following cases can lead to the call being disconnected while the vehicle is in motion:

- You switch into a transmission/reception station, in which no communication channel is free.
- The SIM card used is not compatible with the network available
- A mobile phone with "Twincard" is logged into the network with the second SIM card at the same time

The multimedia system supports calls in HD Voice® for improved speech quality. A requirement for this is that the mobile phone and the mobile phone network provider of the person you are calling support HD Voice®.

Depending on the quality of the connection, the voice quality may fluctuate.

Further information can be obtained from an authorized Mercedes-Benz Center or at: https://www.mercedes-benz.com/connect.

# ■ Telephone menu overview



- Bluetooth® device name of the currently connected mobile phone/of the mobile phone
- Bluetooth<sup>®</sup> device name of the currently connected mobile phone/of the mobile phone (two phone mode)
- 3 Signal strength of the mobile phone network
- Battery status of the connected mobile phone

- Options
- Messages
- Calls up devices
- Numerical pad
- Starts contact search

# Telephony operating modes overview

Depending on your equipment, the following telephony operating modes are available:

- A mobile phone is connected to the multimedia system via Bluetooth<sup>®</sup>.
- Two mobile phones are connected with the multimedia system via Bluetooth® (two phone mode).
  - You can use all the functions of the multimedia system with both mobile phones.

# Connecting a mobile phone

#### Requirements

- Bluetooth® is activated on the mobile phone (see the manufacturer's Operator's Manual).
- Bluetooth<sup>®</sup> is activated on the multimedia system.

Multimedia system:



### Searching for a mobile phone

Select Connect New Device.

### Connecting a mobile phone

- Select a mobile phone. A code is displayed in the multimedia system and on the mobile phone.
- If both codes match, confirm the code on the mobile phone.

# Functions in the telephony menu

In the telephony menu you have the following functions, for example:


- Making calls, e.g.:
  - Accepting a call
  - End Call
  - Answering a call with a message
  - Conference
  - Accepting or rejecting a waiting call

- · Managing contacts, e.g.:
  - Downloading mobile phone contacts
  - Managing the format of a contact's name
  - Deleting favorites
- · Receiving and sending messages, e.g.:
  - Using the read-aloud function
  - Dictating a new message

# Mercedes me Apps

#### Mercedes me calls

Making a call via the overhead control panel



- me button for service or information calls
- SOS button cover
- SOS button (emergency call system)

Making a Mercedes me call

Press me button ①.

#### Making an emergency call

- To open the cover of SOS button ②, press it briefly.
- Press and hold SOS button (3) for at least one second.

If a Mercedes me call is active, an emergency call can still be triggered. This has priority over all other active calls.

# Information about the Mercedes me call using the me button

A call to the Mercedes-Benz Customer Center has been initiated via the me button in the overhead control panel or the multimedia system ( $\rightarrow$  page 351).

Using the voice dialog system you access the desired service:

- · Accident and Breakdown Management
- Mercedes-Benz Customer Center for general information about the vehicle

You can find information on the following topics:

- Activation of Mercedes me connect.
- · Operating the vehicle
- Nearest authorized Mercedes-Benz Center
- Other products and services from Mercedes-Benz

Data is transferred during the connection to the Mercedes-Benz Customer Center ( $\rightarrow$  page 354).

Calling the Mercedes-Benz Customer Center using the multimedia system

## Requirements

- Access to a GSM network is available.
- The contract partner's GSM network coverage is available in the respective region.
- The vehicle must be switched on so that vehicle data can be transferred automatically.

Multimedia system:

→ 🔝 >> Phone >> 👪

Call Mercedes me connect. After confirmation, the multimedia system sends the required vehicle data. The data transfer is shown in the display.

Then you can select a service and be connected to a specialist at the Mercedes-Benz Customer Center.

■ Calling the Mercedes-Benz Customer Center after automatic accident or breakdown detection

## Requirements:

- The vehicle has detected an accident or breakdown situation (→ page 223).
- The vehicle is stationary.
- · The hazard warning lights are switched on.
- i This function is not available in all countries.

The vehicle can detect accident or breakdown situations under certain circumstances.

Requirements for collision detection in the context of accident recovery:

- The vehicle is equipped with an anti-theft alarm system (ATA) (code 551).
- The vehicle is equipped with the interior protection (code 882).
- The vehicle is equipped with the Anti-Theft Protection Package (code P54).
- The collision detection service with theft notification has been activated on Mercedes me connect.

If a collision is detected when the tow-away protection is armed on a locked vehicle, you will receive a notification in the multimedia system when you switch the vehicle on.

The message informs you about the potentially affected area of the vehicle and the strength of the collision.

In the event an accident or breakdown is detected, the emergency guide shows safety notes in the multimedia system display. This may take a few seconds.

(i) The availability of collision detection depends on the vehicle

After quitting the emergency guide display on the multimedia system, a prompt appears asking whether you would like to get support from the Mercedes-Benz Customer Center.

- Select Call
  - After your agreement, or if the Mercedes me connect service "Accident and Breakdown Management" is active, the vehicle data is transferred automatically  $(\rightarrow page 355)$ .
  - The Mercedes-Benz Customer Center takes your call and organizes the breakdown and accident assistance

You may be charged for these services.

- Depending on the severity of the accident, an automatic emergency call can be initiated. This has priority over all other active calls  $(\rightarrow page 360)$ .
- (i) In addition, if the Mercedes me connect service "Telediagnostics" is active, a similar prompt can appear after a delay in the event

- of a breakdown. If you are already in contact with the Mercedes-Benz Customer Center or have already received support, this prompt can be ignored or declined.
- (i) If you answer the prompt for support from the Mercedes-Benz Customer Center with Call Later, the message will be hidden and appear again later.
  - The prompt triggered by the Mercedes me connect service "Telediagnostics", can either be confirmed or declined. After being declined, this will not be shown again.

# Arranging a service appointment via a Mercedes me call

If you have activated the maintenance management service, relevant vehicle data is transferred automatically to the Mercedes-Benz Customer Center You will then receive individual recommendations regarding the maintenance of your vehicle.

Regardless of whether you have consented to the maintenance management service, the multimedia system reminds you after a certain amount of

time that a service is due. A prompt appears asking if you would like to make an appointment.

To arrange a service appointment: select Call.

After your consent, the vehicle data is transferred and the Mercedes-Benz Customer Center takes your preferred appointment date.

The information is then sent to your desired service outlet.

This will contact you to confirm the appointment and if necessary consult about the details.

i If you select Call Later after the service message appears, the message is hidden and reappears at a later time.

## ■ Data transferred during a Mercedes me call

If you initiate a service call using Mercedes me, data is transferred to enable targeted advice and an efficient service.

The following requirements must be fulfilled for the transfer of the data:

- · The vehicle is switched on.
- The required data transfer technology is supported by the mobile phone network provider.

The quality of the mobile connection is sufficient

Multi-stage transfer depends on the following factors:

- · Reason for the initiation of the call
- The available mobile phone transmission technology
- The activated Mercedes me connect services
- The service selected in the voice control system
- (i) The scope of the data transmitted depends on the vehicle model and vehicle equipment. For technical reasons, not all data is available at all times.

# Data transfer if Mercedes me connect services are not activated

If no Mercedes me connect services are activated, the following data is transferred:

- · Vehicle identification number
- · Time of the call
- · Reason for the initiation of the call

- · Confirmation of the data protection prompt
- Country indicator of the vehicle
- · Set language for the multimedia system
- Telephone number of the communication platform installed in the vehicle

If a call is made for a service appointment via the service reminder, the following data is also transmitted:

· Current mileage and maintenance data

If a call is made after automatic accident or breakdown detection using the multimedia system, the following data is also transmitted:

- · Current mileage and maintenance data
- · Current vehicle location

If Accident and Breakdown Management is called via the voice control system, the following data can also be called up from the vehicle by the Mercedes-Benz Customer Center:

· Current vehicle location

## Data processing

The data transmitted within the scope of the call is deleted from the processing system after the call is finished, in so far as this data is not being used for other activated Mercedes me connect services

The incident-specific data is processed and stored in the Mercedes-Benz Customer Center and, if required to process the incident, forwarded to the service partner authorized by the Mercedes-Benz Customer Center. Take note of the data protection information on the Mercedes me Internet page https://www.mercedes.me or in the recorded message immediately after calling the Mercedes-Benz Customer Center

(i) The recorded message is not available in every country.

#### Mercedes me connect

Information on Mercedes me connect

Mercedes me connect consists of multiple services.

You can use the following services via the multimedia system and the overhead control panel, for example:

- Accident and Breakdown Management (me button or situation-dependent display in the multimedia system)
- Mercedes-Benz Emergency Call System (automatic emergency call and SOS button)

The Mercedes me connect Accident and Breakdown Management and the Mercedes-Benz emergency call center are available to you around the clock.

The me button and the SOS button can be found on the vehicle's overhead control panel  $(\rightarrow page 351)$ .

You can also call the Mercedes-Benz Customer Center using the multimedia system  $(\rightarrow page 352)$ .

Please note that Mercedes me connect is a Mercedes-Benz service. In emergencies, first call the national emergency services using the standard national emergency service telephone numbers. In emergencies, you can also use the

Mercedes-Benz emergency call system  $(\rightarrow page 359)$ .

Please note the Mercedes me connect terms of use and the data protection information for Mercedes me connect. You can find these in your Mercedes me user account.

Further information about Mercedes me connect services can be obtained in the Mercedes me Portal: https://me.secure.mercedes-benz.com

# Information on Mercedes me connect Accident and Breakdown Management

(i) Accident and Breakdown Management is not available in every country. Contact an authorized Mercedes-Benz Center to find out whether this function is available in your country.

The Accident and Breakdown Management can include the following functions:

• Supplement to the Mercedes-Benz emergency call system ( $\rightarrow$  page 359)

If necessary, the contact person at the Mercedes-Benz emergency call center forwards the call to Mercedes me connect Accident and Breakdown Management. Forwarding the call is however not possible in all countries.

 Breakdown assistance by a technician on location and/or the towing away of the vehicle to the nearest authorized Mercedes-Benz Center

You may be charged for these services.

Addition to the emergency guide after automatic accident or breakdown detection
 (→ page 352)

In the event of a breakdown or accident, further vehicle data is sent which enables optimal support by the Mercedes-Benz Customer Center and the authorized service partner or breakdown assistance.

• Addition to the Mercedes me connect service Telediagnostics

With the Telediagnostics function, specific wear and failure reports are recorded by the service provider, in so far as these can be clearly interpreted and are available through the monitoring of components that are subject to diagnostics.

If your vehicle detects a breakdown or threat of a breakdown, you may be prompted via the multimedia system to contact the Mercedes-Benz Customer Center for further help. This prompt in the multimedia system only appears when the vehicle is stationary.

i These services are subject to technical restrictions such as the mobile phone coverage, mobile network quality and the ability of the processing systems to interpret the transferred data. In some circumstances, this can result in delays or the failure of the information to appear in the multimedia system.

Please note that the service and breakdown call is a Mercedes-Benz service. In emergencies, be sure to contact the usual national emergency number first or use the Mercedes-Benz emergency call system ( $\rightarrow$  page 359).

More information about Mercedes me connect services can be obtained in the Mercedes me Portal: https://me.secure.mercedes-benz.com

## Data transferred during Mercedes me connect call services

The data transferred during a Mercedes me connect call depends on:

- . The reason for initiation of the call
- The service that is selected in the voice control system
- The activated Mercedes me connect services

You can find out which data is transferred when using the services in the currently valid Mercedes me connect terms of use and the data protection information for Mercedes me connect. You can find these in your Mercedes me user account.

# Overview of the Mercedes me & Apps menu

When you log in with a user account to the Mercedes me Portal, then services and offers from Mercedes-Benz will be available to you.

For more information consult an authorized Mercedes-Benz Center or visit the Mercedes me Portal: https://me.secure.mercedes-benz.com

(i) Make sure you always keep the Mercedes me Apps updated.

You can call up the menu using Apps in the multimedia system.

In the Apps menu, the following options can be available:

- Connecting the vehicle with the Mercedes me user account
- Deleting a connection between a user account Mercedes me and the vehicle
- · Calling up the Mercedes me services
- Calling up apps such as In-Car Office or the web browser depending on availability

#### Web browser overview



- Previous website
- Next website
- Update
- URI
- Adds/removes bookmarks
- Options
- Settings

- i) Under vou have the following options:
  - Tabs
  - Bookmarks & History
  - Reading Mode
  - Share Link
  - Share Content
  - Request Mobile Website
- (i) Websites cannot be shown while the vehicle is in motion.

# Overview of Smartphone Integration

With Smartphone Integration, you can use certain functions on your mobile phone via the multimedia system display.

Only one mobile phone at a time can be connected via Smartphone Integration to the multimedia system. Also for use with two phone mode with Smartphone Integration, only one additional mobile phone can be connected using Bluetooth® with the multimedia system.

The full range of functions for Smartphone Integration is only possible with an internet connec-

tion. The appropriate application must be downloaded on the mobile phone to use Smartphone Integration. The mobile phone must be switched on and connected to the multimedia system via the USB port using a suitable cable.

Apps for Smartphone Integration:

- Apple CarPlay<sup>®</sup> (wireless connection via Bluetooth<sup>®</sup> also possible)
- Android Auto (wireless connection via Bluetooth® also possible)
- (i) For safety reasons, the first activation of Apple CarPlay® or Android Auto on the multimedia system must be carried out when the vehicle is stationary with the parking brake.

You can start Smartphone Integration using the Devices menu.

You can end Smartphone Integration via the Devices or by disconnecting the connecting cable between the mobile phone and multimedia system.

(i) Mercedes-Benz recommends disconnecting the connection via the device manager or the

connecting cable only when the vehicle is stationary.

#### Overview of transferred vehicle data

When using Smartphone Integration, certain vehicle data is transferred to the mobile phone. This enables you to get the best out of selected mobile phone services. Vehicle data is not directly accessible.

The following system information is transmitted:

- Software release of the multimedia system
- System ID (anonymized)

The transfer of this data is used to optimize communication between the vehicle and the mobile phone.

To do this, and to assign several vehicles to the mobile phone, a vehicle identifier is randomly generated.

This has no connection to the vehicle identification number (VIN) and is deleted when the multimedia system is reset ( $\rightarrow$  page 328).

The following driving status data is transmitted:

· Transmission position engaged

- Distinction between parked, standstill, rolling and driving
- Day/night mode of the driver's display
- Drive type

The transfer of this data is used to alter how content is displayed to correspond to the driving situation.

The following position data is transmitted:

- Coordinates
- speed
- Compass direction
- · Acceleration direction

The mobile phone uses this data to improve the accuracy of navigation, for example, when driving through a tunnel.

### Mercedes-Benz emergency call system

# Information on the Mercedes-Benz emergency call system

Your vehicle is equipped with the Mercedes-Benz emergency call system ("eCall"). This feature can help save lives in the event of an accident, eCall in no way replaces assistance provided from dialing 911.

Mercedes-Benz eCall only functions in areas where mobile phone coverage is available from the wireless service providers. Insufficient network coverage from the wireless service providers may result in an emergency call not being transmitted.

eCall is a standard feature in your Mercedes-Benz vehicle. In order to function as intended, the system relies on the transmission of data detailed in the Transmitted Data section that follows.

To disable eCall, a customer must visit an authorized Mercedes-Benz Service department to deactivate the vehicle's communication module.

Deactivation of this module prevents the activation of any and all Mercedes me connect serv-

ices. After the deactivation of eCall, automatic emergency call and manual emergency call will not be available

The vehicle must be switched on before an automatic emergency call can be made.

- (i) eCall is activated at the factory.
- (i) eCall can be deactivated by an authorized Mercedes-Benz dealer. Please note that in the event ownership of the vehicle is transferred to another owner in its deactivated state. eCall will remain deactivated unless the new owner visits an authorized Mercedes-Benz dealership to reactivate the system.

# Overview of the Mercedes-Benz emergency call system

eCall can help to reduce the time between an accident and the arrival of emergency services at the site of the accident. It helps locate an accident site in places that are difficult to access. However, even if a vehicle is equipped with eCall, this does not mean the system is ON. As such, eCall does not replace dialing 911 in the event of an accident.

An emergency call can be made automatically or manually.

Only make emergency calls if you or others are in need of rescue. Do not make an emergency call in the event of a breakdown or a similar situation

## Messages on the display

SOS NOT READY: the vehicle is not on or eCall not available

During an active emergency call, (Sos) appears in the display.

You can find more information on the regional availability of eCall at: https://www.mercedesbenz-mobile.com/extra/ecall/

(i) If there is a malfunction of the emergency call system, the loudspeakers, microphone, air bag or the SOS button, for example, are faulty.

You can recognize a malfunction in the emergency call system by the following displays:

- A corresponding message will also appear in the driver's display.
- The SOS button lights up red continuously.

# Triggering an automatic Mercedes-Benz emergency call

### Requirements:

- The vehicle is switched on.
- The starter battery is sufficiently charged.

The Mercedes-Benz emergency call system triggers an emergency call automatically in the following cases:

- After activation of the restraint systems such as air bags or Emergency Tensioning Devices after an accident
- After an automatically initiated emergency stop by Active Emergency Stop Assist

The emergency call has been made:

- A voice connection is made to the Mercedes-Benz emergency call center.
- A message with accident data is transmitted to the Mercedes-Benz emergency call center.
   The Mercedes-Benz emergency call center can transmit the vehicle position data to one of the emergency call centers.

The SOS button in the overhead control panel flashes until the emergency call is finished.

It is not possible to immediately end an automatic emergency call.

If no connection can be made to the emergency services either, a corresponding message appears in the media display.

Dial the local emergency number on your mobile phone.

If an emergency call has been initiated:

- Remain in the vehicle if the road and traffic conditions permit you to do so until a voice connection is established with the emergency call center operator.
- Based on the call, the operator decides whether it is necessary to call rescue teams and/or the police to the accident site.
- If no vehicle occupant answers, an ambulance is sent to the vehicle immediately.

# Triggering a manual Mercedes-Benz emergency call

To use the SOS button in the overhead control panel: press the SOS button at least one second long (→ page 351).

or

To use voice control: use the voice commands of the MBUX Voice Assistant.

The emergency call has been made:

- A voice connection is made to the Mercedes-Benz emergency call center.
- A message with accident data is transmitted to the Mercedes-Benz emergency call center.

The Mercedes-Benz emergency call center can transmit the vehicle position data to one of the emergency call centers.

 Remain in the vehicle if the road and traffic conditions permit you to do so until a voice connection is established with the emergency call center operator. • Based on the call, the operator decides whether it is necessary to call rescue teams and/or the police to the accident site.

If no connection can be made to the emergency services, a corresponding message appears in the central display.

Dial the local emergency number on your mobile phone.

# Ending an unintentionally triggered manual Mercedes-Benz emergency call

Select on the multifunction steering wheel. Depress button for several seconds.

# Data transfer of the Mercedes-Benz emergency call system

In the event of an automatic or manual emergency call the following data is transmitted, for example:

- Vehicle's GPS position data
- GPS position data on the route (a few hundred meters () before the incident)
- · Direction of travel

- Vehicle identification number
- Vehicle drive type
- Number of people detected in the vehicle
- Whether Mercedes me connect is available or not
- · Whether the emergency call was initiated manually or automatically
- · Time of the accident
- Language setting on the multimedia system

Data transmitted is vehicle information. For any questions about the collection, use and sharing of the eCall system data, please contact MBUSA's Customer Assistance Center at 800-FOR-MERC

For Canada, please contact MBC's Customer Assistance Center at 1-800-387-0100.

Customer requests for covered information should be submitted via the same channels.

For accident clarification purposes, the following measures can be taken up to an hour after the emergency call has been initiated:

· The current vehicle position can be determined.

• A voice connection to the vehicle occupants can be established

# 362 MBUX multimedia system

# Radio & media

# Overview of the symbols and functions in the media menu

Symbol	Designation	Function
•	Play	Select to start or continue playback.
•	Rest	Select to pause the playback.
	Repeat a track	Select to repeat the current track or the active playlist.  Select once: the active playlist is repeated.  Select twice: the current track is repeated.  Select three times: the function is deactivated.
×	Random playback	Select to play back the tracks in random order.
[]	Skip forwards/back	Select to skip to the next or to the previous track.
•••	Additional options	Select to show additional options.
<b>I</b>	Categories	Select to show and search through available categories such as playback lists, albums or artists.
	Search	Select to search in the active menu. You can search for artists, genres or moods, for example.

The following functions and settings are available in the Media menu:

- Connecting external data storage media with the multimedia system (e.g. using USB or Bluetooth®)
- Playing back audio or video files

# **364** MBUX multimedia system

# Overview of the symbols and functions in the radio menu

Symbol	Designation	Function
	Home	Select to return to the home screen.
<b>(3)</b>	Messaging	Select to call up messaging.
M/M	Skip forwards/back	Select to skip to the next or to the previous station.
0	Settings	Select to have further options shown. The setting options are country-dependent.
HD	HD radio™	Select to switch the HD Radio™ function on or off.  This function is not available in all countries.
E   I	Station list	Select to have the station list shown.
P	Search	Select to search in the active menu. You can search for artists, genres or moods, for example.

# Additional functions of TuneIn Radio

(i) A relatively large volume of data can be transmitted when using TuneIn Radio.

Symbol	Designation	Function
٥	Settings	The following additional settings are available in the TuneIn Radio menu:  • Selecting stream  • Logging on to or out of the TuneIn account
*	Favorites	Select during playback to save the station currently set as a favorite.
0/0	Play/Pause	Select to start, stop or continue playback.
画	Browse	Select to choose a category and then a radio station.

### Additional functions of the satellite radio

SIRIUS XM® satellite radio offers more than 175 digital-quality radio channels providing commercial-free music, sports, news and entertainment, for example. SIRIUS XM® satellite radio employs a fleet of high-performance satellites to broadcast

around the clock throughout the USA and Canada. The satellite radio program is available for a monthly fee. Information about this can be obtained from a Sirius XM® Service Center and at https://www.siriusxm.com (USA).

(i) Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. and its subsidiaries. All other marks, channel names

and logos are the property of their respective owners. All rights reserved.

### 366 MBUX multimedia system

Symbol	Designation	Function
•	Settings	The following additional settings are available in the satellite radio menu:  Activate child safety lock to lock channels with adult content  Set alarm program for music and sport alerts  Create TuneMix lists to listen to music seamlessly
0	Play	Select to start or continue playback.
•	Rest	Select to pause the playback.

Depending on the frequency band selected, different functions are available to you.

Select the desired frequency band in the radio menu head runner.

## Calling up TuneIn Radio

### Requirements:

 There is a user account at https:// www.mercedes.me.

- The vehicle is linked to the Mercedes me user account.
- The TuneIn Radio service is activated in the Mercedes me portal.
- The data volume is available.
   Depending on the country, data volume may need to be purchased.
- A fast Internet connection for data transmission free of interference.

- (i) New data volume can be purchased **directly from a mobile phone network provider** via the Mercedes me Portal.
- (i) The functions and services are countrydependent. For more information, consult an authorized Mercedes-Benz Center.

### Multimedia system:

- ¬→ 🔝 >> Radio
- Select TuneIn Radio.

The TuneIn menu appears. The last station set starts playing.

(i) The connection quality depends on the local mobile phone reception.

# Setting up satellite radio

### Requirements:

- Satellite radio equipment is available.
- · Registration with a satellite radio provider has been completed.
- If registration is not included when purchasing the system, your credit card details will be required to activate your account.

### Multimedia system:



Select Service Information.

The service information screen appears showing the radio ID and the current subscription status.

- Establish a telephone connection.
- Follow the service staff's instructions. The activation process may take up to ten minutes.
- You can also have the satellite service activated online. To do so, please visit https:// www.siriusxm.com (USA) or https:// www.siriusxm.ca (Canada).

### Music and sport alerts

Multimedia system:



# Setting music and sport alerts

This function enables you to program an alert for your favorite artists, tracks or sporting events. Music alerts can be saved whilst a track is being played and sport alerts can be saved during a live game. You can also specify sport alerts via the menu option. The system then continuously searches through all the channels.

Set a music or sports alert, to be informed of matches in the live program.

# Activating messages for a category

Select a category and activate \_\_\_\_\_.

# Adding messages for a category

Select a category and add a message +

### 368 MBUX multimedia system

Select Artist Alerts or Song Alerts in the dialog window.

The message is set for the activated ✓ track and artist. If a match is found, a prompt appears asking whether you wish to change to the station.

# Deleting messages in a category

Select a category, mark the desired messages and delete ...

or

Do not mark any messages and delete all entries .

# Sound settings

# Overview of functions in the sound menu

The setting options and functions available depend on the sound system installed. You can find out which sound system is installed in your vehicle in the Digital Operator's Manual.

### Standard sound system

The following functions are available:

- Equalizer
  - Treble, mid-range and bass
- · Balance and fader
- Volume
  - Automatic adjustment

### ASSYST PLUS service interval display

# Function of the ASSYST PLUS service interval display

The ASSYST PLUS service interval display on the driver's display provides information on the remaining time or distance before the next service due date

You can hide this service display using the back button on the steering wheel.

Depending on how the vehicle is used, the ASSYST PLUS service interval display may shorten the service interval, e.g. in the following cases:

- Mainly short-distance driving
- When the engine is often left idling for long periods
- In the event of frequent cold start phases

Mercedes-Benz recommends avoiding such operating conditions.

You can obtain information concerning the servicing of your vehicle from a qualified specialist workshop, e.g. an authorized Mercedes-Benz Center.

## Displaying the service due date

Driver display:



The next service due date is displayed.

To exit the display: press the back button on the steering wheel.

Bear in mind the following related topic:

• Operating the driver display ( $\rightarrow$  page 305).

# Information on regular maintenance work

**NOTE** Premature wear through failure to observe service due dates

Maintenance work which is not carried out at the right time or incompletely can lead to increased wear and damage to the vehicle.

- Adhere to the prescribed service intervals.
- Always have the prescribed maintenance work carried out at a qualified specialist workshop.

### Notes on special service requirements

The prescribed service interval is based on normal operation of the vehicle. Have the maintenance work carried out more often than prescribed if operating conditions are difficult or the vehicle is subject to increased stress.

The ASSYST PLUS service interval display is only an aid. It is the responsibility of the driver of the vehicle to have maintenance work carried out more often than prescribed due to actual operating conditions and/or stresses.

Examples of arduous operating conditions:

- · Regular city driving with frequent intermediate stops
- Mainly short-distance driving
- · Frequent operation in mountainous terrain or on poor road surfaces
- · When the engine is often left idling for long periods
- · Operation in particularly dusty conditions and/or if air-recirculation mode is frequently used

In these or similar operating conditions, have the interior air filter, air filter, engine oil and oil filter, for example, changed more frequently. If subject to increased stress, check the tires more. Further information can be obtained at a qualified specialist workshop.

## **Battery disconnection periods**

The ASSYST PLUS service interval display can calculate the service due date only when the battery is connected.

Display and note down the service due date on the driver's display before disconnecting the battery (→ page 369).

# Maintenance Management

## Notes about Maintenance Management

If the Maintenance Management service is activated, relevant data is automatically transferred to the Mercedes-Benz customer center.

The customer center transmits the data to the service partner that you have entered on the

Mercedes me website at: http:// www.mercedes.me. You will then receive individual recommendations regarding the maintenance of your vehicle.

- (i) The calculation of the optimal transmission time of the maintenance request to the service partner is subject to technical limitations that may cause the maintenance recommendation to be perceived as too early or too late or not to be made at all. In this case, you can conveniently arrange a maintenance appointment with the customer center via the maintenance reminder in the multimedia system.
- Maintenance Management and the maintenance reminder in the multimedia system are not available in every country. Contact an authorized Mercedes-Benz Center to find out whether this function is available in your country.

# Data transferred when using Maintenance Management

When the service is activated, relevant data is automatically transferred to determine the required scope of maintenance as well as malfunction detection and malfunction rectification.

Details on data transfer can be found in the data protection information for the Mercedes me connect services. These can be found at: https://www.mercedes.me under "My Mercedes me account", "Terms of use".

 Maintenance Management and the maintenance reminder in the multimedia system are not available in every country.

# Telediagnosis

# Notes about Telediagnosis

i) This service is not available in all countries.

The vehicle can detect if certain wear parts need to be replaced or if malfunctions have occurred in vehicle systems. If the Telediagnosis service is activated, relevant data is automatically transmit-

ted to the manufacturer. If fault conditions are detected by the vehicle system self-diagnosis, the system transmits recommendations for action to the Mercedes-Benz customer center depending on the fault detected. The customer center transmits the data to the service partner that you have entered on the Mercedes me website at: http://www.mercedes.me.

For selected faults, the notification that a malfunction has been detected may appear in the multimedia system with a request to contact the Mercedes-Benz customer center. From this message, a call can be made directly to the customer center for assistance.

- (i) The transmission of a notification to the multimedia system depends on the country, vehicle model and equipment and requires a fast data connection, over which the service provider has no influence.
- (i) Reliable fault detection is subject to technical limitations. Therefore, only a limited selection of faults can be detected and recommendations for action transmitted to the customer center and the service partners. Mercedes-Benz AG is continuously working on the

expansion of this service. The fault detection depends on the country, vehicle model and equipment.

# Data transferred when using Telediagnostics

When the service is activated, relevant data is automatically transferred to determine the required scope of maintenance as well as malfunction detection and malfunction rectification.

Details on data transfer can be found in the data protection information for the Mercedes me connect services. These can be found at: https://www.mercedes.me under "My Mercedes me account", "Terms of use".

(i) The scope of the transmitted data depends on the vehicle model and its equipment. For technical reasons, not all data is available at all times.

### **Engine compartment**

## Opening and closing the hood

A

**DANGER** Risk of fatal injuries when carrying out maintenance work during the charging process

During the charging process, the high-voltage on-board electrical system is under high voltage.

Do not perform any maintenance work during the charging process.

A

**WARNING** Risk of accident due to driving with the hood unlocked

The hood may open and block your view.

- Never release the hood when driving.
- Before every trip, ensure that the hood is locked.

**WARNING** Risk of accident and injury when opening and closing the hood

The hood may suddenly drop into the end position.

There is a risk of injury for anyone in the hood's range of movement.

 Do not open or close the hood if there is a person in the hood's range of movement.

▲ WARNING Risk of burns when opening the hood

If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:

- You may come into contact with hot gases.
- You may come into contact with other escaping hot operating fluids.
- Before opening the hood, allow the engine to cool down.

In the event of a fire in the engine compartment, keep the hood closed and call the fire service.

WARNING Risk of injury due to moving parts

Components in the engine compartment may continue to run or start unexpectedly even when the drive system is switched off.

Observe the following if you must open the hood:

- Switch off the vehicle.
- Never touch the danger zones surrounding moving components, e.g. the rotation area of the fan.
- Remove jewelery and watches.
- Keep items of clothing and hair away from moving parts.

**WARNING** Risk of injury from touching live components

The ignition system and the fuel injection system operate with a high voltage. You could receive an electric shock.

Never touch components of the ignition system or fuel injection system when the vehicle is switched on.

The live components include the following, for example:

- · Ignition coils
- · Fuel injectors
- Electric lines to the ignition coils and the fuel injectors

**WARNING** Risk of burns from hot component parts in the engine compartment


Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

- ► Allow the engine to cool down and only touch component parts described in the following.
- WARNING Risk of injury from using the windshield wipers when the hood is open


If the windshield wipers start moving when the hood is open, you could be trapped by the wiper linkage.

Always switch off the windshield wipers and the vehicle first if you need to open the hood.

# Opening the hood



To release the hood, pull on handle 1.



Push handle 2 of the hood catch upwards and lift the hood until it opens automatically.

# Closing the hood

NOTE Damage to the hood due to pressing the hood closed with your hand

If the hood is closed manually, there is a risk of dents.

- ▶ Do not close the hood manually.
- Lower the hood to a height of around 12 in (30 cm) and then allow it to fall, applying a little force as you let it go.
- If the hood can still be lifted slightly, open the hood again and close it with a little more force until it engages correctly.

# Engine oil

Checking the engine oil level using the driver's display

### Requirements

- · The engine has been warmed up.
- The vehicle is parked on a level surface.
- The engine is running at idle speed.
- · The hood is closed.

Determining the engine oil level can take up to 30 minutes with a normal driving style and even longer with an active driving style.

Driver's display:

### ¬→ Service

The engine oil level is shown.

One of the following messages will appear on the driver's display:

- Engine Oil Level Measuring Now...: the engine oil level cannot be determined yet.
- Repeat the request after a maximum of 30 minutes' driving.
- Engine Oil Level OK and the bar display for indicating the engine oil level on the driver's display is green and is between "min" and "max": the engine oil level is correct.
- Engine Oil Level Refill 1,0 liq.gal. and the bar display for indicating the engine oil level on the driver's display is yellow and is below "min":
- Add 1.1 US qt (1 I) of engine oil.
- Engine Oil Level Reduce and the bar display for indicating the engine oil level on the driver's display is yellow and is above "max":

- Drain off any excess engine oil that has been added. To do so, consult a qualified specialist workshop.
- For Engine Oil Level Switch on Vehicle
- Switch on the vehicle to check the engine oil level.
- Engine Oil Level System Inoperative: The oil level sensor is defective or not connected.
- Consult a qualified specialist workshop.
- Engine Oil Level System Currently Unavailable
- Close the hood.
- Topping up engine oil

**WARNING** Risk of burns from hot component parts in the engine compartment

Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

- Allow the engine to cool down and only touch component parts described in the following.
- **WARNING** Risk of fire and injury from engine oil


If engine oil comes into contact with hot component parts in the engine compartment, it may ignite.

- Make sure that no engine oil is spilled next to the filler opening.
- Allow the engine to cool off and thoroughly clean the engine oil from component parts before starting the vehicle.
- NOTE Engine damage caused by an incorrect oil filter, incorrect oil or additives
- Do not use engine oils or oil filters which do not correspond to the specifications explicitly prescribed for the service intervals.
- Follow the instructions on the service interval display for changing the engine

- oil and observe the prescribed change intervals
- Do not use additives.
- ! NOTE Damage caused by adding too much engine oil

Excessive engine oil can damage the engine or the catalytic converter.

- Have excess engine oil removed in a qualified specialist workshop.
- Depending on driving style, the vehicle consumes up to 0.9 US qt (0.8 liters) of oil per 600 miles (1,000 km). The oil consumption may also be higher than this when the vehicle is new or if you frequently drive at high engine speeds.



- Turn cap ① counter-clockwise and remove it.
- Add engine oil.
- Replace cap ① and turn it clockwise until it engages.
- ► Check the oil level again ( $\rightarrow$  page 374).

### Checking the coolant level

**WARNING** Risk of burns from hot component parts in the engine compartment

Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

- Allow the engine to cool down and only touch component parts described in the following.
- ▲ WARNING Risk of scalding from hot coolant

If you open the cap, you could scald yourself.

- Allow the engine to cool down before opening the cap.
- When opening the cap, wear protective gloves and safety glasses.
- Open the cap slowly to release pressure.
- Have the coolant checked or refilled only at a qualified specialist workshop.

# Refilling the windshield washer system

**WARNING** Risk of injury due to moving parts

Components in the engine compartment may continue to run or start unexpectedly even when the drive system is switched off.

Observe the following if you must open the hood:

- Switch off the vehicle.
- Never touch the danger zones surrounding moving components, e.g. the rotation area of the fan.
- Remove jewelery and watches.
- Keep items of clothing and hair away from moving parts.

**WARNING** Risk of burns from hot component parts in the engine compartment


Certain component parts in the engine compartment can be very hot, e.g. the engine, the cooler and parts of the exhaust system.

Allow the engine to cool down and only touch component parts described in the following.

**WARNING** - Risk of fire and injury from windshield washer concentrate

Windshield washer concentrate is highly flammable. It could ignite if it comes into contact with hot engine component parts or the exhaust system.

Make sure that no windshield washer concentrate spills out next to the filler opening.



- Open cap 1 by the tab.
- Add washer fluid.
- (i) Further information about the windshield washer fluid ( $\rightarrow$  page 455).

# Keeping the air/water duct free

Keep the area between the hood and the windshield free of deposits, e.g. ice, snow or leaves.

# Cleaning and care

Information on washing the vehicle in a car wash

WARNING Risk of accident due to reduced braking effect after washing the vehicle

The braking effect is reduced after washing the vehicle.

After the vehicle has been washed, brake carefully while paying attention to the traffic conditions until the braking effect has been fully restored.

**NOTE** Damage from automatic braking

If one of the following functions is activated, the vehicle will brake automatically in certain situations:

- Active Brake Assist
- Active Distance Assist DISTRONIC
- HOLD function
- · Active Parking Assist

To avoid damage to the vehicle, switch off these systems, e.g. when towing or using a car wash.

- NOTE Damage due to unsuitable car wash
- Before driving into a car wash make sure that the car wash is suitable for the vehicle dimensions.
- Ensure there is sufficient ground clearance between the underbody and the guide rails of the car wash.

Ensure that the clearance width of the car wash, in particular the width of the guide rails, is sufficient.

To avoid damage to your vehicle when using a car wash, ensure the following beforehand:

- Active Distance Assist DISTRONIC is deactivated.
- The HOLD function is switched off.
- The 360° camera or the reversing camera is off.
- The side windows and sliding sunroof are completely closed.
- · The outside mirrors are folded in.
- The blower for the ventilation and heating is switched off.
- The windshield wiper switch is in position **0**.
- The key is at least 10 ft (3 m) away from the vehicle. Otherwise the tailgate could open unintentionally.
- For car washes with conveyor system:
  - Neutral  $oldsymbol{\mathbb{N}}$  is engaged.

- If you would like to leave the vehicle while it is being washed, make sure the key is in the vehicle. The park position **P** is otherwise automatically engaged.
- i Removing the wax from the windshield and wiper rubbers after a car wash will prevent smearing and reduce wiper noise.

### Car wash mode

In car wash mode, the vehicle is prepared for driving into an automatic car wash. Car wash mode can be activated up to a speed of 12 mph  $(20 \text{ km/h}) (\rightarrow \text{page } 379)$ .

When car wash mode is activated, the Automatic Car Wash Mode Active message will appear on the driver display. The following adjustments will be made:

- The outside mirrors will be folded in.
- To prevent the windshield washer system from starting up automatically, the rain sensor will be deactivated.
- · Air-recirculation mode will be activated.

- The rear passenger compartment window wiper will be deactivated.
- Parking Assist PARKTRONIC will be deactivated
- Active Brake Assist will be deactivated, if applicable.
- Vehicles with 360° camera: the front image will be activated after approximately eight seconds.
- Vehicles with HANDS-FREE ACCESS: kick detection will be deactivated.

If one of the settings cannot be selected, this will be indicated by a **X** after the respective setting.

Pressing Switch Off will cancel car wash mode. Car wash mode will automatically be deactivated above a speed of 12 mph (20 km/h).

You can also switch off car wash mode via the MBUX multimedia system ( $\rightarrow$  page 379).

The following settings will be reset when car wash mode is deactivated:

· The outside mirrors will be folded out.

- The rain sensor will be activated.
- · Air-recirculation mode will be deactivated.
- The rear passenger compartment window wiper will be activated.
- Parking Assist PARKTRONIC will be reset to the previously selected setting.
- Active Brake Assist will be activated, if applicable.
- Vehicles with 360° camera: the front image will be deactivated at speeds above 11 mph (18 km/h).
- Vehicles with HANDS-FREE ACCESS: kick detection will be activated.

### Switching car wash mode on/off

### Requirements

- The vehicle is stationary.
- · The vehicle is switched on.

#### Multimedia system:

→ 🔝 ➤ Settings ➤ Vehicle ➤ Driving

### Activate car wash mode

- Select Automatic Car Wash Mode.
- Select Activate.

If one of the settings cannot be selected, this will be shown by a **X** next to the respective setting.

 For an overview of the settings configured when you activate car wash mode (→ page 378).

### Deactivating car wash mode

- Select Switch Off.
   The settings of car wash mode will be reverted.
- Car wash mode will automatically be deactivated as soon as the speed exceeds 12 mph (20 km/h).

## Notes on using a power washer

A

**WARNING** Risk of an accident when using power washers with round-spray nozzles

The water jet can cause externally invisible damage.

Components damaged in this way may unexpectedly fail.

- Do not use a power washer with roundspray nozzles.
- Have damaged tires or chassis parts replaced immediately.

To avoid damage to your vehicle, observe the following when using a power washer:

- The key is at least 10 ft (3 m) away from the vehicle. Otherwise the tailgate could open unintentionally.
- Maintain a distance of at least 11.8 in (30 cm) to the vehicle.
- Vehicles with decorative car film: Parts of your vehicle are wrapped with a decorative car film. Maintain a distance of at least 27.6 in (70 cm)

between the film-wrapped parts of the vehicle and the nozzle of the power washer. Move the nozzle of the power washer around while cleaning. The water temperature of the power washer must not exceed 140 °F (60 °C).

- Please observe the information on the correct distance in the equipment manufacturer's operating instructions.
- Do not direct the nozzle of the power washer directly at sensitive parts, e.g. tires, gaps, electrical components, batteries, lights or ventilation louvers.

# Washing the vehicle by hand

- ! NOTE Engine damage due to water ingress
- Take care not to point the water jet directly towards the air inlet grille below the hood.

Observe the relevant legal requirements (e.g. in some countries, washing by hand is permitted only in specially designated wash bays).

- Use a mild cleaning agent (e.g. car shampoo).
- Do not use an acidic cleaning agent.
- Wash the vehicle with lukewarm water using a soft car sponge. When doing so, do not expose the vehicle to direct sunlight.
- Carefully hose the vehicle off with water and dry using a chamois.
- Observe the notes on the care of car parts (→ page 382).

# Notes on paintwork/matte finish paintwork care

To avoid damaging the paintwork and interfering with the driving assistance systems, please observe the following notes:

### Paint

- Insect remains: soak with insect remover and rinse off the treated areas afterwards.
- Bird droppings: soak with water and rinse off afterwards.
- Tree resin, oils, fuels and greases: remove by rubbing gently with a cloth soaked in petroleum ether or lighter fluid.

- Coolant and brake fluid: remove with a damp cloth and clean water.
- Tar stains: use tar remover.
- · Wax: use silicone remover.
- Do not attach stickers, films or similar materials. Only have film attached to the bumper at a qualified specialist workshop.
- Remove dirt immediately, where possible. Do not use acidic solutions and acidic cleaning agents.

#### Matte finish

- Only use care products approved for Mercedes-Benz.
- Do not attach stickers, films or similar materials. Only have film attached to the bumper at a qualified specialist workshop.
- Do not polish the vehicle or the light-alloy wheels.
- Only use car washes that correspond to the latest engineering standards.
- Do not use a car wash program with a final hot wax treatment.

• Do not use paint cleaners, buffing or polishing products, gloss preservers, e.g. wax.

In the event of paintwork damage:

- Always have paintwork repairs carried out at a qualified specialist workshop.
- Make sure the radar sensors function (→ page 225).

# Notes on cleaning decorative car films

Please observe the "Notes on paintwork/matt paintwork care" ( $\rightarrow$  page 380). These notes also apply for matt decorative car films.

To avoid damage, please observe the notes on cleaning decorative car films.

### Cleaning

- When cleaning with a power washer, maintain a minimum distance of 27.6 in (70 cm) between the film-covered parts of the vehicle and the nozzle of the power washer.
- To clean, use lots of water and a mild cleaning agent without additional or abrasive products,

e.g. a car shampoo approved for Mercedes-

- Do not use any acidic cleaning agents.
- Remove dirt immediately, if possible. Avoid hard rubbing to avoid damaging the decorative car film irreparably.
- In case of dirt embedded in the surface or a dull decorative car film: use the 'Paint Cleaner' cleaning agent recommended and approved for Mercedes-Benz.
- Insect remains: Soak with insect remover and rinse off the treated areas afterwards.
- Bird droppings: Soak with water and rinse off afterwards.
- Dry vehicles covered with car film after every wash using a soft, absorbent cloth to prevent water stains.

# Preventing damage to the decorative car film

- The durability and color of decorative car films are affected by:
  - Solar radiation
  - Temperature, e.g. heat gun

- Weather
- Stone chips and dirt
- Chemical cleaning products
- Products containing grease
- Do not use polishes on matt decorative car films. Polishing results in the film-covered surface developing a shine.
- Do not use wax on matt or structured decorative car films. This may result in permanent stains.

Scratches, corrosive deposits, etched areas and damage caused by inadequate care cannot always be completely repaired. In such cases, please contact a qualified specialist workshop.

For more information about special care and cleaning products, please contact the manufacturer.

Laminated surfaces may exhibit optical differences to surfaces which were not protected by a decorative film when the decorative film is removed.

(i) Have work or repairs on decorative car film carried out at a qualified specialist workshop, e.g. a Mercedes-Benz Service Center.

# Notes on cleaning and care for vehicle parts

A

**WARNING** Risk of entrapment if the windshield wipers are switched on while the windshield is being cleaned

If the windshield wipers are set in motion while you are cleaning the windshield or wiper blades, you can be trapped by the wiper arm.

- Always switch off the windshield wipers and the vehicle before cleaning the windshield or wiper blades.
- NOTE Damage caused by acidic cleaning agents
- Do not use acidic cleaning agents. Otherwise, the surfaces could be damaged.

To avoid damage to the vehicle, observe the notes on cleaning and care for the following car parts:

### Wheels and rims

- Use water and acid-free alloy wheel cleaners.
- Do not use acidic alloy wheel cleaners to remove brake dust. This could damage wheel bolts and brake components.
- To avoid corrosion of the brake discs and pads, drive the vehicle for a few minutes after cleaning before parking it. The brake discs and pads will warm up and dry off.

### Windows

! NOTE Damage to electronic components due to excess fluids

When cleaning the windows from the inside, fluids such as cleaning agents or water may run down and get behind trim parts of the vehicle interior and cause damage to electronic components.

- Use cleaning agents as sparingly as possible.
- Immediately absorb any excess fluids.

- Clean the windows inside and outside with a damp cloth and with a cleaning agent recommended for Mercedes-Benz.
- Do not use dry cloths or abrasive or solventbased cleaning agents to clean the insides of windows.
- (i) Clean the windshield thoroughly with cleaning agents recommended for Mercedes-Benz after changing the wiper blades or applying a wax treatment to the vehicle. Failure to observe these instructions for use may result in damage, grease marks or glaring spots.
- Remove any exterior condensation or dirt on the windshield in front of the multifunction camera. Driving systems and driving safety systems may otherwise be impaired or unavailable(→ page 225).

### Wiper blades

- Move the wiper arms into the replacement position(→ page 145).
- Fold out the wiper arms and clean the wiper blades using a damp cloth.

(i) Please note that the wiper blades are coated. This coating may leave residue on a cloth. Do not rub the wiper blades excessively and do not clean them too frequently.

### Exterior lighting

- Clean the lenses with a wet sponge and a mild cleaning agent, e.g. car shampoo.
- Use only cleaning agents or cleaning cloths that are suitable for plastic lenses.

### Vehicle socket (high-voltage battery)

- Use clean water and a soft cloth to clean the vehicle socket.
- Do not use power washers or cleaning agents such as soap.

#### Sensors

- Clean the sensors in the front and rear end of the vehicle with car shampoo, plenty of water and a soft cloth ( $\rightarrow$  page 225).
- · When using a power washer, maintain a minimum distance of 11.8 in (30 cm).

### Running boards

• Use water and acid-free cleaning agents.

 Do not clean the aluminum insert of the running board with alkaline or acidic cleaning agents such as, e.g. wheel cleaners. Do not use acidic wheel cleaners to remove brake dust. The aluminum inserts may otherwise be damaged.

#### Cameras

- · Open the camera cover via the multimedia system ( $\rightarrow$  page 279).
- Use a soft cloth and clean water to clean the camera lenses
- Do not use a power washer.
- Remove any exterior condensation or dirt on the windshield in front of the multifunction camera. Driving systems and driving safety systems may otherwise be impaired or unavailable( $\rightarrow$  page 225).

### Trailer hitch

- Observe the care instructions in the operator's manual of the trailer hitch manufacturer.
- Do not clean the ball neck with a power washer or solvent.

- Remove any surface rust on the ball, e.g. with a wire brush
- Remove the dirt with a lint-free cloth.
- After cleaning, lightly oil or grease the ball.
- (i) Consult the operator's manual of the trailer hitch manufacturer before using trailers with a swav-control hitch.

### Notes on care of the interior

**WARNING** Risk of injury from plastic parts breaking off after the use of solvent-based care products

Care and cleaning products containing solvents can cause surfaces in the cockpit to become porous. When the airbags are deployed, plastic parts may break away.

Do not use any care or cleaning products containing solvents to clean the cockpit.

# **WARNING** Risk of injury or fatal injuries from bleached seat belts

Bleaching or dyeing seat belts can severely weaken them.

This can, for example, cause seat belts to tear or fail in an accident.

Never bleach or dye seat belts.

NOTE Property damage due to disinfectants

The interior includes a number of sensitive surfaces such as displays, plastics and leather.

Disinfectants can contain alcohol and other substances that penetrate and damage surfaces. Technology behind buttons and displays can also be damaged.

Do not use disinfectant on interior surfaces.

To avoid damage to the vehicle, observe the following notes on cleaning and care:

#### Seat belts

- · Clean with lukewarm and soapy water.
- Do not use chemical cleaning agents.
- Do not dry by heating them to over 176°F (80°C) or exposing them to direct sunlight.

### Display

- · Switch off the display and let it cool down.
- Clean the surface carefully with a microfiber cloth and a suitable display care product (TFT-LCD).
- Do not use any other agents.

### Head-up display

- Clean with a soft, non-static, lint-free cloth.
- · Do not use cleaning agents.

### Plastic trim

- Clean with a damp microfiber cloth.
- For heavy soiling: Use a cleaner recommended for Mercedes-Benz.
- Do not attach stickers, films or similar materials.

 Do not allow cosmetics, insect repellent or sun cream to come in contact with the plastic trim.

### Real wood and trim elements

- · Clean with a microfiber cloth.
- Black piano-lacquer look: clean with a damp cloth and soapy water.
- For heavy soiling: Use a cleaner recommended for Mercedes-Benz.
- Do not use solvent-based cleaning agents, polishes or waxes.

#### Headliner

• Clean with a brush or dry shampoo.

#### Carpet

 Use a carpet and textile cleaning agent recommended for Mercedes-Benz.

### Steering wheels made of imitation leather

- Use a damp cotton cloth and a 1% soap solution to clean the entire steering wheel. Do not spot clean.
- Use cleaning and care products recommended for Mercedes-Benz.

- · Do not use a microfiber cloth.
- Do not use oil-based cleaning and care products.

### Steering wheel made of genuine leather or DINA-MICA

- NOTE Damage caused by wrong cleaners
- Do not use solvent-based cleaning agents such as tar remover or wheel cleaner: neither should you use polishes or waxes. Otherwise you may damage the finish
- Clean with a damp cloth and a 1% soapy water solution and then wipe with a dry cloth.
- · For heavy soiling: Use a cleaner recommended for Mercedes-Benz.
- · Leather care: Use a leather care agent that has been recommended for Mercedes-Benz.
- Do not allow the leather to become too damp.
- · Do not use a microfiber cloth.

Leather is a natural product. It has natural surface properties, such as differences in structure, marks caused by growth and injury or subtle color differences. These surface properties are characteristics of leather and not material defects. Leather is also subject to a natural aging process during which the surface properties change.

#### Genuine leather seat covers

- Vacuum up dirt such as crumbs or dust and then clean the seat covers with a damp cotton cloth and wipe down with a dry cloth. Regularly clean the seat covers.
- · For heavy soiling: use a leather care agent recommended for Mercedes-Benz aftercare.
- Leather care: Use a leather care agent that has been recommended for Mercedes-Benz.
- · Do not use a microfiber cloth.
- Do not allow the leather to become too damp.
- Do not use oil-based cleaning and care products.
- Leather is a natural product. It has natural surface properties, such as differences in

structure, marks caused by growth and injury or subtle color differences. These surface properties are characteristics of leather and not material defects. Leather is also subject to a natural aging process during which the surface properties change.

Waves or wrinkling in the seat cover may occur due to the stress on the seat: this is caused by the natural leather material. Regular cleaning and care of the leather reduces soiling, wear marks and aging damage and thus significantly extends its life span. Clothing that can leave stains (e.g. jeans) may discolor the leather.

### DINAMICA seat covers

- · Vacuum up dirt such as crumbs or dust and then use a damp cloth to clean.
- Do not use a microfiber cloth.

## Imitation leather seat covers

 Vacuum up dirt such as crumbs or dust and then use a damp cotton cloth and a 1% soap solution to clean the entire seat cover. Do not spot clean.

- Use cleaning and care products recommended for Mercedes-Benz.
- Do not use a microfiber cloth.
- Do not use oil-based cleaning and care products.

### Cloth seat covers


- Vacuum up dirt such as crumbs or dust and then use a damp microfiber cloth and a 1% soap solution to clean the entire seat cover. Do not spot clean.
- Use cleaning and care products recommended for Mercedes-Benz.
- Do not use oil-based cleaning and care products.

### EASY-PACK trunk box

- Clean with a damp cloth.
- Do not use any alcohol-based thinners, gasoline or abrasive cleaning agents.

### Emergency

## Removing the safety vest




There is a safety vest compartment in the stowage compartments of all doors for storing a safety vest.

To remove: pull out safety vest bag 

by loop

- Open safety vest bag (1) and pull out the safety vest.
- To stow: fold the reflective safety jacket, roll it up and stow it in safety jacket bag 1.
- Slide safety jacket bag (1) along the lower edge of the armrest into the safety jacket compartment. Meanwhile, ensure that loop 2 hangs out well within reach.
- Remove a new reflective safety jacket from its packaging material before sliding it into the safety jacket compartment. The packaging material may otherwise cause it to slip out or make removing it difficult.

Observe the legal requirements in each country.



- Maximum number of washes
- Maximum wash temperature
- 3 Do not bleach
- On not iron
- Do not tumble dry
- O Do not dry clean
- O Class 2 safety vest

The requirements defined by the legal standard are only fulfilled if the safety vest is the correct size and is fully closed.

Replace the safety vest in the following cases:

• The reflective strips are damaged or dirty

#### 388 Breakdown assistance


- The maximum permissible number of washes is exceeded.
- The fluorescence has faded, e.g. due to continuous exposure to sunlight.

Dispose of the safety vest in an environmentally responsible manner:

• To do so, contact your local waste disposal company.

## Warning triangle

Removing the warning triangle




Warning triangle ① is located under the cargo floor in the loading sill when the vehicle is delivered.

- Remove warning triangle 1.
- Setting up the warning triangle



- ► Fold legs ③ down and out to the side.

### First-aid kit (soft-sided) overview



First-aid kit (soft sided) ① is in the cargo compartment in the left-hand stowage net.

### Flat tire

### Notes on flat tires

**WARNING** Risk of accident due to a flat tire

A flat tire severely affects the driving characteristics as well as steering and braking.

### Tires without run-flat characteristics:

- Do not drive on with a flat tire.
- Change the flat tire immediately with an emergency spare wheel or spare wheel. Alternatively, consult a qualified specialist workshop.

#### Tires with run-flat characteristics:

Observe the information and warning notes on MOExtended tires (run-flat tires).

In the event of a flat tire, you have the following options depending on your vehicle's equipment:

- Vehicles with MOExtended tires: it is possible to continue your journey for a short period of time. Make sure you observe the notes on MOExtended tires (run-flat tires)  $(\rightarrow page 389).$
- Vehicles with a TIREFIT kit: you can seal the tire so that it is possible to continue your journey for a short period of time. To do this, use the TIREFIT kit ( $\rightarrow$  page 391).

- Vehicles with Mercedes me connect: you can make a call for breakdown assistance via the overhead control panel in the case of a breakdown ( $\rightarrow$  page 351).
- All vehicles: change the wheel  $(\rightarrow)$  page 436).
- i) The emergency spare wheel is available only in certain countries ( $\rightarrow$  page 442). Vehicles equipped with MOExtended tires are not equipped with a TIREFIT kit at the factory. It is therefore recommended that you additionally equip your vehicle with a TIREFIT kit if you mount tires on your vehicle that do not feature run-flat characteristics, e.g. winter tires. A TIREFIT kit may be obtained from a qualified specialist workshop.

Vehicles with a Mercedes-Benz emergency call system that are not equipped with a TIREFIT kit: in the event of a flat tire, contact the Customer Assistance Center for the Mercedes-Benz emergency call system.

### Notes on MOExtended tires (run-flat tires)

WARNING Risk of accident when driving in limp-home mode

When driving in emergency mode the handling characteristics are impaired.

- Do not exceed the specified maximum speed of the MOExtended tires.
- Avoid any abrupt steering and driving maneuvers as well as driving over obstacles (curbs, pot holes, off-road). This applies, in particular, to a loaded vehicle.
- Stop driving in the emergency mode if you notice:
- Banging noise
- Vehicle vibration
- Smoke which smells like rubber
- Continuous ESP® intervention
- Cracks in the tire side walls
- After driving in emergency mode, have the rims checked by a qualified specialist

#### 390 Breakdown assistance

- workshop with regard to their further use.
- The defective tire must be replaced in every case.

With MOExtended tires (run-flat tires), you can continue to drive your vehicle even if there is a total loss of pressure in one or more tires. However, the tire affected must not show any clearly visible damage.

You can recognize MOExtended tires by the MOExtended marking which appears on the side wall of the tire.

Vehicles with tire pressure loss warning system: MOExtended tires may only be used in conjunction with an activated tire pressure loss warning system.

Vehicles with tire pressure monitoring system: MOExtended tires may only be used in conjunction with an activated tire pressure monitoring system. If a pressure loss warning message appears in the driver's display, proceed as follows:

- · Check the tire for damage.
- If driving on, observe the following notes.

Driving distance possible in emergency mode after the pressure loss warning:


Load condition	Driving distance possi- ble in emergency mode	
Partially laden	50 miles (80 km)	
Fully laden	19 miles (30 km)	

The driving distance possible in emergency mode may vary depending on the driving style. Observe the maximum permissible speed of 50 mph (80 km/h).

If a tire has gone flat and cannot be replaced with an MOExtended tire, you can use a standard tire as a temporary measure.


### TIREFIT kit storage location

# Plug-in hybrid



The TIREFIT kit (1) is located on the left-hand side of the cargo compartment in the as-delivered condition.

Not plug-in hybrid



- Tire sealant bottle
- Tire inflation compressor

The TIREFIT kit is located under the cargo floor in the as-delivered condition.

Depending on the vehicle version, the TIREFIT kit may be located in a different position in the cargo compartment.

- (i) Depending on the power category (LK), the tire inflation compressor weighs as follows:
  - LK1 12 V/10 A, 120 W, 1.8 lbs (0.8 kg)
  - LK2 12 V/15 A, 180 W, 2 lbs (0.9 kg)

You can find information on the power category (LK) and/or electrical data on the back of the tire inflation compressor.

The tire inflation compressor is maintenancefree. In the event of a malfunction, please contact a qualified specialist workshop.

# Using the TIREFIT kit

### Requirements

- · Tire sealant bottle and tire inflation compressor are ready for use ( $\rightarrow$  page 390).
- TIREFIT sticker is present.
- Gloves are present.

TIREFIT kit storage location:  $(\rightarrow page 390)$ 

You can use TIREFIT tire sealant to seal perforation damage of up to 0.16 in (4 mm), particularly in the tire tread. You can use TIREFIT in outside temperatures down to -4 °F (-20 °C).

### **WARNING** Risk of accident when using tire sealant

The tire sealant may be unable to seal the tire properly, especially in the following cases:

- There are large cuts or punctures in the tire (larger than damage previously mentioned)
- · The wheel rims have been damaged
- After journeys with very low tire pressure or with flat tires
- Do not continue driving.
- Consult a qualified specialist workshop.

### **WARNING** Risk of injury and poisoning from tire sealant

The tire sealant is harmful and causes irritation. Do not allow it to come into contact with the skin, eyes or clothing, and do not swallow it. Do not inhale tire sealant fumes. Keep the tire sealant away from children.

#### 392 Breakdown assistance

If you come into contact with the tire sealant, observe the following:

- Rinse off the tire sealant from your skin immediately using water.
- If tire sealant gets into your eyes, thoroughly rinse out the eyes using clean water.
- If tire sealant has been swallowed, immediately rinse out the mouth thoroughly and drink plenty of water. Do not induce vomiting and seek medical attention immediately.
- Change out of any clothes contaminated with tire sealant immediately.
- If allergic reactions occur, seek medical attention immediately.
- NOTE Overheating due to the tire inflation compressor running too long
- Do not run the tire inflation compressor for longer than ten minutes without interruption.


Comply with the manufacturer's safety notes on the sticker on the tire inflation compressor.

Have the tire sealant bottle replaced at a qualified specialist workshop every five years.

Do not remove any foreign bodies that have entered the tire.



- Affix part o of the TIREFIT sticker to the instrument cluster within the driver's field of vision.
- Affix part ② of the TIREFIT sticker near the valve on the wheel with the defective tire.



- Pull plug (a) with the cable and hose (5) out of the tire inflation compressor housing.
- Push the plug of hose (3) into flange (3) of tire sealant bottle (1) until the plug engages.
- Insert tire sealant bottle head downwards into recess ft the tire inflation compressor.



- Remove the valve cap from valve 7 on the defective tire
- Screw filling hose (8) onto valve (7).
- Insert plug 4 into a 12 V socket in your vehicle.
- Switch on the vehicle.
- Press on and off switch (3) on the tire inflation compressor.

The tire inflation compressor will be switched on. The tire will be inflated. First, tire sealant will be pumped into the tire. The pressure may briefly rise to approximately 500 kPa (5 bar/ 73 psi).

## Do not switch off the tire inflation compressor during this phase!

Let the tire inflation compressor run for a maximum of ten minutes

The tire should then have attained a tire pressure of at least 200 kPa (2.0 bar/29 psi).

If tire sealant leaks out, make sure you clean the affected area as quickly as possible. It is preferable to use clean water.

If you get tire sealant on your clothing, have it cleaned as soon as possible with perchloroethylene.

# If, after ten minutes, a tire pressure of 200 kPa (2.0 bar/29 psi) has not been attained:

- Switch off the tire inflation compressor.
- Unscrew the filling hose from the valve of the defective tire.

Please note that tire sealant may leak out when you unscrew the filling hose.

Drive forwards or in reverse very slowly for approximately 33 ft (10 m).

Pump up the tire again. After a maximum of ten minutes, the tire pressure must be at least 200 kPa (2.0 bar/ 29 psi).

WARNING Risk of accident due to the specified tire pressure not being achieved

If the specified tire pressure is not achieved after the specified time, the tire is too badly damaged. The tire sealant cannot repair the tire in this instance.

The braking characteristics as well as the driving characteristics may be greatly impaired.

- Do not continue driving.
- Consult a qualified specialist workshop.

If, after ten minutes, a tire pressure of 200 kPa (2.0 bar/29 psi) has been attained:

**WARNING** Risk of accident from driving with sealed tires

A tire temporarily sealed with tire sealant impairs the handling characteristics and is not suitable for higher speeds.

#### 394 Breakdown assistance

- Adapt your driving style accordingly and drive carefully.
- Do not exceed the maximum speed limit with a tire that has been repaired using tire sealant.
- Observe the maximum permissible speed of 50 mph (80 km/h) for a tire sealed with tire sealant.
- Affix the upper section of the TIREFIT sticker to the instrument cluster in a location where it will be easily seen by the driver.
- ! NOTE Staining caused by leaking tire sealant

After use, excess tire sealant may leak out from the filling hose.

Therefore, place the filling hose in the plastic bag that contained the TIREFIT kit.



**ENVIRONMENTAL NOTE** Environmental pollution caused by environmentally irresponsible disposal

Tire sealant contains pollutants.

- Have the tire sealant bottle disposed of professionally, e.g. at an authorized Mercedes-Benz Center.
- Switch off the tire inflation compressor.
- Unscrew the filling hose from the valve of the defective tire.
- Stow the tire sealant bottle and the tire inflation compressor.
- Pull away immediately.
- Stop driving after approximately ten minutes and check the tire pressure using the tire inflation compressor.

The tire pressure must now be at least 130 kPa (1.3 bar/19 psi).

# **WARNING** Risk of accident due to the specified tire pressure not being attained


If the specified tire pressure is not reached, the tire is too badly damaged. The tire sealant cannot repair the tire in this instance.

The braking and driving characteristics may be greatly impaired.


- Do not continue driving.
- Consult a qualified specialist workshop.

In cases such as the one mentioned above, contact an authorized Mercedes-Benz Center. Or call 1-800-FOR-MERCedes (in the USA) or 1-800-387-0100 (in Canada).

- Correct the tire pressure if it is still at least 130 kPa (1.3 bar/19 psi). See the Tire and Loading Information placard on the B-pillar on the driver's side or the tire pressure table in the fuel filler flap for values.
- ► To increase the tire pressure: switch on the tire inflation compressor.



- To reduce the tire pressure: press pressure release button (1) next to manometer (2).
- When the tire pressure is correct, unscrew the filling hose from the valve of the sealed tire.
- Screw the valve cap onto the valve of the sealed tire.



- Pull the tire sealant bottle out of the tire inflation compressor. Press the locking tabs on the yellow cap together to do this.
  - The filling hose stays on the tire sealant bottle.
- Drive to the nearest qualified specialist workshop and have the tire, tire sealant bottle and filling hose replaced there.

## Battery (vehicle)

## Notes on the 12 V battery

WARNING Risk of an accident due to work carried out incorrectly on the battery

Work carried out incorrectly on the battery can, for example, lead to a short circuit, This can restrict functions relevant for safety systems and impair the operating safety of your vehicle.

You could lose control of the vehicle in the following situations in particular:

- When braking
- In the event of abrupt steering maneuvers and/or when the vehicle's speed is not adapted to the road conditions
- In the event of a short circuit or a similar incident, contact a qualified specialist workshop immediately.
- Do not drive on.
- Always have work on the battery carried out at a qualified specialist workshop.

- Further information on ABS (→ page 227)
- Further information on ESP® ( $\rightarrow$  page 228)

For safety reasons, Mercedes-Benz recommends that you use only batteries that have been approved for your vehicle by Mercedes-Benz.

All vehicles except vehicles with lithium-ion batteries

A

**WARNING** Risk of explosion due to electrostatic charge

Electrostatic charge can ignite the highly explosive gas mixture in the battery.

To discharge any electrostatic charge that may have built up, touch the metal vehicle body before handling the battery.

The highly flammable gas mixture is created while the battery is charging and during jump-starting.

A

**WARNING** Danger of chemical burns from the battery acid

Battery acid is caustic.

- Avoid contact with the skin, eyes or clothing.
- Do not lean over the battery.
- Do not inhale battery gases.
- Keep children away from the battery.
- Immediately rinse battery acid off thoroughly with plenty of clean water and seek medical attention immediately.

#### All vehicles



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of batteries

Batteries contain pollutants. It is illegal to dispose of them with the household rubbish.



Dispose of batteries in an environmentally responsible manner.

Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

If you have to disconnect the 12 V battery, contact a qualified specialist workshop.

Observe the safety notes and protective measures when handling batteries.



Risk of explosion if the 12 V battery is used improperly.



Fire, open flames and smoking are prohibited when you are handling the battery. Avoid creating sparks.



Electrolyte or battery acid is corrosive. Avoid contact with the skin, eyes or clothing. Wear suitable protective clothing, especially gloves, an apron and a safety mask. Immediately rinse electrolyte or acid splashes off with clean water. Consult a doctor immediately.



Do not place heavy objects on the surface of the battery or use the battery to support a person in any way.



Wear eye protection.



Keep children away.



Observe this Operator's Manual.

Observe the following if you are intending not to use the vehicle for an extended period of time:

- If available: activate standby mode
   (→ page 225, 224).
- Alternatively: connect the battery to a battery charger approved by Mercedes-Benz or consult a qualified specialist workshop to disconnect the battery.

### Notes on the 48 V battery

WARNING Risk of an accident due to work carried out incorrectly on the battery

Work carried out incorrectly on the battery can, for example, lead to a short circuit. This can restrict functions relevant for safety systems and impair the operating safety of your vehicle.

You could lose control of the vehicle in the following situations in particular:

- When braking
- In the event of abrupt steering maneuvers and/or when the vehicle's speed is not adapted to the road conditions
- In the event of a short circuit or a similar incident, contact a qualified specialist workshop immediately.
- ▶ Do not drive on.
- Always have work on the battery carried out at a qualified specialist workshop.
- Further information on ABS ( $\rightarrow$  page 227)

• Further information on ESP® ( $\rightarrow$  page 228)



**ENVIRONMENTAL NOTE** Environmental damage due to improper disposal of batteries



Batteries contain pollutants. It is illegal to dispose of them with the household trash.



**Li-ion** Dispose of batteries in an environmentally responsible manner. Take discharged batteries to a qualified specialist workshop or to a collection point for used batteries.

Have any work on the 48 V battery carried out exclusively at a qualified specialist workshop. Comply with safety notes and take protective measures when handling batteries.



Risk of explosion if the 48 V battery is used improperly.



The surface of the 48 V battery may be hot.



Fire, naked flames and smoking are prohibited when handling the battery. Avoid creating sparks.



Electrolyte or battery acid is corrosive. Avoid contact with the skin, eyes or clothing. Wear suitable protective clothing, in particular gloves, an apron and a face mask. Immediately rinse off splashes of electrolyte or acid with plenty of clean water. Consult a doctor immediately.



Do not place heavy objects on the surface of the battery or use the battery to support a person in any way.



Do not perform any work on the battery. Always have any work on the battery carried out at a qualified specialist workshop. Do not disconnect the battery yourself. Do not remove the battery yourself. Do not attempt to open the battery.



Keep children away.



Wear safety glasses.



Observe this Operator's Manual.

Observe the following if you do not intend to use the vehicle over an extended period of time:

If available: activate standby mode
 (→ page 225, 224).

# Notes on the high-voltage battery



**DANGER** Risk of fire and explosion from excessive internal pressure of the high-voltage battery

In the event of a vehicle fire, flammable gas can escape and ignite.

If there is an unusual smell, smoke or burn marks, stop the charging process immediately.

- Leave the danger zone immediately.
   Secure the danger area at a sufficient distance.
- Call the fire service.

Observe the notes on charging the high-voltage battery ( $\rightarrow$  page 200).



Risk of explosion.



Fire, open flames and smoking are prohibited when you are handling the battery. Avoid creating sparks.



Electrolyte or battery acid is corrosive. Avoid contact with the skin, eyes or clothing. Wear suitable protective clothing, especially gloves, an apron and a safety mask. Immediately rinse electrolyte or acid splashes off with clean water. Consult a doctor immediately.



Wear safety glasses.



Keep children away.



Observe this Operator's Manual.

## Notes on starting assistance and charging the 12 V battery

#### All vehicles

When charging the battery and during starting assistance, always use the jump-start connection point in the engine compartment.

NOTE Damage to the battery due to overvoltage

When charging using a battery charger without a maximum charging voltage, the battery or the on-board electronics may be damaged.

Only use battery chargers with a maximum charging voltage of 14.8 V.

# **WARNING** Risk of explosion due to igniting hydrogen gas

If you cause a short circuit or sparks occur, the hydrogen gas may ignite when a battery is charging.

- Ensure that the positive terminal of a connected battery does not come into contact with vehicle parts.
- Never place metal objects or tools on a batterv.
- When connecting and disconnecting the battery, always observe the sequence of battery terminals described.
- When jump starting, take care to connect only battery terminals of identical polarity.
- When jump starting, always observe the sequence described for connecting and disconnecting the jumper cables.
- Do not connect or disconnect the battery terminals when the engine is running.

# **A** WARNING Risk of explosion due to a mixture of explosive gases

A mixture of explosive gases can escape from the battery during charging and jump starting.

- Fire, open flames, smoking and creating sparks must be avoided.
- Make sure that there is sufficient ventilation
- Do not stand over the battery.

## WARNING Risk of explosion from a frozen battery

A discharged battery may freeze at temperatures slightly above or below freezing point.

During starting assistance or battery charging, battery gas can be released.

Always allow a battery to thaw before charging it or performing starting assistance.

If, at low temperatures, the indicator lamps/warning lamps in the instrument cluster do not light up, it is highly likely that the discharged battery

has frozen. In this case, you may neither charge the battery nor jump-start the vehicle.

The service life of a battery that has been thawed may be drastically reduced. The starting characteristics can be impaired, particularly at low temperatures.

We recommend having the thawed-out battery inspected at a qualified specialist workshop.

### Plug-in hybrid

If your vehicle has been started with starting assistance, it may not be possible to use the electric drive for approximately 30 minutes.

Starting assistance is not considered to be a normal operating condition.

#### All vehicles



**NOTE** Damage caused by numerous or extended attempts to start the engine

Numerous or extended attempts to start the engine may damage the catalytic converter due to non-combusted fuel.



Avoid numerous and extended attempts to start the engine.

Observe the following points during starting assistance and when charging the battery:

- Use only undamaged jumper cables / charging cables with a sufficient cross-section and insulated terminal clamps.
- Non-insulated parts of the terminal clamps must not come into contact with other metal parts while the jumper cable / charging cable is connected to the battery / jump-start connection point.
- The jumper cables / charging cables must not come into contact with any parts that may move when the engine is running
- Always make sure that neither you nor the battery is electrostatically charged.
- Keep away from fire and open flames.
- Do not lean over a battery.

Also observe the following points when charging the battery:

- Use only chargers tested and approved for Mercedes-Benz.
- Read the operating instructions for the charger before charging the battery.

Also observe the following points during starting assistance:

- Starting assistance may only be provided using vehicles, batteries or other jump start devices with a nominal voltage of 12 V.
- · The vehicles must not touch each other.
- Vehicles with a gasoline engine: only jumpstart your vehicle when the engine and exhaust system are cold.

# Starting assistance and charging the 12 V battery

# Preparing starting assistance/charging


- Secure the vehicle by applying the electric parking brake.
- Shift the transmission to position P.

- Switch off the vehicle and all electrical consumers.
- Open the hood.



Open cover 

of the jump-start connection point.



Open cover (3) of positive contact (2) on the jump-start connection point.

## Starting assistance

Connect positive terminal 2 on your vehicle to positive terminal of the donor battery using the jumper cable. Always begin with positive clamp 2 on your own vehicle first.

- Start the engine of the donor vehicle and run it at idling speed.
- Connect the negative terminal of the donor battery to ground point (4) of your vehicle using the jumper cable. Begin with the donor battery first.
- Start the engine of your own vehicle.
- Let the engines run for several minutes.
- Before disconnecting the jumper cables, switch on an electrical consumer in your own vehicle, e.g. the rear window defroster or the lighting.

When the starting assistance procedure is complete:

- Remove the jumper cables from ground point 4 first and the negative terminal of the donor battery, then from positive contact 2 and the positive terminal of the donor battery. Begin each time with the contacts on your own vehicle first.
- Close cover 3 of positive terminal 2 after removing the jumper cables.

Close cover 1.

If your vehicle has been started with starting assistance, it may not be possible to use the electric drive for approximately 30 minutes.

Further information can be obtained at a qualified specialist workshop.

## Charging

- Connect positive contact ② on the vehicle to the positive terminal of the charger using the charging cable. Always begin with positive contact ② on the vehicle.
- Connect the negative terminal of the charger and ground point on the vehicle with the charging cable. Start with the charger.
- Start the charging process.

When the charging process is complete:

- After removing the charging cable, close cover
  of of positive contact 2.
- Close cover ①.

Further information can be obtained at a qualified specialist workshop.

## Replacing the 12 V battery

Observe the notes on the 12 V battery (→ page 395).

Mercedes-Benz recommends that you have the 12 V battery replaced at a qualified specialist workshop, e.g. at an authorized Mercedes-Benz Center.

Observe the following notes if you want to replace the battery yourself:

 Always replace a faulty battery with a battery that meets the specific vehicle requirements.

The vehicle is equipped with an AGM (Absorbent Glass Mat) technology battery or a lithiumion battery. Full vehicle functionality is guaranteed only with an AGM or lithium-ion battery. For safety reasons, Mercedes-Benz recom-

mends that you use only batteries that have been tested and approved for your vehicle by Mercedes-Benz.

- Use detachable parts such as vent hoses, elbow fittings or terminal covers from the battery to be replaced.
- Make sure that the vent hose is always connected to the original opening on the side of the battery.

Install any existing or supplied cell caps.

Otherwise, gases or battery acid could escape.

Make sure that detachable parts are reconnected in the same way.

# Tow starting or towing away

### Permitted towing methods

I NOTE Damage from automatic braking

If one of the following functions is activated, the vehicle will brake automatically in certain situations:

- Active Brake Assist
- Active Distance Assist DISTRONIC
- HOLD function
- · Active Parking Assist

To avoid damage to the vehicle, switch off these systems, e.g. when towing or using a car wash.

Mercedes-Benz recommends transporting your vehicle in the case of a breakdown, rather than towing it away.

For towing with both axles on the ground, use a tow rope or tow rod. Do not use tow bar systems.

!	NOTE Damage to the vehicle due to tow-
	ing away incorrectly

Observe the instructions and notes on towing away.

**Towing with a raised axle:** towing should be performed by a towing company.

#### Vehicles with rear wheel drive

Permitted towing methods		
Both axles on the ground	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h)	
Front axle raised	No	
Rear axle raised	Yes, if the steering wheel is fixed in the center position with a steering wheel lock	

#### 4MATIC vehicles

Permitted towing methods		
Both axles on the ground	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h)	
Front axle raised	No	
Rear axle raised	No	

# Permitted towing methods (plug-in hybrid)

- i The following information does not apply to Mercedes-AMG E Performance vehicles.
- ! NOTE Mercedes-AMG vehicles
  - Observe the notes in the Supplement. You could otherwise fail to recognize dangers.

Mercedes-Benz recommends transporting your vehicle in the case of a breakdown, rather than towing it away.

For towing with both axles on the ground, use a tow rope or tow rod. Do not use tow bar systems.

- ! NOTE Damage to the vehicle due to towing away incorrectly
- Observe the instructions and notes on towing away.

Observe the information on towing and transporting the vehicle in the vehicle Operator's Manual. In the following situations, only transporting the vehicle is permitted:

- . The driver's display is not working
- The Source Towing Not Permitted See Operator's Manual display message appears on the driver's display.

Exception: If the vehicle is located in a danger zone, it can be recovered from the danger zone despite the Towing Not Permitted See
Operator's Manual display message or the display

not working. It must not be towed further than 55 yd (50 m) with both axles on the ground. A towing speed of 6 mph (10 km/h) must not be exceeded. Beyond these limits, only transporting is permitted.

#### Vehicles with rear wheel drive

Permitted towing methods		
Both axles on the ground	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h), only forwards with the driver in the vehicle	
Front axle raised	No	
Rear axle raised	Yes, if the steering wheel is fixed in the center position with a steering wheel lock	

#### 4MATIC vehicles

Permitted towing methods	
Both axles on the ground	Yes, for a maximum of 31 miles (50 km) at 31 mph (50 km/h), only forwards with the driver in the vehicle
Front axle raised	No
Rear axle raised	No

# Towing the vehicle with both axles on the ground

- Observe the notes on the permitted towing methods.
- Make sure that the battery is connected and charged.

Observe the following points when the battery is discharged:

- · the vehicle cannot be started.
- the electric parking brake cannot be released or applied

- Vehicles with automatic transmission: the transmission cannot be shifted to position N or P.
- Vehicles with automatic transmission: if the transmission cannot be shifted to position N or if the display does not show anything. transport the vehicle ( $\rightarrow$  page 406). A towing vehicle with lifting equipment is required for vehicle transportation.
- NOTE Damage due to towing away at excessively high speeds or over long distances

The drivetrain could be damaged when towing at excessively high speeds or over long distances.

- ► A towing speed of 30 mph (50 km/h) must not be exceeded.
- ► A towing distance of 30 miles (50 km) must not be exceeded.

**WARNING** Risk of accident when towing a vehicle which is too heavy

If the vehicle to be tow-started or towed away is heavier than the permissible gross mass of your vehicle, the following situations can occur.

- The towing eve may become detached.
- The vehicle/trailer combination may swerve or rollover.
- Before tow-starting or towing away, check if the vehicle to be tow-started or towed away exceeds the permissible gross mass.

If a vehicle has to be tow-started or towed away. its permissible gross mass must not exceed the permissible gross mass of the towing vehicle.

- Information on the permissible gross mass of the vehicle can be found on the vehicle identification plate ( $\rightarrow$  page 448).
- Vehicles with automatic transmission: do not open the driver's door or front passenger

- door: the transmission otherwise automatically shifts to position **P**.
- Install the towing eye  $(\rightarrow)$  page 407).
- Fasten the towing device.
  - NOTE Damage due to incorrect connection of the tow bar
- Only connect the tow rope or tow bar to the towing eyes.
- Deactivate the automatic locking mechanism  $(\rightarrow page 80)$ .
- Do not activate the HOLD function.
- Deactivate the tow-away alarm ( $\rightarrow$  page 96).
- Deactivate Active Brake Assist ( $\rightarrow$  page 259).
- Vehicles with automatic transmission: shift to position N.
- Release the electric parking brake.

WARNING Risk of accident due to limited safety-related functions during the towing process

Safety-related functions are limited or no longer available in the following situations:

- . The vehicle is switched off.
- The brake system or power steering system is malfunctioning.
- The energy supply or the on-board electrical system is malfunctioning.

When your vehicle is towed away, significantly more effort may be required to steer and brake than is normally required.

- Use a tow bar.
- Make sure that the steering wheel can move freely before towing the vehicle away.

! NOTE Damage due to excessive tractive power

If you pull away sharply, the tractive power may be too high and the vehicles could be damaged.

▶ Pull away slowly and smoothly.

# Loading the vehicle for transport


**Plug-in hybrid:** vehicles should be transported only by professional recovery companies.

- Observe the notes on towing away  $(\rightarrow)$  page 404).
- Connect the towing device to the towing eye in order to load the vehicle.
- (i) You can also attach the tow bar to the trailer hitch.
- Shift the automatic transmission to position **N**.
- The automatic transmission may be locked in position P in the event of damage to the

electrics. To shift to [N], provide the on-board electrical system with power ( $\rightarrow$  page 400).

- Load the vehicle onto the transporter.
- Shift the automatic transmission to position **P**.
- Use the electric parking brake to secure the vehicle against rolling away.
- Secure the vehicle only by the wheels.


#### 4MATIC vehicles



Make sure that the front and rear axles come to rest on the same transportation vehicle.

- NOTE Damage to the drive train due to incorrect positioning of the vehicle
- Do not position the vehicle above the connection point of the transport vehicle.

# Towing eye storage location




The towing eye (1) is located under the cargo floor in the loading sill.

# Installing/removing the towing eye



AMG Line



# All other vehicles

AMG Line: press the mark on cover (1) on the rear bumper inward and remove the cover. Use a suitable object, e.g. a screwdriver, to pry off cover ② on the front bumper from underneath. Take the cover from the opening, but do not remove it.

- All other vehicles: press the mark on cover on inward and remove.
- Screw in the towing eye clockwise to the stop.

Vehicles with a trailer hitch: vehicles with a trailer hitch do not have a fixture at the back for the towing eye. Connect the tow bar to the trailer hitch.

- After removing the towing eye, engage cover in the bumper.
- NOTE Damage to the vehicle due to incorrect use of the towing eye or trailer hitch

When a towing eye or trailer hitch is used to recover a vehicle, the vehicle may be damaged in the process.

- Only use the towing eye or trailer hitch to tow away or tow start the vehicle.
- Do not use the towing eye or trailer hitch to tow the vehicle during recovery.

## Tow-starting the vehicle

#### Vehicles with automatic transmission

- Observe the following note on material damage:
- NOTE Damage to the automatic transmission due to tow starting

The automatic transmission may be damaged in the process of tow starting vehicles with automatic transmission.

Vehicles with automatic transmission must not be tow started.

### **Electrical fuses**

#### Notes on electrical fuses

A

**WARNING** Risk of accident and injury due to overloaded lines

If you manipulate or bridge a faulty fuse or if you replace it with a fuse with a higher amperage, the electric line could be overloaded.

This could result in a fire.

- Always replace faulty fuses with specified new fuses containing the correct amperage.
- I NOTE Damage due to incorrect fuses

Using incorrect fuses can result in damage to electrical components or systems or their functions being considerably restricted.

 Use only fuses approved for Mercedes-Benz with the respective specified fuse rating.

Blown fuses must be replaced with fuses of the same rating, which you can recognize by the color and the label. The fuse ratings and further information to be observed can be found in the fuse assignment diagram.

Fuse assignment diagram: on the fuse box in the cargo compartment ( $\rightarrow$  page 411).

**NOTE** Damage or malfunctions caused by moisture

Moisture may cause damage to the electrical system or cause it to malfunction.

- When the fuse box is open, make sure that no moisture can enter the fuse box
- When closing the fuse box, make sure that the seal of the lid is positioned correctly on the fuse box.

If the newly inserted fuse also blows, have the cause traced and rectified at a qualified specialist workshop.

Ensure the following before replacing a fuse:

- · The vehicle is secured against rolling away.
- All electrical consumers are switched off.
- · The vehicle is switched off.

The fuses are located in various fuse boxes:

- Fuse box in the engine compartment on the driver's side ( $\rightarrow$  page 409)
- Fuse box on the driver's side of the cockpit  $(\rightarrow page 410)$

- Fuse box in the front-passenger footwell  $(\rightarrow page 410)$
- Fuse box in the cargo compartment  $(\rightarrow page 411)$

# Opening and closing the fuse box in the engine compartment

## Requirements

• A dry cloth and a screwdriver are available.

Observe the notes on electrical fuses  $(\rightarrow page 408)$ .


# Opening

**A** WARNING Risk of injury from using the windshield wipers when the hood is open


If the windshield wipers start moving when the hood is open, you could be trapped by the wiper linkage.

Always switch off the windshield wipers and the vehicle first if you need to open the hood.

 $\triangleright$  Open the hood ( $\rightarrow$  page 371).



- Turn both retaining clips 2 on cover 1 on the driver's side a quarter-turn clockwise.
- Fold cover (1) upwards.



- Remove any existing moisture from the fuse box using a dry cloth.
- Loosen screws (3) and remove fuse box lid (4) from the top.

## Closing


Check whether the seal is positioned correctly in lid <a>a</a>.

- Insert lid (a) into the bracket at the rear of the fuse box.
- Fold down lid 4 of the fuse box and tighten screws 3.
- Fold down cover ①.
- Turn both retaining clips ② on cover ① a quarter-turn counter-clockwise.
- Close the hood.

# Opening and closing the fuse box in the cockpit

# Requirements

 Please observe the notes on electrical fuses (→ page 408).



The fuse box is on the driver's side at the side of the cockpit under a cover.


- To open: Flip open cover 1 in the direction of the arrow and remove it.
- To close: Reinsert cover ①.

Mercedes-Benz recommends that you have the fuse box opened at a Mercedes-Benz Service Center.

# Opening and closing the fuse box in the front passenger footwell

# Requirements

Observe the notes on electrical fuses  $(\rightarrow page 408)$ .



- To open: fold out and remove cover ①.
- To close: reinsert cover 1.

# Opening and closing the fuse box in the load compartment

## Requirements

Observe the notes on electrical fuses  $(\rightarrow$  page 408).



- ▶ To open: fold out and remove cover ①.
- ► To close: reinsert cover ①.

The fuse assignment diagram is on the side of the fuse box.

# Notes on noise or unusual handling characteristics

Make sure there are no vibrations, noises or unusual handling characteristics when the vehicle is in motion. This may indicate that the wheels or tires are damaged. Hidden tire damage could also be causing the unusual handling characteristics.

If you suspect that a tire is defective, reduce your speed immediately and have the tires and wheels checked at a qualified specialist workshop.

## Notes on regularly inspecting wheels and tires

**WARNING** Risk of injury through damaged tires

Damaged tires can cause tire pressure loss.

Check the tires regularly for signs of damage and replace any damaged tires immediately.

# **WARNING** Risk of hydroplaning due to insufficient tire tread

Insufficient tire tread will result in reduced tire grip.

In heavy rain or slush the risk of hydroplaning is increased, in particular where speed is not adapted to suit the conditions.

Thus, you should regularly check the tread depth and the condition of the tread across the entire width of all tires.

Minimum tread depth for:

- Summer tires: 1/8 in (3 mm)
- M+S tires: ½in (4 mm)
- For safety reasons, replace the tires before the legally-prescribed limit for the minimum tread depth is reached.

Carry out the following checks on all wheels regularly, at least once a month or as required, for example, prior to a long journey or driving offroad:

• Check the tire pressure ( $\rightarrow$  page 413).

- · Visually inspect wheels and tires for damage.
- Check the valve caps.
- Visually inspect the tire tread depth and the tire contact surface across the entire width.

The minimum tread depth for summer tires is  $\frac{1}{10}$  in (3 mm) and for winter tires  $\frac{1}{10}$  in (4 mm).



Six marks  $\odot$  show where the bar indicators (arrow) are integrated into the tire tread. They are visible once a tire tread depth of approximately  $V_{16}$  in (1.6 mm) has been reached.

#### Notes on snow chains

WARNING Risk of accident due to incorrectly installed snow chains

If you have installed snow chains on the front wheels, they may drag against the vehicle body or chassis components.

- Never install snow chains on the front wheels.
- Only install snow chains on the rear wheels in pairs.
- NOTE Damage to components of the vehicle body or chassis due to mounted snow chains

If you mount snow chains to the front wheels of 4MATIC vehicles, you may damage components of the vehicle body or chassis.

Only mount snow chains to the rear wheels of 4MATIC vehicles.

Observe the following notes when using snow chains.

- Snow chains are only permissible for certain wheel/tire combinations. You can obtain information about this from a Mercedes-Renz Service Center.
- · For safety reasons, only use snow chains that have been specifically approved for your vehicle by Mercedes-Benz, or snow chains with the same quality standard.
- Comply with the installation instructions of the snow chain manufacturer.
- If snow chains are fitted, the maximum permissible speed is 30 mph (50 km/h).
- . Vehicles with Active Parking Assist: do not use Active Parking Assist when snow chains are fitted.
- i You can deactivate ESP® to pull away  $(\rightarrow page 230)$ . This allows the wheels to spin, achieving increased tractive power.

### Turning snow chain mode on or off

Multimedia system:





Turning Snow Chain Mode on or off.

When the function is active, the vehicle adjusts to snow chains having been mounted. Among other things, it limits the maximum steering angle of the rear wheels, and the turning circle increases.

Furthermore, some of the driving systems and driving safety systems are not available when snow chain mode is active

#### Tire pressure

Notes on tire pressure



WARNING Risk of accident due to insufficient or excessive tire pressure

Underinflated or overinflated tires pose in particular the following risks:

The tires can burst.

- The tires can wear excessively and/or unevenly.
- The driving characteristics as well as the steering and braking characteristics may be greatly impaired.
- Comply with the recommended tire pressures and check the tire pressure of all tires, including the spare wheel, regularly:
- Monthly
- · When the load changes
- Before embarking on a longer journey
- If operating conditions change, e.g. offroad driving
- Adjust the tire pressure, if necessary.

Tire pressure which is too high or too low can:

- Shorten the service life of the tires.
- · Cause increased tire damage.
- Adversely affect driving characteristics and thus driving safety, e.g. due to hydroplaning.

# **WARNING** Risk of accident due to too low a tire pressure

Tires with pressure that is too low can overheat and burst as a consequence.

In addition, they also suffer from irregular wear, which can significantly impair the braking properties and the handling characteristics.

Avoid excessively low tire pressure.

Tire pressure which is too low can cause:

- · Tire defects as a result of overheating
- Impaired handling characteristics
- Irregular wear
- Increased fuel consumption

# **WARNING** Risk of accident due to too high a tire pressure

Tires with excessively high pressure can burst. In addition, they also suffer from irregular wear, which can significantly impair the brak-

ing properties and the handling characteristics.

Avoid excessively high tire pressures.

Tire pressure which is too high can cause:

- · Increased braking distance
- · Impaired handling characteristics
- Irregular wear
- Impaired driving comfort
- · Susceptibility to damage

# **WARNING** Risk of accident due to repeated pressure drop in the tires

The wheels, valves or tires could be damaged.

Too low a tire pressure can lead to the tires bursting.

- Examine the tires for foreign objects.
- Check whether the tire has a puncture or the valve has a leak.
- If you are unable to rectify the damage, contact a qualified specialist workshop.

You can find information on the recommended tire pressures for the vehicle's factory-installed tires on the following labels:

- Tire and Loading Information placard on the B-pillar of your vehicle ( $\rightarrow$  page 420).
- Tire pressure table on the inside of the fuel filler flap ( $\rightarrow$  page 415).

Observe the maximum tire pressure  $(\rightarrow page 427)$ .

Use a suitable pressure gauge to check the tire pressure. The outer appearance of a tire does not permit any reliable conclusion about the tire pressure.

Only correct tire pressure when the tires are cold. Conditions for cold tires:

- . The vehicle has been parked with the tires out of direct sunlight for at least three hours.
- The vehicle has traveled less than 1 mile (1.6 km).

The vehicle's tires heat up when driving. As the temperature of the tires increases, so too does the tire pressure.

Vehicles with a tire pressure monitoring system: you can also see the tire pressure in the driver's display ( $\rightarrow$  page 418).

The tire pressure recommended for increased load/speed in the tire pressure table can affect the ride comfort.

WARNING Risk of accident due to unsuitable accessories on tire valves

If you mount unsuitable accessories onto tire valves, the tire valves may be overloaded and malfunction, which can cause tire pressure loss.

Only screw standard valve caps or valve caps specifically approved by Mercedes-Benz for your vehicle onto the tire valve.


#### Notes on trailer operation

Always inflate the rear axle tires to the recommended tire pressure on the tire pressure table for increased load.

#### Tire pressure table

The tire pressure table is on the inside of the fuel filler flap.

(i) The data shown in the images is example data.




The tire pressure table shows the recommended tire pressure for all tires approved for this vehicle. The recommended tire pressure apply for cold tires under various operating conditions, i.e. loading and/or speed of the vehicle.

If one or more tire sizes precede a tire pressure. the following tire pressure information is only valid

for those tire sizes and their respective load condition.

The load conditions "partially laden" and "fully laden" are defined in the table for different numbers of passengers and amounts of luggage. The actual number of seats may differ from this.



Some tire pressure tables only show the rim diameter instead of the complete tire size, e.g. R18.

The rim diameter is part of the tire size and can be found on the tire side wall ( $\rightarrow$  page 427).

- Tire and Loading Information placard (→ page 420)
- Maximum tire pressures (→ page 427)

## Checking the tire pressure manually

- Read the tire pressure recommended for the current operating conditions from the tire and loading information placard or the tire pressure table. Observe the notes on tire pressure.
- Remove the valve cap of the tire to be checked.
- Press the tire pressure gauge securely onto the valve.
- Read the tire pressure.
- If the tire pressure is lower than the recommended value, increase the tire pressure to the recommended value.
- ▶ If the tire pressure is higher than the recommended value, release air. To do so, press down the metal pin in the valve, e.g. using the

- tip of a pen. Then check the tire pressure again using the tire pressure gauge.
- Screw the valve cap onto the valve.

#### Further related subjects:

- Notes on tire pressure (→ page 413)
- Tire pressure table (→ page 415)
- Tire and loading information placard (→ page 420)

# Tire pressure monitoring system

Function of the tire pressure monitor

**DANGER** Risk of accident due to incorrect tire pressure

Each tire, including the spare (if provided), should be checked monthly when cold and inflated to the inflation pressure recommended by the vehicle manufacturer on the vehicle placard or tire inflation pressure label. (If your vehicle has tires of a different size than the size indicated on the vehicle placard or tire inflation pressure label, you should deter-

mine the proper tire inflation pressure for those tires.)

As an added safety feature, your vehicle has been equipped with a tire pressure monitoring system (TPMS) that illuminates a low tire pressure telltale when one or more of your tires is significantly under-inflated. Accordingly, when the low tire pressure telltale illuminates, you should stop and check your tires as soon as possible, and inflate them to the proper pressure. Driving on a significantly under-inflated tire causes the tire to overheat and can lead to tire failure. Under-inflation also reduces fuel efficiency and tire tread life, and may affect the vehicle's handling and stopping ability. Please note that the TPMS is not a substitute for proper tire maintenance, and it is the driver's responsibility to maintain correct tire pressure, even if under-inflation has not reached the level to trigger illumination of the TPMS low tire pressure telltale.

Your vehicle has also been equipped with a TPMS malfunction indicator to indicate when the system is not operating properly. The

TPMS malfunction indicator is combined with the low tire pressure telltale. When the system detects a malfunction, the telltale will flash for approximately one minute and then remain continuously illuminated. This sequence will continue upon subsequent vehicle start-ups as long as the malfunction exists.

When the malfunction indicator is illuminated. the system may not be able to detect or signal low tire pressure as intended, TPMS malfunctions may occur for a variety of reasons, including the installation of replacement or alternate tires or wheels on the vehicle that prevent the TPMS from functioning properly.



The system uses a tire pressure sensor to check the pressure and temperature of the tires fitted on the vehicle.

The tire pressure and tire temperature appear on the driver's display.

If there is a substantial pressure loss or if the tire temperature is excessive, you will be warned by display messages ( $\rightarrow$  page 527) or the (!)

warning lamp on the driver's display  $(\rightarrow page 553)$ .

The tire pressure monitor is only an aid. It is the driver's responsibility to set the tire pressure to the recommended cold tire pressure suitable for the operating circumstances.

In most cases, the tire pressure monitor will automatically update the reference values after you have changed the tire pressure. You can, however, also update the reference values manually by restarting the tire pressure monitor  $(\rightarrow page 418)$ .

#### System limits

The system may be impaired or may not function. particularly if:

- incorrect reference values were taught in.
- sudden pressure loss occurs due to a foreign object penetrating the tire, for example.
- there is a malfunction caused by another radio signal source.

# Checking the tire pressure with the tire pressure monitoring system

### Requirements

• The vehicle is switched on.

#### Driver display:

- → 🔝 >> Service
- Press OK to confirm.

One of the following displays appears:

• Current tire pressure of each wheel:



 Tire pressure displayed after driving for a few minutes.: current values are not yet known to the system. The pressure/temperature values of each tire are displayed as soon as they are known to the system.

- Tire Pressure Monitor Active: the teach-in process of the system is not yet complete. The tire pressure are already being monitored.
- Compare the current tire pressure with the recommended tire pressure for the current operating status (→ page 415). Additionally, observe the notes on cold tires (→ page 413).
- The values displayed in the driver display may deviate from those of the tire pressure gauge as they relate to sea level. At high elevations, the tire pressure value indicated by a pressure gauge are higher than those shown on the driver display.

Bear in mind the following related topic:

- Notes on tire pressure (→ page 413)
- Restarting the tire pressure monitoring system

## Requirements

 The recommended tire pressure is correctly set for the respective operating condition on each of the four wheels (→ page 413). Restart the tire pressure monitoring system in the following situations:

- · The tire pressure has changed.
- The wheels or tires have been changed or newly installed.

# Driver display:

- → 🔝 ➤ Service
- Press **OK** to display the tire pressure.
- Press OK again to display the options.
- Select Tire Pressure and confirm with OK.
  The driver display shows the message Use current pressures as new reference values?.
- Select Yes and confirm the restart with OK.
   The driver display shows the message Tire
   Pressure Monitor Restarted.

Current warning messages are deleted and the U yellow warning lamp goes out.

After you have driven for a few minutes, the system checks whether the current tire pressures are within the specified range. The current tire pressures are then accepted as reference values and monitored.

If the tire pressure values are not within the prescribed range, the message Please Correct Tire Pressure appears.

Bear in mind the following related topic:

Notes on tire pressure (→ page 413)

# Tire pressure loss warning system

# ■ Function of the tire pressure loss warning system

The tire pressure loss warning system warns the driver by means of display messages when there is a severe tire pressure loss.

### System limits

The system may be impaired or may not function particularly in the following situations:

- incorrect reference values were taught in
- sudden pressure loss caused by a foreign object penetrating the tire, for example
- an even pressure loss on more than one tire occurs

The system has a restricted or delayed function particularly in the following situations:

- poor ground conditions, e.g. snow or gravel
- · driving with snow chains
- when adopting a very sporty driving style with high cornering speeds or sudden acceleration
- · driving with a high load

The tire pressure loss warning system is only an aid. It is the driver's responsibility to set the tire pressure to the recommended cold tire pressure suitable for the operating situation and to check it.

Be sure to also observe the following further related subjects:

- Notes on tire pressure (→ page 413)
- Display messages about the tires
   (→ page 527)

# Restarting the tire pressure loss warning system

### Requirements

 The recommended tire pressure is correctly set for the respective operating condition on each of the four wheels (→ page 413).

Restart the tire pressure loss warning system in the following situations:

- The tire pressure has changed.
- The wheels or tires have been changed or newly installed.

Driver display:

→ 🙀 >> Service

- Select Tire Pressure and confirm with OK.
  The driver display shows the message Run
  Flat Indicator Active.
- Press the steering wheel button OK to initiate the restart.

  The driver display shows the message Are the

current pressure values OK?.

Select Yes.

Press the steering wheel button OK to confirm the restart.

The driver display shows the message Run Flat Indicator Restarted.

Be sure to also observe the following further related topics:

Notes on tire pressure (→ page 413)

### Loading the vehicle

Notes on the Tire and Loading Information placard

A

**WARNING** Risk of accident from overloaded tires


Overloaded tires may overheat and burst as a consequence. Overloaded tires can also impair the steering and handling characteristics and lead to brake failure.

- Observe the load rating of the tires.
- The load rating must be at least half the permissible axle load of the vehicle.
- Never overload the tires by exceeding the maximum load.

The Tire and Loading Information placard is on the B-pillar on the driver's side of the vehicle.



Tire and Loading Information placard



i The data shown in the illustration are sample data.

The Tire and Loading Information placard shows the following information:

 Maximum number of seats ② according to the maximum number of people permitted to travel in the vehicle.

- Maximum permissible load (3) comprises the gross weight of all vehicle occupants, luggage and additional load.
- The recommended tire pressures are valid for the maximum permissible load and up to the maximum permissible vehicle speed.

#### Please also note:

- Information on permissible weights and loads on the vehicle identification plate  $(\rightarrow page 448)$ .
- Information on the tire pressure in the tire pressure table ( $\rightarrow$  page 415).

#### Further related subjects:

- Determining the maximum permissible load  $(\rightarrow page 421)$ .
- Notes on the tire pressure (→ page 413).

# Steps for determining the correct load limit

The following steps were developed according to the regulations of Title 49, Code of U.S. Federal

Regulations, Part 575, which are binding on all manufacturers, and the National Traffic and Motor Vehicle Safety Act of 1966.

- (1): Locate the statement "The combined weight of occupants and cargo should never exceed XXX kg or XXX lbs." on your vehicle's placard.
- (2): Determine the combined weight of the driver and passengers that will be riding in vour vehicle.
- (3): Subtract the combined weight of the driver and passengers from XXX kg or XXX lbs.
- (4): The resulting figure equals the available amount of cargo and luggage load capacity. For example, if the "XXX" amount equals 1400 lbs. and there will be five 150 lb passengers in your vehicle, the amount of available cargo and luggage load capacity is 650 lbs.  $(1400 - 750 (5 \times 150) = 650 \text{ lbs.})$
- (5): Determine the combined weight of luggage and cargo being loaded on the vehicle. That weight may not safely exceed the available cargo and luggage load capacity calculated in Step 4.

- (6): If your vehicle will be towing a trailer, load from your trailer will be transferred to your vehicle. Consult this manual to determine how this reduces the available cargo and luggage load capacity of your vehicle.
- Not all vehicles are permitted to tow a trailer. Towing a trailer is only permitted if a trailerhitch is installed. Please consult an authorized Mercedes-Benz dealer if you have any guestions about towing a tralier with your vehicle.

Even if you have calculated the total load carefully. you should still make sure that the maximum permissible gross weight and the maximum gross axle weight rating of your vehicle are not exceeded. Details can be found on the vehicle identification plate.

Have your loaded vehicle - including driver. occupants and load - weighed on a vehicle weighbridge.

The measured values may not exceed the maximum permissible values stated on the vehicle identification plate.

#### Further related subjects:

- · Calculation example for determining the maximum load ( $\rightarrow$  page 422)
- · Tire and loading information placard  $(\rightarrow page 420)$
- Tire pressure table(→ page 415)
- Vehicle identification plate (→ page 448)

# The following table shows examples of how to cal-

load

culate total and cargo load capacities with varying seating configurations and different numbers and weights of vehicle occupants. The following examples use a maximum load of 1500 lbs (680 kg).

Calculation example for determining the maximum

This is for illustration purposes only. Make sure you are using the actual load limit for your vehicle stated on your vehicle's Tire and Loading Information Placard ( $\rightarrow$  page 420).

The higher the weight of all the vehicle occupants, the smaller the maximum load for luggage.

# Step 1

	Example 1	Example 2
Combined maximum weight of vehicle occupants and load (data from the Tire and Loading Information Placard)	1500 lbs (680 kg)	1500 lbs (680 kg)


	Example 1	Example 2
Number of persons in the vehicle (driver and occupants)	5	1
Occupant distribution	Front: 2 Rear: 3	Front: 1
Weight of the vehicle occupants	Vehicle occupant 1: 150 lbs (68 kg) Vehicle occupant 2: 180 lbs (82 kg) Vehicle occupant 3: 160 lbs (73 kg) Vehicle occupant 4: 140 lbs (63 kg) Vehicle occupant 5: 120 lbs (54 kg)	Vehicle occupant 1: 200 lbs (91 kg)
Total weight of all vehicle occupants	750 lbs (340 kg)	200 lbs (91 kg)

# Step 3

	Example 1	Example 2
Permissible load (maximum gross vehicle weight from the Tire and Loading Information Placard minus the total weight of all occupants)	1500 lbs (680 kg) - 750 lbs (340 kg) = 750 lbs (340 kg)	1500 lbs (680 kg) - 200 lbs (91 kg) = 1300 lbs (589 kg)

## Tire labeling

## Overview of tire labeling




- Uniform Tire Quality Grading Standards
- DOT (Department of Transportation), (TIN) Tire Identification Number
- Maximum tire load (→ page 426)
- Maximum tire pressure (→ page 427)

- 6 Manufacturer
- Tire characteristics (→ page 427)
- Tire size designation, load-bearing capacity, speed rating and load index (→ page 427)
- Tire name
- (i) The data shown in the illustration is example data.

# Tire quality grading

In accordance with the US Department of Transportation's "Uniform Tire Quality Grading Standards," tire manufacturers are required to grade their tires on the basis of the following three performance factors:



- Tread wear grade
- Traction grade
- Temperature grade
- (i) The data shown in the illustration is example data.
- i The classification is not legally stipulated for Canada, but it is generally stated.

## Tread wear grade

The treadwear grade is a comparative rating based on the wear rate of the tire when tested under controlled conditions on a specified government test course. For example, a tire graded 150 would wear one and one-half (1\1/2\) times as

well on the government course as a tire graded 100

The relative performance of tires depends upon the actual conditions of their use, however, and may depart significantly from the norm due to variations in driving habits, service practices and differences in road characteristics and climate.

# Traction grade

DANGER Risk of accident due to inadequate traction

The traction grade assigned to this tire is based on straight-ahead braking traction tests.

- Always adapt your driving style and drive at a speed to suit the prevailing traffic and weather conditions.
- **NOTE** Damage to the drivetrain from wheelspin
- Avoid wheelspin.

The traction grades, from highest to lowest, are AA, A, B, and C. Those grades represent the tire's ability to stop on wet pavement as measured under controlled conditions on specified government test surfaces of asphalt and concrete. A tire marked C may have poor traction performance.

## Temperature grade

WARNING Risk of accident from tire overheating and tire failure

Excessive speed, underinflation, or excessive loading, either separately or in combination, can cause excessive heat build-up and possible tire failure.

- Observe the recommended tire pressure.
- Regularly check the pressure of all the tires.
- Adjust the tire pressure, if necessary.

The temperature grades are A (the highest), B, and C, representing the tire's resistance to the generation of heat and its ability to dissipate heat when tested under controlled conditions on a specified indoor laboratory test wheel. Sustained

high temperature can cause the material of the tire to degenerate and reduce tire life, and excessive temperature can lead to sudden tire failure. The grade C corresponds to a level of performance which all passenger car tires must meet under the Federal Motor Safety Standard No. 109. Grades B and A represent higher levels of performance on the laboratory test wheel than the minimum required by law.

# DOT, Tire Identification Number (TIN)

US tire regulations stipulate that every tire manufacturer or retreader must imprint a TIN in or on the side wall of each tire produced.



(i) The data shown in the illustration is example data

The TIN is a unique identification number to identify tires and comprises the following:

- DOT (Department of Transportation): tire symbol marks indicating that the tire complies with the requirements of the US Department of Transportation.
- Manufacturer identification code: manufacturer identification code ② contains details of the tire manufacturer. New tires have a code with two symbols. Retreaded tires have a code with four symbols. Further information on retreaded tires (→ page 432).
- Tire size: identifier (3) describes the tire size.
- Tire type code: tire type code an be used by the manufacturer as a code to describe specific characteristics of the tire.
- Manufacturing date: manufacturing date sprovides information about the age of a tire.
   The 1st and 2nd positions represent the calendar week and the 3rd and 4th positions

state the year of manufacture (e.g. "3208" represents the 32nd week of 2008).

#### Information on the maximum tire load

A

WARNING Risk of accident from overloaded tires

Overloaded tires may overheat and burst as a consequence. Overloaded tires can also impair the steering and handling characteristics and lead to brake failure.

- Observe the load rating of the tires.
- The load rating must be at least half the permissible axle load of the vehicle.
- Never overload the tires by exceeding the maximum load.



 The data shown in the illustration is example data.

Maximum tire load ① is the maximum permissible weight for which the tire is approved.

Do not overload the tires by exceeding the specified load limit. The maximum permissible load can be found on the vehicle's Tire and Loading Information placard on the B-pillar on the driver's side ( $\rightarrow$  page 420).

# Specifications for maximum tire pressure



(i) The data shown in the illustration is example data.

Never exceed maximum tire pressure (1) specified for the tire. Always observe the recommended tire pressure for your vehicle when adjusting the tire pressure ( $\rightarrow$  page 415).

### Information on tire characteristics



(i) The data shown in the illustration is example data.


This information describes the type of tire cord and the number of layers in side wall 1 and under tire tread 2.

# Tire size indication, load-bearing capacity, speed rating and load index

WARNING Risk of injury through exceeding the specified tire load-bearing capacity or the permissible speed rating

Exceeding the specified tire load rating or the permissible speed rating may lead to tire damage and to the tires bursting.

- Therefore, only use tire types and sizes approved for your vehicle model.
- Observe the tire load rating and speed rating required for your vehicle.



- Preceding letter
- Nominal tire width in millimeters
- Aspect ratio in %
- Tire code
- Rim diameter
- Load-bearing index
- Speed rating
- Load index
- i The data shown in the illustration is example data.

Information about reading tire data can be obtained from any qualified specialist workshop.

# Preceding letter 1:

- Without: passenger vehicle tire according to European manufacturer standards.
- "P": passenger vehicle tire according to US manufacturer standards
- "LT": light truck tire according to US manufacturer standards
- "T": compact emergency spare wheel with high tire pressure only designed for temporary use in an emergency.

# Aspect ratio (3):

Ratio between section height and tire width in percent (section height divided by tire width).

# Tire code (1) (tire type):

- "R" radial tire
- "D": bias ply tire
- . "B": bias belted tire
- "ZR": radial tire with a permissible maximum speed above 149 mph (240 km/h) (optional)

# Rim diameter 6:

The diameter of the bead seat (not the diameter of the rim flange). The rim diameter is specified in inches (in).

# Load-bearing index 6:

Numerical code that specifies the maximum load-bearing capacity of a tire (e.g. "91" corresponds to 1,356 lbs (615 kg)).

The load-bearing capacity of the tire must be at least half the permissible axle weight of the vehicle. Do not overload the tires by exceeding the specified load limit.

#### See also:

- Maximum permissible load on the Tire and Loading Information Placard (→ page 420)
- Maximum tire load (→ page 426)
- Load index

# Speed rating 2:

Indicates the approved maximum speed of the tire.

(i) An electronic speed limiter prevents your vehicle from exceeding a speed of 130 mph (210 km/h).

Make sure that your tires have the required speed rating. You can obtain information on the required speed rating from a Mercedes-Benz Service Center.

#### Summer tires

Index	Speed rating
Q	up to 100 mph (160 km/h)
R	up to 106 mph (170 km/h)
S	up to 112 mph (180 km/h)
T	up to 118 mph (190 km/h)
Н	up to 130 mph (210 km/h)
V	up to 149 mph (240 km/h)
W	up to 168 mph (270 km/h)

<sup>1 &</sup>quot;ZR" stated in the tire code.

Index	Speed rating
Υ	up to 186 mph (300 km/h)
ZRY 1	up to 186 mph (300 km/h)
ZR (Y) <sup>1</sup>	over 186 mph (300 km/h)
ZR <sup>1</sup>	over 149 mph (240 km/h)

- Specifying the speed rating as "ZR" index in the tire code (4) is optional for tires up to 186 mph (300 km/h).
- If your tire code (4) includes "ZR" and there is no speed rating , ask the tire manufacturer what the maximum permissible speed is.
- If the load-bearing index (6) and speed rating are in brackets, the permissible maximum speed of the tire is above 186 mph (300 km/h). To find out the maximum permissible speed, ask the tire manufacturer.

#### All-weather tires and winter tires

Index	Speed rating
Q M+S <sup>2</sup>	up to 100 mph (160 km/h)
T M+S <sup>2</sup>	up to 118 mph (190 km/h)
H M+S <sup>2</sup>	up to 130 mph (210 km/h)
V M+S <sup>2</sup>	up to 149 mph (240 km/h)

Winter tires bear the A snowflake symbol and fulfill the requirements of the Rubber Manufacturers Association (RMA) and the Rubber Association of Canada (RAC) regarding the tire traction on snow.

# Load index (3):

- · No specification given: standard load (SL) tire
- "XL" or "Extra Load": extra load tire or reinforced tire
- · "Light Load": light load tire

<sup>2</sup> Or "M+S 🔌 " for winter tires.

 "C", "D", "E": load range that depends on the maximum load that the ire can carry at a certain pressure.

# Definition of terms for tires and loading

**Tire structure and characteristics:** describes the number of layers or the number of rubber-coated belts in the tire contact surface and the tire wall. These are made of steel, nylon, polyester and other materials.

**Bar:** metric unit for tire pressure. 14.5038 pounds per square inch (psi) and 100 kilopascal (kPa) is the equivalent of one bar.

**DOT (Department of Transportation):** DOT-marked tires fulfill the requirements of the US Department of Transportation.

Average weight of the vehicle occupants: the number of vehicle occupants for which the vehicle is designed, multiplied by 150 lb (68 kg).

**Uniform tire quality grading standards:** a uniform standard to grade the quality of tires with regard to tread quality, tire traction and temperature characteristics. The quality grading assessment is

made by the manufacturer following specifications from the U.S. government. The quality grade of a tire is imprinted on the side wall of the tire.

Recommended tire pressure: the recommended tire pressure is the tire pressure specified for the tires fitted to the vehicle at the factory.

The tire and load information table contains the recommended tire pressure for cold tires, the maximum permissible load and the maximum permissible vehicle speed.

The tire pressure table contains the recommended tire pressure for cold tires under various operating conditions, i.e. loading and/or speed of the vehicle.

Increased vehicle weight due to optional equipment: the combined weight of all standard and optional equipment available for the vehicle, regardless of whether it is actually installed on the vehicle or not.

Rim: the part of the wheel on which the tire is mounted.

**GAWR (Gross Axle Weight Rating):** the GAWR is the maximum gross axle weight rating. The actual load on an axle must never exceed the gross axle

weight rating. The gross axle weight rating can be found on the vehicle identification plate on the B-pillar on the driver's side.

**Speed rating:** the speed rating is part of the tire identification. It specifies the speed range for which a tire is approved.

GVW (Gross Vehicle Weight): the gross vehicle weight comprises the weight of the vehicle including fuel, tools, spare wheel, fitted accessories, occupants, luggage and the trailer tongue weight, if applicable. The gross vehicle weight must not exceed the gross vehicle weight rating GVWR as specified on the vehicle identification plate on the B-pillar on the driver's side.

**GVWR (Gross Vehicle Weight Rating):** the GVWR is the maximum permitted gross weight of the fully laden vehicle (weight of the vehicle including all accessories, occupants, fuel, luggage and the trailer tongue weight if applicable). The gross vehicle weight rating is specified on the vehicle identification plate on the B-pillar on the driver's side.

Maximum weight of the laden vehicle: the maximum weight is the sum of the unladen weight of the vehicle, the weight of the accessories, the

maximum load and the weight of optional equipment installed at the factory.

Kilopascal (kPa): metric unit for tire pressure. 6.9 kPa corresponds to 1 psi. Another unit for tire pressure is bar. 100 kilopascal (kPa) equals 1 bar.

**Load index:** in addition to the load-bearing index. the load index may also be imprinted on the side wall of the tire. This specifies the load-bearing capacity of the tire more precisely.

Unladen weight: the weight of a vehicle with standard equipment including the maximum capacity of fuel, service fluids and coolant. It also includes the air conditioning system and optional equipment if these are installed in the vehicle, but does not include passengers or luggage.

Maximum tire load: the maximum tire load is the maximum permissible weight in kilograms or lbs for which a tire is approved.

Maximum permissible tire pressure: maximum permissible tire pressure for one tire.

Maximum load on one tire: maximum load per tire. This is calculated by dividing the maximum axle load of one axle by two.

PSI (pounds per square inch): standard unit of measurement for tire pressure.

Aspect ratio: ratio between tire height and tire width in percent.

**Tire pressure:** pressure inside the tire applying an outward force to every square inch of the tire. The tire pressure is specified in pounds per square inch (psi), in kilopascals (kPa) or in bar. The tire pressure should only be corrected when the tires are cold.

Cold tire pressure: the tires are cold when the vehicle has been parked for at least 3 hours without direct sunlight on the tires, or the vehicle has been driven for less than 1 mile (1.6 km).

Tire contact surface: the part of the tire that comes into contact with the road.

Tire bead: the purpose of the tire bead is to ensure that the tire sits securely on the wheel rim. There are several wire cores in the tire bead to prevent the tire from changing length on the wheel rim.

**Side wall:** the part of the tire between the tread and the tire bead.

Weight of optional equipment: the combined weight of the optional equipment weighing more than the replaced standard parts and more than 5 lbs (2.3 kg). This optional equipment, such as high-performance brakes, level control system, a roof luggage rack or high-performance batteries, is not included in the unladen weight and the weight of the accessories.

TIN (Tire Identification Number): a unique identification number which can be used by a tire manufacturer to identify tires, for example in a product recall, and thus identify the purchasers. The TIN is made up of the manufacturer's identity code, tire size, tire type code and the manufacturing date.

Load-bearing index: the load-bearing index is a code that contains the maximum load-bearing capacity of a tire.

**Traction:** traction is the grip resulting from friction between the tire and the road surface

Wear indicator: narrow bars (tread wear bars) that are distributed over the tire contact surface. If the tire tread is level with the bars, the wear limit of 1/16 in (1.6 mm) has been reached.

#### 432 Wheels and tires

**Distribution of vehicle occupants:** distribution of vehicle occupants over designated seat positions in a vehicle.

Maximum permissible payload weight: nominal load and luggage load plus 150 lb (68 kg) multiplied by the number of seats in the vehicle.

# Changing a wheel

Notes on selecting, mounting and replacing tires

- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- **WARNING** Risk of accident due to incorrect wheel and tire dimensions

If wheels and tires of the wrong size are installed, the service brakes or components in the brake system and in the wheel suspension may be damaged.

Always replace wheels and tires with ones that fulfill the specifications of the original part.

For wheels, pay attention to the following:

- Designation
- Type

For tires, pay attention to the following:

- Designation
- Manufacturer
- Type

WARNING Risk of injury through exceeding the specified tire load-bearing capacity or the permissible speed rating

Exceeding the specified tire load rating or the permissible speed rating may lead to tire damage and to the tires bursting.

- Therefore, only use tire types and sizes approved for your vehicle model.
- Observe the tire load rating and speed rating required for your vehicle.

! NOTE Vehicle and tire damage caused by non-approved tire types and sizes

For safety reasons, only use tires, wheels and accessories which have been specially approved by Mercedes-Benz for your vehicle.

These tires are specially adapted to the active safety systems, such as ABS, ESP® and 4MATIC, and marked as follows:

- MO = Mercedes-Benz Original
- MOE = Mercedes-Benz Original Extended (tires with run-flat characteristics for certain wheels only)
- MO1 = Mercedes-Benz Original (only certain AMG tires)

Otherwise, certain properties, such as driving characteristics, vehicle noise emissions, consumption, etc. could be adversely affected. Furthermore, other tire sizes could result in the tires rubbing against the body and axle components when loaded. This could result in damage to the tire or the vehicle.

! NOTE Risk to driving safety from retreaded tires

Retreaded tires are neither tested nor recommended by Mercedes-Benz, since previous damage cannot always be detected on retreaded tires.

For this reason driving safety cannot be guaranteed.

- Do not use used tires if you have no information about their previous usage.
- ! NOTE Possible wheel and tire damage when driving over obstacles

Large wheels have a smaller section width. As the section width decreases, the risk of wheels and tires being damaged when driving over obstacles increases.

- Avoid obstacles or drive especially carefully.
- Reduce your speed when driving over curbs, speed bumps, manhole covers and potholes.
- Avoid particularly high curbs.
- ! NOTE Possible wheel and tire damage when parking on curbs or in potholes

Parking on curbs or in potholes can damage the wheels and tires.

- Only park on as level a surface as possible.
- Avoid curbs and potholes when parking.
- I NOTE Damage to electronic components due to the use of mounting tools

Vehicles with a tire pressure monitoring system: there are electronic components in the wheel.

Using mounting tools in the area of the valve may damage the electronic components.

- Tire mounting tools should not be used in the area of the valve.
- Always have tires changed at a qualified specialist workshop.
- ! NOTE Damage to summer tires at low ambient temperatures

At low ambient temperatures, tears could form when driving with summer tires, causing permanent damage to the tires.

At temperatures below 45 °F (7 °C) use M+S tires.

Accessory parts which are not approved for your vehicle by Mercedes-Benz, or which are not used correctly, can impair the operating safety.

Before purchasing and using non-approved accessories, visit a qualified specialist workshop and inquire about:

- Suitability
- Legal stipulations
- · Factory recommendations

#### 434 Wheels and tires

# WARNING Risk of accidents with sports tires

The special tire tread in combination with the optimized tire compound means that the risk of skidding or hydroplaning on wet roads is increased.

In addition, the tire grip is greatly reduced at a low outside temperature and tire running temperature.

- Switch on ESP® and adapt your driving style accordingly.
- ► Use M+S tires at outside temperatures of less than 45°F (7°C).
- Only use tires suitable for the intended use.

Observe the following when selecting, mounting and replacing tires:

- The use of certain tire types in certain regions and areas of operation can be advisable.
- Only use tires and wheels of the same type (summer tires, winter tires, MOExtended tires) and of the same make.

• Only install wheels of the same size on one axle (left and right).

It is only permissible to install a different wheel size in the event of a flat tire in order to drive to the specialist workshop.

- Vehicles with tire pressure monitoring system: all installed wheels must be equipped with functioning sensors for the tire pressure monitoring system.
- At temperatures below 45 °F (7 °C), use winter tires or all-season tires marked M+S for all wheels.

Winter tires provide the best possible grip in wintry road conditions.

- For M+S tires, only use tires with the same tread pattern.
- Observe the maximum permissible speed for the fitted M+S tires.

If the tires' maximum speed is below that of the vehicle, this must be indicated by an appropriate label in the driver's field of vision.

• Break in new tires at moderate speeds for the first 60 miles (100 km).

- Replace the tires after six years at the latest, regardless of wear.
- When replacing with tires without run-flat characteristics: Vehicles with MOExtended tires are not equipped with a TIREFIT kit at the factory. Equip the vehicle with a TIREFIT kit after switching to tires without run-flat characteristics, e.g. winter tires.

For more information on wheels and tires, contact a qualified specialist workshop.

Be sure to also observe the following further related subjects:

- Notes on tire pressure (→ page 413)
- Tire and Loading Information Placard (→ page 420)
- Tire size indication, load-bearing capacity, speed rating and load index (→ page 427)
- Tire pressure table (→ page 415)
- Notes on the emergency spare wheel (→ page 442)

## Notes on rotating wheels

**WARNING** Risk of injury through different wheel sizes

Rotating the front and rear wheels can severely impair the driving characteristics.

The wheel brakes or suspension components may also be damaged.

Rotate front and rear wheels only if the wheels and tires are of the same dimensions.

Observe the instructions and safety notes on "Changing a wheel" ( $\rightarrow$  page 432).

The front and rear wheels are subject to different wear:

- Front wheels wear more on the tire shoulder.
- Rear wheels wear more in the center of the tire

Do not drive with tires that have too little tread depth. This significantly reduces traction on wet roads (hydroplaning).

On vehicles that have the same size front and rear wheels, rotate the wheels according to the intervals in the tire manufacturer's warranty booklet in vour vehicle documents. If this is not available. rotate the tires every 3,000 to 6,000 miles (5,000 to 10,000 km), depending on wear. Do not change the direction of wheel rotation.

# Notes on storing wheels

When storing wheels, observe the following notes:

- After removing wheels, store them in a cool, dry and preferably dark place.
- · Protect the tires from contact with oil, grease or fuel.


# Overview of the tire-change tool kit

With the exception of some country-specific variants, vehicles are not equipped with a tire-change tool kit. For more information on which tirechanging tools are required and approved for performing a wheel change on your vehicle, consult a qualified specialist workshop.

Required tire-change tool kit may include, forexample:

- lack
- Chock
- · Lug wrench
- · Alignment bolt

The tire-change tool kit (1) is located under the cargo floor.



The tire-change tool kit includes the following:

- Jack
- · Lug wrench
- · Wheel studs

#### 436 Wheels and tires

- Where applicable, extension piece for wheel studs (depending on vehicle version)
- · Folding chock
- · Ratchet wrench
- · Alignment bolt

## Preparing the vehicle for a wheel change

#### Requirements:

- The vehicle is not on a slope.
- The vehicle is on solid, non-slippery and level ground.
- The required tire-change tool kit is available.
- i If your vehicle is not equipped with the tirechange tool kit, consult a qualified specialist workshop to find out about suitable tools.
- Apply the electric parking brake manually.
- Move the front wheels to the straight-ahead position.
- Shift the transmission to position P.
- Switch off the vehicle.

- Make sure that the vehicle cannot be started.
- Place chocks or other suitable items under the front and rear of the wheel that is diagonally opposite the wheel you wish to change.
- Unload the vehicle.

# Removing and fitting wheel trim/hub caps

#### Requirements

 The vehicle is prepared for a wheel change (→ page 436).


#### Plastic hub cap Removal:

Turn the center cover of the hub cap anticlockwise and remove the hub cap.

#### Installation:

- Ensure that the center cover of the hub cap is turned anti-clockwise.
- Position hub cap and turn the center cover clockwise until hub cap engages physically and audibly.

## Aluminum hub cap



### Removal:

- Position socket ② from the tire-change tool kit on the hub cap ①.
- ► Attach wheel wrench ③ to the socket ②.
- Using the wheel wrench (3), turn the hub cap counterclockwise and remove it.

#### Installation:

- Follow the steps above in reverse order.
- i Specified tightening torque: 18 lb-ft (25 Nm).


## Raising the vehicle when changing a wheel

### Requirements

- There are no persons in the vehicle.
- The vehicle has been prepared for a wheel change ( $\rightarrow$  page 436).
- The wheel trims and hub caps have been removed ( $\rightarrow$  page 436).

Important notes on using the jack:

- Use only a vehicle-specific jack that has been approved by Mercedes-Benz to raise the vehicle.
- · The jack is only designed for raising and holding the vehicle for a short time while a wheel is being changed and not for maintenance work under the vehicle.
- The jack must be placed on a firm, flat and non-slip surface. If necessary, use a large, flat, load-bearing, non-slip underlay.
- . The foot of the jack must be positioned vertically under the jack support point.




Rules of conduct when the vehicle is raised:

- Never place your hands or feet under the vehicle.
- Never lie under the vehicle.
- Do not start the vehicle and do not release the electric parking brake.
- Do not open or close any doors or the tailgate.



Using the lug wrench, loosen the wheel bolts on the wheel you wish to change by about one full turn. Do not unscrew the screws completely.

#### 438 Wheels and tires



Position of the jack support points

- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- **WARNING** Risk of injury from incorrect positioning of the jack


If you do not position the jack correctly at the appropriate jacking point of the vehicle, the jack could tip with the vehicle raised.

Only position the jack at the appropriate jacking point of the vehicle. The base of the jack must be positioned vertically under the jacking point of the vehicle.

! NOTE Damage to the vehicle due to the jack

If you do not position the jack at the jack support points provided for this purpose, you could damage your vehicle.

- Only position the jack at the jack support points provided for this purpose.
- Take the ratchet out of the tire-change tool kit and place it on the hexagon nut of the jack so that the letters "AUF" are visible.



- Position support ② of jack ④ on jack support point ①.
- ➤ Turn ratchet ③ clockwise until support ② sits completely on jack support point ⑥ and the base of the jack lies evenly on the ground.
- Turn ratchet (3) until the tire is raised a maximum of 1.2 in (3 cm) from the ground.
- ▶ Loosen and remove the wheel ( $\rightarrow$  page 439).

### Requirements

- The vehicle is raised ( $\rightarrow$  page 437).
- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

When changing a wheel, avoid applying any force to the brake discs, as this could impair the level of comfort when braking.

! NOTE Damage to the wheels' plastic elements when changing a wheel

Plastic elements on wheels may be damaged when removing and repositioning the wheel.

Do not raise the wheels by the plastic elements when removing and repositioning.

- ! NOTE Damage to threading from dirt on wheel bolts
- Do not place wheel bolts in sand or on a dirty surface.
- Unscrew the uppermost wheel bolt completely.



- Screw centering pin (1) into the thread instead of the wheel bolt.
- Unscrew the remaining wheel bolts completely.
- Remove the wheel.
- Install the new wheel (→ page 439).

## Fitting a new wheel

### Requirements

- The wheel to be changed is removed and the centering pin is screwed in (→ page 439).
- NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- **WARNING** Risk of accident from losing a wheel

Oiled, greased or damaged wheel bolt/wheel nut threads or wheel hub/wheel mounting bolt threads can cause the wheel bolts/wheel nuts to come loose.

- Never oil or grease the threads.
- In the event of damage to the threads, contact a qualified specialist workshop immediately.
- Have the damaged wheel bolts or damaged hub threads replaced.

#### 440 Wheels and tires

- Do not continue driving.
- Observe the information on the choice of tires (→ page 432).

For tires with a specified direction of rotation, an arrow on the side wall of the tire indicates the correct direction of rotation. Observe the direction of rotation when fitting.

I NOTE Damage to the wheels' plastic elements when changing a wheel

Plastic elements on wheels may be damaged when removing and repositioning the wheel.

- Do not raise the wheels by the plastic elements when removing and repositioning.
- Slide the wheel to be mounted onto the centering pin and push it on.


**WARNING** Risk of injury from tightening wheel bolts and nuts

If you tighten the wheel bolts or wheel nuts when the vehicle is raised, the jack could tip.

- Only tighten wheel bolts or wheel nuts when the vehicle is on the ground.
- Be sure to observe the instructions and safety notes on "Changing a wheel" (→ page 432).
- For safety reasons, only use wheel bolts which have been approved by Mercedes-Benz and for the wheel in question.
- I NOTE Damage to paintwork of the wheel rim when screwing in the first wheel bolt

If the wheel has too much play when screwing in the first wheel bolt, the wheel rim paint can be damaged.

Press the wheel firmly against the wheel hub when screwing in the first wheel bolt. Tighten the wheel bolts evenly in a diagonal pattern in the order indicated until they are finger-tight.



- Unscrew and remove the centering pin.
- Tighten the last wheel bolt until it is fingertight.
- If the collapsible spare wheel has been fitted, inflate the collapsible emergency spare wheel (→ page 444).
- Lower the vehicle and tighten wheel bolts with the prescribed tightening torque. (→ page 441).

# Lowering the vehicle after a wheel change

### Requirements

- The new wheel has been installed (→ page 439).
- ! NOTE Damage to the emergency spare wheel when lowering the vehicle

Lowering the vehicle without previously inflating the emergency collapsible spare wheel can damage its rim.

- Inflate the emergency collapsible spare wheel using the tire inflation compressor before lowering the vehicle.
- I NOTE Risk of vehicle jack becoming trapped by the AIRMATIC system

If the AIRMATIC system has released air when raising the vehicle, the jack can become trapped when the vehicle is lowered.

- Start the engine. This adapts the vehicle level.
- Remove the jack from under the vehicle.

To lower the vehicle: place the ratchet onto the hexagon nut of the jack so that the letters "AB" are visible and turn counter-clockwise.



- Tighten the wheel bolts evenly in a diagonal pattern in the order indicated ① to ⑤ with an initial maximum force of 59 lb-ft (80 Nm).
- ➤ Tighten the wheel bolts evenly in a diagonal pattern in the order indicated ① to ⑤ with the specified tightening torque of 111 lb-ft (150 Nm).

**WARNING** Risk of accident due to incorrect tightening torque

The wheels could come loose if the wheel bolts or wheel nuts are not tightened to the prescribed torque.

- Ensure that the wheel bolts or wheel nuts are tightened to the prescribed tightening torque.
- If you are not sure, do not move the vehicle. Contact a qualified specialist workshop and have the tightening torque checked immediately.
- Check the tire pressure of the newly installed wheel and adjust it if necessary.
- i The following does not apply if the new wheel is an emergency spare wheel.
- Vehicles with a tire pressure loss warning system: restart the tire pressure loss warning system (→ page 419).
- Vehicles with a tire pressure monitoring system: restart the tire pressure monitoring system (→ page 418).

## Emergency spare wheel

## Notes on the emergency spare wheel

WARNING Risk of accident caused by incorrect wheel and tire dimensions

The wheel or tire sizes and the tire type of the emergency spare wheel or spare wheel and the wheel to be replaced may differ. The emergency spare wheel or spare wheel can significantly impair driving characteristics of the vehicle.

To prevent hazardous situations:

- Drive carefully.
- Never install more than one emergency spare wheel or spare wheel that differs in size.
- Only use an emergency spare wheel or spare wheel briefly.
- Do not deactivate FSP<sup>®</sup>.
- Have the emergency spare wheel or spare wheel of a different size replaced at the nearest qualified specialist work-

shop. The new wheel must have the correct dimensions.

(i) The emergency spare wheel is secured in the load compartment under the load compartment floor.

Observe the following notes on fitting an emergency spare wheel:

- The maximum permissible speed with an emergency spare wheel fitted is 50 mph (80 km/h).
- Do not mount snow chains on the emergency spare wheel.
- Replace the emergency spare wheel after six years at the latest, regardless of wear.
- Use the included wheel bolts of the emergency spare.
- Check the tire pressure of the fitted emergency spare wheel. Correct the pressure as necessary.
- (i) The specified tire pressure is stated on the label of the emergency spare wheel.

Vehicles with tire pressure loss warning system: if an emergency spare wheel is fitted, the tire pressure loss warning system cannot function reliably. Only restart the system again when the emergency spare wheel has been replaced with a new wheel.

Vehicles with tire pressure monitoring system: if an emergency spare wheel is fitted, the tire pressure monitoring system cannot function reliably. For a few minutes after an emergency spare wheel is fitted, the system may still display the tire pressure of the removed wheel. Only restart the system again when the emergency spare wheel has been replaced with a new wheel.

Be sure to also observe the following further related subjects:

- Notes on tire pressure (→ page 413)
- Tire and Loading Information Placard (→ page 420)
- Tire pressure table (→ page 415)
- Notes on mounting tires (→ page 432)
- Fitting an emergency spare wheel (→ page 436)

## Collapsible spare wheel

## Notes on the collapsible spare wheel

(i) The collapsible spare wheel is only available in AMG vehicles

**WARNING** Risk of accident caused by incorrect wheel and tire dimensions

The wheel or tire sizes and the tire type of the emergency spare wheel or spare wheel and the wheel to be replaced may differ. The emergency spare wheel or spare wheel can significantly impair driving characteristics of the vehicle.

To prevent hazardous situations:

- Drive carefully.
- Never install more than one emergency spare wheel or spare wheel that differs in size.
- Only use an emergency spare wheel or spare wheel briefly.
- Do not deactivate ESP®.

Have the emergency spare wheel or spare wheel of a different size replaced at the nearest qualified specialist workshop. The new wheel must have the correct dimensions.

**WARNING** Risk of injury- or death due to unsecured collapsible spare wheel

If the collapsible spare wheel is not secured correctly, it may shift, tip over or be thrown.

This can result in the vehicle occupants being seriously injured.

- Always store the collapsible spare wheel in the emergency spare wheel bag.
- Always ensure that the lashing straps on the emergency spare wheel bag are securely fastened to the rear tie-down eyelets on the load compartment floor and firmly tightened.
- (i) The collapsible spare wheel is secured in the spare wheel bag in the load compartment.

(i) The collapsible spare wheel is only available in certain countries.

Observe the following notes on fitting an emergency spare wheel:

- The collapsible spare wheel is an emergency spare wheel that is only suitable for temporary use under restricted conditions following a flat tire, e.g. to the nearest workshop.
- The side walls of the tire are folded when uninflated. Before using the collapsible spare wheel, inflate it with the compressor supplied.
- Check the tire pressure of the installed collapsible spare wheel and adjust it as necessary.
- The maximum permissible speed with a fitted collapsible spare wheel is 50 mph (80 km/h).
- Do not fit the collapsible spare wheel with snow chains.
- Replace the collapsible spare wheel after six years at the latest, regardless of wear.

#### 444 Wheels and tires

(i) Vehicles with a tire pressure monitoring system: if a collapsible spare wheel is fitted the tire pressure monitoring system cannot function reliably. The system may still display the tire pressure of the removed wheel for a few minutes. Only restart the system when the collapsible spare wheel has been replaced with a new wheel.

Be sure to also observe the following further related topics:

- Notes on tire pressure (→ page 413)
- Tire pressure table (→ page 415)

# Inflating the collapsible spare wheel

NOTE Damage to the collapsible spare wheel when lowering the vehicle

Lowering the vehicle without previously inflating the collapsible spare wheel can damage its rim.

Inflate the collapsible spare wheel using the tire inflation compressor before lowering the vehicle.


- ! NOTE Overheating due to the tire inflation compressor running too long
- Do not run the tire inflation compressor for longer than eight minutes without interruption.

#### Requirements

- Comply with the manufacturer's safety notes on the sticker on the tire inflation compressor and on the tire sealant bottle.
- Mount the collapsible spare wheel as described (→ page 436).

The collapsible spare wheel must be installed before it is inflated.

 Remove the tire inflation compressor from the stowage space under the load compartment floor (→ page 390).



- Pull the connector (5) and filling hose out of the tire inflation compressor housing.
- Unscrew the cap from the valve on the collapsible spare wheel.
- Screw the union nut 1 of the filling hose onto the valve.

If necessary, first unscrew the connector from the union nut.

- Make sure the on/off switch 2 of the tire inflation compressor is set to 0.
- Insert the connector (5) into a socket in your vehicle.
- 12-V-socket: (→ page 128)
- Observe the notes on sockets: (→ page 128)
- Switch on the vehicle.
- Press the on/off switch 2 on the tire inflation compressor to I. The tire inflation compressor is switched on. The tire is inflated. The tire pressure is shown on the manometer (3).
- Inflate the tire to the specified tire pressure. The specified tire pressure is printed in yellow on the collapsible spare wheel.
- When the specified tire pressure has been reached, press the on/off switch 2 on the tire inflation compressor to 0. The tire inflation compressor is switched off.
- Switch off the vehicle.
- If the tire pressure is higher than the specified pressure, press the pressure release valve but-

- ton 4 until the correct tire pressure has been reached.
- Unscrew the union nut 1 of the filling hose from the valve.
- If necessary, screw the connector back onto the union nut
- Screw the valve cap of the collapsible spare wheel onto the valve again.
- Stow the connector (5) and filling hose in the lower section of the compressor housing.
- > Stow the tire inflation compressor in the vehicle.

#### Notes on technical data

- I NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement.
   You could otherwise fail to recognize dangers.

The data stated only applies to vehicles with standard equipment. You can obtain further information from an authorized Mercedes-Benz Center.

## Vehicle electronics

Two-way radios

Notes on installing two-way radios



**WARNING** Risk of accident due to improper work on two-way radios

If two-way radios are manipulated or retrofitted incorrectly, the electromagnetic radiation from the two-way radios can interfere with the vehicle electronics and jeopardize the operating safety of the vehicle.

You should have all work on electrical and electronic components carried out at a qualified specialist workshop.



**WARNING** Risk of accident due to improper operation of two-way radios

If you use two-way radios in the vehicle improperly, their electromagnetic radiation can disrupt the vehicle's electronics. This is the case in the following situations, in particular:

- The two-way radio is not connected to an exterior antenna.
- The exterior antenna is installed incorrectly or is not a low-reflection antenna.


This could jeopardize the operating safety of the vehicle.

Have the low-reflection exterior antenna installed at a qualified specialist workshop.

- When operating two-way radios in the vehicle, always connect them to the lowreflection exterior antenna.
- NOTE Invalidation of the operating permit due to failure to comply with the instructions for installation and use

The operating permit may be invalidated if the instructions for installation and use of two-way radios are not observed.

- Only use approved frequency bands.
- Observe the maximum permissible output power in these frequency bands.
- Only use approved antenna positions.



Vehicles without panoramic sliding sunroof

Rear roof area

Rear root area

On vehicles with a panoramic sliding sunroof, installing an antenna is not permitted.

Use Technical Specification ISO/TS 21609 (Road Vehicles – "EMC guidelines for installation of aftermarket radio frequency transmitting equip-

ment") when retrofitting two-way radios. Comply with the legal requirements for detachable parts.

If your vehicle has fittings for two-way radio equipment, use the power supply and antenna connectors provided in the pre-installation. Observe the manufacturer's supplements when installing.

# Two-way radio transmission output

The maximum transmission output (PEAK) at the base of the antenna must not exceed the values in the following table.

Frequency band and maximum transmission output

Frequency band	Maximum transmis- sion output
2 m frequency band 144-174 MHz	50 W
Terrestrial Trunked Radio (TETRA) 380-460 MHz	10 W

Frequency band	Maximum transmis- sion output
Two-way radio 2G	2 W
Two-way radio 3G/4G/5G	0.5 W

The following can be used in the vehicle without restrictions:

- two-way radios with a maximum transmission output of 100 mW
- two-way radios with transmitter frequencies in the 380–410 MHz frequency band and a maximum transmission output of 2 W (TETRA)
- mobile phones (2G/3G/4G/5G)

There are no restrictions regarding the position of the antenna on the outside of the vehicle for the following frequency bands:

- Terrestrial Trunked Radio (TETRA)
- 2G/3G/4G/5G

# Radio regulations

# Regulatory radio identifiers and specific notes

Manufacturer information about radio-based vehicle components can be found using the key phrase "Regulatory radio information" in the Digital Operator's Manual in the vehicle, on the internet and in the app.

Further information and updates are available at the following web address:

https://
regulatoryradioinformation.corpinter.net/us



# Information about the specific absorption rate (SAR)

Information on the specific absorption rate (SAR) can be found under the key word "Regulatory

information" in the vehicle's Digital Operator's Manual, on the Internet and in the app.


Further information and updates are available at the following web address:


https://regulatoryradioinformation.corpinter.net/us



Vehicle identification plate, VIN and engine number overview

## Vehicle identification plate





Vehicle identification plate (USA only)

- Gross vehicle weight rating
- Maximum permissible front axle load
- Maximum permissible rear axle load
- Paint code
- (5) VIN (vehicle identification number)




Vehicle identification plate (Canada only)

- Gross vehicle weight rating
- Maximum permissible front axle load
- Maximum permissible rear axle load
- Paint code
- VIN (vehicle identification number)

The gross vehicle weight rating comprises the vehicle weight, all vehicle occupants, the fuel and the load. The gross axle weight rating is the maximum weight that can be carried on one axle (front or rear axle).


Do not exceed the gross vehicle weight rating or the gross axle weight rating for the front or rear axle.

# VIN below the right front seat



- Imprinted VIN (vehicle identification number)
- Floor covering

## Additional plates



- Plate with information regarding emissions testing, including confirmation of emissions guidelines at the U.S. federal level and for California
- Engine number stamped into the crankcase
- VIN (vehicle identification number) as a label at the lower edge of the windshield

# Operating fluids

## Notes on operating fluids

- ! NOTE Mercedes-AMG vehicles
- Observe the notes in the Supplement. You could otherwise fail to recognize dangers.
- **WARNING** Risk of injury due to harmful operating fluids

Operating fluids can be toxic.

- When using, storing and disposing of operating fluids, observe the imprints on the respective original containers.
- Always keep operating fluids in the sealed original container.
- Always keep children away from operating fluids.

**ENVIRONMENTAL NOTE** Pollution of the environment due to irresponsible disposal of operating fluids

Incorrect disposal of operating fluids can cause considerable damage to the environment.

 Dispose of operating fluids in an environmentally responsible manner.

Operating fluids include the following:

- Fuels
- Lubricants
- Coolant
- Brake fluid
- · Windshield washer fluid
- · Climate control system refrigerant

Only use products approved by Mercedes-Benz. Damage caused by the use of products that have not been approved is not covered by the Mercedes-Benz warranty or goodwill gestures.

• MB-Freigabe (e.g. MB-Freigabe 229.51)

the container.

• MB-Approval (e.g. MB-Approval 229.51)

Further information on approved operating fluids:

- in the Mercedes-Benz Specifications for Operating Fluids by entering the designation
  - At https://operatingfluids.mercedesbenz.com
- At a qualified specialist workshop

# **WARNING** Risk of fire or explosion from fuel

Fuels are highly flammable.

- Fire, open flames, smoking and creating sparks must be avoided.
- Before and during refueling, switch off the vehicle and, if installed, the stationary heater.

# **MARNING** Risk of injury from fuels

Fuels are poisonous and hazardous to your health.

- Do not swallow fuel or let it come into contact with skin, eyes or clothing.
- Do not inhale fuel vapor.
- Keep children away from fuel.
- Keep doors and windows closed during the refueling process.

If you or other people come into contact with fuel, observe the following:

- Immediately rinse fuel off your skin with soap and water.
- If fuel comes into contact with your eyes, immediately rinse them thoroughly with clean water. Seek medical attention immediately.
- If you swallow fuel, seek medical attention immediately. Do not induce vomiting.

Change immediately out of clothing that has come into contact with fuel.

Flexible-fuel vehicles can be refueled with the following fuel types:

- · premium-grade unleaded gasoline
- F85 fuel
- a mixture of E85 fuel and premium-grade unleaded gasoline

Flexible-fuel vehicles can be identified by the **Ethanol up to E85** sticker on the inside of the fuel filler flap.

Depending on the country, the fuels you can use in your vehicle may differ from the information in the Operator's Manual. The fuels that have been approved for your vehicle can be found on the instruction label on the inside of the fuel filler flap.

#### Fuel

# Information on fuel quality for vehicles with gasoline engine

Observe the notes on operating fluids ( $\rightarrow$  page 450).

NOTE Damage caused by the wrong type of fuel

Even small amounts of the wrong type of fuel can result in damage to the fuel system, the engine and the emission control system.

Refuel only with low-sulfur gasoline.

This fuel may contain up to 10 %- ethanol by volume. Your vehicle is suitable for use with F10- fuel.

Never refuel with any of the following fuels:

- Diesel
- Gasoline with more than 10 %- ethanol by volume, e.g. E15, E85, E100

- Gasoline with more than 3% methanol by volume-, e.g. M15, M30, M85, M100
- · Gasoline with metallic additives

If you accidentally did fill up with the wrong fuel:

- Do not start the vehicle.
- Consult a qualified specialist workshop.

If the available fuel is not sufficiently low in sulfur, it may produce unpleasant odors.

Refuel only with fuel that has at least the octane number specified on the information label inside the fuel filler flap ( $\rightarrow$  page 197).

Never refuel using gasoline with an even lower RON.

! NOTE Premature engine wear through unleaded regular gasoline

Impairment of the longevity and performance of the engine.

If unleaded premium grade gasoline is unavailable and you have to refuel using unleaded regular gasoline:

- Only fill the fuel tank to half full with unleaded regular gasoline and refill as soon as possible with unleaded premium grade gasoline.
- Do not drive at the maximum design speed.
- Avoid sudden acceleration and engine speeds over 3000 rpm.

Further information on fuel is available in the following locations:

- At a gas station
- · At a qualified specialist workshop
- On the https://www.mbusa.com (USA only)

# Information on additives in gasoline (vehicles with gasoline engine)

Observe the notes on operating fluids ( $\rightarrow$  page 450).

Even small amounts of the wrong additive may lead to malfunctions occurring.

Only add cleaning additives recommended by Mercedes-Benz to the fuel.

Mercedes-Benz recommends that you use brandname fuels with additives.

In some countries, the fuel available may not have sufficient additives. Deposits could build up in the fuel injection system as a result. In this case, in consultation with a qualified specialist workshop (e.g. an authorized Mercedes-Benz Service Center), mix the fuel with the cleaning additive recommended by Mercedes-Benz. Observe the notes and mixing ratios indicated on the tank.

#### ■ Tank content and fuel reserve

The total capacity of the fuel tank may vary depending on the vehicle equipment.

# Total fuel tank capacity

Model	
All models	16.4 gal (62.0 liters)

#### Fuel tank reserve

Model	
All models	1.8 gal (7.0 liters)

## Engine oil

# Notes on engine oil

Observe the notes on operating fluids ( $\rightarrow$  page 450).



- I NOTE Engine damage caused by an incorrect oil filter, incorrect oil or additives
- Do not use engine oils or oil filters other than those which meet the specifications necessary for the prescribed service intervals.
- Do not alter the engine oil or oil filter in order to achieve longer change intervals than prescribed.
- Do not use additives.
- Have the engine oil changed after the prescribed intervals.

Mercedes-Benz recommends having the oil changed at a qualified specialist workshop.

Only use engine oils approved for your vehicle by Mercedes-Benz.

# Engine oil quality and filling quantity

# Engine oil specification

Model	MB-Freigabe or MB Approval	
All models	229.71, 229.72*	

\* Recommended for the lowest possible fuel consumption (lowest SAE viscosity class in each case; observe possible restrictions of the approved SAE viscosity classes).

Use only engine oils of viscosity class SAE 0W-20. The following values refer to an oil change, including the oil filter.

# Engine oil filling quantity

Model	Quantity	
All models	6.3 US qt (6.0 liters)	

#### Notes on brake fluid

Please observe the notes on operating fluids ( $\rightarrow$  page 450).

**WARNING** Risk of an accident due to vapor pockets forming in the brake system

The brake fluid constantly absorbs moisture from the air. This lowers the boiling point of the brake fluid. If the boiling point is too low, vapor pockets may form in the brake system when the brakes are applied hard.

This causes the braking effect to be impaired.

Have the brake fluid renewed at the specified intervals.

Have the brake fluid regularly replaced at a qualified specialist workshop.

Only use a brake fluid according to MB-Freigabe or MB-Approval 331.0 approved by Mercedes-Benz.

#### Coolant

#### Notes on coolant

Observe the notes on operating fluids ( $\rightarrow$  page 450).

**WARNING** - Risk of fire and injury from antifreeze

If antifreeze comes into contact with hot component parts in the engine compartment, it may ignite.

- Allow the engine to cool down before adding antifreeze.
- Make sure that no antifreeze spills out next to the filler opening.
- Thoroughly clean off any antifreeze from component parts before starting the vehicle.
- NOTE Damage caused by incorrect coolant
  - Only use coolant that has been premixed with the required antifreeze protection.

Information on coolant is available at the following locations:

- In the Mercedes-Benz Specification for Operating Fluids 320.1
  - At https://operatingfluids.mercedesbenz.com
- At a qualified specialist workshop

NOTE Overheating at high outside temperatures

If an inappropriate coolant is used, the cooling system is not sufficiently protected against overheating and corrosion at high outside temperatures.

- Only use coolant approved for Mercedes-Benz.
- Observe the instructions in the Mercedes-Benz Specifications for Operating Fluids 320.1.

Have the coolant regularly replaced at a qualified specialist workshop.

Proportion of antifreeze concentrate in the cooling system:

- A minimum of 50% (antifreeze protection down to about -35°F (-37°C))
- A maximum of 55% (antifreeze protection down to -49°F (-45°C))

# Coolant filling capacity

# Coolant (engine)

Model	Capacity
All models	14.8 US qt (14.0 liters)

## Notes on windshield washer fluid

Observe the notes on operating fluids  $(\rightarrow page 450)$ .

**WARNING** - Risk of fire and injury from windshield washer concentrate

Windshield washer concentrate is highly flammable. It could ignite if it comes into contact with hot engine component parts or the exhaust system.

Make sure that no windshield washer concentrate spills out next to the filler opening.

**NOTE** Damage to the exterior lighting due to unsuitable windshield washer fluid

Unsuitable windshield washer fluid may damage the plastic surface of the exterior lighting.

Only use windshield washer fluid which is also suitable for use on plastic surfaces. e.g. MB SummerFit or MB WinterFit.

- ! NOTE Blocked spray nozzles caused by mixing windshield washer fluids
- Do not mix MB SummerFit and MB WinterFit with other windshield washer fluids.

Do not use distilled or de-ionised water. Otherwise, the fill level sensor may be triggered erroneously.

Recommended windshield washer fluid:

- · Above freezing point: e.g. MB SummerFit
- Below freezing point: e.g. MB WinterFit

For the correct mixing ratio, refer to the information on the antifreeze container.

Mix washing water with windshield washer fluid all year round.

## Refrigerant

# Notes on refrigerant

Observe the notes on operating fluids ( $\rightarrow$  page 450).

! NOTE Damage due to incorrect refrigerant

If a non-approved refrigerant is used, the climate control system may be damaged.

- ▶ Use only R-1234yf refrigerant.
- NOTE Damage to the climate control system due to incorrect refrigerant compressor oil
- Only use refrigerant compressor oil that has been approved by Mercedes-Benz.
- Do not mix the approved refrigerant compressor oil with a different refrigerant compressor oil.

Work on the climate control system may be carried out only at a qualified specialist workshop. All applicable regulations, as well as SAE standard J639, must be adhered to.

The information label on the climate control system for the refrigerant type and the refrigerant compressor oil (PAG oil) is located on the inside of the hood.



Information label

- Hazard and service warning symbols
- Refrigerant filling capacity
- 3 Applicable standards
- PAG oil part number
- GWP (global warming potential) of the refrigerant used
- Refrigerant type

Symbols 1 indicate the following:

- Possible dangers
- Maintenance work to be carried out at a qualified specialist workshop

# Filling capacity for refrigerant and PAG oil

# Refrigerant filling capacity

Model	
All models	$21.2 \pm 0.4$ oz $(600 \pm 10 \text{ g})$

# Filling capacity for PAG oil


Model	
All models	$2.8 \pm 0.4 \text{ oz}$ $(80 \pm 10 \text{ g})$

# Vehicle data

## Vehicle dimensions

The heights specified may vary as a result of the following factors:

- Tires
- Load
- · Condition of the suspension
- · Special equipment



- Height when open
- 2 Headroom

# Height when open and headroom

Model	<ul><li>Height when open</li></ul>	Headroom
All models	85.4 in (2168 mm)	78.3 in (1989 mm)

## Vehicle dimensions

All models		
Vehicle length	185.7 in (4716 mm)	
Vehicle width including exterior mirrors	81.7 in (2075 mm)	
Vehicle height	65.3 in (1659 mm)	
Wheelbase	113.7 in (2888 mm)	
Maximum ground clearance	8.2 in (208 mm)	
Minimum ground clearance	8.2 in (208 mm)	
Turning radius	38.7 ft (11.8 m)	

# Weights and loads

Bear in mind that items of special equipment increase the curb weight and reduce the payload. Vehicle-specific weight information can be found on the vehicle identification plate.

## Off-road driving


Also observe the notes on driving off-road, driving in mountainous terrain and fording ( $\rightarrow$  page 178).

# Fording

NOTE Damage caused by water when fording

Water can enter the engine compartment and vehicle interior in the following cases:

- The maximum permissible fording depth is exceeded when traveling through standing water.
- · A bow wave forms during fording.
- · Water accumulates when fording.
- Do not exceed the maximum permissible fording depth.
- Drive slowly through water.
- When driving through flowing water, be aware that the permissible fording depth is lower due to the accumulation of water.



The maximum permissible fording depth ① with roadworthy load is 11.8 in (30 cm).

Ready-to-drive load means:

- · Full fuel tank
- · All fluids are topped up
- With driver

# Notes on the angle of approach/departure

The specified values are maximum values for vehicles that are in ready-to-drive condition.



# Angle of approach/departure

Model	Front	Rear
All models	22.6°	23.1°

# Maximum gradeability

The vehicle's gradeability depends on the weight distribution in the vehicle, the terrain conditions and the road surface conditions.

The specified value applies when:

- · the vehicle is ready to drive.
- The surface conditions of the ground are good, enabling good traction.

A gradeability of 100 % corresponds to an incline of  $45\,^{\circ}$  .

Observe the notes on driving in mountainous terrain ( $\rightarrow$  page 178).

## Gradeability

Model	Maximum grade- ability	
All models	70%	

## Trailer hitch

#### General notes on the trailer hitch

Modifications to the cooling system may be necessary, depending on the vehicle model. Retrofitting a trailer hitch is permissible only if a trailer load is specified in your vehicle documents.

Further information can be obtained at a qualified specialist workshop.

Observe the information and notes on the trailer hitch ( $\rightarrow$  page 299).

# Mounting dimensions

Missing values were not available by the editorial deadline.

# Overhang dimension length

Model	Overhang dimension
All models	

#### Trailer load

(i) The tongue weight is not included in the trailer load.

The values for the **trailer load, braked** apply with a minimum start-off gradeability of 12%.

Missing values were not available at the time of going to press.

## Trailer load, braked

Model	
All models	

### Trailer load, unbraked

Model	
All models	

# Maximum tongue weight- and load capacity

I NOTE Damage caused by the trailer coming loose

If the tongue weight used is too low, the trailer may come loose.

- The tongue weight must not be below 110.2 lbs (50 kg).
- Use a tongue weight that is as close as possible to the maximum permissible tongue weight.
- NOTE Damage caused by the bicycle rack coming loose

When using a bicycle rack, both the maximal tongue weight and the maximal load capacity should be observed.

Do not exceed the permissible load capacity.

Missing values were not available at the time of going to press.

# Tongue weight

Model	Maximum tongue weight
All models	

# Load capacity

Model	Maximum load capa- city
All models	

# Permissible rear axle load (trailer operation)

Missing values were not available at the time of going to press.

Not for plug-in hybrid:

# Trailer operation axle load

All models	

## Display messages

#### Introduction

# Information about display messages

Display messages appear on the driver display.

Display messages with graphical symbols are simplified in the Operator's Manual and may differ from the symbols on the driver display. The driver display shows high-priority display messages in red. Certain display messages will be accompanied by a warning tone.

Please act in accordance with the display messages and follow the additional notes in the Operator's Manual.

For some display messages, symbols will also be shown:

- (i) Further information
- Hide display message

You can select the respective symbol by swiping left or right on the left-hand Touch Control. Press (i) to display further information on the central display. Press x to hide the display message.

You can hide display messages to be acknowledged by pressing the back button or with the left-hand Touch Control. The display messages will then be stored in the message memory.

Rectify the cause of a display message as quickly as possible.

High-priority display messages cannot be hidden. The driver display will show these display messages continuously until the cause of the display message has been rectified.

# Calling up saved display messages

Driver's display:

¬→ Service

The Message Memory: XXmessage appears on the driver's display.

- Scroll through the display messages by swiping upwards or downwards on the left-hand Touch Control.
- To exit the display: press the back button.

## Occupant safety

## Display messages



Restraint System Malfunction Service Required

# Possible causes/consequences and ▶ Solutions

- \* The restraint system is malfunctioning ( $\rightarrow$  page 43).
  - **A** WARNING Risk of injury due to malfunctions in the restraint system
  - Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.
  - Have the restraint system checked and repaired immediately at a qualified specialist workshop.

# Plug-in hybrid:

**DANGER** Risk of death due to the restraint system malfunctioning

Components in the restraint system may be activated unintentionally or not deploy as intended in an accident. In the event of an accident, the high-voltage on-board electrical system may not be deactivated as intended.

You may receive an electric shock if you touch the damaged components of the high-voltage on-board electrical system.

- Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- After an accident, switch off the vehicle immediately.

# Display messages



Front Left Malfunction Service Required (Example)

# Possible causes/consequences and ▶ Solutions

\* The restraint system is malfunctioning ( $\rightarrow$  page 43).

WARNING Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

► Have the restraint system checked and repaired immediately at a qualified specialist workshop.

# Plug-in hybrid:



**DANGER** Risk of death due to the restraint system malfunctioning

Components in the restraint system may be activated unintentionally or not deploy as intended in an accident. In the event of an accident, the high-voltage on-board electrical system may not be deactivated as intended.

You may receive an electric shock if you touch the damaged components of the high-voltage on-board electrical system.

- ▶ Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- After an accident, switch off the vehicle immediately.

## Display messages



Left Window Airbag Malfunction Service Required (Example)

Front Passenger Airbag Disabled See Operator's Manual

# Possible causes/consequences and ▶ Solutions

\* The restraint system is malfunctioning ( $\rightarrow$  page 43).

MARNING Risk of injury or fatal injury due to a malfunction in the window curtain airbag

The window curtain airbag might be triggered unintentionally or might not be triggered at all in the event of an accident.

- Have the window curtain airbag checked and repaired immediately at a qualified specialist workshop.
- \* The front passenger air bag and the front passenger knee air bag have been disabled even though an adult or a person of adult build is on the front passenger seat. If additional forces are applied to the seat, the weight the system detects may be too low.

**WARNING** Risk of injury or fatal injury due to a disabled front passenger airbag

If the front passenger airbag is disabled, the front passenger airbag will not be deployed in the event of an accident and cannot perform its intended protective function.

A person in the front passenger seat could then, for example, come into contact with the vehicle's interior, especially if the person is sitting too close to the cockpit.

- Make sure, both before and during the journey, that the status of the front passenger airbag is correct.
- Stop the vehicle immediately in accordance with the traffic conditions.
- Make sure that no objects are trapped under the front passenger seat.
- lacktriangle Check the status of the automatic front passenger air bag shutoff (ightarrow page 45).

Display messages	Possible causes/consequences and ▶ Solutions
	If necessary, consult a qualified specialist workshop immediately.
Front Passenger Airbag Enabled See Operator's Manual	* The front passenger air bag and the front passenger knee air bag will be enabled while the vehicle is in motion in the following situations:
	<ul> <li>even when a child, a small adult or an object weighing less than the system weight threshold is located on the from passenger seat</li> </ul>
	even when the front passenger seat is not occupied
	The system may detect objects or forces that are adding to the weight applied to the seat.
	<b>WARNING</b> Risk of injury or death when using a child restraint system while the front passenger airbag is enabled
	If you secure a child in a child restraint system on the front passenger seat and the front passenger airbag is enabled, the front passenger airbag can deploy in the event of an accident.
	The child could be struck by the airbag.
	▶ Ensure, both before and during the journey, that the status of the front passenger airbag is correct.
	NEVER use a rearward facing child restraint on a seat protected by an ACTIVE AIRBAG in front of it, DEATH or SERIOUS INJURY to the CHILD can occur.
	Stop the vehicle immediately in accordance with the traffic conditions.
	Make sure that no objects are trapped under the front passenger seat.

# **466** Display messages and warning/indicator lamps

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Check the status of the automatic front passenger air bag shutoff (→ page 45).</li> <li>If necessary, consult a qualified specialist workshop immediately.</li> </ul>
Occupant Presence Reminder Inoperative	<ul> <li>* The occupant presence reminder is malfunctioning</li> <li>Consult a qualified specialist workshop.</li> </ul>
Do Not Leave People or Animals in the Vehicle	<ul> <li>* The occupant presence reminder suspects that there are persons or animals in the rear passenger compartment of the vehicle.</li> <li>▶ Do not leave any persons or animals behind when leaving the vehicle.</li> </ul>

# SmartKey

Display messages	Possible causes/consequences and ▶ Solutions
Obtain a New Key	<ul> <li>* Have the key replaced.</li> <li>▶ Consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	The key battery is weak or discharged.
	<ul> <li>Check the battery using the indicator lamp (→ page 73).</li> <li>Replace the key battery, if necessary (→ page 75).</li> </ul>
	<ul> <li>* The vehicle is processing in order to teach in the new key.</li> <li>▶ Wait until processing is complete.</li> </ul>
Initializing Key Please Wait	
8	* A warning tone will also sound. This message reminds you to take your key with you when you leave the vehicle.
Don't Forget Your Key	
Place the Key in the Marked Space See Opera-	<ul> <li>* Key detection is malfunctioning.</li> <li>Change the location of the key in the vehicle.</li> </ul>
tor's Manual	▶ Place the key in the slot for starting the engine with the key ( $\rightarrow$ page 171).

## Lights

Display messages	Possible causes/consequences and ▶ Solutions
Check Left Low Beam (example)	<ul> <li>* The corresponding light source is malfunctioning.</li> <li>Drive on carefully.</li> <li>Consult a qualified specialist workshop immediately.</li> <li>(i) LED light sources: the display message for the corresponding light appears only when all the light-emitting diodes in the light are faulty.</li> </ul>
Malfunction See Operator's Manual	* The exterior lighting is malfunctioning.  ▶ Consult a qualified specialist workshop.
Automatic Driving Lights Inoperative	<ul> <li>* The light sensor for automatic driving lights is malfunctioning.</li> <li>Consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Switch On Headlights	* You are driving without low-beam headlamps.  Turn the light switch to the D or AUTO position.
Switch Off Lights	* You are leaving the vehicle and the lights are still switched on.  Turn the light switch to the AUTO position.
DIGITAL LIGHT Functions Limited	* The DIGITAL LIGHT system is malfunctioning. The lighting system will continue to work even without the functions of the DIGITAL LIGHT system.  Consult a qualified specialist workshop.
Adaptive Highbeam Assist Currently Unavailable See Operator's Manual	<ul> <li>* Adaptive Highbeam Assist is temporarily unavailable. The system limits have been reached (→ page 139). Once the cause of the problem is no longer present, the system will be available again. The Adaptive Highbeam Assist Now Available display message will appear. Drive on. Operate the high beam manually until Adaptive Highbeam Assist is available again. </li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Adaptive Highbeam Assist Inoperative	<ul> <li>* Adaptive Highbeam Assist is malfunctioning.</li> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> <li>Until then, operate the high beam manually.</li> </ul>
Adaptive Highbeam Assist Plus Currently Unavailable See Operator's Manual	<ul> <li>* Adaptive Highbeam Assist Plus is temporarily unavailable.         The system limits have been reached (→ page 140).         Once the cause of the problem is no longer present, the system will be available again. The Adaptive Highbeam Assist Plus Now Available display message will appear.         Drive on.         Operate the high beam manually until Adaptive Highbeam Assist Plus is available again.     </li> </ul>
Adaptive Highbeam Assist Plus Inoperative	<ul> <li>* Adaptive Highbeam Assist Plus is malfunctioning.</li> <li>Drive on.</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> <li>Until then, operate the high beam manually.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Hazard Warning Light Mal- function	<ul> <li>* The hazard warning lamp switch is malfunctioning.</li> <li>Consult a qualified specialist workshop.</li> </ul>

### Climate control

Display messages	Possible causes/consequences and ▶ Solutions
Currently Not Available Charging of the High-voltage Battery Not Completed	* The high-voltage battery is charging. Pre-entry climate control cannot be switched on.  Wait until the charging process has achieved a minimum condition of charge.
Currently Not Available Charge High-voltage Battery	* The charge of the high-voltage battery is too low. Pre-entry climate control cannot be switched on.  ➤ Charge the high-voltage battery (→ page 200).

Display messages	Possible causes/consequences and ▶ Solutions
Pre-entry Climate Control Available Again via Smart- Key after Vehicle Start	* You have attempted to switch on pre-entry climate control more than twice with the vehicle switched off.  Start the vehicle for ten seconds.  Pre-entry climate control is operational again.
Pre-entry Climate Control via SmartKey Currently Not Available. High-voltage Battery Low	<ul> <li>* The charge of the high-voltage battery is too low. Pre-entry climate control cannot be switched on.</li> <li>▶ Charge the high-voltage battery (→ page 200).</li> <li>When the high-voltage battery is sufficiently charged, pre-entry climate control will be operational again.</li> </ul>

## Drive system

Display messages	Possible causes/consequences and ▶ Solutions
Towing Not Permitted See Operator's Manual	<ul> <li>* The drive system is malfunctioning.</li> <li>▶ Have the vehicle transported using only a transporter or trailer (→ page 403).</li> </ul>
Acoustic Presence Indicator Inoperative	<ul> <li>* The sound generator (acoustic vehicle warning system) is malfunctioning. No vehicle noises are being produced. The vehicle may not be heard by other road users.</li> <li>Drive with particular care.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Charger Cable Connected	* You cannot pull away while the charging cable is connected.  Disconnect the charging cable from the vehicle.
Not Possible to Unlock Charging Cable See Opera- tor's Manual	* The charging cable connector cannot be removed from the vehicle socket.  If the charging cable is under strain, relieve the strain on the charging cable connector by carefully pulling on the charging cable.

Display messages	Possible causes/consequences and ▶ Solutions
Authentication Failed Use Different Authentication Method or Charging Station	<ul> <li>Plug-and-Charge is not expected to be available at this charging station.</li> <li>Use an alternative authentication method or payment method.</li> <li>or</li> <li>Start the charging process at a different charging station.</li> </ul>
Only Electric Drive Available Power Limited	<ul> <li>* The fuel tank is empty and the combustion engine is switched off. The output of your vehicle is limited because you are driving in electric mode.</li> <li>Refuel immediately.</li> <li>Subsequently, there may be temporary restrictions in the availability of electric mode over a distance of 31 mi (50 km).</li> <li>If there is fuel in the vehicle, there is a malfunction with the combustion engine.</li> <li>Consult a qualified specialist workshop.</li> </ul>
"Electric" Drive Program Currently Unavailable	<ul> <li>* The state of charge of the high-voltage battery or the ambient conditions are not sufficient for the Electric drive program.</li> <li>▶ Drive on and observe the notes on plug-in hybrid operation (→ page 166).</li> <li>or</li> <li>▶ Charge the high-voltage battery (→ page 200).</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Reduced Drive System Per- formance See Operator's Manual	<ul> <li>* The drive system switches to emergency operation mode due to a malfunction.</li> <li>Drive on carefully.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Preparing Drive System	* The insulation of the drive system is being tested. This process can last for up to ten seconds.
Battery Overheated Stop! Everyone Get Out! Out-doors if Possible	<ul> <li>* Plug-in hybrid: the high-voltage battery has overheated. There is a risk of fire.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions.</li> <li>If possible, stop the vehicle in the open air and ensure that all vehicle occupants get out.</li> <li>① Supporting vehicle functions may activate automatically, e.g. air-recirculation mode as part of climate control.</li> <li>Do not continue driving.</li> <li>If smoke is present, leave the danger zone and call the fire service immediately.</li> <li>Consult a qualified specialist workshop even if there are no external signs of a fire.</li> </ul>
Malfunction	* The drive system is malfunctioning. A warning tone will also sound.  Consult a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Malfunction Service Required	<ul> <li>* The drive system is malfunctioning.</li> <li>▶ Consult a qualified specialist workshop.</li> </ul>
Have High-Voltage System Checked See Operator's Manual	* A function restriction has occurred in the drive system.  Consult a qualified specialist workshop.
Service Required Do Not Change Transmission Posi- tion	<ul> <li>* The transmission is malfunctioning. It is no longer possible to change the transmission position.</li> <li>If transmission position  is selected, consult a qualified specialist workshop and do not change the transmission position.</li> <li>For all other transmission positions, park the vehicle safely.</li> <li>Consult a qualified specialist workshop or breakdown service.</li> </ul>
Do Not Restart Vehicle Service Required	* It is not possible to restart the drive system due to a malfunction.  Do not switch off the drive system; drive on to the nearest qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Drive Power and Range Reduced See Operator's Manual	<ul> <li>* A malfunction has occurred in the high-voltage battery.</li> <li>Output and range will be severely restricted.</li> <li>➤ Switch the vehicle off and lock it.</li> <li>➤ After waiting for a short time, unlock the vehicle and start it again.</li> <li>If the display message appears again:</li> <li>➤ Drive on carefully.</li> <li>➤ Fully charge the high-voltage battery (→ page 200).</li> <li>If the output and range are still reduced, there is a malfunction in the drive system.</li> </ul>
Cannot Start Vehicle See Operator's Manual	<ul> <li>Drive on carefully.</li> <li>Consult a qualified specialist workshop.</li> <li>* It is not possible to start the vehicle.</li> <li>A malfunction has occurred in the drive system.</li> <li>Switch the vehicle off and lock it.</li> <li>After waiting for a short time, unlock the vehicle and start it again.</li> <li>If the display message appears again and the vehicle does not start, consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Drive Malfunction Achieva- ble Speed Limited Stop Soon	<ul> <li>* The drive system is malfunctioning.</li> <li>The maximum vehicle speed is restricted. The drive system will shut off within a few kilometers.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions and switch off the drive system. Do not continue driving.</li> <li>Do not tow the vehicle; stop towing if necessary.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Drive Malfunction Achieva- ble Speed Severely Limited See Operator's Manual	<ul> <li>* The drive system is malfunctioning.</li> <li>The maximum vehicle speed is restricted.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Malfunction	<ul> <li>* The drive system is malfunctioning. The output of your vehicle is restricted.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Stop Switch Off Vehicle	<ul> <li>* The drive system is malfunctioning.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions and switch off the drive system. Do not continue driving.</li> <li>Do not tow the vehicle; stop towing if necessary.</li> <li>Consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	* The drive system is outside the normal operating temperature range, e.g. due to extremely low or high outside temperatures.
	The output is severely restricted.
Performance Extremely Limited	Once the operating temperature of the drive system returns to normal, the full output will be available again. The display message will disappear.
	* If the drive system power output is still reduced, there is a malfunction in the drive system.
	▶ Drive on carefully.
	Consult a qualified specialist workshop.
<b>₽</b> 0	* Vehicles with gasoline engine: The pressure in the fuel tank is reduced before the fuel filler flap is opened. This pressure reduction can take up to 15 minutes.
Please Wait Depressurizing Fuel Tank	
<b>₽</b> 0	* Vehicles with gasoline engine: The pressure in the fuel tank is released and the fuel filler flap opens.
Fuel Tank Is Depressurized Ready for Refueling	

#### Display messages



Tank Ventilation Malfunction Service Required

#### Possible causes/consequences and ▶ Solutions

- \* Vehicles with gasoline engine: There is a malfunction in the fuel system.
  - Consult a qualified specialist workshop.

#### Vehicle

#### Display messages



#### Possible causes/consequences and ▶ Solutions

\* The driver display is inoperative due to a failed software update.

The display message will be shown every time the engine is started.

**WARNING** Risk of accident if the driver's display fails

If the driver's display fails or malfunctions, you may not be aware of any functional limitations to safety-critical systems. This may affect the operating safety of the vehicle.

Park the vehicle safely as soon as possible and notify a qualified specialist workshop.

If the operating safety of your vehicle is impaired, park the vehicle immediately and safely. Contact a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
	If the driver display fails, you may not recognize function restrictions affecting systems relevant to safety or the speed display, for example. The operating safety of the vehicle may be impaired (→ page 325).
	► Have the vehicle checked by a qualified specialist workshop immediately.
Cannot Start Vehicle See Operator's Manual	<ul> <li>* The vehicle cannot be started.</li> <li>➤ Switch the vehicle off and switch it back on.</li> <li>➤ If the display message still appears, consult a qualified specialist workshop.</li> <li>* Vehicles with 48 V on-board electrical system: the state of charge of the 48 V battery is too low. You can no longer start the vehicle.</li> <li>➤ Switch off electrical consumers that are not required.</li> <li>➤ Connect a suitable charger approved for Mercedes-Benz with sufficient charging power to the jump-start connection point of the 12 V battery (→ page 400).</li> <li>The 48 V battery is charged via the voltage converter in the vehicle.</li> </ul>
Vehicle Ready to Drive Shutdown Occurs When Locked or After a Few Minutes	<ul> <li>* You are leaving the vehicle in a ready-to-drive state.</li> <li>Description of the vehicle, secure it against rolling away and take the key with you.</li> <li>If you do not leave the vehicle, switch off the electrical consumers, e.g. the seat heating. Otherwise, the 12-V battery may discharge and starting the engine may be possible only with the help of a second battery (starting assistance).</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Vehicle Ready to Drive Shutdown Occurs When Locked or Automatically in XX Mins	* You are about to leave the vehicle and the engine is running.  The vehicle will switch off automatically in 20 minutes.
	To prevent the vehicle from switching off automatically, confirm the message in the central display of the multimedia system.
	* You are in the vehicle. Park position P is engaged and the engine is running.
	After a certain time of being at a standstill, this display message will appear in the driver's display. The vehicle will then be automatically switched off after a total parked time of 20 minutes.
	To prevent the vehicle from switching off automatically, confirm the message in the central display of the multimedia system.
Head-up Display Currently Unavailable See Operator's Manual	<ul> <li>* The head-up display is temporarily unavailable. Possible causes are:</li> <li>• malfunctions in the power supply</li> <li>• signal interference</li> </ul>
	<ul> <li>Stop in accordance with the traffic conditions and switch the vehicle off and on again.</li> <li>If the display message still appears, consult a qualified specialist workshop.</li> </ul>
Head-up Display Inoperative	<ul> <li>* The head-up display has an internal error.</li> <li>Consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Head-up Display Bright- ness Currently Reduced See Operator's Manual	<ul> <li>* The brightness of the head-up display is reduced. Possible causes:</li> <li>• Dirt on the windshield in the camera's field of vision</li> <li>• Faulty exterior brightness signals</li> </ul>
	<ul> <li>Switch on the windshield wipers.</li> <li>Clean the windshield if necessary.</li> <li>Switch the vehicle off and switch it back on</li> <li>If the display message still appears, consult a qualified specialist workshop.</li> </ul>
Steering Malfunction Drive Carefully Service Required	<ul> <li>* A power steering malfunction has occurred. Steering characteristics may be impaired as a result.</li> <li>Drive on carefully.</li> <li>Consult a qualified specialist workshop.</li> </ul>
(A)	* The power steering assistance is malfunctioning.
Steering Malfunction Increased Physical Effort See Operator's Manual	<ul> <li>WARNING Risk of an accident due to altered steering characteristics</li> <li>If the power assistance of the steering fails partially or completely, you will need to use more force to steer.</li> <li>If safe steering is possible, drive on carefully.</li> <li>Visit or consult a qualified specialist workshop immediately.</li> </ul>

#### Display messages Possible causes/consequences and ▶ Solutions \* The steering is malfunctioning. Steering capability is significantly impaired. WARNING Risk of accident if steering capability is impaired **Steering Malfunction Stop** If the steering does not function as intended, the vehicle's operating safety is jeopardized. Immediately See Opera-▶ Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do tor's Manual not continue driving under any circumstances. Consult a qualified specialist workshop. \* The rear axle steering is temporarily unavailable. The turning circle may become wider. Stop the vehicle in accordance with the traffic conditions and restart the vehicle. If the display message does not disappear: Rear Axle Steering Currently Malfunctioning Drive on carefully. Consult a qualified specialist workshop. \* The rear axle steering is malfunctioning. The rear axle has no steering capability. The steering wheel may be at an angle when you drive in a straight line. Rear Axle Steering Malfunc-Adapt your speed and drive on carefully. tion Service Required

Consult a qualified specialist workshop immediately.

Display messages	Possible causes/consequences and ▶ Solutions
Rear Axle Steering Malfunction Stop Immediately	* The rear axle steering is malfunctioning.  The rear axle has no steering capability.  The steering wheel may be tilted considerably when you drive in a straight line.  Depending on the steering wheel's tilted position, the steering wheel will also vibrate and a continuous warning tone will sound.
	<b>★</b> WARNING Risk of accident if steering capability is impaired
	If the steering does not function as intended, the vehicle's operating safety is jeopardized.  Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.  Consult a qualified specialist workshop.
	▶ When stopping, bear the enlarged vehicle width in mind.
Snow Chain Mode Maximum Speed Exceeded	<ul> <li>* The maximum permissible speed for snow chain mode has been exceeded.</li> <li>Drive more slowly.</li> </ul>
	<ul><li>* At least one door is open.</li><li>▶ Close all doors.</li></ul>

Display messages	Possible causes/consequences and ▶ Solutions
$\sim$	* The hood is open.
<i>∕</i> 0−−0 <i>⟩</i>	WARNING Risk of accident due to driving with the hood unlocked
	The hood may open and block your view.
	Never release the hood when driving.
	▶ Before every trip, ensure that the hood is locked.
	<ul><li>Stop the vehicle immediately in accordance with the traffic conditions.</li><li>Close the hood.</li></ul>
6-05	* The tailgate is open.
	▲ DANGER Risk of exhaust gas poisoning
	Combustion engines emit poisonous exhaust gases such as carbon monoxide. Exhaust gases can enter the vehicle interior if the tailgate is open when the engine is running, especially if the vehicle is in motion.  Always switch off the engine before opening the tailgate.
	Never drive with the tailgate open.
	Close the tailgate.

Display messages	Possible causes/consequences and ▶ Solutions
Rear Left Backrest Not Latched (example)	* The seat backrest of the corresponding seat is not engaged.  Fold the seat backrest back until it engages.
Add Washer Fluid	<ul> <li>* The washer fluid level in the washer fluid reservoir has dropped below the minimum.</li> <li>▶ Add washer fluid (→ page 376).</li> </ul>
Windshield Wiper Malfunction	<ul> <li>* The windshield wiper is malfunctioning.</li> <li>Nestart the vehicle.</li> <li>If the display message still appears:</li> <li>Consult a qualified specialist workshop.</li> </ul>

## Engine

Display messages	Possible causes/consequences and ▶ Solutions
To Switch Off Vehicle Press and Hold Start/Stop Button for at Least 3 Sec- onds or Press 3 Times	<ul> <li>You have pressed the start/stop button while the vehicle is in motion.</li> <li>▶ Information about switching off the vehicle while driving (→ page 170).</li> </ul>
T_	* The coolant level is too low.
1	I NOTE Engine damage due to insufficient coolant
Check Coolant Level See	Avoid long journeys with insufficient coolant.
Operator's Manual	<ul> <li>Add coolant (→ page 376).</li> <li>Have the engine cooling system checked at a qualified specialist workshop.</li> </ul>
Carlant Star Suitab Off	* The coolant is too hot.  Stop immediately in accordance with the traffic conditions and switch off the vehicle.
Coolant Stop Switch Off Vehicle	

Display messages	Possible causes/consequences and ▶ Solutions
	▲ WARNING Risk of burns when opening the hood
	If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:
	You may come into contact with hot gases.
	You may come into contact with other escaping hot operating fluids.
	▶ Before opening the hood, allow the engine to cool down.
	In the event of a fire in the engine compartment, keep the hood closed and call the fire service.
	► Wait until the engine has cooled down.
	Make sure that the air supply to the radiator is not obstructed.
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop. In doing so, ensure that the coolant temperature display remains below the red marking.
Fuel Reserve	* The fuel supply has dropped into the reserve range.  Refuel.

Display messages	Possible causes/consequences and ▶ Solutions
Fuel Filler Cap Open	<ul> <li>* The fuel filler cap is not closed correctly or the fuel system is leaking.</li> <li>Close the fuel filler cap.</li> <li>If the fuel filler cap was already properly closed: consult a qualified specialist workshop.</li> </ul>

## Transmission

Display messages	Possible causes/consequences and ▶ Solutions
Shift to P Only When Vehi- cle Is Stationary	<ul> <li>* It is possible to select the park position P only if the vehicle is stationary.</li> <li>Depress the brake pedal to stop.</li> <li>Shift the transmission to park position P when the vehicle is stationary.</li> </ul>
Depress Brake to Shift from P	<ul> <li>You have attempted to shift the transmission out of park position P and into another transmission position.</li> <li>Depress the brake pedal.</li> <li>Select transmission position D, R or neutral N.</li> </ul>
To Deselect P or N Depress Brake and Start Vehicle	<ul> <li>You have attempted to shift the transmission out of park position P or neutral N and into another transmission position.</li> <li>Depress the brake pedal.</li> <li>Start the vehicle.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	➤ Change the transmission position.
Depress Brake to Shift to D or R	<ul> <li>You have attempted to select transmission position D or R.</li> <li>Depress the brake pedal.</li> <li>Select transmission position D or R.</li> </ul>
Depress Brake to Shift to R	<ul> <li>You have attempted to select transmission position R.</li> <li>Depress the brake pedal.</li> <li>Select transmission position R.</li> </ul>
Service Required Apply Parking Brake to Park	<ul> <li>* A malfunction has occurred in the emergency power supply to park position P.</li> <li>Consult a qualified specialist workshop.</li> <li>Until then, always select park position P manually before you switch off the vehicle.</li> <li>Before leaving the vehicle, apply the electric parking brake.</li> </ul>
Risk of Vehicle Rolling Away Driver's Door Open Position P Not Selected	<ul> <li>* The driver's door is not fully closed and transmission position D, R or neutral N is selected.</li> <li>The vehicle may roll away.</li> <li>▶ Select park position P when switching off the vehicle.</li> </ul>
Risk of Vehicle Rolling Away Apply Parking Brake When Parking	<ul> <li>* The transmission is malfunctioning. Park position P cannot be selected.</li> <li>Park the vehicle safely.</li> <li>Use the electric parking brake to secure the vehicle against rolling away.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	On gradients, turn the front wheels so that the vehicle will roll towards the curb if it starts moving.
Risk of Vehicle Rolling Away N Activated Manually No Automatic Change to P	* While the vehicle was at a standstill or driving at very low speed, neutral <b>N</b> was engaged with the engine running or the vehicle switched on.
	NOTE Damage to the vehicle due to rolling away
	When the vehicle is switched off or the driver's door is opened, automatic engagement of park position [P] is deactivated.
	The vehicle may roll away.
	➤ Be ready to brake.
	Do not leave the vehicle unattended.
	Depress the brake pedal until the vehicle comes to a standstill.
	Engage park position P when the vehicle is stationary with the brake pedal depressed.
	To continue driving with the brake pedal depressed, select transmission position <b>D</b> or <b>R</b> .
N Automatically Activated Please Shift to Transmis- sion Position Again	* Neutral N was automatically engaged when the vehicle was rolling or being driven.
	i) When you open the driver's door in neutral N, park position P will be engaged automatically.
	► Engage park position P when the vehicle is stationary with the brake pedal depressed.
	To continue driving with the brake pedal depressed, select transmission position <b>D</b> or <b>R</b> .

Display messages	Possible causes/consequences and ▶ Solutions
N is Engaged Shift to Desired Drive Range	<ul> <li>* The accelerator pedal was depressed while the vehicle was rolling or moving in neutral N.</li> <li>▶ To accelerate the vehicle, select transmission position D or R.</li> </ul>
To shift to N, hold selector lever longer in N position	* Selector lever not held for long enough in position N.  The change from parking position P to neutral N is possible only if the selector lever is held in N for a longer period of time.  If the selector lever is not held down for long enough, parking position P remains engaged.  When changing from parking position P to neutral N, hold the selector lever in position N for longer.
Reversing Not Possible Service Required	<ul> <li>* The transmission is malfunctioning. It is not possible to select transmission position R.</li> <li>▶ Consult a qualified specialist workshop.</li> </ul>
Transmission Malfunction Stop	<ul> <li>* The transmission is malfunctioning. The transmission shifts to neutral N automatically.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions.</li> <li>Depress the brake pedal.</li> <li>Engage park position P.</li> <li>Consult a qualified specialist workshop.</li> </ul>
Service Required Do Not Change Transmission Posi- tion	<ul> <li>* The transmission is malfunctioning. It is no longer possible to change the transmission position.</li> <li>If transmission position  is selected, consult a qualified specialist workshop and do not change the transmission position.</li> <li>For all other transmission positions, park the vehicle safely.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	Consult a qualified specialist workshop or breakdown service.
Auxiliary Battery Malfunction (white display message)	<ul> <li>* There is a malfunction in the auxiliary battery.</li> <li>Consult a qualified specialist workshop.</li> <li>Until then, always select park position P manually before you switch off the vehicle.</li> <li>Before leaving the vehicle, apply the electric parking brake.</li> </ul>
Auxiliary Battery Malfunction (red display message)	<ul> <li>* There is a malfunction in the auxiliary battery.</li> <li>Consult a qualified specialist workshop.</li> <li>Until then, always select park position P manually before you switch off the vehicle.</li> <li>Before leaving the vehicle, apply the electric parking brake.</li> </ul>

#### **Brakes**

#### Display messages



(USA only)



(Canada only)

Parking Brake See Operator's Manual

#### Possible causes/consequences and ▶ Solutions

\* The yellow place indicator lamp is lit. The electric parking brake is malfunctioning.

#### To apply:

- Switch the vehicle off and switch it back on
- Apply the electric parking brake manually ( $\rightarrow$  page 222).

If it is not possible to apply the electric parking brake:

- Consult a qualified specialist workshop.
- Where necessary, also secure the parked vehicle against rolling away.
- \* The yellow (P) indicator lamp and the red (PARK (USA only) or (P) (Canada only) indicator lamp are lit. The electric parking brake is malfunctioning.

#### To release:

- Switch the vehicle off and switch it back on
- Release the electric parking brake manually ( $\rightarrow$  page 222).

or

Release the electric parking brake automatically (→ page 221).

If it is still not possible to release the electric parking brake:

Do not continue driving. Consult a qualified specialist workshop.

## Display messages Possible causes/consequences and > Solutions \* The yellow (Park (USA only) or (Canada only) indicator lamp is lit and the red (Park (USA only) or (Canada only) indicator lamp is flashing. The electric parking brake is malfunctioning. The electric parking brake could not be applied or released. Switch the vehicle off and switch it back on To apply: $\triangleright$ Release and then apply the electric parking brake manually ( $\rightarrow$ page 222). To release: Apply and then release the electric parking brake manually. If the electric parking brake cannot be applied or the red [PARK] (USA only) or [PARK] (Canada only) indicator lamp continues to flash: Do not continue driving. Consult a qualified specialist workshop. ▶ Where necessary, also secure the parked vehicle against rolling away. \* The yellow (B) indicator lamp is lit and the red PARK indicator lamp (USA only) or (B) indicator lamp (Canada only) flashes for approximately ten seconds after the electric parking brake has been applied or released. It then remains lit or goes out. The electric parking brake is malfunctioning. If the state of charge is too low: Charge the 12 V battery (→ page 400).

Display messages	Possible causes/consequences and ▶ Solutions
	To apply:
	Apply the electric parking brake manually.
	If it is not possible to apply the electric parking brake:
	Consult a qualified specialist workshop.
	Where necessary, also secure the parked vehicle against rolling away.
	To release:
	If the conditions for automatic release are fulfilled and the electric parking brake is not released automatically, release the electric parking brake manually (→ page 222).
	If it is still not possible to release the electric parking brake:
	Do not continue driving. Consult a qualified specialist workshop.

#### Display messages

# **PARK**

(USA only)



(Canada only)

Release Parking Brake



(USA only)



(Canada only)

Switch on Vehicle to Release the Parking Brake

### Possible causes/consequences and ▶ Solutions

- \* The red PARK indicator lamp (USA only) or Dindicator lamp (Canada only) is flashing.
  - The electric parking brake is applied while you are driving:
  - A condition for automatic release of the electric parking brake has not been fulfilled ( $\rightarrow$  page 221).
  - You are performing emergency braking using the electric parking brake (ightarrow page 222).
  - Check the conditions for automatic release of the electric parking brake.
  - Release the electric parking brake manually.
- \* The red PARK (USA only) or (©) (Canada only) indicator lamp is lit.

  You have attempted to release the electric parking brake with the vehicle switched off.
  - Switch on the vehicle.

#### Display messages

## **BRAKE**

(USA only)



(Canada only) **Brake Immediately** 

# **BRAKE**

(USA only)



(Canada only)

Malfunction See Operator's Manual

### Possible causes/consequences and ▶ Solutions

\* A malfunction has occurred while the HOLD function was activated.

A horn may also sound at regular intervals.

You cannot start the vehicle system.

Immediately depress the brake pedal firmly until the display message disappears. You cannot start the vehicle system again.

\* The brake force boosting function is impaired.

The hill start assist may be impaired.

**WARNING** Risk of an accident due to a brake system malfunction

If the brake system is malfunctioning, braking characteristics may be impaired.

- Drive on carefully.
- Have the brake system checked immediately at a qualified specialist workshop.

#### Display messages

# BRAKE

(USA only)



(Canada only)

Malfunction Stop



(USA only)



(Canada only)

Check Brake Fluid Level

#### Possible causes/consequences and ▶ Solutions

\* The brake force boosting function is impaired and the braking characteristics may be affected.

**A** WARNING Risk of accident and injury if brake force boosting is malfunctioning

If brake force boosting is malfunctioning, increased brake pedal force may be necessary for braking. The braking characteristics may be impaired. The braking distance can increase in emergency braking situations.

- Stop in a safe location immediately. Do not continue driving.
- Consult a qualified specialist workshop.

\* There is insufficient brake fluid in the brake fluid reservoir.


**WARNING** Risk of an accident due to low brake fluid level

If the brake fluid level is too low, the braking effect and the braking characteristics may be impaired.

- Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.
- Consult a qualified specialist workshop.
- Do not add brake fluid.

Display messages	Possible causes/consequences and ▶ Solutions
Check Brake Pads See	* The brakepads have reached the wear limit.
Operator's Manual	Consult a qualified specialist workshop.

#### Driving and driving safety systems



# Display messages ABS Inoperative See Operator's Manual

#### Possible causes/consequences and ▶ Solutions

\* ABS and ESP® are malfunctioning.

Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

The brake system will continue to operate normally. Braking distance may increase in an emergency braking situation.

▲ WARNING Risk of skidding if ABS and ESP® are malfunctioning

The wheels may block during braking and ESP® does not perform any vehicle stabilization.

The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addition, other driving safety systems are switched off.

- Drive on carefully.
- ► Have ABS and ESP® checked immediately at a qualified specialist workshop.



Currently Unavailable See Operator's Manual \* ESP® is temporarily unavailable.

Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

**A** WARNING Risk of skidding if ESP is malfunctioning®

If ESP® is malfunctioning, ESP® cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.

Drive carefully on a suitable stretch of road, making slight steering movements at a speed above 19 mph (30 km/h).

Display messages	Possible causes/consequences and ▶ Solutions
	If the display message does not disappear, consult a qualified specialist workshop immediately. Drive carefully.
	* ESP® is malfunctioning.
Inoperative See Operator's	Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.  The brake system will continue to operate normally. Braking distance may increase in an emergency braking situation.
Manual	<b>▲ WARNING</b> Risk of skidding if ESP <sup>®</sup> is malfunctioning
	If ESP® is malfunctioning, ESP® cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.
	Drive on carefully.
	► Have ESP® checked at a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
EBD	* EBD, ABS and ESP® are malfunctioning.  Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.
	<b>★ WARNING</b> Risk of skidding if EBD, ABS and ESP <sup>®</sup> are malfunctioning
(ABS)	The wheels may block during braking and ESP® does not perform any vehicle stabilization.
	The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addition, other driving safety systems are switched off.
2 5	▶ Drive on carefully.
Inoperative See Operator's Manual	Have the brake system checked immediately at a qualified specialist workshop.
	* The HOLD function is deactivated because the vehicle is slipping or a condition for activation is not fulfilled.
HOLD	Reactivate the HOLD function later or check the activation conditions for the HOLD function (→ page 230).
Restricted Mode Activated	* The valet service mode is activated. Vehicle acceleration is restricted (→ page 232).
Drive Power Reduced	* The beginner driver mode is activated. Vehicle acceleration is restricted (→ page 233).

Display messages	Possible causes/consequences and ▶ Solutions
ATTENTION ASSIST: Take a Break!	<ul> <li>* ATTENTION ASSIST has detected fatigue or an increasing lack of concentration on the part of the driver (→ page 233).</li> <li>▶ If necessary, take a break.</li> </ul>
100	* Cruise control cannot be activated as not all activation conditions are fulfilled.
mph	ightharpoonup Observe the activation conditions for cruise control ( $ ightharpoonup$ page 235).
Cruise Control Inoperative	* Cruise control is malfunctioning.
	Consult a qualified specialist workshop.
Cruise Control Off	* Cruise control has been deactivated.
	If there is an additional warning tone, cruise control has been deactivated automatically ( $\rightarrow$ page 235).
Traffic Sign Assist Cur- rently Unavailable See Operator's Manual	* Traffic Sign Assist is temporarily unavailable.
	Once the cause of the problem is no longer present, the system will be available again.
Operator 5 Manual	Continue driving in compliance with traffic regulations.
Traffic Sign Assist Inopera-	* Traffic Sign Assist is malfunctioning.
tive	Continue driving in compliance with traffic regulations.

Display messages	Possible causes/consequences and ▶ Solutions
	or  Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message does not disappear: consult a qualified specialist workshop.
DSR Not in Curr. Drive Prog.	<ul> <li>* DSR is not available in the currently selected drive program.</li> <li>▶ Change the drive program.</li> </ul>
DSR Inoperative	* DSR is malfunctioning.  ► Consult a qualified specialist workshop.
Do Not Exceed 25 mph	<ul> <li>* The maximum speed of 25 mph (40 km/h) for DSR has been exceeded.</li> <li>▶ Drive more slowly.</li> </ul>

# Driver assistance systems

Display messages	Possible causes/consequences and ▶ Solutions
mph	* Active Distance Assist DISTRONIC cannot be activated as not all activation conditions are fulfilled.  ▶ Comply with the activation conditions of Active Distance Assist DISTRONIC (→ page 240).
Suspended	* If you depress the accelerator pedal beyond the setting of Active Distance Assist DISTRONIC, the system will switch to passive mode (→ page 237).
Off	* Active Distance Assist DISTRONIC was deactivated. If a warning tone also sounds, Active Distance Assist DISTRONIC has deactivated automatically (→ page 240).
Active Distance Assist Cur- rently Unavailable See Operator's Manual	* Active Distance Assist DISTRONIC is temporarily unavailable.  The ambient conditions are outside the system limits (→ page 237).  As soon as the ambient conditions are within the system limits, the system will become available again.  ▶ Drive on carefully.  or

Display messages	Possible causes/consequences and ▶ Solutions
	If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.
Active Distance Assist Inoperative	<ul> <li>* Active Distance Assist DISTRONIC is malfunctioning.</li> <li>Other driving systems and driving safety systems may also be malfunctioning.</li> <li>Drive on carefully.</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Distance Assist Now Available	<ul> <li>* Active Distance Assist DISTRONIC is operational again.</li> <li>▶ Switch on Active Distance Assist DISTRONIC (→ page 240).</li> </ul>
Active Brake Assist Functions Currently Limited See Operator's Manual	<ul> <li>* For vehicles with the Driving Assistance Package, the following functions may be temporarily unavailable or only partially available:</li> <li>Active Brake Assist with cross-traffic function</li> <li>Evasive Steering Assist</li> <li>PRE-SAFE® PLUS</li> </ul>
	Vehicles with Blind Spot Assist: PRE-SAFE <sup>®</sup> PLUS is temporarily unavailable.  The ambient conditions are outside the system limits (→ page 254).  Vehicles without the Driving Assistance Package: Active Brake Assist is temporarily unavailable.

Display messages	Possible causes/consequences and ▶ Solutions
	Drive on carefully. As soon as the ambient conditions are within the system limits, the system will become available again. or
	If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.
Active Brake Assist Functions Limited See Opera-	* For vehicles with the Driving Assistance Package, the following functions may be temporarily unavailable or only partially available:
tor's Manual	Active Brake Assist with cross-traffic function
	Evasive Steering Assist
	PRE-SAFE® PLUS
	Vehicles without the Driving Assistance Package: Active Brake Assist is temporarily unavailable or only partially available.
	▶ Drive on carefully.
	Or
	Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message does not disappear: consult a qualified specialist workshop.
Active Steering Assist Cur-	* Active Steering Assist is temporarily unavailable.
rently Unavailable See Operator's Manual	The ambient conditions are outside the system limits ( $\rightarrow$ page 246).
Operator 5 ividitual	As soon as the ambient conditions are within the system limits, the system will become available again.

Display messages	Possible causes/consequences and ▶ Solutions
	<ul><li>Drive on</li><li>Check the tire pressure if necessary.</li></ul>
Active Steering Assist Inoperative	<ul> <li>* Active Steering Assist is malfunctioning. Active Distance Assist DISTRONIC remains available.</li> <li>Drive on</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
	<ul> <li>* Active Steering Assist has reached the system limits (→ page 246).</li> <li>You have not steered independently for a considerable period of time.</li> <li>► Take over the steering and drive on in accordance with the traffic conditions.</li> </ul>
Active Steering Assist Currently Unavailable Due to Multiple Emergency Stops	<ul> <li>* Active Steering Assist is temporarily unavailable due to several emergency stops having been performed.</li> <li>Take over the steering and stop in accordance with the traffic conditions.</li> <li>Switch the vehicle off and switch it back on Active Steering Assist is available once more.</li> </ul>
Initiating Emergency Stop	<ul> <li>* Your hands are not on the steering wheel. Active Steering Assist will initiate an emergency stop (→ page 246).</li> <li>▶ Put your hands on the steering wheel.</li> <li>Information on canceling an emergency stop (→ page 248).</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Active Emergency Stop Assist Currently Unavaila- ble See Operator's Manual	<ul> <li>* Active Emergency Stop Assist is temporarily unavailable. The ambient conditions are outside the system limits (→ page 248). As soon as the ambient conditions are within the system limits, the system will become available again.  Drive on or  If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.  * Vehicles without the Driving Assistance Package: Active Emergency Stop Assist is temporarily unavailable due to multiple emergency stops.  Take over the steering and stop in accordance with the traffic conditions.  Switch the vehicle off and switch it back on. Active Emergency Stop Assist is available once more.</li> </ul>
Active Emergency Stop Assist Inoperative	<ul> <li>* Active Emergency Stop Assist is malfunctioning.</li> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Active Lane Change Assist Currently Unavailable See Operator's Manual	<ul> <li>* Active Lane Change Assist is temporarily unavailable. The ambient conditions are outside the system limits (→ page 250). As soon as the ambient conditions are within the system limits, the system will become available again.</li> <li>▶ Drive on.</li> <li>or</li> <li>▶ If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> </ul>
Active Lane Change Assist Inoperative	<ul> <li>* Active Lane Change Assist is malfunctioning.</li> <li>Drive on.</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Automatic Lane Change Currently Unavailable See Operator's Manual	<ul> <li>* Active Lane Change Assist is temporarily unavailable. The ambient conditions are outside the system limits (→ page 250). As soon as the ambient conditions are within the system limits, the system will become available again. Drive on or If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Automatic Lane Change Inoperative	<ul> <li>* Active Lane Change Assist is malfunctioning.</li> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Stop & Go Assist Currently Unavailable See Operator's Manual	* Active Stop-and-Go Assist is temporarily unavailable. Active Distance Assist DISTRONIC and Active Steering Assist are still available.  The ambient conditions are outside the system limits (→ page 237).  As soon as the ambient conditions are within the system limits, the system will become available again.  ▶ Drive on.
Active Stop & Go Assist Inoperative See Operator's Manual	* Active Stop-and-Go Assist is malfunctioning.  Active Stop-and-Go Assist has been deactivated. Active Distance Assist DISTRONIC and Active Steering Assist are still available.  Drive on.  or  Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message does not disappear: consult a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Blind Spot Assist Currently Unavailable See Operator's Manual	<ul> <li>* Blind Spot Assist is temporarily unavailable. The system limits have been reached (→ page 264). Once the cause of the problem is no longer present, the system will be available again. Drive on. or If the display message does not disappear, stop the vehicle in accordance with the traffic conditions and restart the vehicle. </li> </ul>
Blind Spot Assist Inoperative	<ul> <li>Blind Spot Assist or the exit warning is malfunctioning.</li> <li>Drive on.</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Blind Spot Assist Not Avail- able When Towing Trailer See Operator's Manual	* When you establish the electrical connection to the trailer, Blind Spot Assist will be unavailable.  Press the left-hand Touch Control and acknowledge the display message.
Active Blind Spot Assist Currently Unavailable See Operator's Manual	* Active Blind Spot Assist is temporarily unavailable.  The system limits have been reached (→ page 264).  Once the cause of the problem is no longer present, the system will be available again.

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Active Lane Keeping Assist Limited Range of Functions See Operator's Manual	<ul> <li>* Active Lane Keeping Assist is available but restricted.</li> <li>Drive on</li> <li>or</li> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Initiating Emergency Stop	<ul> <li>* Your hands are not on the steering wheel. The Active Lane Keeping Assist will initiate an emergency stop (→ page 268).</li> <li>▶ Put your hands on the steering wheel.</li> <li>Information on canceling an emergency stop (→ page 248).</li> </ul>

#### Display messages



Temporarily Unavailable Sensors Dirty

#### Possible causes/consequences and ▶ Solutions

- \* Front and corner radar sensors (hereafter "sensors") are malfunctioning. Possible causes are:
  - The sensors are dirty
  - · Heavy rain or snow
  - Extended country driving without other traffic, e.g. in the desert

Driving systems and driving safety systems may be malfunctioning or temporarily unavailable. The brake system, steering and drive system will continue to function normally.

Drive on carefully.

Once the causes of the problem are no longer present, the driving systems and driving safety systems will be available again and the corresponding symbols will be switched off.

If the display message does not disappear:

- Stop the vehicle in accordance with the traffic conditions.
- Clean all sensor covers from outside ( $\rightarrow$  page 225).
- Restart the vehicle.

#### Display messages



Camera View Reduced See Operator's Manual

#### Possible causes/consequences and ▶ Solutions

- \* The view of the multifunction camera is restricted. Possible causes are:
  - Dirt on the windshield in the field of vision of the multifunction camera
  - · Heavy rain, snow or fog
  - Fogging up of the windshield from inside or outside: in certain weather conditions, fog can form on the inside or outside of the windshield during cold times of year in particular.
  - i This fog on the windshield will be removed automatically within a short time with the aid of a heater. The restriction is temporary.

Driving systems and driving safety systems may be malfunctioning or temporarily unavailable. The brake system, steering and drive system will continue to function normally.

- Drive on carefully.
- ▶ In order to remove the fog from the outside, carry out a single wipe of the windshield ( $\rightarrow$  page 144).
- In order to remove the fog from the inside, press  $\overline{\mathbb{Q}}^{MX}$  ( $\rightarrow$  page 158).

Once the causes of the problem are no longer present, the driving systems and driving safety systems will be available again and the corresponding symbols will be switched off.

If the display message does not disappear after a longer drive of around 15 minutes:

- Stop the vehicle in accordance with the traffic conditions.
- ightharpoonup Clean the windshield, especially in the position of the multifunction camera (ightharpoonup page 225).
- Restart the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
Functions Limited When Towing Trailer	* When the trailer socket is occupied, some driving systems will be available only to a limited extent.  Drive carefully if you are towing a trailer or have the bicycle rack mounted.
PRE-SAFE Inoperative See Operator's Manual	<ul> <li>* The PRE-SAFE® functions are malfunctioning.</li> <li>Consult a qualified specialist workshop.</li> </ul>
PRE-SAFE Pulse Side Inop- erative See Operator's Manual	* The PRE-SAFE® Impulse Side system is malfunctioning or inoperative after having already been triggered.  Consult a qualified specialist workshop.
PRE-SAFE PLUS Inopera- tive See Operator's Manual	* There is a malfunction in the PRE-SAFE® PLUS system.  Drive on or


Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Stop the vehicle in accordance with the traffic conditions and restart the vehicle.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>

# Parking assistance systems

Display messages	Possible causes/consequences and ▶ Solutions
PARKTRONIC Inoperative See Operator's Manual	<ul> <li>Parking Assist PARKTRONIC is malfunctioning.         Once the cause of the problem is no longer present, the system will be available again.         Continue driving while paying attention to the vehicle's surroundings.         or         Stop the vehicle in accordance with the traffic conditions and restart the vehicle.         If the display message still appears, consult a qualified specialist workshop.     </li> </ul>
PARKTRONIC and Maneuvering Assistance Unavailable at Rear When Towing Trailer	* If transport equipment, e.g. a trailer or bicycle rack, is attached to the trailer hitch and the electrical connection is correctly established, Parking Assist PARKTRONIC is not available when backing up. The rear maneuvering assistant is also unavailable in this situation.  Press the left-hand Touch Control and acknowledge the display message.
Active Parking Assist and PARKTRONIC Inoperative See Operator's Manual	<ul> <li>* Active Parking Assist and Parking Assist PARKTRONIC are malfunctioning.</li> <li>Once the cause of the problem is no longer present, the system will be available again.</li> <li>Continue driving while paying attention to the vehicle's surroundings.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
	or  Stop the vehicle in accordance with the traffic conditions and restart the vehicle.  If the display message still appears, consult a qualified specialist workshop.
Active Parking Assist Limited Availability of Maneuvering Assistance See Operator's Manual	<ul> <li>* Active Parking Assist's maneuvering assistant is temporarily unavailable or only partially available.</li> <li>▶ Clean all sensors of the parking and camera system (→ page 382).</li> <li>▶ If the display message still appears, consult a qualified specialist workshop.</li> </ul>

# Mercedes-Benz emergency call system



#### **Battery**

# Display messages Possible causes/consequences and ▶ Solutions \* The 12 V on-board electrical system is malfunctioning. Consult a qualified specialist workshop immediately. 12 V On-board Flectrical System Service Required \* The 12 V battery is no longer being charged and the condition of charge is too low. NOTE Possible engine damage if you continue driving Stop Vehicle See Opera-Do not continue driving under any circumstances. tor's Manual Consult a qualified specialist workshop. Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances. Switch off the vehicle. Consult a qualified specialist workshop.

Display messages	Possible causes/consequences and ▶ Solutions
Switch on vehicle to charge the 12 V battery	<ul> <li>* The vehicle is off and the condition of charge of the 12 V battery is too low.</li> <li>Switch off electrical consumers that are not required.</li> <li>Drive for 30-60 mins.</li> <li>or</li> <li>Charge the 12 V battery when stationary (→ page 400).</li> <li>Plug-in hybrid: Charge the vehicle at a charging station (→ page 200).</li> </ul>
Stop Vehicle To Charge the 12 V Battery Do Not Switch Off Vehicle	<ul> <li>* The state of charge of the 12 V battery is too low.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving.</li> <li>Leave the vehicle running</li> <li>If the display message disappears: drive on.</li> <li>If the display message does not disappear: consult a qualified specialist workshop.</li> </ul>
Stop Vehicle See Operator's Manual	<ul> <li>* The 48 V on-board electrical system is malfunctioning.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving under any circumstances.</li> <li>Switch off the vehicle.</li> <li>Consult a qualified specialist workshop.</li> </ul>

Display messages	Possible causes/consequences and ▶ Solutions
Battery Overheated Stop! Everyone Get Out! Out-doors if Possible	<ul> <li>* The 48 V battery is overheating. There is a risk of fire.</li> <li>Stop the vehicle immediately in accordance with the traffic conditions.</li> <li>If possible, stop the vehicle in the open air and ensure that all vehicle occupants get out.</li> <li>i Supporting vehicle functions may activate automatically, e.g. air-recirculation mode as part of climate control.</li> <li>Do not continue driving.</li> <li>If smoke is present, leave the danger zone and call the fire service immediately.</li> <li>Consult a qualified specialist workshop even if there are no external signs of a fire.</li> </ul>
48 V Battery See Operator's Manual	* The 48 V on-board electrical system has function restrictions.  Comfort functions, such as the climate control system, may be restricted.  It is possible to continue driving.  If the display message remains active continuously, consult a qualified specialist workshop immediately.
Please Wait Charging 48 V Battery	* The 48 V battery is discharged. You have switched on the vehicle while the 12 V battery was being charged with a suitable charger or while another vehicle was providing starting assistance.  The discharged 48 V battery is charged automatically via the voltage converter. After a few minutes, the Starting Possible Again display message will be shown on the driver's display.  Start the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
	Drive the vehicle for a while to charge the 12 V battery and the 48 V battery after disconnecting the charger from the vehicle.
	If the Starting Possible Again display message does not appear after a few minutes:  Try to start the vehicle.  If the vehicle does not start, consult a qualified specialist workshop.
Starting Possible Again	<ul> <li>* The 48 V battery has been charged automatically via the voltage converter.</li> <li>Start the vehicle and drive for a while to charge the 12 V battery and the 48 V battery.</li> </ul>

# Tire pressure monitor

Display messages	Possible causes/consequences and ▶ Solutions
Tire Pressure Monitor Cur- rently Unavailable	* There is interference from a powerful radio signal source. As a result, no signals from the tire pressure sensor are being received. The tire pressure monitoring system is temporarily unavailable.
	The tire pressure monitoring system will restart automatically as soon as the cause has been rectified.  Drive on.
Tire Pressure Monitor Inoperative	* The tire pressure monitoring system is malfunctioning.

Display messages	Possible causes/consequences and ▶ Solutions
	<b>WARNING</b> There is a risk of an accident if the tire pressure monitoring system is malfunctioning
	The tire pressure monitoring system cannot issue a warning if there is pressure loss in one or more of the tires.  Tires with insufficient tire pressure may impair the driving characteristics as well as steering and braking.  Have the tire pressure monitoring system checked at a qualified specialist workshop.
Tire Pressure Monitor Inop- erative Tire Pressure Sen- sors Missing	* The wheels installed do not have suitable tire pressure sensors. The tire pressure monitoring system is deactivated.  Install wheels with suitable tire pressure sensors.
Wheel Sensor(s) Missing	<ul> <li>* There is no signal from the tire pressure sensor in at least one wheel. No pressure value is displayed for the affected tire.</li> <li>Have the faulty tire pressure sensor replaced at a qualified specialist workshop.</li> </ul>
	* The tire pressure in one or more tires has dropped significantly.
	The wheel position is displayed. A warning tone will also sound.
Check Tires	▲ WARNING Risk of an accident due to insufficient tire pressure
	The tires can burst.
	The tires can wear excessively and/or unevenly.

Display messages	Possible causes/consequences and ▶ Solutions
	The driving characteristics as well as the steering and braking may be greatly impaired.
	You could then lose control of the vehicle.
	Observe the recommended tire pressures.
	Adjust the tire pressure if necessary.
	➤ Stop the vehicle in accordance with the traffic conditions.
	ightharpoonup Check the tire pressure ( $ ightharpoonup$ page 413) and the tires.
	* The tire pressure is too low in at least one of the tires, or the difference in tire pressure between the individual wheels is too great.
	Check the tire pressure and add air, if necessary.
Please Correct Tire Pressure	When the tire pressure is correct, restart the tire pressure monitor (→ page 418).
Warning Tire Malfunction	* The pressure in one or more tires has dropped suddenly. The wheel position is displayed.
	▲ WARNING Risk of an accident from driving with a flat tire
	The tires can overheat and be damaged.
	The driving characteristics as well as the steering and braking characteristics may be greatly impaired.
	You could then lose control of the vehicle.

Display messages	Possible causes/consequences and ▶ Solutions
	<ul> <li>Do not drive with a flat tire.</li> <li>Do not exceed the maximum permissible driving distance in emergency mode and the maximum permissible speed with a flat MOExtended tire.</li> <li>Observe the notes on flat tires.</li> </ul>
	Notes on flat tires (→ page 388).  Stop the vehicle in accordance with the traffic conditions.  Check the tires.
Tires Overheated	* At least one tire is overheating. The affected tires are displayed in red. At temperatures close to the limit value, the tires are displayed in yellow.
	<b>WARNING</b> Risk of an accident from driving with overheated tires
	Overheated tires can burst.  Reduce speed so that the tires cool down.
Reduce Speed	* At least one tire is overheating. The affected tires are displayed in red. At temperatures close to the limit value, the tires are displayed in yellow.
	<b>WARNING</b> Risk of an accident from driving with overheated tires
	Overheated tires can burst.


Display messages	Possible causes/consequences and ▶ Solutions
	Reduce speed so that the tires cool down.


#### Tire pressure loss warning system

# Display messages Possible causes/consequences and ▶ Solutions Check Tire and Tire Pres-\* Canada only: sure The tire pressure loss warning system has detected a significant loss of pressure. WARNING Risk of an accident due to insufficient tire pressure . The tires can burst. • The tires can wear excessively and/or unevenly. • The driving characteristics as well as the steering and braking may be greatly impaired. You could then lose control of the vehicle. Observe the recommended tire pressures. Adjust the tire pressure if necessary. Stop the vehicle in accordance with the traffic conditions. Check the tire pressure ( $\rightarrow$ page 413) and the tires.

Display messages	Possible causes/consequences and ▶ Solutions
	ightharpoonup When the tire pressure is correct, restart the tire pressure loss warning system ( $ ightharpoonup$ page 419).
Check Tire Pressure Then Restart Run Flat Indicator	<ul> <li>* Canada only:</li> <li>The tire pressure loss warning system generated a display message and has not been restarted since.</li> <li>▶ When the tire pressure is correct, restart the tire pressure loss warning system (→ page 419).</li> </ul>
Run Flat Indicator Inoperative	<ul> <li>* Canada only:</li> <li>The tire pressure loss warning system is malfunctioning.</li> <li>Consult a qualified specialist workshop.</li> </ul>

#### Engine oil





# Display messages Possible causes/consequences and ▶ Solutions \* The oil pressure is too low. ■ NOTE Engine damage caused by driving with insufficient oil pressure ■ Avoid driving with insufficient oil pressure. ■ Stop the vehicle immediately in accordance with the traffic conditions. Do not continue driving. ■ Switch off the vehicle. ■ Consult a qualified specialist workshop. \* The electrical connection to the oil level sensor has been interrupted or the oil level sensor is faulty. ■ Consult a qualified specialist workshop.

# Warning and indicator lamps

#### Overview of indicator and warning lamps

Some systems will perform a self-test when the vehicle is switched on. Some indicator and warning lamps may briefly light up or flash. This behavior is non-critical. These indicator and warning

lamps indicate a malfunction only if they light up or flash after the vehicle has been started or during a journey.

The indicator and warning lamps are located in the highlighted display sections.

#### Driver display



#### Indicator and warning lamps

Occupant safety

Restraint system ( $\rightarrow$  page 537)

Ä Seat belt ( $\rightarrow$  page 537)

Occupant presence reminder (white)  $(\rightarrow page 537)$ 

Occupant presence reminder (vellow)  $(\rightarrow page 537)$ 

Drive system

Reduced power ( $\rightarrow$  page 539)

System error ( $\rightarrow$  page 539)

Electrical malfunction ( $\rightarrow$  page 539)

vehicle **@**!

Power steering (yellow) ( $\rightarrow$  page 540)

Power steering (red) ( $\rightarrow$  page 540)

Rear-axle steering (yellow) ( $\rightarrow$  page 540)

Rear-axle steering (red) ( $\rightarrow$  page 540)

Engine

Coolant temperature (→ page 542)

Engine diagnostics ( $\rightarrow$  page 542)

Vehicles with gasoline engine: engine operating temperature ( $\rightarrow$  page 542)

Electrical malfunction ( $\rightarrow$  page 542)

Reserve fuel with fuel filler flap location indicator ( $\rightarrow$  page 542)

Brakes

Electric parking brake (yellow)  $(\rightarrow page 546)$ 

USA: electric parking brake (red)  $(\rightarrow page 546)$ 

Canada: electric parking brake (red)  $(\rightarrow page 546)$ 

USA: Recuperative Brake System  $(\rightarrow page 546)$ 

Canada: brakes (yellow)( $\rightarrow$  page 546) (II)

BRAKE USA: brakes (red) ( $\rightarrow$  page 546)

Canada: brakes (red) ( $\rightarrow$  page 546) (D)

Driving and driving safety systems

(ABS) ABS ( $\rightarrow$  page 549)

 $ESP^{\mathbb{R}} (\rightarrow page 549)$ 

 $ESP^{\otimes} OFF (\rightarrow page 549)$ 

FOFF ATTENTION ASSIST (→ page 549)

Traffic Sign Assist (→ page 549)

A Distance warning ( $\rightarrow$  page 549)

≽!ল Active Brake Assist (→ page 549)

OFF ioni Active Brake Assist ( $\rightarrow$  page 549)

Active Brake Assist (→ page 549)

Mercedes-Benz emergency call system

Mercedes-Benz emergency call system  $(\rightarrow page 553)$ 

Tire pressure monitor

 $\bigcirc$  Tire pressure monitor ( $\rightarrow$  page 553)

Exterior lighting

-00-Parking lamp ( $\rightarrow$  page 133)

**■**D Low beam ( $\rightarrow$  page 133)

≣D High beam ( $\rightarrow$  page 134)

 $\Diamond$   $\Diamond$ Turn signal lights ( $\rightarrow$  page 134) 0≑

Rear fog light ( $\rightarrow$  page 133)

# Symbols on the central display

Drive Away Assist (→ page 289)

Rear cross traffic warning (→ page 290)

Close-range braking ( $\rightarrow$  page 291)

#### Occupant safety

#### Warning/indicator lamp



Restraint system warning lamp

#### Possible causes/consequences and ▶ Solutions

\* The restraint system red warning lamp is lit while the vehicle is on. The restraint system is malfunctioning ( $\rightarrow$  page 43).

#### WARNING Risk of injury due to malfunctions in the restraint system

Components in the restraint system may be activated unintentionally or not deploy as planned in an accident.

▶ Have the restraint system checked and repaired immediately at a qualified specialist workshop.

#### Plug-in hvbrid:

#### **DANGER** Risk of death due to the restraint system malfunctioning

Components in the restraint system may be activated unintentionally or not deploy as intended in an accident. In the event of an accident, the high-voltage on-board electrical system may not be deactivated as intended.

You may receive an electric shock if you touch the damaged components of the high-voltage on-board electrical system.

- ▶ Have the restraint system checked and repaired immediately at a qualified specialist workshop.
- After an accident, switch off the vehicle immediately.
- Drive on carefully.
- Note the messages on the driver's display.

Warning/indicator lamp	Possible causes/consequences and ➤ Solutions
	Consult a qualified specialist workshop immediately.
Seat belt warning lamp flashes	* The red seat belt warning lamp flashes and an intermittent warning tone sounds.  The driver or front passenger has not fastened his/her seat belt while the vehicle is in motion.
	► Fasten your seat belt (→ page 43). There are objects on the front passenger seat.
	Remove the objects from the front passenger seat.
Seat belt warning lamp lights up	* The red seat belt warning lamp lights up for six seconds once the vehicle has started.
	In addition, an intermittent warning tone may sound.  The red seat belt warning lamp reminds the driver and front passenger to fasten their seat belts.
	Fasten your seat belt ( $\rightarrow$ page 43).
	If you have placed objects on the front passenger seat, the red seat belt warning lamp may remain lit.
OFF	* The white occupant presence reminder warning lamp is lit. The occupant presence reminder is deactivated.
	<ul> <li>Switch on the occupant presence reminder, see (→ page 72).</li> </ul>
Occupant presence reminder warning lamp (white)	owned on the occupant presence reminder, see (—7 page 72).

### Warning/indicator lamp



Occupant presence reminder warning lamp (yellow)

### Possible causes/consequences and ▶ Solutions

- \* The yellow occupant presence reminder warning lamp is lit. The occupant presence reminder is malfunctioning
- Note the messages on the driver's display.

### Drive system

# Warning/indicator lamp




Reduced warning lamp power



System malfunction warning lamp

# Possible causes/consequences and ▶ Solutions




Note the messages on the driver's display.

\*The red system error warning lamp is lit while the vehicle is in a state of operational readiness READY). There is a malfunction in the drive system.

Note the messages on the driver's display.

### 540 Display messages and warning/indicator lamps

### Warning/indicator lamp



Electrical malfunction warning lamp

### Possible causes/consequences and ▶ Solutions

- \* The red electrical malfunction warning lamp is lit. There is a malfunction with the electrics.
  - Note the messages on the driver's display.

### Vehicle

# Warning/indicator lamp

# **%**!

Power steering warning lamp (yellow)



Power steering warning lamp (red)

# Possible causes/consequences and ▶ Solutions

- \* The yellow power steering warning lamp is lit while the vehicle is running. The power assistance or the steering itself is malfunctioning.
- Note the messages on the driver's display.

\* The red power steering warning lamp is lit while the vehicle is running. The power assistance or the steering itself is malfunctioning.

**WARNING** Risk of accident if steering capability is impaired

If the steering does not function as intended, the vehicle's operating safety is jeopardized.

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	<ul> <li>Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.</li> <li>Consult a qualified specialist workshop.</li> </ul>
	Note the messages on the driver's display.
Rear axle steering warning lamp (yellow)	* The yellow rear axle steering warning lamp is lit while the vehicle is running. The rear axle steering is malfunctioning.  Note the messages on the driver's display.
emp (yellow)	* The red rear axle steering warning lamp is lit while the vehicle is running. The rear axle steering is malfunctioning.
Rear axle steering warning	<b>WARNING</b> Risk of accident if steering capability is impaired
lamp (red)	If the steering does not function as intended, the vehicle's operating safety is jeopardized.  Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.  Consult a qualified specialist workshop.

### **Engine**

### Warning/indicator lamp



Coolant warning lamp (red)

### Possible causes/consequences and ▶ Solutions

\* The red coolant warning lamp is lit while the engine is running.

Possible causes are:

- The temperature sensor is malfunctioning
- · The coolant level is too low
- The air supply to the radiator is obstructed
- The radiator fan is faulty
- The engine coolant pump is faulty

If there is an additional warning tone, the coolant temperature has exceeded the maximum permissible temperature.

### **MARNING** Risk of burns when opening the hood

If you open the hood in the event of an overheated engine or fire in the engine compartment, the following situations may occur:

- You may come into contact with hot gases.
- · You may come into contact with other escaping hot operating fluids.
- ► Before opening the hood, allow the engine to cool down.
- ▶ In the event of a fire in the engine compartment, keep the hood closed and call the fire service.

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	<ul><li>Stop immediately in accordance with the traffic conditions and switch off the vehicle. Do not continue driving.</li><li>Note the messages on the driver's display.</li></ul>
	If the coolant temperature display is at the lower end of the temperature scale:  Consult a qualified specialist workshop.
	If the coolant temperature display is at the upper end of the temperature scale:
	Exit the vehicle and keep a safe distance from it until the engine has cooled down.
	ightharpoonup Check the coolant level ( $ ightharpoonup$ page 376).
	Make sure that the air supply to the radiator is not obstructed.
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop. In doing so, ensure that the coolant temperature display remains below the red area.
ſ <b>Ŀ</b>	* The yellow coolant warning lamp is lit while the engine is running.
	Possible causes are:
	The temperature sensor is malfunctioning
Coolant warning lamp (yellow)	The charge air, transmission oil or battery cooling is faulty
iowj	The radiator shutters are blocked or defective
	Avoiding high loads on the engine, drive to the nearest qualified specialist workshop.

# Display messages and warning/indicator lamps

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
HP	* The yellow Check Engine warning lamp is lit while the engine is running.  A malfunction has occurred in the engine, the exhaust system or the fuel system.
الحسحا	The emissions limit value may have been exceeded and the engine may be running in emergency operation mode.
Check Engine warning lamp	In some states, legal requirements stipulate that you must immediately consult a qualified specialist workshop as soon as the yellow Check Engine warning lamp lights up.
	► Have the vehicle checked as soon as possible at a qualified specialist workshop.
<del>- +</del>	* The red electrical malfunction warning lamp is lit. There is a malfunction in the electrics.
	Note the messages on the driver's display.
Electrical malfunction warn- ng lamp	
	*Vehicles with a gasoline engine: after a cold start, the blue engine operating temperature warning lamp is on. Engine output and engine torque are reduced.
	► Take this into consideration in your driving style.
Engine operating tempera- ture warning lamp	

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
Fuel reserve warning lamp flashes	* The yellow fuel reserve warning lamp lights up while you are driving.  There has been pressure loss in the fuel system. The fuel filler cap is not closed correctly or the fuel system is leaking.  Close the fuel filler cap.  If the fuel filler cap has already been closed correctly:  Consult a qualified specialist workshop.
Fuel reserve warning lamp lights up	* The yellow fuel reserve warning lamp lights up while the engine is running. The fuel supply has dropped into the reserve range.  Refuel.

#### Brakes

### Warning/indicator lamp



Electric parking brake indicator lamp (red) (USA only)



Electric parking brake indicator lamp (red) (Canada only)



Electric parking brake indicator lamp (yellow)

### Possible causes/consequences and ▶ Solutions

\* The red electric parking brake indicator lamp flashes or is lit.

The yellow electric parking brake indicator lamp is also lit in the event of a malfunction.

Note the messages on the driver's display.

# Warning/indicator lamp



RBS warning lamp (USA only)



Brakes warning lamp (yellow) (Canada only)

# Possible causes/consequences and ▶ Solutions

\*The yellow RBS warning lamp (USA only) or the yellow (1) brake warning lamp (Canada only) is lit while the vehicle is running.

WARNING Risk of an accident due to a brake system malfunction

If the brake system is malfunctioning, braking characteristics may be impaired.

- Drive on carefully.
- ► Have the brake system checked immediately at a qualified specialist workshop.

The Hill Start Assist may be malfunctioning.

- Adjust your speed and drive on carefully, leaving a suitable distance to the vehicle in front.
- If the driver's display shows a display message, observe it.
- Consult a qualified specialist workshop.

### Warning/indicator lamp



Brakes warning lamp (USA only)



Brakes warning lamp (Canada only)

### Possible causes/consequences and ▶ Solutions

- $^{\star}$  The red brake warning lamp is lit while the vehicle is running.
- Possible causes are:
- The brake force boosting is malfunctioning and the braking characteristics may be affected.
- There is insufficient brake fluid in the brake fluid reservoir.
- Note the messages on the driver's display.
- **WARNING** Risk of accident and injury if brake force boosting is malfunctioning

If brake force boosting is malfunctioning, increased brake pedal force may be necessary for braking. The braking characteristics may be impaired. The braking distance can increase in emergency braking situations.

- Stop in a safe location immediately. Do not continue driving.
- Consult a qualified specialist workshop.
- **MARNING** Risk of an accident due to low brake fluid level

If the brake fluid level is too low, the braking effect and the braking characteristics may be impaired.

- Pull over and stop the vehicle safely as soon as possible, paying attention to road and traffic conditions. Do not continue driving under any circumstances.
- Consult a qualified specialist workshop.
- Do not add brake fluid.

### Driving and driving safety systems

### Warning/indicator lamp



ABS warning lamp

### Possible causes/consequences and ▶ Solutions

\* The yellow ABS warning lamp is lit while the vehicle is running. ABS is malfunctioning.

If an additional warning tone sounds, EBD is malfunctioning.

Other driving systems and driving safety systems may also be malfunctioning.

Note the messages on the driver's display.



WARNING There is a risk of skidding if EBD or ABS is malfunctioning

The wheels may lock during braking.

The steerability and braking characteristics are heavily impaired and the braking distance may increase. In addition, other driving safety systems are switched off.

- Drive on carefully.
- ► Have the brake system checked immediately at a qualified specialist workshop.



ESP® warning lamp flashes

- \* The yellow ESP® warning lamp flashes while the vehicle is in motion. One or more wheels have reached their grip limit ( $\rightarrow$  page 228).
- Adapt your driving style to suit the road and weather conditions.

# Warning/indicator lamp ESP® warning lamp lights up

### Possible causes/consequences and ▶ Solutions

\* The yellow ESP® warning lamp is lit while the vehicle is running. ESP® is malfunctioning.

Other driving systems and driving safety systems (e.g. BAS) may also be malfunctioning.

Note the messages on the driver's display.

# **A** WARNING Risk of skidding if ESP® is malfunctioning

If  $\mathsf{ESP}^{\circledR}$  is malfunctioning,  $\mathsf{ESP}^{\circledR}$  cannot carry out vehicle stabilization. In addition, other driving safety systems are switched off.

- Drive on carefully.
- ► Have ESP® checked at a qualified specialist workshop.



ESP® OFF warning lamp

\* The yellow ESP® OFF warning lamp is lit while the vehicle is running. FSP® is deactivated.

Other driving systems and driving safety systems may also be inoperative.

### **MARNING** Risk of skidding when driving with ESP® deactivated

ESP® does not act to stabilize the vehicle. The availability of further driving safety systems is also limited.

- Drive on carefully.
- Deactivate ESP® only for as long as the situation requires.

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	If ESP® cannot be activated, ESP® is malfunctioning.  Have ESP® checked immediately at a qualified specialist workshop.
	$ ightharpoonup$ Observe the notes on deactivating ESP $^{ ext{@}}$ ( $ ightharpoonup$ page 228).
ATTENTION ASSIST warning lamp	* The ATTENTION ASSIST warning lamp is lit. ATTENTION ASSIST is malfunctioning.  Consult a qualified specialist workshop.
Traffic Sign Assist warning lamp	* The Traffic Sign Assist warning lamp is lit. Traffic Sign Assist is malfunctioning.  ▶ Note the messages on the driver's display.
Distance warning lamp	* The red distance warning lamp lights up while the vehicle is in motion.  The distance to the vehicle in front is too small for the speed selected.  If there is an additional warning tone, you are approaching an obstacle at too high a speed.  Be prepared to brake immediately.  Increase the distance.

# 552 Display messages and warning/indicator lamps

Warning/indicator lamp	Possible causes/consequences and ▶ Solutions
	Function of Active Brake Assist ( $\rightarrow$ page 254).
Active Brake Assist warning lamp	* The Active Brake Assist warning lamp is on. Due to dirty sensors or a malfunction, the system is not available or the range of functions is restricted.  ▶ Note the messages on the driver's display.
OFF Active Brake Assist warning lamp	<ul> <li>* The Active Brake Assist warning lamp is on. The system is switched off or the range of functions has been automatically restricted. This may be the case if the driver is not wearing a seat belt or another driving system has been activated.</li> <li>▶ Observe the notes on Active Brake Assist (→ page 254).</li> </ul>
Active Brake Assist warning lamp	<ul> <li>* The Active Brake Assist warning lamp is on.     After you drive off, the system's range of functions will be restricted due to the teach-in process.     Depending on the ambient conditions, the teach-in process may take a few minutes.</li> <li>▶ Observe the notes on Active Brake Assist (→ page 254).</li> </ul>

### Mercedes-Benz emergency call system

### Warning/indicator lamp

SOS NOT RFADY

Mercedes-Benz emergency call system warning lamp

### Possible causes/consequences and ▶ Solutions

- \*The Mercedes-Benz emergency call system is malfunctioning. The Mercedes me connect system is also malfunctioning.
  - Consult a qualified specialist workshop.

### Tire pressure monitor

### Warning/indicator lamp



Tire pressure monitoring system warning lamp flashes

### Possible causes/consequences and ▶ Solutions

\*The yellow tire pressure monitor warning lamp (pressure loss/malfunction) flashes for approximately one minute and then remains lit.

The tire pressure monitoring system is malfunctioning.

WARNING There is a risk of an accident if the tire pressure monitoring system is malfunctioning

The tire pressure monitoring system cannot issue a warning if there is pressure loss in one or more of the tires.

Tires with insufficient tire pressure may impair the driving characteristics as well as steering and braking.

► Have the tire pressure monitoring system checked at a qualified specialist workshop.

# Warning/indicator lamp



Tire pressure monitoring system warning lamp lights up

# Possible causes/consequences and ▶ Solutions

\* The yellow tire pressure monitoring system warning lamp (pressure loss/malfunction) is lit. The tire pressure monitoring system has detected tire pressure loss in at least one of the tires.

# WARNING Risk of an accident due to insufficient tire pressure

- · The tires can burst.
- The tires can wear excessively and/or unevenly.
- The driving characteristics as well as the steering and braking may be greatly impaired.

You could then lose control of the vehicle.

- Observe the recommended tire pressures.
- Adjust the tire pressure if necessary.
- Stop the vehicle in accordance with the traffic conditions.
- Check the tire pressure and the tires.

1, 2, 3  (SmartKey) battery	Active Blind Spot Assist     Activating/deactivating     Brake application     Exit warning     Function     Trailer operation  Active Brake Assist     Function     Setting  Active Distance Assist DISTRONIC	267 264 264 267	Active Lane Keeping Assist  Activating/deactivating Function Setting the sensitivity Towing a trailer  Active light function  Active Parking Assist Automatic braking function Cross traffic warning Drive Away Assist	26 27 26 13 28 29
Activating/deactivating (MBUX)	Active Distance Assist DISTRONIC Activating/deactivating Active Emergency Stop Assist Active Lane Change Assist Active Speed Limit Assist Calling up a speed Function Increasing/decreasing the speed Route-based speed adaptation Storing a speed Active Emergency Stop Assist	248 250 242 240 237 240 242 240	Exiting a parking space Function Maneuvering brake function Memory Parking Assist Parking Pausing Active Service System PLUS. Active Speed Limit Assist Active Steering Assist	28 29 29 28 28 36 24
Accident, emergency call	Active headlamps	136 254	Activating/deactivating	24 25 24

Adaptive cruise control 24	42	Setting	153	Anti-collision
Adaptive Highbeam Assist		Air freshener system	159	Drive Away Assist
	40	Air inlet		Anti-lock braking system 227
Adaptive Highbeam Assist Plus		Air pressure		Anti-theft alarm system
Activating/deactivating 14	41		413	Anti-theft protection
Additives		Adjusting	164	Immobilizer
Engine oil 49	53	Adjusting		Anticipatory operating-mode strategy,
	52	Air/water duct	3//	Route-based
After-sales service 30	69	Airflow	1	Apps, Mercedes me
Air bag		Adjusting Setting	154	Mercedes me calls
•	57			Mercedes me connect
Inflating	51	Alarm system		Assistance system
	57	All-wheel drive		ASSYST PLUS
· · · · · · · · · · · · · · · · · · ·	45	Alternative route	341	Battery disconnection periods
0 1	43	Ambient lighting	143	Service interval display
Air conditioning menu		AMG TRACK PACE		Service requirements
	57	Configuring	333	ATA
	56 50	Drag Race	332	Deactivating the alarm
Fragrance system	59	Function	329	Function
Rear passenger compartment climate	0,	Telemetry display	333	Interior protection
	57	Track Race		Interior protection function
Air distribution		Angle of approach/departure	458	Tow-away alarm function
Adjusting 154, 15	57	Animals	. 53	Tow-away protection

ATTENTION ASSIST		Automatic mirror folding function	151	Ball neck	
Function	233	Automatic seat adjustment	105	Installing	
Setting		Automatic transmission		BAS	228
Attention assistant	233	DIRECT SELECT lever	192	Basic information	. 40
Authorized Mercedes-Benz Service Center	31	Drive programs		Battery	
Authorized workshop	31	DYNAMIC SELECT button		High-voltage battery	39
Automatic car wash	377	Engages neutral Engaging drive position	193 194	Battery (12 V battery)	
Automatic car wash mode	379	Engaging reverse gear		ChargingNotes	400
Automatic climate control		Kickdown	196	Notes Notes (starting assistance and charg-	39
Automatic distance control	237	Manual gear shifting	195	ing)	39
Automatic driving lights	134	Oil temperature (driver's display) Selecting park position		Replacing	40
Automatic emergency call	360	Steering wheel paddle shifters		Starting assistance	400
Automatic engine start/stop		Switching gears	192	Battery (48 V)	0.0
Automatic front passenger air bag shutoff		Transmission position display		Notes	39.
Function	48	Transmission positions		Battery (starter battery)	47
Information (child restraint system on		Autonomous braking	254	charging, Remote Online	
the front passenger seat)	62	Axle load		Battery operation	16
PASSENGER AIR BAG indicator lamp	45	Towing a trailer	460	Beginner driver mode	
Automatic Lane Change	0.50	В		Activating/deactivating	23
Active Lane Change Assist		_	100	Function	۷٥,
Automatic measures after an accident	50	Bag hook	123	Belt	
				Fastening	. 4

Notes on wearing correctly		BAS (Brake Assist System) Driving tips		C	
Releasing To adjust the height		EBD (Electronic Brakeforce Distribu-	1/4	Calling the customer center for	250
Bicycle rack		tion)	230	Mercedes-Benz	352
Load capacity	459	Electric parking brake	220	Calls Mercedes me	351
Blind Spot Assist		Handbrake HOLD function		Telephone menu	
Activating/deactivating	268	Limited braking effect (salt-treated	230	Using overhead control panel	
Function		roads)	174	Camera	
Bluetooth®		New/replaced brake pads/brake discs	172		273
Connecting a mobile phone	350	Notes on breaking in a new vehicle	172	Activating using GPS (reversing cam-	
Boost pressure, current (driver's display)	307	Parking brake	220	era)	279
Brake Assist		Post-collision brake 5			279
Active Brake Assist	254	Recuperation	184		382
Brake Assist System	228	Braking assistance	054	0	382 273
Brake Assist System	228	Active Brake AssistBrake Assist System			225
Brake disks			220	Managing activation points	
Brake fluid		Breakdown Changing a wheel	136	Off-road function	277
Brake force distribution		Flat tire		Opening the camera cover (rear view	
		Overview of aids		,	279
Brake pads	1/2	Tow-starting		Rear view camera	
Brakes	007	Towing methods	404	Select view Transparent hood	
ABS (Anti-lock Braking System)		Transporting the vehicle	406		
Active Brake Assist	Z54	Breakdown (Roadside Assistance)	. 24	Car key	/3

Car wash		Vehicle interior		Charging	
Automatic car wash		Vehicle parts	382	12 V battery	
Automatic car wash mode		Vehicle socket for the high-voltage		At time of departure	
Power washer		,	382	Charge level display	
Washing by hand	380	Washing by hand	380	Charging cable control panel	206
Car-to-X-Communication		Wheels/rims	382	Charging station, mode 3	204
Display on map	343	Cargo compartment cover		Configuring weekly profile	334
Care	0.0	Extending/retracting	122	Emergency release of the socket flap	214
	377	Removing/installing		Ending the charging process (alternat-	
Air/water duct		<u> </u>		ing current, mode 2/3)	211
Automatic car wash		Caring for plastic trim		Ending the charging process (direct	
Automatic car wash mode		Caring for rims	382	current, mode 4)	214
Camera		Central display		Indicator lamps on vehicle socket	208
Decorative foil		Operating	318	Mains socket, mode 2	203
Display				Maximum charging current (mains	
Exterior lighting		Central locking system	70	socket)	206
Genuine wood/trim elements	383	Button		Notes on charging the high-voltage	
Head-up display	383	SmartKey		battery	200
Headliner		Change of address	25	Notes on the high-voltage battery	398
Paint		Change of ownership	. 25	Rapid charging station, mode 4	205
Plastic trim				Recuperation	184
Power washer	379	Changing a wheel	107	Starting the charging process (alter-	
Running boards	382	Preparation	430	nating current, mode 2/3)	209
Seat belts		Raising the vehicle		Starting the charging process (direct	- /
Steering wheel		Charge level display	215	current, mode 4)	212
Trailer hitch	382	Charge level/charge display	215	Stowing the charging cable	

USB port	Top Tether  Children  Avoiding dangers in the vehicle  Basic instructions  Special seat belt retractor.  Chock  Clean varnish  Cleaning  Air/water duct  Automatic car wash  Automatic car wash mode  Camera	. 60 . 58 . 66 435 380 377 377 378 382	Activating/deactivating (rear operating unit)	156 154 164 165
Child seatAdjusting the vehicle seat64Basic instructions58Front passenger seat62Installing ISOFIX67Rearward-facing64Risks/dangers60Securing on the rear seat with the seat belt70Securing to the front passenger seat with the seat belt70The most important information in brief58	Decorative foil Genuine wood/trim elements Paint Power washer Sensors Vehicle interior Vehicle parts Vehicle socket for the high-voltage battery Washing by hand Cleaning carpets Cleaning seat covers	383 380 379 382 383 382 382 380 383	Defrosting a window	156 153 158 154 457 159 164

ng
235 235 235 235 235 235 235
235 235 235 235 235 235 235
235 235 235 235 235 235 235
235 235 235 235 235 125, 127
235 235 235 235 125, 127
235 125, 127
125, 127
ntor (CIACI) 37
itel (OAO)
53
ce 34 <i>6</i>
individual
op recording 346
<b>ehicle</b> 34
37

Data storage	Detecting inattentiveness	233	Display	
Data protection rights	Diagnostics connection	30	Care	383
Electronic control units	DIGITAL LIGHT Activating/deactivating	138	Display (driver's display) Overview of displays	310
me connect	Active headlampsAdaptive Highbeam Assist	136 139	Display (MBUX multimedia system) Settings	309
Daytime running lamps, Daytime running lamp mode Activating/deactivating	Adaptive Highbeam Assist Plus	136	Display message  Calling up on driver display  Notes	461 461
Deactivating the alarm	Topographical compensation		Display messages	
Dealership31	Digital Operator's Manual	20	<b>灣</b> 到 mph	
Declaration of conformity  Components relevant to radio regulation 29	Dinghy towing Pulling/towing	303	12 V On-board Electrical Sys-	50/
Decorative foil	DIRECT SELECT lever		tem Service Required	524
Definitions Tires and loading	Automatic transmission Engages neutral Engaging drive position		48 V Battery See Operator's Manual	526
Defrost function	Engaging park position automatically	194	Acoustic Presence Indicator	
Deployed components Limited protection			Inoperative	489
Destination entry	Selecting park position		Break!	507

Automatic Driving Lights Inop-		Currently Not Available Charg-		Engine Oil Pressure Stop	
erative	469	ing of the High-voltage Battery Not		Switch Off Vehicle	534
Battery Overheated Stop!		Completed	472	Front Left Malfunction Service	
Everyone Get Out! Outdoors if Possi-		Currently Unavailable See		Required (Example)	463
ble 477,	, 526	Operator's Manual	503	Fuel Filler Cap Open	492
Brake Immediately	501	Currently Unavailable See		Fuel Reserve	491
© Camera View Reduced See		Operator's Manual	504	Fuel Tank Is Depressurized	
Operator's Manual	520	Do Not Exceed 25 mph	508	Ready for Refueling	481
Charger Cable Connected	474	♣ Do Not Leave People or Ani-		<b>7:</b> Functions Limited When Towing	
BRAKE Check Brake Fluid Level	502	mals in the Vehicle	466	Trailer	521
Check Coolant Level See Oper-		Don't Forget Your Key	468	Have High-Voltage System	
ator's Manual	490	Drive Power and Range		Checked See Operator's Manual	478
Check Engine Oil Level At Next		Reduced See Operator's Manual	479	Initializing Key Please Wait	468
Refueling (Add 1 Quart)	532	Engine Oil Level Cannot Be		Initiating Emergency Stop 512,	, 518
Check Left Low Beam (example)	469	Measured	534	Inoperative See Operator's	
Check Tires	528	Engine Oil Level Reduce Oil		Manual	504
Coolant Stop Switch Off Vehicle	490	Level	533	[ Inoperative See Operator's	
Currently Not Available Charge		Engine Oil Level Stop Switch		Manual	505
High-voltage Battery	472	Off Vehicle	533	<b>EBD</b> Inoperative See Operator's	
				Manual	506

<b>©SOS</b> Inoperative	523	Park Parking Brake See Operator's		Rear Left Backrest Not	
Inoperative	508	Manual	497	Latched (example)	489
Key Not Detected (red display		Performance Extremely Limited	481	Reduce Speed	530
message)	467	Please Correct Tire Pressure	529	PARK Release Parking Brake	500
Key Not Detected (white dis-		Please Wait Charging 48 V Bat-		Replace Key Battery	467
play message)	467	tery	526	Restraint System Malfunction	
Left Window Airbag Malfunc-		Please Wait Depressurizing		Service Required	462
tion Service Required (Example)	464	Fuel Tank	481	<b>9</b> ! Steering Malfunction Drive	
BRAKE Malfunction See Operator's		Pre-entry Climate Control Avail-		Carefully Service Required	485
Manual	501	able Again via SmartKey after Vehicle		<b>9</b> ! Steering Malfunction Increased	
Malfunction See Operator's		Start	473	Physical Effort See Operator's Manual	485
Manual	469	Pre-entry Climate Control via		<b>⊚</b> ! Steering Malfunction Stop	
Malfunction Service Required	478	SmartKey Currently Not Available.		Immediately See Operator's Manual	486
BRAKE Malfunction Stop	502	High-voltage Battery Low	473	Stop Switch Off Vehicle	480
Malfunction	480	Rear Axle Steering Currently		Stop Vehicle See Operator's	
Malfunction	477	Malfunctioning	486	Manual	524
Not in Curr. Drive Prog	508	Rear Axle Steering Malfunction		Stop Vehicle See Operator's	
Obtain a New Key	466	Service Required	486	Manual	525
Off	509	Rear Axle Steering Malfunction		Stop Vehicle To Charge the 12	
HOLD Off	506	Stop Immediately	487	V Battery Do Not Switch Off Vehicle	525

<b>শি</b> ন্ত Suspended	509	Active Blind Spot Assist Currently		Active Lane Change Assist Currently	
Switch Off Lights	470	Unavailable See Operator's Manual	516	Unavailable See Operator's Manual	514
Switch On Headlights	470	Active Blind Spot Assist Inoperative	517	Active Lane Change Assist Inoperative	514
Switch on vehicle to charge the		Active Blind Spot Assist Not Available		Active Lane Keeping Assist Currently	
12 V battery	525	When Towing Trailer See Operator's		Unavailable See Operator's Manual	517
PARK Switch on Vehicle to Release		Manual	517	Active Lane Keeping Assist Inoperative	51
the Parking Brake	500	Active Brake Assist Functions Cur-		Active Lane Keeping Assist Limited	
Tank Ventilation Malfunction		rently Limited See Operator's Manual	510	Range of Functions See Operator's	
Service Required	482	Active Brake Assist Functions Limited		Manual	518
Temporarily Unavailable Sen-		See Operator's Manual	511	Active Parking Assist and	
sors Dirty	519	Active Distance Assist Currently		PARKTRONIC Inoperative See Opera-	
Tires Overheated	530	Unavailable See Operator's Manual	509	tor's Manual	522
Towing Not Permitted See		Active Distance Assist Inoperative	510	Active Parking Assist Limited Availa-	
Operator's Manual	474	Active Distance Assist Now Available	510	bility of Maneuvering Assistance See	
Warning Tire Malfunction	529	Active Emergency Stop Assist Cur-		Operator's Manual	523
Wheel Sensor(s) Missing	528	rently Unavailable See Operator's		Active Steering Assist Currently	
"Electric" Drive Program Currently	020	Manual	513	Unavailable Due to Multiple Emer-	
Unavailable	476	Active Emergency Stop Assist Inoper-		gency Stops	512
AC Charging Inoperative Service	<b>⊤/</b> ∪	ative	513	Active Steering Assist Currently	
	175			Unavailable See Operator's Manual	51
Required	4/3				

Active Steering Assist Inoperative	512	Auxiliary Battery Malfunction (red dis-	407	DC Charging Inoperative Service	175
Active Stop & Go Assist Currently Unavailable See Operator's Manual	515	play message)  Auxiliary Battery Malfunction (white	490	Required  Depress Brake to Shift from P	
Active Stop & Go Assist Inoperative	010	display message)	496	Depress Brake to Shift to D or R	
See Operator's Manual	515	Blind Spot Assist Currently Unavaila-		Depress Brake to Shift to R	493
Adaptive Highbeam Assist Currently		ble See Operator's Manual	516	DIGITAL LIGHT Functions Limited	470
Unavailable See Operator's Manual	470	Blind Spot Assist Inoperative	516	Do Not Restart Vehicle Service	
Adaptive Highbeam Assist Inoperative	471	Blind Spot Assist Not Available When		Required	478
Adaptive Highbeam Assist Plus Cur-		Towing Trailer See Operator's Manual	516	Drive Malfunction Achievable Speed	
rently Unavailable See Operator's		Cannot Start Vehicle See Operator's		Limited Stop Soon	480
Manual	471	Manual	483	Drive Malfunction Achievable Speed	
Adaptive Highbeam Assist Plus Inop-		Charging Fault Change Charging		Severely Limited See Operator's Man-	
erative	471	Mode See Operator's Manual	475	ual	480
Authentication Failed Use Different		Check Brake Pads See Operator's		Front Passenger Airbag Disabled See	
Authentication Method or Charging		Manual	503	Operator's Manual	464
Station	476	Check Tire and Tire Pressure	531	Front Passenger Airbag Enabled See	
Automatic Lane Change Currently		Check Tire Pressure Then Restart Run		Operator's Manual	465
Unavailable See Operator's Manual	514	Flat Indicator	532	Hazard Warning Light Malfunction	472
Automatic Lane Change Inoperative	515	Cruise Control Inoperative	507	Head-up Display Brightness Currently	
		Cruise Control Off	507	Reduced See Operator's Manual	485

Head-up Display Currently Unavaila-		PRE-SAFE Inoperative See Operator's		Run Flat Indicator Inoperative	532
ble See Operator's Manual	484	Manual	521	Service Required Apply Parking Brake	
Head-up Display Inoperative	484	PRE-SAFE PLUS Inoperative See		to Park	493
N Automatically Activated Please Shift		Operator's Manual	521	Service Required Do Not Change	
to Transmission Position Again	494	PRE-SAFE Pulse Side Inoperative See		Transmission Position	495
N is Engaged Shift to Desired Drive		Operator's Manual	521	Shift to P Only When Vehicle Is Sta-	
Range	495	Preparing Drive System	477	tionary	492
Not Possible to Unlock Charging	., -	Reduced Drive System Performance		Snow Chain Mode Maximum Speed	., _
Cable See Operator's Manual	474	See Operator's Manual	477	Exceeded	487
Occupant Presence Reminder Inoper-		Restricted Mode Activated Drive	.,,	Starting Possible Again	527
ative	466	Power Reduced	506	Tire Pressure Monitor Currently	027
Only Electric Drive Available Power	100	Reversing Not Possible Service	000	Unavailable	527
Limited	476	Required	105	Tire Pressure Monitor Inoperative	
	470		473		327
PARKTRONIC and Maneuvering Assis-		Risk of Vehicle Rolling Away Apply	400	Tire Pressure Monitor Inoperative Tire	F00
tance Unavailable at Rear When Tow-	F.0.0	Parking Brake When Parking	493	Pressure Sensors Missing	528
ing Trailer	522	Risk of Vehicle Rolling Away Driver's		To Deselect P or N Depress Brake and	
PARKTRONIC Inoperative See Opera-		Door Open Position P Not Selected	493	Start Vehicle	492
tor's Manual	522	Risk of Vehicle Rolling Away N Activa-		To shift to N, hold selector lever lon-	
Place the Key in the Marked Space		ted Manually No Automatic Change to		ger in N position	495
See Operator's Manual	468	P	494		

To Switch Off Vehicle Press and Hold Start/Stop Button for at Least 3 Sec-		Door Child safety lock (rear door)		Status displays	
onds or Press 3 Times Traffic Sign Assist Currently Unavaila-	490	Emergency key Opening (from the inside) Unlocking (inside)	. 78	Driver's seat  Adjusting (Seat Comfort)  Adjusting electrically	
ble See Operator's Manual Traffic Sign Assist Inoperative	507 507	Door operating unit Function seat	. 16	Easy entry and exit featureSeat heating	110
Transmission Malfunction Stop		DOT, Tire Identification Number (TIN)		Driving off-road	
Vehicle Currently Not Charging Charging Station Fault Vehicle Ready to Drive Shutdown Occurs When Locked or After a Few	475	Downhill Speed Regulation	332 174	Active Brake Assist	254 250 246
Minutes  Vehicle Ready to Drive Shutdown  Occurs When Locked or Automatically in XX Mins	483	Drive program display  Drive programs Selecting	194 190 190	BAS (Brake Assist System) Blind Spot Assist / Active Blind Spot Assist	<ul><li>233</li><li>228</li><li>264</li><li>225</li></ul>
Windshield Wiper Malfunction Displaying road names/house numbers Distance control Distance warning DISTRONIC		Driver's display, Instrument cluster 48 V on-board electrical system Head-up display Menus Notes Operating Service due date	309 307 306 305 305 369	Cruise control	235 230 228 232 230 227

Traffic Sign Assist	225 230 260 296 225 226 174 174	Dynamic low beam Overview  DYNAMIC SELECT Calling up the fuel consumption indicator Configuring drive program I Displaying engine data Displaying vehicle data Drive program display Drive programs Function Selecting the drive program	192 190	ECO Assist  48 V on-board electrical system	187 185 182 181 180 180 181
Rear axle steering Recuperation		E10	452	Electric parking brake	
0 0 0 1	245 246	Easy entry feature Adjusting Function  Easy exit feature	110	Applying automatically	222 222 221
Function Notes		Adjusting Function	111 110	Electronic Stability Program	
Duplicate key  Dynamic handling control system		EASY-PACK trunk box Care EBD, Electronic Brakeforce Distribution	383	Emergency First-aid kit (soft sided) Overview of aids	388

Reflective safety vest	388	Emergency start Engine number Jump-starting Parking (start/stop button)	448 399	Crosswind Assist Function Trailer stabilization  Event Data Recorder.	228 229
Brake Assist System Carrying out Electric parking brake/handbrake	228 222	Engine data Displaying DYNAMIC SELECT	191 191	Exit warning Blind Spot Assist / Active Blind Spot Assist	264
Emergency key		Engine number	448	Exiting a parking space	
Door Tailgate		Engine oil, Oil Additives	453	Active Parking Assist Drive Away Assist	
Emergency operation mode Starting the vehicle	1 71	CapacityChecking the oil level using the driver		PARKTRONIC	280
Emergency release Socket flap		displayMB-Freigabe or MB-Approval	454	Exterior lighting Care  Exterior mirrors	382
Emergency shutoff (high-voltage on-board electrical system)		Quality Refilling Temperature (driver's display)	374	Parking position	150
Emergency stop assistant	248	Engine oil temperature (driver's display)		F	
Emergency Tensioning Devices Inflating	51	Engine output, current (driver's display)	307	Factory settings MBUX reset function	328
Energy flow display Function/notes		ESC, Electronic Stability Control		FavoritesFilm coverings	322
Engine Emergency operation mode		ESP® Activating/deactivating	230	On camera/sensors	225

First aid First-aid kit (soft sided)	388	Inserting/removing the flacon Perfume vial		Quality (gasoline)Refilling	
First-aid kit (soft sided) Fitting accessories	388	Free software	38	Reserve Sulfur content Tank capacity	452
Limited protection		Two-way radio Front air bag		Fuel consumption indicator	192
Flat tire Changing a wheel	436	InflatingFront headlamps		Fuel reserve  Function in the event of an accident	52
MOExtended Notes TIREFIT kit	388	Front passenger air bag Disabling/enabling	47	Fuses	
Flat towing Pulling/towing		Front passenger air bag shutoff, PASSENGER AIR BAG OFF Information (child restraint system on		Cargo compartment Cockpit Engine compartment	410
Floor mats	132	the front passenger seat)	62	Fuse assignment diagram Notes	408
Foil covering Radar and ultrasonic sensors		Adjusting (Seat Comfort)		Passenger footwell	410
Fording water		Fuel Additives	452	G-meter, Accelerometer	307
Fragrance  Fragrance system  Activating/deactivating  Adjusting	159	Depressurize the fuel tank (plug-in hybrid with gasoline engine)E10	452	Garage door opener Clearing the memory Opening/closing a door Problem	220

Garage door openers		Hazard warnings		Windshield	160
Programming buttons	218	Car-to-X-Communication	343	Help call	
Synchronizing the rolling code 2	219	Head restraint		Mercedes-Benz emergency call system	359
Gasoline4	452	Adjusting (rear passenger compart-		High beam	134
Gearshift		ment)	103	High-voltage battery	
DIRECT SELECT lever 1	192	Adjusting manually (front, 4-way)	102	Charge level display	215
Manual 1	195	Removing/installing (rear passenger	104	Charging at time of departure	
General driving tips 1	174	compartment)	104	Charging cable control panel	
		Head-up display	000	Charging station, mode 3	
Glide mode1		Care	383 307	Configuring weekly profile	334
	170	Function	113	Ending the charging process (alternat-	
Glove box	110	Memory function Operating		ing current, mode 2/3)	211
Locking/unlocking 1		Switching on/off	309	Ending the charging process (direct	214
Grab handles	98	Headlamp flashing		current, mode 4) Energy flow display	
Н		_		General notes on charging	
	200	Headlamp range control		Mains socket, mode 2	203
	220	Headlamps	133	Maximum charging current (mains	
Handling characteristics		Heating		socket)	206
Unusual 4	412	Activating/deactivating	155	Notes	398
HANDS-FREE ACCESS	85	Center console		Rapid charging station, mode 4	
Haptic accelerator pedal, Pressure point 1	187	Climate control		Recuperation	184
Hazard warning lights		Rear window		Starting the charging process (alter-	000
		SeatSteering wheel		nating current, mode 2/3)	209

Starting the charging process (direct current, mode 4)	202 204 208 168 25 245 232 230 231 318	PASSENGER AIR BAGIndividual drive program	95 53 534 45 190 150 413 439 6,8	Internet
I Identification plate Engine Refrigerant Vehicle		Interior lighting Adjusting Ambient lighting Switch-off delay time Interior protection	142 143 144	Deactivating

Knee bag	57	Combination switchDIGITAL LIGHT		Load-bearing capacity Tires	427
Lane Change Assist  Lane Keeping Assist  Lane recognition  Active Lane Change Assist  Active Lane Keeping Assist	<ul><li>268</li><li>250</li></ul>	Dynamic low beam	136 135 134 142 142	Loading Bag hook Definitions Notes Roof luggage rack. Tie-down eyes.	123 430 113 124 123
Language Notes Setting	328	Responsibility for lighting systems Switch-off delay time Switching on the daytime running lamps	133 142 142	Loading guidelines  Loading information table  Loads	420 113
License plate (front)	29	Switching the Intelligent Light System on/off	138 136	Locking/unlocking Automatic locking (MMS)	. 80
Lighting  Dynamic low beam Interior lighting	136	Turn signals  Limited Warranty  Live Traffic Information	. 33	Doors (from the inside) Emergency key KEYLESS-GO Loud sound	. 80
Lights Active headlampsAdaptive Highbeam AssistAdaptive Highbeam Assist PlusAssistance functionsAutomatic driving lights	139 140 136	Load capacity Bicycle rack  Load index Tires	459	PRE-SAFE® Sound  Low-beam headlamps Activating/deactivating  Lubricants  Luggage	133 450

Luggage rack		Drive Away Assist		MBUX multimedia system	215
Lumbar support	102	Maneuvering brake function		Activating / deactivating DSR	
		Maneuvering brake function	291	Activating/deactivating standby mode Calling up the zero layer	
M		Maneuvering support	290	Configuring display settings	309
Maintaining safe distance		Manual gearshifting		Drive programs	190
Active Distance Assist DISTRONIC	240	Activating/deactivating	195	Factory setting	
Maintaining the headliner	383		1,0	Home screen	318
_		Map	242	Language settings	
Maintaining the steering wheel	303	Displaying online map contents		Media	
Maintenance		1 7 8	343	Memory Park Assist	
Vehicle	. 24	Moving		Mercedes me & Apps	
Maintenance Management			343 343	Notes	
Notes	370	9 1		Operating the zero layer	
Transferred data	370	Map functions	343	Overview	
Malfunction		Massage programs 105,	106	Set collision detection	
Restraint system	. 43	Maximum full-stop braking	228	Setting route-based speed adaptation	244
Malfunction message		Maximum load rating		Snow chain mode	413
Driver's display	461	S	120	Standby mode function	224
	101	Maximum permissible load	400	Steering wheel heater / seat heating	110
Maneuvering	000	Calculation example		Telephone	348
Drive Away Assist		Determining		Touchscreen	318
Maneuvering brake function	291	Maximum tire pressure	427	Zero layer	313
Maneuvering assistant		MBUX		MBUX Voice Assistant	
Activating/deactivatingCross traffic warning		Dashcam	345	Function	320

Voice prompting	Arranging a service appointment Calling the Mercedes-Benz customer center after automatic accident/		Mirrors  Mirror folding function  Outside mirrors  Rearview mirror	149
Overview of functions/symbols	Information Mercedes-Benz customer center	352 352	Mobile phone Notes on wireless charging Wireless charging (front) Model type	131
Head-up display	Mercedes me connect Accident/Breakdown Management	355 355	Modification Limited protection  MOExtended tires, Run-flat tires  Multimedia system	389
Exiting a parking space.       295         Function.       292         Parking.       294         Recording.       293         Setting.       296	Mercedes-Benz emergency call system, Emergency call Automatic emergency call		N Navigation Activating Destination entry	
Menus (driver's display)  Notes	Information  Manual emergency call	359 360	Notes Overview	337
Mercedes me App Activating on-demand features	wiessage memory	461	Non-operational time Activating/deactivating standby mode Notes on breaking in a new vehicle	

O Objects in the vehicle interior Limited protection	On-board electronics Two-way radios	Operator s Maridar digitar
Occupant presence reminder Activating/deactivating	Online services	6 Automatic anti-glare mode
Occupant safety Air bag	Limiting (tailgate) 8  Opening the tailgate using your foot HANDS-FREE ACCESS 8  Opening/closing a door 22	Memory function
Information on the correct seat position 41 Occupant presence reminder 72 Pets in the vehicle 53 PRE-SAFE® 49	Operating fluids Additives 45	P Paddle shifters
Off-road ABS	Refrigerant (air conditioning system) 45 Windshield washer fluid	Panic alarm, Alarm Activating/deactivating

PARKTRONIC	283 292 280 282 283 280 283	Storing the position of the front- passenger outside mirror using reverse gear	280 45 422 421 403	Indicator lamps on vehicle socket	168 206 204 203 204 166
Maneuvering brake function Memory Parking Assist PARKTRONIC  Parking brake  Parking for an extended period  Parking lamps  Parking lights  Parking position  Exterior mirrors	292 280 220 224 133 133	Personalization	206 205 211 214 184	Power meter  Route-based operating-mode strategy  Sets recuperation  Starting the charging process (alter-	310 187 184 209 212 202 . 51

Power washer	Protection Limited	Rain sensor Sliding sunroof
activating/deactivating for departure time	Protection against collision  Maneuvering brake function	Windshield wipers
For departure time	Driving style	Rear axle steering
Pre-heating	Hill Start Assist	Securing
Function	QR code rescue card	control
PRE-SAFE® Impulse Side Function	Qualified specialist workshop	Adjusting the backrest angle
Inflating	R Radar and ultrasonic sensors	Rear view camera 360° Camera
Preventative occupant protection system 49	Radio regulations Regulatory radio identification	Opening the camera cover
Profile	Rain closing function Sliding sunroof	Rear window heating

Rear window wiper Activating/deactivating Replacing wiper blade	placement key	
Rearview mirror Automatic anti-glare mode	Fuel 453 Roadside Assistance (breakdown)	
Rearward-facing child seat Information	MBUX reset function	
Recuperation Function	sidual heat	
Reflective safety vest	Straint system Roof luggage rack Basic information	
Refueling depressurize the fuel tank (plug-in hybrid with gasoline engine)	Deployment situations	341 . 341 . 341
Regulatory radio information Specific absorption rate  Remote Online Charging the starter battery	Malfunction         43         Selecting a type           Protection         41         Route guidance with augmented reality           Self-test         43         Activating           Warning lamp         43         Displaying road names/house numbers	341 . 341 . 341
Regulatory radio information Specific absorption rate  Remote Online	Limited protection. 53 Navigation. Selecting a type  Protection. 41 Route guidance with augmented reality Self-test. 43 Warning lamp. 43 Displaying road names/house num-	

Route-based operating-mode strategy
Function
Route-based speed adaptation
Function
Setting
Run-flat characteristics
Running boards
Care
Notes 82
\$
Safety system
Satellite radio
Logging in
Setting music and sport alerts 367
Seat, Through-loading feature
Adjusting (Seat Comfort)
Adjusting electrically 101
Adjusting the angle of the backrests
(rear passenger compartment) 121
Automatic adjustment 105
Configuring settings 105
Correct driver's seat position 98

Folding back the backrest (rear passenger compartment) Folding backrest forward (rear) Locking the backrest (rear passenger compartment) Lumbar support Massage programs	120 118 120 102 105
Memory function	113
Resetting settings (massage programs) Settings	106
Side impact air bag	57
Workout programs	105
Seat belt	
Automatic tightening Rear passenger compartment seat	50
belt status display	45
Warning lamp	44
Seat belt adjustment	
Activating/deactivatingFunction	50 50
Seat belt warning	44
Seat belts	
Activating/deactivating seat belt adjustment	50
aajaotiiioiittiiiiiiiiiiiiiiiiiiiiiiiiii	50

CareFasteningNotes on wearing correctlyReleasingTo adjust the height	383 43 42 56 43
Seat heating Activating/deactivating	106
Seat ventilation Activating/deactivating	107
Selecting a gear	195
Selector lever	192
Self-test Automatic front passenger air bag shu toff	45 43
Sensors Cleaning Information	382 225
Service	369
Service center	31
Service due date	369

Service interval display...... 369

Shifting Automatic transmission Gearshift recommendation	195 196	Closing with SmartKey Opening with the SmartKey Opening/closing	89	Software update	
ManualSteering wheel paddle shifters	195 195	ProblemRain closing function	94	Sound  Menu  PRE-SAFE® Sound	
Shortening the braking distance		SmartKey		Wheels/tires	
Brake Assist System		Acoustic locking verification signal		Sound settings	
Shunting assistant	296	Battery  Deactivating a function		Spare parts	
Side impact air bag	57	Function			
Side windows		Key ring attachment		Spare wheel, Emergency spare wheel	
Child safety lock (rear passenger		Mechanical key		Special seat belt retractor	
compartment)	. 72	Panic alarm		Specialist workshop	. 31
Closing with SmartKey		Power consumption		Specific absorption rate (SAR)	448
Convenience closing feature	0.0	Unlocking setting	/4	Speed	
Convenience opening  Opening with the SmartKey		Smartphone Integration, iPhone®		Save, cruise control	
Opening/closing		Android Auto		Save, DISTRONIC	240
Problem	90	Apple CarPlay®		Speed adaptation, Route-based	242
Size designation		Snow chain mode	413	Speed control	
	427	Snow chains	413	Active Distance Assist DISTRONIC	237
Skid chains	413	Socket		Cruise control	235
Sliding sunroof, Panorama roof with power tilt/sliding panel		12 V 115 V (rear passenger compartment)		Speed rating Tires	427
Automatic functions	93	Socket flap	200		

Start-off assist Drive Away Assist Hill Start Assist Optimized acceleration	232	Status display Front passenger air bag Rear passenger compartment seat belt Steer Assist		Stowage areas	116
Start/stop button Parking the vehicle		Active Steering AssistSTEER CONTROL	246 230	Door	116
Starting the vehicle	170	STEER CONTROL	230	Substances hazardous to health	. 25
Switching on the power supply / vehi- cle	169	Steering Rear axle steering	178	Sulfur content	452
Start/stop function	180	Steering wheel	170	Switch-off delay time Exterior	1/19
Starter battery charging, Remote Online	172	Adjusting electrically	109 57	Interior	144
	1 <i>7</i> 2 1 <i>7</i> 0	Manually adjusting  Memory function  Steering wheel adjustments	108 113	Switching air-recirculation mode on/off  System settings  MBUX reset function	328
Starting assistance	400	Steering wheel heating	107	Overview	325
Starting the engine Emergency operation mode		Decoupling from the seat heating  Steering wheel paddle shifters		Tailgate, Trunk lid	
Remote OnlineStart/stop button	172	Step		Closing Emergency key	
Starting-off aid Drive Away Assist	232	Stop and go ECO start/stop function  Stopping Parking the vehicle		HANDS-FREE ACCESS Limiting the opening angle Opening	85 87
Optimized acceleration	1/3	raiking the vehicle	Z 1 0		

Tank capacity		Notes	348	Tire labeling	
Fuel	453	Notes on wireless charging (mobile		Characteristics	427
Reserve	453	phone)		DOT, Tire Identification Number (TIN)	
Tank filler cap / flap	197	Operating modes		Load index	
Technical data		Secure Simple Pairing		Load-bearing capacity	42/
Axle load (trailer operation)	460	Telephone menu overview	350	Maximum tire load	
Fastening points of the trailer hitch		Wirelessly charging a(mobile phone,	101	Maximum tire pressure	
Information		front)	131	Size designation	
Mounting dimensions of a trailer hitch		Telephony operating modes		Speed rating	
Overhang dimension of the trailer hitch		Bluetooth® telephony	350	Temperature grade	
Radio regulations		Temperature		Tire Quality Grading Traction grade	
Specific absorption rate (SAR)		Adjusting	154	Tread wear grade	121
Tongue weight	459	Setting			727
Towing capacity		Temperature grade	424	Tire pressure	410
Vehicle dimensions	457	THERMATIC		Checking	410
Telediagnosis		Air conditioning control panel	152	Checking manually Maximum	
Diagnostic data	370	9 1	133	Notes	
Telediagnostics		THERMOTRONIC	4.5.4	Restarting the tire pressure loss warn-	410
Transferred data	371	Air conditioning control panel	154	ing system	419
Telemetry display		Tie-down eyes	123	Tire pressure loss warning system,	117
	000	TIN (Tire Identification Number)	425	function	419
Telephone, Smartphone	0.50	Tire and Loading Information placard	420	Tire pressure table	415
Bluetooth®		Tire characteristics		TIREFIT kit	
Connecting a mobile phone					
Menu	35 l	Tire information table	420		

				Index	585
Tire pressure loss warning system		Installing		TIREFIT kit	
Function		Labeling	424	Traction grade	
Restarting	419	Load index		Tread wear grade	
Tire pressure monitor		Load-bearing capacity		Unusual handling characteristics	412
Function	416	Maximum pressure	427	Toll system	
Tire pressure monitoring system		Maximum tire load		Debiting toll fees	337
Restarting	418	MOExtended		Windshield	
Tire pressure table		Noise Notes on installing		Tongue weight	459
Tire Quality Grading		Removing		Top Tether	. 68
		Removing/installing hub cap		Topographical compensation, Predictive	
Tire sealant	391	Replacing		headlamp range control	136
Tire tread	412	Restarting the tire pressure loss warn-	,		
Tire-change tool	435	ing system	419	Torque (driver's display)	307
Tire-change tool kit		Rotating	435	Touch Control	
_	<del>1</del> 00	Selecting	432	Driver's display	
TIREFIT kit, Tire inflation compressor	200	Size designation	427	MBUX	
Storage location	390	Snow chains		Touch-sensitive controls	. 23
Tires		Speed rating		Touchscreen	318
Breakdown		Storing	435	Tow bar system	
Characteristics		Temperature grade		Towing away	303
Checking		Tire and Loading Information placard	420		
Checking the temperature		Tire pressure loss warning system,	440	Tow-away protection	
Checking the tire pressure manually		function		Tow-starting	408
Definitions	430	Tire pressure table			
DOT, Tire Identification Number (TIN)	425	Tire Quality Grading	424		

Towing Towing methods	268 460	Axle load Care Coupling up/uncoupling a trailer Fastening points General notes Mounting dimensions	382 301 459 459	Tread wear grade
Notes	407	Overhang dimension Tongue weight Towing capacity Trailer Maneuvering Assist	459 459 459	Two-way radios         447           Installation
Both axles on the ground  Overview  Track Race	403 329	Trailer Maneuvering Assist Function Using		U         Unfastening         56           Unlocking setting         74
Traction grade  Traffic information  Traffic Jam Assistant  Traffic light warning/display	343 244	Trailer operation  Active Blind Spot Assist  Attaching the ball neck  Coupling up/uncoupling a trailer  Setting	301	Updates
Traffic Sign Assist Function Setting Trailer drawbar, Pulling/towing Trailer hitch	260 264 303	Trailer stabilization	229	User profiles Adding a user

V Valet Service Mode    Activating/deactivating	Pulling  OR code rescue card  Raising  Set collision detection  Standby mode function  Starting (start/stop button)  starting, emergency operation mode  Stopping  Switching off (start/stop button)  Switching on (start/stop button)  Towing away	437 223 224 170 171 216	Vehicle dimensions	408 448 448 448 448
Diagnostics connection	TransportingVentilating / comfort opening		Cooling/heating (Remote Online)  Vehicle key	
Equipment	Vehicle camerasVehicle data	225	Vehicle operation outside the USA or Canada	. 24
Limited Warranty	Angle of approach/departure Display, MBUX		Vehicle sensors Vehicle socket	225
Locking/unlocking (emergency key) 80 Locking/unlocking (from inside) 78 Lowering 441		191 458 457	Care Emergency release of the socket flap Indicator lamps	
Maintenance	Vehicle height Vehicle length Vehicle width Weights Wheelbase	457 457 457 457 457	Vehicle start Emergency operation mode Remote Online Start/stop button	171 172

Vehicle tool kit	
TIREFIT kit	390
Towing eye	407
Ventilating	. 89
Ventilation	164
Vents	
Air vents	164
VIN	
Engine compartment	448
Identification plate	448
Seat	448
Vision	
Defrosting windows	158
Windshield heater	160
Voice assistant	
Voice prompting	320
W	
Warning system	. 95
Warning triangle	388
	000
Warning/indicator lamp	E 40
ABS warning lamp	549

<b>≽</b> !⊲	Active Brake Assist warning	
lamp		552
<b>₹</b>	ATTENTION ASSIST warning	
lamp		551
<b>(</b> (1)	Brakes warning lamp (Canada	
only)		548
BRAKE	Brakes warning lamp (USA only)	548
<b>(</b> ())	Brakes warning lamp (yellow)	
(Cana	da only)	547
	Check Engine warning lamp	544
<b></b>	Coolant warning lamp (red)	542
	Coolant warning lamp (yellow)	543
	Distance warning lamp	551
(P)	Electric parking brake indicator	
lamp (	(red) (Canada only)	546
PARK	Electric parking brake indicator	
lamp (	(red) (USA only)	546
(P)	Electric parking brake indicator	
lamp (	(yellow)	546
	•	

Electrical malfunction warning	
amp 540,	544
Engine operating temperature	
varning lamp	544
🐉 ESP® OFF warning lamp	550
ESP® warning lamp flashes	549
ESP® warning lamp lights up	550
Fuel reserve warning lamp flashes	545
Fuel reserve warning lamp	
ights up	545
SOS Mercedes-Benz emergency call	
system warning lamp	553
Occupant presence reminder	
varning lamp (white)	538
Occupant presence reminder	
varning lamp (yellow)	539
<b>9</b> ! Power steering warning lamp	
red)	540

(yellow)  RBS RBS warning lamp (USA only)  RBI Rear axle steering warning		PASSENGER AIR BAG  Washer fluid Topping up Windshield washer fluid  Washing by hand	376 455	DOT, Tire Identification Number (TIN) Installing Load index Load-bearing capacity	430 425 439 427 427
lamp (red)  Rear axle steering warning lamp (yellow)	<ul><li>541</li><li>541</li></ul>	Water tank Wear Limited protection		Maximum tire pressureMOExtendedNoise	427 389 412
Reduced warning lamp power  Restraint system warning lamp  Restraint system warning lamp flashes	539 537 538	Weather information Web browser Weight information	357	Removing	
Seat belt warning lamp lights up  System malfunction warning lamp	538 539	Wheel change Installing a new wheel Lowering the vehicle	439 441	Rotating	435 432 427
Tire pressure monitoring system warning lamp flashes	553	Removing a wheel		Speed rating Storing Temperature grade	427 435 424
tem warning lamp lights up		Wheels  Breakdown  Care  Checking  Checking the tire pressure manually	382 412	Tire characteristics	420 427 424 413 416
Driver's display	534	Checking the tire temperature		Tire Quality Grading	

Traction grade Tread wear grade Unusual handling characteristics  Wi-Fi Setting up a hotspot  Window curtain air bag  Windows Care Convenience opening De-icing Opening with the SmartKey. Opening/closing Removing mist  Windshield De-icing Defrosting Defrosting Demisting Radio waves	382 89 156 89 88	Windshield wipers Activating/deactivating Replacing the wiper blades Replacing the wiper blades (windshield) Replacing wiper blades (rear window) Winter operation Activating/deactivating snow chain mode Snow chains Wiper blades Care Replacing (windshield) Wipers Wireless charging Mobile phone (front) Notes Workout programs.	145 145 148 413 413 382 145 144 131 130
Windshield heater, Windshield heating	160	Z	
Windshield washer fluid	455 376	Zero layer Function Overview	



